

HISTORICAL

Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze

See General Information for Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze

WEIFANG XINHUITONG METAL WORK CO LTD

EX27983

The Cross Section Of Yuqing Street

And Tengfei Rd

Weifang, Shandong 261021 CHINA

Malleable Iron and Ductile Iron Threaded Fittings (EN 10242)

Malleable Iron and Ductile Iron Thread Pipe Fitting fabricated with dimensional specifications in accordance with DIN EN 10242. Threads compliance to ISO 7-1.

Model/Fig.	Configuration	Size (in.)	Rated Pressure (psig)
90	90° Elbows	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500
92	Male and female elbows	1/2, 3/4, 1	500
90R	90° Reducing Elbows	3/4 x 1/2 1 x 3/4, 1 x 1/2; 1-1/4 x 1, 1-1/4 x 3/4; 1-1/2 x 1-1/4, 1-1/2 x 1; 2 x 1-1/2; 2-1/2 x 2;	500
120	45° Elbows	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
130	Tees	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500
130R	Reducing Tees on the branch	3/4 x 1/2; 1 x 3/4, 1 x 1/2; 1-1/4 x 1, 1-1/4 x 3/4, 1-1/4 x 1/2; 1-1/2 x 1-1/4, 1-1/2 x 1, 1-1/2 x 3/4, 1-1/2 x 1/2; 2 x 1-1/2, 2 x 1-1/4, 2 x 1, 2 x 3/4, 2 x 1/2; 2-1/2 x 2, 2-1/2 x 1-1/2, 2-1/2 x 1-1/4, 2-1/2 x 1; 3 x 2, 3 x 1-1/2, 3 x 1-1/4, 3 x 1; 4 x 3, 4 x 2;	500
130E	Tees, Increasing on the branch	1/2 x 3/4, 1/2 x 1; 3/4 x 1, 3/4 x 1-1/4; 1 x 1-1/2, 1 x 1-1/4; 1-1/4 x 2, 1-1/4 x 1-1/2,	500
130H	Tees, Reducing on the run and branch	1-1/2 x 1 x 1-1/4, 2 x 1-1/4 x 1-1/2, 2 x 1 x 1-1/2;	500
130G	Tees, Reducing on the run and branch	1 x 3/4 x 3/4; 1-1/4 x 1 x 1; 1-1/2 x 1 x 1, 1-1/2 x 1-1/4 x 1-1/4; 2 x 1-1/4 x 1-1/4, 2 x 1-1/2 x 1-1/2;	500

180	Equal Cross	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4;	500
180R	Reducing Cross	3/4 x 1/2; 1 x 3/4, 1 x 1/2; 1-1/4 x 1, 1-1/4 x 3/4; 1-1/2 x 1;	500
241	Bushings	3/4 x 1/2; 1 x 3/4, 1 x 1/2; 1-1/4 x 1, 1-1/4 x 3/4, 1-1/4 x 1/2; 1-1/2 x 1-1/4, 1-1/2 x 1, 1-1/2 x 3/4, 1-1/2 x 1/2; 2 x 1-1/2, 2 x 1-1/4, 2 x 1, 2 x 3/4, 2 x 1/2; 2-1/2 x 2, 2-1/2 x 1-1/2, 2-1/2 x 1-1/4, 2-1/2 x 1; 3 x 2-1/2, 3 x 2, 3 x 1-1/2, 3 x 1-1/4, 3 x 1; 4 x 3, 4 x 2-1/2, 4 x 2;	500
270	Socket	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4;	500
240	Reducing Socket	3/4 x 1/2; 1 x 3/4, 1 x 1/2; 1-1/4 x 1, 1-1/4 x 3/4, 1-1/4 x 1/2; 1-1/2 x 1-1/4, 1-1/2 x 1, 1-1/2 x 3/4, 1-1/2 x 1/2; 2 x 1-1/2, 2 x 1-1/4, 2 x 1, 2 x 3/4, 2 x 1/2; 2-1/2 x 2, 2-1/2 x 1-1/2, 2-1/2 x 1-1/4; 3 x 2-1/2, 3 x 2, 3 x 1-1/2; 4 x 3, 4 x 2-1/2, 4 x 2;	500
300	Cap	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500
280	Hexagon Nipples	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500
291	Plain plug	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500

Malleable Iron and Ductile Iron Threaded Fittings (ANSI/ASME B16.3)

Malleable Iron and Ductile Iron Thread Pipe Fitting fabricated with dimensional specifications in accordance with ASME B16.3, Class 150. Threads in accordance with ANSI B1.20.1.

Model/Fig.	Configuration	Size (in.)	Rated Pressure (psig)
A90	90° Elbows	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500
A92	90° Street elbows	1/2, 3/4, 1;	500
A90R	90° Reducing Elbows	3/4 x 1/2; 1 x 3/4, 1 x 1/2; 1-1/4 x 1, 1-1/4 x 3/4, 1-1/4 x 1/2; 1-1/2 x 1-1/4, 1-1/2 x 1, 1-1/2 x 3/4; 2 x 3/4, 2 x 1-1/2, 2 x 1-1/4, 2 x 1; 2-1/2 x 2, 2-1/2 x 1-1/2; 3 x 2-1/2, 3 x 2; 4 x 3;	500
A120	45° Elbows	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500
A130	Tees	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500

A130R	Reducing Tees	$1/2 \times 1/2 \times 3/4$, $1/2 \times 1/2 \times 1$; $3/4 \times 3/4 \times 1/2$, $3/4 \times 3/4 \times 1$, $3/4 \times 3/4 \times 1-1/4$; $1 \times 1 \times 1/2$, $1 \times 1 \times 3/4$, $1 \times 3/4 \times 3/4$, $1 \times 1 \times 1-1/4$, $1 \times 1 \times 1-1/2$, $1 \times 1 \times 2$, $1-1/4 \times 1-1/4 \times 1/2$, $1-1/4 \times 1-1/4 \times 3/4$, $1-1/4 \times 1 \times 1$, $1-1/4 \times 1-1/4 \times 1$, $1-1/4 \times 1-1/4 \times 2$; $1-1/2 \times 1-1/2 \times 1/2$, $1-1/2 \times 1-1/2 \times 3/4$, $1-1/2 \times 1-1/4 \times 1$, $1-1/2 \times 1-1/2 \times 1$, $1-1/2 \times 1 \times 1$, $1-1/2 \times 1-1/4 \times 1-1/4$, $1-1/2 \times 1-1/2 \times 1-1/4$, $1-1/2 \times 1-1/2 \times 2$; $2 \times 2 \times 1/2$, $2 \times 2 \times 3/4$, $2 \times 2 \times 1$, $2 \times 2 \times 1-1/4$, $2 \times 1-1/4 \times 1-1/4$, $2 \times 2 \times 1-1/2$, $2 \times 1-1/2 \times 1$, $2 \times 1-1/2 \times 1-1/4$, $2 \times 1-1/2 \times 1-1/2$, $2 \times 2 \times 2-1/2$; $2-1/2 \times 2-1/2 \times 3/4$, $2-1/2 \times 2-1/2 \times 1$, $2-1/2 \times 2-1/2 \times 1-1/4$, $2-1/2 \times 2-1/2 \times 1-1/2$, $2-1/2 \times 2 \times 2$, $2-1/2 \times 2-1/2 \times 2$, $2-1/2 \times 2-1/2 \times 3$; $3 \times 3 \times 3/4$, $3 \times 3 \times 1$, $3 \times 3 \times 1-1/4$, $3 \times 3 \times 1-1/2$, $3 \times 3 \times 2$, $3 \times 3 \times 2-1/2$; $4 \times 4 \times 1-1/2$, $4 \times 4 \times 2$, $4 \times 4 \times 2-1/2$, $4 \times 4 \times 3$;	500
A180	Equal Cross	$1/2$, $3/4$, 1 , $1-1/4$, $1-1/2$, 2 , $2-1/2$, 3 , 4	500
A180R	Reducing Cross	$3/4 \times 1/2$; $1 \times 3/4$, $1 \times 1/2$; $1-1/4 \times 1$, $1-1/4 \times 3/4$; $1-1/2 \times 1-1/4$, $1-1/2 \times 1$, $1-1/2 \times 3/4$; $2 \times 1-1/2$, $2 \times 1-1/4$, 2×1 , $2 \times 3/4$; $2-1/2 \times 2$; 3×2 ;	500
A240	Reducing Coupling	$3/4 \times 1/2$; $1 \times 3/4$, $1 \times 1/2$; $1-1/4 \times 1$, $1-1/4 \times 3/4$, $1-1/4 \times 1/2$; $1-1/2 \times 1-1/4$, $1-1/2 \times 1$, $1-1/2 \times 3/4$, $1-1/2 \times 1/2$; $2 \times 1-1/2$, $2 \times 1-1/4$, 2×1 , $2 \times 3/4$, $2 \times 1/2$; $2-1/2 \times 2$, $2-1/2 \times 1-1/2$, $2-1/2 \times 1-1/4$, $2-1/2 \times 1$, $2-1/2 \times 3/4$; $3 \times 2-1/2$, 3×2 , $3 \times 1-1/2$, $3 \times 1-1/4$, 3×1 , $3 \times 3/4$; 4×3 , $4 \times 2-1/2$, 4×2 , $4 \times 1-1/2$;	500
A270	Coupling	$1/2$, $3/4$, 1 , $1-1/4$, $1-1/2$, 2 , $2-1/2$, 3 , 4	500
A300	Caps	$1/2$, $3/4$, 1 , $1-1/4$, $1-1/2$, 2 , $2-1/2$, 3 , 4	500

Malleable Iron and Ductile Iron Threaded Fittings (ANSI/ASME B16.14)

Malleable Iron and Ductile Iron Thread Pipe Fitting fabricated with dimensional specifications in accordance with ASME B16.14. Threads in accordance with ANSI B1.20.1.

Model/Fig.	Configuration	Size (in.)	Rated Pressure (psig)
A241	Outside head	$3/4 \times 1/2$; $1 \times 3/4$, $1 \times 1/2$; $1-1/4 \times 1$, $1-1/4 \times 3/4$; $1-1/2 \times 1-1/4$, $1-1/2 \times 1$; $2 \times 1-1/2$, $2 \times 1-1/4$; $2-1/2 \times 2$, $2-1/2 \times 1-1/2$; $3 \times 2-1/2$, 3×2 ; 4×3 ;	500
A291	Cored plug	$1/2$, $3/4$, 1 , $1-1/4$, $1-1/2$, 2 , $2-1/2$, 3 , 4	500

La presencia del nombre de una empresa o producto en esta base de datos no garantiza por sí misma que los productos así identificados hayan sido fabricados bajo el servicio de seguimiento de UL. Solo aquellos productos que lleven la marca UL deben considerarse como certificados y garantizados bajo el servicio de seguimiento de UL. Busque siempre la marca en el producto.

UL permite la reproducción del material contenido en el directorio de certificación en línea sujeta a las siguientes condiciones: 1. La información de la guía, las ensamblajes, las construcciones, los diseños, los sistemas y/o certificaciones (archivos) deben presentarse en su totalidad y de forma no engañosa, sin ninguna manipulación en los datos (o dibujos). 2. Debe aparecer la declaración "Reimpreso desde el directorio de certificaciones en línea con permiso de UL" junto al material extraído. Además, el material reimpreso debe incluir una nota de derechos de autor en el siguiente formato: "©2024 UL LLC."