

BALL VALVE

SB-ATI-VS050


TYPE


S 127

BODY 150# **FULL BORE RATING ASME B16.5** ASSEMBLING 150# RF BODY **CARBON STEEL** STEM **AISI 304 MATERIALS** SEATS **TEFLON** BALL **AISI 304 OPERATING** (5) Т (5) USE: CONDITIONS

(1) All gaskets have to be asbestos free NOTES:

- (2) All dimensions are in mm
- (3) When the valve is closed, the ball should remain within the limits of the valve body (dimension "L")
- (4) SCREWS: ASME B18.2.1/UNC ASTM A193 B7 (5) P=15 Bar with T=50° C P=11 Bar with T=100° C P=7 Bar with T=150° C





TYPE

"B"

INCH.		1/2"	3/4"	1"	11/4"	11/2"	2"	21/2"	3"	4"	5"	6"	8"			
L (3)		35	35	43	51	64	85	103	120	155	182	234	310			
	Н		62	80	85	103	111	135	144	170	183	235	277			
	٧		145	185	185	280	280	370	370	470	470	600	745			
SCDEW	N°	8	8	8	8	8	8	8	8	16	16	16	16			
SCREW (4)	DIMEN.	½"x30	½"x30	½"x30	½"x35	½"x35	5/8"x40	5/8"x40	5⁄8"x45	5⁄8"x45	3⁄4"x50	¾"x50	¾"x50			
	Weight Kg.		1,9	2,8	4,8	7,0	6,5	10,2	14,0	21,0	31,0	49,0	89,0			
TYPE		"A"									"B"					

2	REVISED OPERATING CONDITIONS	ATI	16/07/07	The master version of this document is stored as a digital file
1	REVISED	ATI	23/11/06	in a software archive - Approval process is digitally managed,
0	ISSUED	ATI	31/01/05	details do not show on paper copies.
Rev.	Description	Author	Date	

We reserve the ownership under the law of this document with prohibition of even partial reproduction and to make it known to third persons without our written authorization