SYMBOL		DESCRIPTION	SYMBO)L	DESCRIPTION	SYMBOL		DESCRIPTION	SYMBOL		DESCRIPTION
	F	FUSE	4 4	K	CONTACTOR	<u> </u>	S	OPERATED BY TURNING		R	RESISTOR
\	Q	DISCONNECTOR	+	К	OPERATING DEVICE	Ω	S	OPERATED BY KEY	Ţ.	R	SHUNT
J	Q	SWITCH DISCONNECTOR		К	BREAK AND MAKES AUXILIARY CONTACT	1 2 (} (}-£	s	1— EMERGENCY PUSH—BUTTON 2— EMERGENCY PUSH—BUTTON LACTING		R	HEATING ELEMENT
	F	SWITCH DISCONNECTOR WITH FUSE	1 /	Q K	NORMALLY CLOSED AND NORMALLY OPEN MAKE CONTACTS		S	BREAK AND MAKE CONTACT WITH SPRING RETURN	<u> </u>	С	CAPACITOR
	F	FUSE SWITCH DISCONNECTOR		F	ACTUATING DEVICE OF A THERMAL RELAY	١	S	SINGLE POLE N-POSITION SWITCH	*	\ \	DIODE
<u>\</u>	Q	CIRCUIT BREAKER	\	F	SELF-OPERATING THERMAL SWITCH CONTACT		S	LIMIT SWITCH BREAK CONTACT AND MAKE CONTACT		L	INDUCTOR
*	Q	CIRCUIT BREAKER WITH AUTOMATIC RELEASE, THERMAL AND ELECTROMAGNETIC OPERATION	€\ € \	K	RELAY COIL OF A SLOW—OPERATING RELAY	\otimes	н	SIGNAL LAMP		Т	TRANSFORMER
\ [‡]	0					ξ⇔	Н	SIGNAL LAMP FLASHING TYPE	¢	X	TERMINAL STRIP
[]>			>\1 >	K	RELAY COIL OF A SLOW—RELEASING RELAY		Н	INDICATOR ELECTROMECH.	ф	X	TERMINAL STRIP ON PLC
Q Id	δ	CIRCUIT BREAKER WITH AUTOMATIC RELEASE, OPERATING BY DIFFERENTIAL CURRENT				<u>-</u> Z	Н	HORN	\$	X	TERMINAL STRIP ON LOCAL PANELS
			1 E 2 H	S	1— OPERATED BY HANDLE 2— OPERATED BY PUSHING		Y	SOLENOID VALVE	φ	X	TERMINAL STRIP ON OTHER BOARD
					process is digitally managed, details do n è gestito via software e le firme non sono						Mod
SSUE FOR ORDER S. DAL MOLIN 21.06.2012 SSUE FOR BID S. DAL MOLIN 28.05.2012			SAB	IZ F	PLANT	desmet ballestra		SIMBOL LIST Dis. Job: 2F11			= KC-64.4B +