

desmet ballestra

ITEM 77WG2

N°REQUIRED 1

CUSTOMER

DOUBLE FLAP DISCHARGER WITH PNEUMATIC CONTROL

PLANT SLS drying unit | JOB 1E35

DWG. 1E35 . 35 . 095-1

FLOW SHEET 1E35 . 10 . 011

SHEET 1 OF 1

Rev.	Date	Drawn	Description
0	11.11.09	G.R.	ISSUED FOR CONSTRUCTION
1	01.02.10	G.R.	TYPE PNEUMATIC CYLINDER MODIFIED

The master version of this document is stored as a digital file in a database – Approval process is digitally managed and no signature is visible on the document.

NOZZLES

POS.	SIZE	RATING	N°	SERVICE	THK.	NOZZLES ORIENT.
S1	200	UNI 6082	1	PRODUCT INLET	–	
S2	200	UNI 6082	1	PRODUCT OUTLET	–	

DESIGN DATA		SHELL	JACKET	COIL
OPERATING PRESSURE	Bar (g)	0		
DESIGN PRESSURE	Bar (g)	0		
HYDROSTATIC TEST PRESSURE	Bar (g)	–		
PNEUMATIC TEST PRESSURE	Bar (g)	–		
OPERATING TEMPERATURE	°C	30		
DESIGN TEMPERATURE	°C	50		
FLUID/SPECIFIC WEIGHT #	Kg/dm3	–		
HEAT EXCHANGE SURFACE	m2	–		
HEAT TREATMENT		–		
X-RAY TEST		–		
PENETRATING LIQUIDS TEST		–		
JOINT EFFICIENCY		–		
CORROSION ALLOWANCE	mm	–		
GEOMETRIC CAPACITY	litri	~20		
INSPECTION INSTITUTE		DESMET BALLESTRA S.p.A.		
CODE		STD. BALLESTRA		

WEIGHTS

EMPTY 50 ~ Kg

STD. DETAILS	ENCLOSED DWG.
WORKING DWG	ST. 40683/4

SPARE PARTS LIST

① PNEUMATIC CYLINDER STROKE 90mm-BELLOWS (PARKER)
CODE : P1D-T040MS-0090NG075

② BEARING SKF 6004 2RS Øi 20 x 42 x 12

③ GASKET MATERIAL FOAM RUBBER 300 x 140 Thk. 4

MATERIALS

SHELL	ALLUMINIUM

INSULATION : NO

NOTE :

Rif. 2D14-35-103