


We reserve the ownership under the law of this drawing with prohibition of even partial reproduction and to make it known to third persons without our written authorization.



<div></div> <div>desmet ballestra</div>				ITEM 33AB1A		CUSTOMER				DWG. 1E35 . 35 . 073-1					
						PULSATION DAMPNER				FLOW SHEET 1E35 . 10 . 010					
N'REQUIRED 1				PLANT SULPHUREX		JOB 1E35		SHEET 1 OF 1							
Rev.	Date	Drawn	Description												
0	12.11.09	G.R.	ISSUED FOR BID												
1	21.01.10	G.R.	ORIENTATION DEFINED												
The master version of this document is stored as a digital file in a database. Approval process is digitally managed and no signature is visible on the document.															
NOZZLES							DESIGN DATA				SHELL	JACKET	COIL		
POS.	SIZE	RATING	N°	SERVICE	THK.	NOZZLES ORIENT.	OPERATING PRESSURE Bar (g)				3				
S1	3/4"	ASME B1.20.1 NPT 3000#	1	POLMONATION	3,91	Ø	DESIGN PRESSURE Bar (g)				6				
							HYDROSTATIC TEST PRESSURE Bar (g)				7.8				
							PNEUMATIC TEST PRESSURE Bar (g)				—				
							OPERATING TEMPERATURE °C				50				
							DESIGN TEMPERATURE °C				80				
							FLUID/SPECIFIC WEIGHT 1,2 Kg/dm3				NaOH or NH3 solution				
							HEAT EXCHANGE SURFACE m2				—				
							HEAT TREATMENT				—				
							X-RAY TEST				—				
							PENETRATING LIQUIDS TEST				—				
							JOINT EFFICIENCY				0,7				
							CORROSION ALLOWANCE mm				—				
							GEOMETRIC CAPACITY litri				~25				
							INSPECTION INSTITUTE				DESMET BALLESTRA S.p.A.				
							CODE				ASME VIII DIV.1				
							WEIGHTS								
							EMPTY ~37 Kg				OPERATING ~74 Kg				
											WATER FILLED ~62 Kg				
							STD. DETAILS						ENCLOSED DWG.		
							GENERAL NOTES						SB-PRS-SP001/0		
							PAINTING						SB-ATI-SP002/4		
NAME PLATE POSITION						AS DWG	WELDING BEVEL						SP. 1344/0		
MATERIALS OR EQUIVALENT							NAME PLATE						SB-PRS-00120/0		
SHELL				A 312 Tp304		NAME PLATE SUPPORT						ST. 0377/1			
CAPS				A 403 Wp304											
NOZZLES				A 312 Tp304											
						INSULATION: NO									
NOTE :															
RIF. 1D54.35.030															