CLIENTE Customas LOCALITA Localita DWG 1412-65-008 (1E35-65-008) 1A12/1E35 5<u>x</u> Of MILANO (ITALIA) **JOINTS** TEXTILE **EXPANSION** MULTI * DIMENSION TO BE ESTABLISHED BY VENDOR N' 4 LIMIT SWITCH STUD BOLTS RESISTING TO CONDITIONS SHOWN ON TABLE reserve the omershy under the lay of this drawing with prohibition of lenow to theird persons without our entites authorization. **EXTERNAL** FLANGE REINFORCEMENT NTERNAL (SAME MATERIAL OF FLANGE INTERNAL FLANGE) JOINT LATERAL DEFLECTION MAX 1/5 se PIPE JOINT AXIAL MOVEMENT 3 ±

to nebce

400

reproduction

even partial

renderto

con divisto di riprodurio

cheagh

riserviano la proprieta a ternim di legge di questo

terzi senza nostra autorizzazione scribta.

I .													
			PIPE		[PIPE	WORKING CONDITIONS			ONS	MATERIALS		
ITE	M PIECES	WATERIAL CERTIFIED	S17F	A mm	FLUID	LINE REFER.	TEMP.	PRESS.	AXIAL	LATERAL mm	FLG. WELDED ON THE PIPE	LIMIT SWITCH STUD BOLTS	
127	11 1	†	323,B	15	ÁZ	12009		0,09	+45	12	Fe36	A36	
1242			914.40			12035	400	0.09	~63	7	Fe 510 D	1572Gr.42	
124		 	355.6			12030		0.09	-18	7	Fe36	Δ36	
124		1	355,6	40	АН	12037	100	0.09	-32	3	Fe36	Δ36	
120%			355,6	24	AH	12014	180	0,09	-20	7	Fe36	Δ36	
124			355,6	14	AH	12012	330		-10	16	Fe 510 D	A572 Gr. 42	
124		İ	609,6	24	AH	12026	700	0.09	+55	43	Alsi304	11	
127	16 1	1	355.6	16	AH					13/3	A151304) bt	
124			914,40	90	AH	12035	400	0,09	-80	100	Fe510D	id	
											ļ	<u> </u>	
					<u> </u>								
		1	1	1	1			ı	1	1	1	I	

I TIRANTI DI FINE CORSA SARANNO EVIDENZIATI DAL COSTRUTTORE E

NON DOVRANNO ESSERE SMONTATI IN OPERA.
Limit awitch stud bolts must by indicated by the manufacturer and must not by disassembled on site.

					1	
-					1	
1	1550	ED FOR JOB 1E35	ALE			23.02.10
0	1551	ED FOR CONTRUCTION	FG			2.03,98
REV.		DESCRIZIONE - DESCRIPTION	CZIMP. PRICP.D	CONTRA	APPR.	BATA BATE