The state of the s		Created with	
Company Name	IIT Bombay	Project Title	Connection Design Examples
Group/Team Name	Osdag	Subtitle	Cleat Angle Shear Connection
Designer	Engineer #1	Job Number	1.1.3.3.1
Date	20 /06 /2018	Client	Manas M. Ghosh, INSDAG, Kolkata

Design Conclusion	
Cleat Angle	Pass
Cleat Angle	
Connection Properties	
Connection	
Connection Title	Double Angle Web Cleat
Connection Type	Shear Connection
Connection Category	·
Connectivity	Beam-Beam
Beam Connection	Bolted
Column Connection	Bolted
Loading (Factored Load)	
Shear Force (kN)	145
Components	·
Column Section	WB 450
Material	Fe 410
Beam Section	MB 400
Material	Fe 410
Hole	STD
Cleat Section	100 100 x 10
Thickness (mm)	10
Cleat Leg Size B (mm)	100
Cleat Leg Size A (mm)	100
Hole	STD
Bolts on Beam	
Туре	Bearing Bolt
Grade	4.6
Diameter (mm)	24
Bolt Numbers	3
Columns (Vertical Lines)	1
Bolts Per Column	3
Gauge (mm)	0
Pitch (mm)	60
End Distance (mm)	44

Edge Distance (mm)	60	
Bolts on Column		
Туре	Bearing Bolt	
Grade	4.6	
Diameter (mm)	24	
Bolt Numbers	6	
Columns (Vertical Lines)	1	
Bolts Per Column	3	
Gauge (mm)	0	
Pitch (mm)	60	
End Distance (mm)	44	
Edge Distance (mm)	60.0	
Assembly		
Column-Beam Clearance (mm)	10.0	

The Control of the Co		Created with OSdag	
Company Name	IIT Bombay	Project Title	Connection Design Examples
Group/Team Name	Osdag	Subtitle	Cleat Angle Shear Connection
Designer	Engineer #1	Job Number	1.1.3.3.1
Date	20 /06 /2018	Client	Manas M. Ghosh, INSDAG, Kolkata

Design Preferences	
Bolt	
Hole Type	Standard
Material Grade (MPa) (overwrite)	800.0
Slip factor	N/A
Detailing	
Type of Edges	Sheared or hand flame cut
Minimum Edge-End Distance	1.7 times the hole diamter
Gap between beam & support (mm)	10.0
Are members exposed to corrosive influences?	No
Design	
Design Method	Limit State Design

The control of the co		Created with OSdag	
Company Name	IIT Bombay	Project Title	Connection Design Examples
Group/Team Name	Osdag	Subtitle	Cleat Angle Shear Connection
Designer	Engineer #1	Job Number	1.1.3.3.1
Date	20 /06 /2018	Client	Manas M. Ghosh, INSDAG, Kolkata

Design Check: S	Secondary Beam Connectivity		
Check	Required	Provided	Remark
Bolt shear capacity (kN)		V_{dsb} = ((2*400*0.6126*24*24)/($\sqrt{3}$ *1.25*1000)) = 130.435 [cl. 10.3.3]	
Bolt bearing capacity (kN)		V_{dpb} = (2.5*0.519*24*8.9*400)/(1.25*1000) = 88.687 [cl. 10.3.4]	
Bearing capacity of beam web (kN)		V_{dpb} = (2.5*0.519*24*8.9*410)/(1.25*1000) = 90.904 [cl. 10.3.4]	
Bearing capacity of cleat (kN)		V_{dpb} = (2.5*0.519*24*10*410)/(1.25*1000) = 102.139 [cl. 10.3.4]	
Bearing capacity (kN)		Min (88.687, 90.904, 102.139) = 88.687	
Bolt capacity (kN)		Min (130.435, 88.687) = 88.687	
Critical bolt shear (kN)	≤ 88.687	41.578	Pass
No. of bolts		3	
No.of column(s)	≤ 2	1	
No. of bolts per column		3	
Bolt pitch (mm)	\geq 2.5* 24 = 60, \leq Min(32*8.9, 300) = 285 [cl. 10.2.2]	60	Pass
Bolt gauge (mm)	\geq 2.5*24 = 60, \leq Min(32*8.9, 300) = 285 [cl. 10.2.2]	0	
End distance (mm)	≥ 1.7*26.0 = 44, ≤ 12*8.9 = 106.8 [cl. 10.2.4]	44	Pass
Edge distance	≥ 1.7*26.0 = 44, ≤ 12*8.9 = 106.8	60	Pass


(mm)	[cl. 10.2.4]		
Block shear capacity (kN)	≥ 145	V _{db} = 149.247 [cl. 6.4.1]	Pass
Cleat height (mm)	≥ 0.6*400.0=240.0, ≤ 400.0- 16.0-14.0-15.4-15.0- 5=334.6 [cl. 10.2.4, Insdag Detailing Manual, 2002]	240.0	Pass
Cleat moment capacity (kNm)	(2*130.435*60 ²)/(60*1000) = 4.06	$M_{\rm d}$ = (1.2*250* Z)/(1000*1.1) = 172.8 [cl. 8.2.1.2]	Pass

The Control of the Co		Created with OSdag	
Company Name	IIT Bombay	Project Title	Connection Design Examples
Group/Team Name	Osdag	Subtitle	Cleat Angle Shear Connection
Designer	Engineer #1	Job Number	1.1.3.3.1
Date	20 /06 /2018	Client	Manas M. Ghosh, INSDAG, Kolkata

Design Check: Pr	imary Beam Connectivity		
Check	Required	Provided	Remark
Bolt shear capacity (kN)		V_{dsb} = ((400*0.6126*24*24)/($\sqrt{3}$ *1.25*1000)) = 65.218 [cl. 10.3.3]	
Bolt bearing capacity (kN)		V _{dpb} = (2.5*0.519*24*9.2*400)/(1.25*1000) = 91.676 [cl. 10.3.4]	
Bearing capacity of beam web (kN)		V _{dpb} = (2.5*0.519*24*9.2*410)/(1.25*1000) = 93.968 [cl. 10.3.4]	
Bearing capacity of cleat (kN)		V_{dpb} = (2.5*0.519*24*10*410)/(1.25*1000) = 102.139 [cl. 10.3.4]	
Bearing capacity (kN)		Min (91.676, 93.968, 91.676) = 91.676	
Bolt capacity (kN)		Min (65.218, 91.676) = 65.218	
Critical bolt shear (kN)	≤ 65.218	43.794	Pass
No. of bolts		6	
No.of column(s) per angle	≤ 2	1	
No. of bolts per column per angle		3	
Bolt pitch (mm)	\geq 2.5* 24 = 60, \leq Min(32*9.2, 300) = 295 [cl. 10.2.2]	60	Pass
Bolt gauge (mm)	\geq 2.5*24 = 60, \leq Min(32*9.2, 300) = 295 [cl. 10.2.2]	0	
End distance (mm)	≥ 1.7*26.0 = 44, ≤ 12*9.2 = 110.4 [cl. 10.2.4]	44	Pass
	≥ 1.7*26.0 = 44, ≤12*9.2 =		

Edge distance (mm)	110.4 [cl. 10.2.4]	60.0	Pass
Block shear capacity (kN)	≥145	V _{db} = 149.247 [cl. 6.4.1]	Pass
Cleat height (mm)	≥ 0.6*400.0=240.0, ≤ 400.0- 16.0-14.0-15.4-15.0- 5=334.6 [cl. 10.2.4, Insdag Detailing Manual, 2002]	240.0	Pass
Cleat moment capacity (kNm)	(2*65.218*60 ²)/(60*1000) = 4.383	$M_{\rm d}$ = (1.2*250* Z)/(1000*1.1) = 172.8 [cl. 8.2.1.2]	Pass

The state of the s		Cre	eated with Sdag
Company Name	IIT Bombay	Project Title	Connection Design Examples
Group/Team Name	Osdag	Subtitle	Cleat Angle Shear Connection
Designer	Engineer #1	Job Number	1.1.3.3.1
Date	20 /06 /2018	Client	Manas M. Ghosh, INSDAG, Kolkata



The state of the s		Created with OSdag	
Company Name	IIT Bombay	Project Title	Connection Design Examples
Group/Team Name	Osdag	Subtitle	Cleat Angle Shear Connection
Designer	Engineer #1	Job Number	1.1.3.3.1
Date	20 /06 /2018	Client	Manas M. Ghosh, INSDAG, Kolkata

Additional Comments	