

```
=====
macOS HARDENING SCRIPTS - combined source bundle
Generated: 2026-05-15 20:58:59 CDT
Host: evws-MacBook-Pro.local
```

```
Files included:
  harden.sh (23018 bytes)
  lock-remote-access.sh (12990 bytes)
  run-with-ls-silent.sh (2838 bytes)
=====
```

```
=====
FILE: harden.sh
SHA-256: 21dea44f4483ed9ff7d7e8d10b03c6c394d75c1acbbdf233633bb380b4bf8254
=====
```

```
le
re
t
s
)
ooth)
p
1  #!/usr/bin/env bash
2  # harden.sh - macOS hardening for high-threat-model use
3  #
4  # Threat model: persistent, well-resourced adversary.
5  # Honest caveat: a script cannot defend you against a true APT. The sing
6  # biggest win on macOS for this threat model is Apple's Lockdown Mode
7  # (System Settings → Privacy & Security → Lockdown Mode). Toggle it befo
8  # trusting anything below. Tor Browser (cask installed here) is the righ
9  # tool for anonymous browsing - the tor daemon installed below only give
10 # you a SOCKS proxy, NOT anonymity for arbitrary apps.
11 #
12 # What this script does:
13 #   • Pre-flight audit (FileVault, SIP, Gatekeeper, open ports, XProtect
14 #   • Disables every Sharing service (SSH, ARD, SMB, AFP, printer, Bluet
15 #   • Enables Application Firewall + stealth + logging
16 #   • Strips telemetry / diagnostic submission / personalized ads
17 #   • Spotlight & Safari privacy defaults
18 #   • Login window: no guest, no autologin, hide last user, lock on slee
19 #   • Forces all auto-update channels ON
20 #   • Switches DNS to Quad9 (DNSSEC-validating) on every active service
21 #   • Installs: lynis, nmap, gpg, ykman, clamav, tor, dnscrypt-proxy
22 #   • Installs (cask): tor-browser, signal, santa, little-snitch
23 #   • Installs Wazuh agent (OSSEC's actively-maintained successor)
24 #   • Starts tor daemon (SOCKS on 127.0.0.1:9050) - see caveat above
25 #   • Updates ClamAV signatures (freshclam)
26 #   • Runs Lynis audit at the end and saves a report
27 #
28 # What this script will NOT do (you must do manually):
29 #   • Enable Lockdown Mode (GUI only)
30 #   • Turn on FileVault (GUI / recovery-key flow)
31 #   • Approve Santa system extension (GUI)
32 #   • Configure YubiKey enrollment per account
33 #
34 # Run:  chmod +x harden.sh && ./harden.sh
35 # Log:  ~/security-hardening-YYYYMMDD-HHMMSS.log
36
37 set -uo pipefail
38
```

```

39 # -----
40 # Setup
41 # -----
42 LOG="$HOME/security-hardening-$(date +%Y%m%d-%H%M%S).log"
43 touch "$LOG"; chmod 600 "$LOG"
44 exec > >(tee -a "$LOG") 2>&1
45
46 RED=$'\033[0;31m'; GRN=$'\033[0;32m'; YLW=$'\033[0;33m'; BLU=$'\033[0;34
m'; NC=$'\033[0m'
47 log() { printf "%s[*]%s %s\n" "$BLU" "$NC" "$*"; }
48 ok() { printf "%s[+]%s %s\n" "$GRN" "$NC" "$*"; }
49 warn() { printf "%s[!]%s %s\n" "$YLW" "$NC" "$*"; }
50 err() { printf "%s[x]%s %s\n" "$RED" "$NC" "$*"; }
51 section() { printf "\n%s== %s ==%s\n" "$BLU" "$*" "$NC"; }
52 try() { "$@" || warn "command failed (continuing): $*"; }
53
54 # Guardrails
55 [[ "$(uname)" == "Darwin" ]] || { err "macOS only"; exit 1; }
56 [[ "$EUID" -ne 0 ]] || { err "Do NOT run as root - script will sudo wher
e needed"; exit 1; }
57
58 # Brief abort window
59 cat <<EOF
60
61 ${YLW}This will make significant system changes (sharing off, firewall o
n,
62 defaults rewritten, DNS changed, brew packages installed, Wazuh agent
63 installed). Press Ctrl-C within 10 seconds to abort.${NC}
64
65 Log: $LOG
66 EOF
67 sleep 10
68
69 # Prime sudo + keepalive
70 log "Priming sudo (you'll be prompted once)..."
71 sudo -v || { err "sudo required"; exit 1; }
72 ( while true; do sudo -n true; sleep 50; kill -0 "$$" 2>/dev/null || exi
t; done ) 2>/dev/null &
73 SUDO_KEEPALIVE=$!
74 trap 'kill $SUDO_KEEPALIVE 2>/dev/null || true' EXIT
75
76 # -----
77 # 1. Pre-flight audit
78 # -----
79 section "1. Pre-flight audit"
80 log "macOS version:"; sw_vers
81 log "Hardware:"; system_profiler SPHardwareDataType | grep -E "
(Model|Chip|Processor|Serial)" | sed 's/^/ /'
82 log "FileVault:"; try fdesetup status
83 log "SIP:"; try csrutil status
84 log "Gatekeeper:"; try spctl --status
85 log "Secure Boot (if Intel T2):"
86 try /usr/libexec/remotectl dumpstate 2>/dev/null | grep -i 'secure boo
t' || true
87 log "Open listening TCP ports (before):"
88 sudo lsof -nP -iTCP -sTCP:LISTEN 2>/dev/null | tee "$HOME/open-ports-bef
ore.txt" || true
89 log "Open UDP sockets (before):"

```

```

e 90 sudo lsof -nP -iUDP 2>/dev/null | tee "$HOME/open-udp-before.txt" || tru
91
92 # -----
93 # 2. Homebrew
94 # -----
95 section "2. Homebrew"
96 if ! command -v brew >/dev/null 2>&1; then
97     log "Installing Homebrew..."
98     /bin/bash -c "$(curl -fsSL https://raw.githubusercontent.com/Homebrew
w/install/HEAD/install.sh)"
99     if [[ -x /opt/homebrew/bin/brew ]]; then eval "$(/opt/homebrew/bin/b
rew shellenv)"
100     elif [[ -x /usr/local/bin/brew ]]; then eval "$(/usr/local/bin/brew
shellenv)"; fi
101 fi
102 try brew update
103
104 # -----
105 # 3. Disable ALL remote-access / sharing services (comprehensive)
106 # -----
107 section "3. Disable remote access & sharing services"
108
109 # SSH Remote Login (-f skips the y/n prompt that otherwise hangs piped r
uns)
110 try sudo systemsetup -f -setremotelogin off
111
112 # Apple Remote Desktop (ARD)
113 try sudo /System/Library/CoreServices/RemoteManagement/ARDAgent.app/Cont
ents/Resources/kickstart \
114     -deactivate -stop -uninstall
115
116 # Disable every known remote-access / sharing launchd unit.
117 # Some won't exist on this machine - launchctl disable still records the
flag.
118 SYSTEM_LABELS=(
119     com.openssh.sshd
120     com.apple.screensharing
121     com.apple.screensharing.agent
122     com.apple.screensharing.MessagesAgent
123     com.apple.screensharing.menuextra
124     com.apple.RemoteDesktop.agent
125     com.apple.smbd
126     com.apple.AppleFileServer
127     com.apple.netbiosd
128     com.apple.AEServer
129     com.apple.studentd
130     com.apple.classroomd
131     com.apple.teacherd
132     com.apple.amp.mediasharingd
133     com.apple.AssetCache.builtin
134     com.apple.AssetCacheLocatorService
135     com.apple.AssetCacheManagerService
136     com.apple.AssetCacheTetheratorService
137     com.apple.InternetSharing
138 )
139 for L in "${SYSTEM_LABELS[@]}"; do
140     try sudo launchctl disable "system/$L"

```

```

141 sudo launchctl print "system/$L" >/dev/null 2>&1 && try sudo launchc
tl bootout "system/$L"
142 done
143
144 # Printer Sharing
145 try cupsctl --no-share-printers
146 try cupsctl --no-remote-admin
147 try cupsctl --no-remote-any
148
149 # Internet Sharing
150 try sudo defaults write /Library/Preferences/SystemConfiguration/com.app
le.nat NAT-dict Enabled -int 0
151
152 # Bluetooth Sharing (OBEX)
153 try defaults -currentHost write com.apple.Bluetooth PrefKeyServicesEnabl
ed -bool false
154 try defaults write com.apple.bluetooth PrefKeyFTPServerEnabled -bool fa
lse
155 try defaults write com.apple.bluetooth PrefKeyOBEXServerEnabled -bool fa
lse
156
157 # AirDrop / Handoff / Universal Clipboard / Continuity (sharingd is a us
er LaunchAgent)
158 USER_UID=$(id -u)
159 try launchctl disable "gui/$USER_UID/com.apple.sharingd"
160 try defaults write com.apple.NetworkBrowser DisableAirDrop -bool true
161 try defaults -currentHost write com.apple.coreservices.useractivityd Act
ivityAdvertisingAllowed -bool false
162 try defaults -currentHost write com.apple.coreservices.useractivityd Act
ivityReceivingAllowed -bool false
163
164 # Quick post-disable audit
165 log "Remote Login (should be Off):"; try sudo systemsetup -getremotelogi
n
166 log "ARD status:"; try sudo /System/Library/CoreServi
ces/RemoteManagement/ARDAgent.app/Contents/Resources/kickstart -status
167 ok "Remote access & sharing services disabled (covers SSH, ARD, Screen S
haring, SMB, AFP,"
168 ok "NetBIOS, Apple Events, Classroom (studentd/classroomd/teacherd), Med
ia Sharing,"
169 ok "Content Caching/AssetCache, Internet Sharing, Printer Sharing, Bluet
ooth Sharing,"
170 ok "AirDrop/Handoff/Universal Clipboard)"
171
172 # _____
173
173 # 4. Application firewall + stealth
174 # _____
175
175 section "4. Application firewall (alf)"
176 SFW=/usr/libexec/ApplicationFirewall/socketfilterfw
177 try sudo "$SFW" --setglobalstate on
178 try sudo "$SFW" --setstealthmode on
179 try sudo "$SFW" --setallowsigning off
180 try sudo "$SFW" --setallowsigningapp off
181 try sudo "$SFW" --setloggingmode on
182 try sudo "$SFW" --setloggingopt detail
183 ok "alf on, stealth on, signed-pass-through off, logging on"
184
185 # _____
186
186 # 5. Privacy / telemetry

```

```

187 # -----
188 section "5. Telemetry, diagnostics, ads"
189 DM="/Library/Application Support/CrashReporter/DiagnosticMessagesHistory
.plist"
190 try sudo defaults write "$DM" AutoSubmit -bool false
191 try sudo defaults write "$DM" AutoSubmitVersion -int 4
192 try sudo defaults write "$DM" ThirdPartyDataSubmit -bool false
193 try sudo defaults write "$DM" ThirdPartyDataSubmitVersion -int 4
194 try defaults write com.apple.CrashReporter DialogType none
195 try defaults write com.apple.assistant.support "Siri Data Sharing Opt-In
Status" -int 2
196 try defaults write com.apple.AdLib forceLimitAdTracking -bool t
rue
197 try defaults write com.apple.AdLib allowApplePersonalizedAdvertising -bo
ol false
198 try defaults write com.apple.AdLib allowIdentifierForAdvertising -bool f
alse
199 # Safari
200 try defaults write com.apple.Safari UniversalSearchEnabled -bool f
alse
201 try defaults write com.apple.Safari SuppressSearchSuggestions -bool t
rue
202 try defaults write com.apple.Safari SendDoNotTrackHTTPHeader -bool t
rue
203 try defaults write com.apple.Safari WebKitStorageBlockingPolicy -int 2
204 try defaults write com.apple.Safari WebKitPreferences.storageBlockingPol
icy -int 2
205 try defaults write com.apple.Safari AutoOpenSafeDownloads -bool f
alse
206 try defaults write com.apple.Safari WarnAboutFraudulentWebsites -bool t
rue
207 # Quarantine on for downloads
208 try defaults write com.apple.LaunchServices LSQuarantine -bool true
209 ok "Telemetry / ads / Safari hardened"
210
211 # -----
212 # 6. Login window + screen lock
213 # -----
214 section "6. Login window & screen lock"
215 try sudo defaults write /Library/Preferences/com.apple.loginwindow Guest
Enabled -bool NO
216 try sudo defaults write /Library/Preferences/com.apple.loginwindow SHOWF
ULLNAME -bool YES
217 try sudo defaults delete /Library/Preferences/com.apple.loginwindow auto
LoginUser 2>/dev/null
218 try sudo rm -f /etc/kcpassword
219 try defaults write com.apple.screensaver askForPassword -int 1
220 try defaults write com.apple.screensaver askForPasswordDelay -int 0
221 # Login window banner
222 try sudo defaults write /Library/Preferences/com.apple.loginwindow Login
windowText \
223 "Unauthorized access prohibited. All activity is logged."
224 ok "Login window hardened"
225
226 # -----
227 # 7. Software updates: everything ON
228 # -----

```

```

229 section "7. Auto-updates"
230 try sudo softwareupdate --schedule on
231 SU=/Library/Preferences/com.apple.SoftwareUpdate
232 try sudo defaults write $SU AutomaticCheckEnabled -bool true
233 try sudo defaults write $SU AutomaticDownload -int 1
234 try sudo defaults write $SU AutomaticallyInstallMacOSUpdates -bool true
235 try sudo defaults write $SU CriticalUpdateInstall -int 1
236 try sudo defaults write $SU ConfigDataInstall -int 1
237 try sudo defaults write /Library/Preferences/com.apple.commerce AutoUpda
te -bool true
238 ok "Auto-update fully enabled (incl. critical/XProtect data)"
239
240 # -----

241 # 8. DNS - Quad9 (DNSSEC, malware blocking)
242 # -----

243 section "8. DNS → Quad9"
244 while IFS= read -r svc; do
245     [[ -n "$svc" && "$svc" != \** ]] || continue
246     log " $svc"
247     try sudo networksetup -setdnsservers "$svc" 9.9.9.9 149.112.112.112
2620:fe::fe 2620:fe::9
248 done < <(networksetup -listallnetworkservices | tail -n +2)
249 try sudo dscacheutil -flushcache
250 try sudo killall -HUP mDNSResponder
251 ok "DNS hardened on all active services"
252
253 # -----

254 # 9. Security tooling (brew)
255 # -----

256 section "9. Install audit & defensive tooling"
257 try brew install lynis nmap gpg pinentry-mac ykman clamav tor dnscrypt-p
roxy stronghold
258 try brew install --cask tor-browser signal santa little-snitch
259 ok "Tools installed (where available)"
260
261 # -----

262 # 10. OSSEC (Wazuh agent - OSSEC's actively-maintained fork)
263 # -----

264 section "10. OSSEC / Wazuh agent"
265 # OSSEC proper no longer has a maintained macOS brew formula. Wazuh is t
he
266 # actively-developed fork and is what you actually want for a HIDS today
.
267 ARCH=$(uname -m)
268 case "$ARCH" in
269     arm64) WAZ_ARCH="arm64" ;;
270     x86_64) WAZ_ARCH="intel64" ;;
271     *) WAZ_ARCH="" ;;
272 esac
273 if [[ -n "$WAZ_ARCH" ]]; then
274     WAZ_PKG="/tmp/wazuh-agent.pkg"
275     # latest 4.x release page is stable; this URL pattern is what Wazuh
docs use
276     if curl -fsSL "https://packages.wazuh.com/4.x/macos/" -o /tmp/wazuh-
index.html 2>/dev/null; then
277         WAZ_FILE=$(grep -oE "wazuh-agent-[0-9.]+-[0-9]+\.${WAZ_ARCH}\.pk

```

```

g" /tmp/wazuh-index.html | sort -V | tail -1)
278         if [[ -n "$WAZ_FILE" ]]; then
279             log "Downloading $WAZ_FILE"
280             if curl -fsSL "https://packages.wazuh.com/4.x/macos/$WAZ_FIL
E" -o "$WAZ_PKG"; then
281                 try sudo installer -pkg "$WAZ_PKG" -target /
282                 ok "Wazuh agent installed. Configure manager IP in /Libr
ary/Ossec/etc/ossec.conf"
283             else
284                 warn "Wazuh agent download failed - install manually fro
m packages.wazuh.com"
285             fi
286         else
287             warn "Could not parse Wazuh release index - install manually
from packages.wazuh.com"
288         fi
289     else
290         warn "Could not reach packages.wazuh.com - install Wazuh agent m
anually"
291     fi
292 else
293     warn "Unknown CPU arch $ARCH; skipping Wazuh"
294 fi
295
296 # -----
297 # 11. Tor daemon (SOCKS proxy on 127.0.0.1:9050) - NOT anonymity for app
s
298 # -----
299 section "11. Tor daemon"
300 warn "Reminder: this daemon ≠ anonymity. Use Tor Browser for browsing."
301 try brew services start tor
302
303 # -----
304 # 12. ClamAV signatures
305 # -----
306 section "12. ClamAV signature update"
307 CLAMDIR="$(brew --prefix)/etc/clamav"
308 if [[ -d "$CLAMDIR" ]]; then
309     [[ -f "$CLAMDIR/freshclam.conf" ]] || cp "$CLAMDIR/freshclam.conf.sa
mple" "$CLAMDIR/freshclam.conf" 2>/dev/null || true
310     try sed -i '' 's/^Example/#Example/' "$CLAMDIR/freshclam.conf"
311     try freshclam
312 fi
313
314 # -----
315 # 13. GPG agent
316 # -----
317 section "13. GPG"
318 mkdir -p "$HOME/.gnupg" && chmod 700 "$HOME/.gnupg"
319 if [[ ! -f "$HOME/.gnupg/gpg-agent.conf" ]]; then
320     printf "default-cache-ttl 600\nmax-cache-ttl 7200\npinentry-program
%s/bin/pinentry-mac\n" \
321         "$(brew --prefix 2>/dev/null || echo /opt/homebrew)" > "$HOME/.g
nupg/gpg-agent.conf"
322 fi
323 ok "GPG agent configured"

```

```

324
325 # -----
326 # 14. Lynis audit (baseline report)
327 # -----
328 section "14. Lynis audit"
329 LYNIS_REPORT="$HOME/lynis-report-$(date +%Y%m%d-%H%M%S).txt"
330 try sudo lynis audit system --quick --no-colors --logfile /tmp/lynis.log
--report-file /tmp/lynis-report.dat > "$LYNIS_REPORT" 2>&1
331 ok "Lynis report: $LYNIS_REPORT"
332
333 # -----
334 # 15. Post-flight comparison
335 # -----
336 section "15. Post-flight"
337 log "Open listening TCP ports (after):"
338 sudo lsof -nP -iTCP -sTCP:LISTEN 2>/dev/null | tee "$HOME/open-ports-aft
er.txt" || true
339 diff "$HOME/open-ports-before.txt" "$HOME/open-ports-after.txt" || true
340
341 # -----
342 # 16. Summary + required manual steps
343 # -----
344 section "Summary"
345 ok "Automated hardening complete. Log: $LOG"
346 warn ""
347 warn "REQUIRED MANUAL STEPS (script cannot do these):"
348 warn "  1. System Settings → Privacy & Security → Lockdown Mode → ON"
349 warn "      (single biggest win for your threat model)"
350 warn "  2. System Settings → Privacy & Security → FileVault → confirm ON
"
351 warn "  3. System Settings → Privacy & Security → approve Santa system e
xtension"
352 warn "  4. Enroll YubiKey on every account that matters (Apple ID, email
, GitHub, banks)"
353 warn "  5. Open Tor Browser at least once to seed bridges if needed"
354 warn "  6. Configure Wazuh manager IP in /Library/OSsec/etc/ossec.conf (
or remove if unused)"
355 warn "  7. Configure Little Snitch rules on first launch (default-deny o
utbound)"
356 warn ""
357 warn "OPERATIONAL ADVICE for nation-state threat models:"
358 warn "  • A hardened laptop is not enough. Compartmentalize: separate de
vice for sensitive work."
359 warn "  • Contact EFF, Access Now Digital Security Helpline, or Citizen
Lab for tailored advice."
360 warn "  • Patches > HIDS against APTs. The auto-update settings above ar
e the most useful change here."
361 warn "  • Review the Lynis report and act on its Suggestions section."

```

```

=====
FILE: lock-remote-access.sh

```

```

SHA-256: d9f0f31c60516844e298a0f3a91c899154e2dfd0cfd026700328bbfac42d2fc0
=====

```

```

1 #!/usr/bin/env bash

```



```

2 # lock-remote-access.sh
3 # Audits and disables every macOS remote-access / sharing technology I k
now of.
4 # Safe to run repeatedly (idempotent). Each step uses `try` so a missing
5 # service / SIP-protected unit won't halt the script.
6 #
7 # Covers:
8 #   • SSH Remote Login (com.openssh.sshd / systemsetup)
9 #   • Apple Remote Desktop (ARD) (kickstart -deactivate)
10 #   • Screen Sharing (VNC) (com.apple.screensharing + help
rs)
11 #   • SMB File Sharing (com.apple.smbd)
12 #   • AFP File Sharing (com.apple.AppleFileServer)
13 #   • NetBIOS (legacy SMB advertising) (com.apple.netbiosd)
14 #   • Printer Sharing (cups)
15 #   • Internet Sharing (NAT defaults)
16 #   • Remote Apple Events (com.apple.AEServer)
17 #   • Apple Classroom (managed-edu) (com.apple.studentd / classroomd
/ teacherd)
18 #   • Content Caching (com.apple.AssetCache.builtin &
locator)
19 #   • Media (iTunes/Music) Sharing (com.apple.amp.mediasharingd)
20 #   • Bluetooth Sharing (OBEX) (per-host pref)
21 #   • AirDrop (sharingd: best-effort kill, see
notes)
22 #
23 # Run: /Users/evw/dev/security/lock-remote-access.sh
24 # Log: ~/lock-remote-access-YYYYMMDD-HHMMSS.log
25
26 set -uo pipefail
27
28 LOG="$HOME/lock-remote-access-$(date +%Y%m%d-%H%M%S).log"
29 touch "$LOG"; chmod 600 "$LOG"
30 exec > >(tee -a "$LOG") 2>&1
31
32 RED=$'\033[0;31m'; GRN=$'\033[0;32m'; YLW=$'\033[0;33m'; BLU=$'\033[0;34
m'; NC=$'\033[0m'
33 log() { printf "%s[*]%s %s\n" "$BLU" "$NC" "$*"; }
34 ok() { printf "%s[+]%s %s\n" "$GRN" "$NC" "$*"; }
35 warn() { printf "%s[!]%s %s\n" "$YLW" "$NC" "$*"; }
36 err() { printf "%s[x]%s %s\n" "$RED" "$NC" "$*"; }
37 section() { printf "\n%s== %s ==%s\n" "$BLU" "$*" "$NC"; }
38 try() { "$@" || warn "command exited non-zero (continuing): $*"; }
39
40 [[ "$(uname)" == "Darwin" ]] || { err "macOS only"; exit 1; }
41 [[ "$EUID" -ne 0 ]] || { err "Do NOT run as root - script will sudo wher
e needed"; exit 1; }
42
43 log "Priming sudo (you'll be prompted once)..."
44 sudo -v || { err "sudo required"; exit 1; }
45 ( while true; do sudo -n true; sleep 50; kill -0 "$$" 2>/dev/null || exi
t; done ) 2>/dev/null &
46 SUDO_KEEPALIVE=$!
47 trap 'kill $SUDO_KEEPALIVE 2>/dev/null || true' EXIT
48
49 # Labels we want disabled in the system domain. Some won't exist on this
50 # machine - that's fine; launchctl disable still records the disabled fl
ag.
51 SYSTEM_LABELS=(
52     com.openssh.sshd
53     com.apple.screensharing
54     com.apple.screensharing.agent

```

```

55     com.apple.screensharing.MessagesAgent
56     com.apple.screensharing.menuextra
57     com.apple.RemoteDesktop.agent
58     com.apple.smbd
59     com.apple.AppleFileServer
60     com.apple.netbiosd
61     com.apple.AEServer
62     com.apple.studentd
63     com.apple.classroomd
64     com.apple.teacherd
65     com.apple.amp.mediasharingd
66     com.apple.AssetCache.builtin
67     com.apple.AssetCacheLocatorService
68     com.apple.AssetCacheManagerService
69     com.apple.AssetCacheTetheratorService
70 )
71
72 # These plists, if present, can be unloaded too (belt + suspenders).
73 SYSTEM_PLISTS=(
74     /System/Library/LaunchDaemons/com.apple.screensharing.plist
75     /System/Library/LaunchDaemons/com.apple.smbd.plist
76     /System/Library/LaunchDaemons/com.apple.AppleFileServer.plist
77     /System/Library/LaunchDaemons/com.apple.netbiosd.plist
78     /System/Library/LaunchDaemons/com.apple.AEServer.plist
79     /System/Library/LaunchDaemons/com.apple.studentd.plist
80     /System/Library/LaunchDaemons/com.apple.classroomd.plist
81     /System/Library/LaunchDaemons/com.apple.teacherd.plist
82     /System/Library/LaunchDaemons/com.apple.amp.mediasharingd.plist
83     /System/Library/LaunchDaemons/com.apple.AssetCache.builtin.plist
84     /System/Library/LaunchDaemons/com.apple.AssetCacheLocatorService.pli
st
85     /System/Library/LaunchDaemons/com.apple.AssetCacheManagerService.pli
st
86     /System/Library/LaunchDaemons/com.apple.AssetCacheTetheratorService.
plist
87 )
88
89 audit_label() {
90     local label="$1"
91     local enabled disabled loaded
92     # Disabled flag (true means we've disabled it)
93     if sudo launchctl print-disabled system 2>/dev/null | grep -q "\"$la
bel\" => disabled"; then
94         disabled="DISABLED"
95     elif sudo launchctl print-disabled system 2>/dev/null | grep -q "\"$
label\""; then
96         disabled="enabled"
97     else
98         disabled="unknown"
99     fi
100     # Currently loaded?
101     if sudo launchctl print "system/$label" >/dev/null 2>&1; then
102         loaded="loaded"
103     else
104         loaded="not-loaded"
105     fi
106     printf "    %-50s [%s, %s]\n" "$label" "$disabled" "$loaded"
107 }
108
109 # _____
110 section "AUDIT (before)"

```

```

111 # -----
112 log "SSH (Remote Login):"
113 try sudo systemsetup -getremotelogin
114
115 log "Apple Remote Desktop (ARD) status:"
116 try sudo /System/Library/CoreServices/RemoteManagement/ARDAgent.app/Contents/Resources/kickstart -status 2>/dev/null
117
118 log "Printer Sharing:"
119 try cupsctl | grep -i share
120
121 log "Internet Sharing (NAT) state:"
122 try sudo defaults read /Library/Preferences/SystemConfiguration/com.apple.nat NAT 2>/dev/null
123
124 log "LaunchD labels (before):"
125 for L in "${SYSTEM_LABELS[@]}"; do audit_label "$L"; done
126
127 # -----
128
128 section "DISABLE: SSH (Remote Login)"
129 # -----
130
130 try sudo systemsetup -f -setremotelogin off      # -f skips the y/n prompt
131
132 # -----
133
133 section "DISABLE: Apple Remote Desktop (ARD)"
134 # -----
135
135 try sudo /System/Library/CoreServices/RemoteManagement/ARDAgent.app/Contents/Resources/kickstart \
136     -deactivate -stop -uninstall
137
138 # -----
139
139 section "DISABLE: launchd units (screen sharing, file sharing, classroom , etc.)"
140 # -----
141
141 for L in "${SYSTEM_LABELS[@]}"; do
142     log "disable system/$L"
143     try sudo launchctl disable "system/$L"
144     # Try to bootout if currently loaded (modern equivalent of unload -w
145     sudo launchctl print "system/$L" >/dev/null 2>&1 && try sudo launchctl bootout "system/$L"
146 done
147
148 # Best-effort unload of known plists (will fail under SIP – that's OK, the
149 # launchctl disable above already prevents future starts)
150 for P in "${SYSTEM_PLISTS[@]}"; do
151     [[ -f "$P" ]] || continue
152     try sudo launchctl unload -w "$P"
153 done
154
155 # -----
156
156 section "DISABLE: Printer Sharing"

```

```

157 # -----
158 try cupsctl --no-share-printers
159 try cupsctl --no-remote-admin
160 try cupsctl --no-remote-any
161
162 # -----
163 section "DISABLE: Internet Sharing"
164 # -----
165 try sudo defaults write /Library/Preferences/SystemConfiguration/com.apple
le.nat NAT -dict Enabled -int 0
166 try sudo launchctl disable system/com.apple.InternetSharing 2>/dev/null
167
168 # -----
169 section "DISABLE: Bluetooth Sharing (OBEX)"
170 # -----
171 try defaults -currentHost write com.apple.Bluetooth PrefKeyServicesEnabl
ed -bool false
172 # Per-folder OBEX exchange defaults
173 try defaults write com.apple.bluetooth PrefKeyFTPServerEnabled -bool fal
se
174 try defaults write com.apple.bluetooth PrefKeyOBEXServerEnabled -bool fa
lse
175
176 # -----
177 section "DISABLE: AirDrop / sharingd-mediated proximity sharing"
178 # -----
179 # sharingd is core to AirDrop, Handoff, Continuity, Universal Clipboard,
etc.
180 # It runs as a LaunchAgent in the user's gui domain.
181 USER_UID=$(id -u)
182 try launchctl disable "gui/$USER_UID/com.apple.sharingd"
183 # AirDrop discoverability for the current user
184 try defaults write com.apple.NetworkBrowser DisableAirDrop -bool true
185 # Handoff / Continuity off
186 try defaults -currentHost write com.apple.coreservices.useractivityd Act
ivityAdvertisingAllowed -bool false
187 try defaults -currentHost write com.apple.coreservices.useractivityd Act
ivityReceivingAllowed -bool false
188
189 # -----
190 section "VERIFY (after)"
191 # -----
192 log "SSH (should be Off):"
193 try sudo systemsetup -getremotelogin
194
195 log "ARD status (should be 'is not running' / similar):"
196 try sudo /System/Library/CoreServices/RemoteManagement/ARDAgent.app/Cont
ents/Resources/kickstart -status 2>/dev/null
197
198 log "Printer Sharing (should show _share_printers=0):"
199 try cupsctl | grep -i share
200
201 log "Internet Sharing NAT (should be Enabled=0):"

```

```

202 try sudo defaults read /Library/Preferences/SystemConfiguration/com.apple
e.nat NAT 2>/dev/null
203
204 log "LaunchD labels (after):"
205 for L in "${SYSTEM_LABELS[@]}"; do audit_label "$L"; done
206
207 log "Open listening TCP ports (should be empty if you don't run servers)
:"
208 try sudo lsof -nP -iTCP -sTCP:LISTEN
209
210 ok "Remote-access lockdown complete. Log: $LOG"
211 warn ""
212 warn "NOTES:"
213 warn "    • sharingd disabling will weaken AirDrop, Handoff, Universal Cli
pboard, AirPlay-to-Mac."
214 warn "    That's intentional for high-threat models. To re-enable later:
"
215 warn "        launchctl enable gui/\$(id -u)/com.apple.sharingd"
216 warn "    • SIP protects /System/Library/LaunchDaemons/* - 'launchctl unlo
ad' may print errors."
217 warn "    That's expected. The 'launchctl disable' above is what actual
y prevents future starts."
218 warn "    • Some services will only appear in the audit if they were ever
launched on this Mac."
219 warn "    'unknown' for a label simply means launchd has no record of it
- effectively off."
220 warn "    • Reboot once after running this to ensure all disabled units st
ay down across launchd restarts."

```

=====

```

FILE: run-with-ls-silent.sh

```

```

SHA-256: 87bc028a581d6fce077e41140d12d82fe7626aa9cb640a16d1a1e8795023bdc8

```

=====

```

1  #!/usr/bin/env bash
2  # run-with-ls-silent.sh
3  # Flip Little Snitch to "Silent Mode - Allow Connections" for the durati
on of
4  # a command (default: harden.sh), then restore the previous mode no matt
er how
5  # the wrapped command exits (success, failure, or Ctrl-C).
6  #
7  # Little Snitch activeSilentMode values:
8  #   0 = Alert Mode (prompt on unknown)
9  #   1 = Silent Mode - Allow Connections
10 #   2 = Silent Mode - Deny Connections
11 #
12 # Usage:
13 #   ./run-with-ls-silent.sh                # wraps ./harden.sh
14 #   ./run-with-ls-silent.sh /path/to/cmd a b # wraps any command
15
16 set -uo pipefail
17
18 LS_CLI="/Applications/Little Snitch.app/Contents/Components/littlesnitch
"
19 WRAPPED=( "${@:-/Users/evw/dev/security/harden.sh}" )
20
21 RED=$'\033[0;31m'; GRN=$'\033[0;32m'; YLW=$'\033[0;33m'; BLU=$'\033[0;34
m'; NC=$'\033[0m'
22 log() { printf "%s[ls-silent]%s %s\n" "$BLU" "$NC" "$*"; }
23 ok() { printf "%s[ls-silent]%s %s\n" "$GRN" "$NC" "$*"; }

```

```

24 warn() { printf "%s[ls-silent]%s %s\n" "$YLW" "$NC" "$*"; }
25 err() { printf "%s[ls-silent]%s %s\n" "$RED" "$NC" "$*"; }
26
27 [[ "$(uname)" == "Darwin" ]] || { err "macOS only"; exit 1; }
28 [[ -x "$LS_CLI" ]] || { err "Little Snitch CLI not found at $L
S_CLI"; exit 1; }
29 [[ "$EUID" -ne 0 ]] || { err "Do NOT run as root - script will
sudo where needed"; exit 1; }
30
31 # Prime sudo + keepalive (the LS CLI requires root for read/write-prefer
ence,
32 # and the wrapped command will also need its own sudo).
33 log "Priming sudo..."
34 sudo -v || { err "sudo required"; exit 1; }
35 ( while true; do sudo -n true; sleep 50; kill -0 "$$" 2>/dev/null || exi
t; done ) 2>/dev/null &
36 SUDO_KEEPALIVE=$!
37
38 # Capture current mode so we can restore it
39 PREV_MODE="$(sudo "$LS_CLI" read-preference activeSilentMode 2>/dev/null
| tr -d '[:space:]')"
40 case "$PREV_MODE" in
41     0|1|2) ok "Current Little Snitch mode: $PREV_MODE (will restore on e
xit)";;
42     *) warn "Could not read activeSilentMode (got: '$PREV_MODE') - d
efaulting restore target to 0 (Alert)"
43         PREV_MODE=0 ;;
44     esac
45
46 restore_mode() {
47     local rc=$?
48     log "Restoring Little Snitch mode → $PREV_MODE"
49     sudo "$LS_CLI" write-preference activeSilentMode "$PREV_MODE" >/dev/
null 2>&1 \
50         && ok "Mode restored." \
51         || err "FAILED to restore mode. Set it back manually in Little S
nitch settings."
52     kill "$SUDO_KEEPALIVE" 2>/dev/null || true
53     exit "$rc"
54 }
55 # Restore on any exit path
56 trap restore_mode EXIT INT TERM HUP
57
58 # Flip to silent-allow
59 log "Setting Little Snitch → Silent Mode (Allow Connections)..."
60 if sudo "$LS_CLI" write-preference activeSilentMode 1 >/dev/null 2>&1; t
hen
61     ok "Silent-allow active."
62 else
63     err "Could not set silent mode. Aborting before running wrapped comm
and."
64     exit 1
65 fi
66
67 # Run the wrapped command
68 log "Running: ${WRAPPED[*]}"
69 "${WRAPPED[@]}"
70 # trap handles restore + exit code propagation

```

=== END OF BUNDLE ===