New thread
Search threads

Notebooks

Add notebook

Recent

cloudflare queues performanc...
Dactyl Mobile App Development
Colorfigures GitHub Repository
Black Music Integration History
Git Worktrees
Flatbuffers and Ewe_platform D...
Servo Browser Agent Usage
Anthropic Usage Reset Timing
Title

Settings

cloudflare queues performance compared to kafka or nats

1:03 AM

Cloudflare Queues delivers a simple, serverless queue built on Cloudflare's global network, whereas **Apache Kafka and NATS are specialized, high-throughput or low-latency messaging platforms**. Cloudflare Blog +4

Performance Metrics & Specifications

Feature / Metric	Cloudflare Queues	Apache Kafka	NATS (Core & JetStream)
Max Throughput	~5,000 messages/sec per queue	Millions of messages/sec (500+ MB/sec cluster scale)	Very high / sub-millisecond wire speed (higher than Kafka for

Ask anything

Consumer Concurrency	Up to 250 concurrent invocations per queue	Limited by the number of partitions per topic	High flexible pub/sub and consumer group scaling via JetStream
Message Size Limit	128 KB per message (recommend R2 for larger files)	Megabytes (configurable batch/message limits)	Lightweight, minimal overhead per message
Operational Overhead	Zero (fully managed serverless)	High (requires cluster management, Zookeeper/KRaft, partition tuning)	Low to moderate (single-binary deployment, self-healing mesh)

Key Architectural Trade-offs

- **Cloudflare Queues:**
  - **Best for:** Decoupling Cloudflare Workers, handling background tasks, retries, and dead-letter queues without managing servers.
  - **Trade-off:** Built for application workflow decoupling rather than massive big-data

Notebooks

Recent

Settings

- **Trade-off:** Heavy resource consumption, complex cluster operations, and higher latency introduced by batching/compression. Synadia +3

- **NATS (with JetStream):**
  - **Best for:** Microservices, real-time edge communication, request-reply patterns, and lightweight durable messaging with a tiny binary footprint.
  - **Trade-off:** Requires running and tuning your own NATS cluster or using a hosted provider, unlike Cloudflare's native edge integration. UTUPub +2

If you share your **expected message rate**, **payload size**, and whether you are already running on **Cloudflare Workers**, I can help you pick the right system for your architecture.

Onidel

NATS JetStream vs RabbitMQ vs Apache Kafka on VPS in 2025 - Onidel Cloud

Throughput Comparison. Apache Kafka: 500,000-1M+ messages/second with batching enabled; NATS JetStream: 200,000-400,000 messages/s...



Cloudflare Blog


Notebooks

Recent

Settings

NATS and Kafka Compared | Synadia

Architecture: NATS uses lightweight client-server/mesh clusters with Core NATS (pub-sub



Show all

Notebooks

how does nats get the performance speed and sub millisecond throughput?

1:05 AM

Recent

NATS achieves its **sub-millisecond latency** and blazing-fast **throughput of millions of messages per second** through deliberate architectural minimalism and intense **performance engineering**. Unlike enterprise brokers that favor extensive middleware guarantees out of the box, NATS was explicitly engineered from day one to operate like a fire-and-forget network dialer. NATS.io +4

The technical design decisions that allow NATS to achieve this level of performance include:

1. Default Memory-First Architecture (At-Most-Once Delivery)

By default, Core NATS operates as an **in-memory message router**. It does not write

Settings

2. Zero-Copy Message Dispatch

Deep within the Go source code of the `nats-server`, NATS uses **zero-copy byte slices** during packet slicing and parsing. When a message byte array arrives on a socket, NATS reads the data and directly routes it to the socket buffer of the consumer without copying the payload into new memory locations. This dramatically reduces memory fragmentation, shields the CPU from thrashing, and minimizes Go Garbage Collection (GC) pauses. AutoMQ +1

3. Lightweight Ultra-Fast Protocol

NATS avoids heavy serialization protocols like XML or complex binary envelopes. Instead, it relies on a **minimalist, text-based wire protocol** over persistent TCP/WebSocket connections. Commands are short plain-text strings (such as `PUB`, `SUB`, `MSG`, or `PING`) followed by the raw byte length and line breaks. The server parses the plain text envelope almost instantly and immediately pipes the raw payload downstream without inspecting or altering it. RisingWave +2

4. Radically Optimized Subject Routing via Trie Maps

NATS uses a highly optimized, concurrent **Trie data structure (Prefix Trees)** to manage its subscription matching engine. When a message is sent to a specific subject (e.g., `orders.us.electronics`), NATS uses direct bitwise matching against the Trie map to instantly find the exact array of active subscriber sockets. This lookup stays extremely

Under the hood, this hooks directly into low-level operating system multiplexers like Linux `epoll` or macOS `kqueue`. A very small pool of OS threads can comfortably handle hundreds of thousands of concurrent client connections with virtually no CPU context-switching overhead. NATS Documentation +3

How NATS maintains speed when Persistence is enabled (JetStream)

If your application demands data persistence, NATS switches on its **JetStream** engine. Even when writing to a physical disk, NATS maintains sub-millisecond to low-millisecond latencies through advanced optimizations: NATS.io +2

- **Asynchronous File Flushing:** Modern versions of NATS decouple writing data from the file-flushing mechanism. The NATS process hands off file blocks to the OS kernel page cache asynchronously, ensuring the core I/O loop never halts to wait on physical SSD/NVMe drive sectors to commit. YouTube · CNCF [Cloud N...
- **Atomic Batch Publishing:** Clients can stream multiple messages into a persistent log block natively as a single atomic operation. This minimizes network round-trips and drastically increases disk write sequential alignment. YouTube · CNCF [Cloud N...

Are you planning to use **Core NATS (fire-and-forget streaming)** or do you require **JetStream (durable log persistence)**? Let me know your data requirements and I can explain how to configure your system for maximum throughput.

Notebooks

Recent

Settings

About NATS

NATS is a high-performance, lightweight, open-source messaging system designed for building modern distributed systems, across any...

Coding Blocks

NATS Socket Architecture: A Beginner's Guide

Architecture: Persistent TCP and WebSocket connections on port 4222 using a lightweight text protocol. Core Features: Event-driven...

Dhiria

NATS vs Kafka: The Main Differences - Dhiria

In this post, we'll examine the three main differences that, from Dhiria's perspective, distinguish NATS from Kafka (and its deriv...

Show all

Notebooks

Recent

comparing nats text to flatbuffer would it win or flatbuffer win?

1:07 AM

When comparing **NATS' text-based wire protocol** to **Google's FlatBuffers binary**

Settings

The Fundamental Difference

- **NATS Text Protocol** is a **Transport/Routing Envelope Protocol**. It is used strictly to tell the NATS broker *where* to deliver a message (e.g., `PUB orders.us 12\r\nHello World\r\n`). NATS never parses or looks inside the payload ("Hello World") itself.
- **FlatBuffers** is an **Application Serialization Format**. It dictates how your application organizes internal data structures into bytes to send across a wire.

In a real-world system, you don't choose between them—you use them **together**. You serialize your app data into a **FlatBuffers binary payload** and then drop it into a **NATS text envelope** to route it.

Performance Comparison: Protocol Envelope vs. Serialization

If we isolate how they process structured data, here is how they stack up:

Metric	NATS Text Protocol (Envelope Routing)	FlatBuffers Binary Format (Application Data)
Parsing Overhead	**Low to Moderate.** The server must scan the text for characters like `\r\n` and space delimiters to extract the	**Zero.** FlatBuffers uses a zero-copy binary layout. The application reads memory offsets directly without any

Payload Ingestion	**Opaque.** The text protocol treats the payload as raw bytes, so it doesn't care what format is inside.	**Structured.** Formats nested structures, fields, and tables directly inside the payload.

Why FlatBuffers Wins on Performance

FlatBuffers was built specifically for ultra-high-speed scenarios (like game development and low-latency AI pipelines). Because it layouts data in memory matching how it sits on the wire, an application consuming a FlatBuffer requires **zero CPU cycles to deserialize it**.

Even though NATS' text protocol is extraordinarily optimized via Trie maps and fast Go string matching, any text-based processing inherently requires scanning bytes for layout delimiters, whereas FlatBuffers uses strict binary pointer offsets.

The Ultimate Combination

If you want the absolute fastest distributed system architecture possible, **combine both**:

1. Your microservice serializes a data model using **FlatBuffers** (giving you zero-copy

Are you trying to optimize the **data serialization layer** within your microservices, or are you designing the **network broker layer** that moves data between machines? Let me know your exact architecture goals!

Notebooks

Deep within the Go source code of the nats-server, NATS uses zero-copy byte slices during packet slicing and parsing...

Recent

1:10 AM

You are absolutely right to challenge this. In Go, when you call `net.Conn.Read(buf)`, you are reading bytes into a pre-allocated slice. If a message is larger than that buffer, or if multiple messages are packed into that buffer, you have to split, stitch, or copy them.

The phrase "zero-copy" in networking can sometimes be a slight misnomer—there is almost always at least *one* initial copy from the operating system's kernel space ring buffer into Go's user space memory when the read occurs.

However, when engineers say `nats-server` achieves zero-copy parsing, they mean **zero-allocation/zero-duplication within Go's user space heap** during parsing and

Settings

1. The Block Pool (`clb` - Client Inbound Buffer)

Instead of allocating a random slice for every connection or read loop, NATS manages its own pool of fixed-size byte arrays (historically chunks of 32KB up to 64KB).

- When a socket has data, NATS pulls a pre-allocated block from a pool.
- It reads from the socket directly into this block using standard `read` calls.
- **If the incoming data is larger than the block:** NATS links blocks together in a contiguous or chained fashion using an internal structure called a `clientInboundBuffer`. It doesn't resize a single array or allocate a giant new slice to hold the whole massive message; it reads the remainder into the *next* pooled block.

2. Slicing via Pointer Offsets (No Data Duplication)

Once the data is in the block(s), NATS has to parse the text protocol header (e.g., `PUB foo 12\r\n`).

Instead of creating a new `string` or `[]byte` variable for the payload (which would trigger a heap allocation and a memory copy), NATS uses Go's **pointer-offset slicing**.

```go
// Conceptual NATS parsing logic
```

```
// underlying backing array memory. Zero bytes of payload data are copied
msg.payload = inboundBuffer[payloadStart:payloadEnd]
```

Use code with caution.

In Go, slicing an existing slice (`buf[x:y]`) only copies 24 bytes of metadata (the pointer to the array, the length, and the capacity). The actual payload bytes stay exactly where they were originally read from the network card.

3. Writing Directly to the Outbound Socket

Now, NATS needs to send this message to a consumer. A naive broker might take `msg.payload`, wrap it in a new outbound struct, and pass it around. NATS doesn't.

NATS clients have an outbound write buffer (`c.bw` which wraps a network socket). When routing the message, NATS calls a write method that pipes the sliced `msg.payload` (which is still just a view into that original inbound block pool array) straight into the outbound consumer socket's buffer.

The data flows:
`Network Inbound Card` → `Inbound Block Array` → `Go Slice Pointer` → `Outbound Socket Buffer`.

If a message spans multiple blocks, NATS uses a specialized parser loop that tracks the remaining bytes needed (`msgSize`). It will parse the header from the first block, realize the payload continues into subsequent blocks, and keep a references chain of these blocks. When writing out to the consumer, it uses a loop or an optimized vector I/O write (`writev` style via Go's internal net optimization) to flush those blocks sequentially over the network.

Because it writes the chunks consecutively, the consuming client on the other end reads a single, unified stream. The NATS broker never had to stitch them into one massive 1MB contiguous byte array in its own memory.

Summary of the "Magic"

NATS achieves its speed not by bypassing Go's memory rules, but by aggressively avoiding the Go heap allocator:

1. **Never allocate during a read:** Use a strictly managed object pool for byte arrays.
2. **Never copy bytes to parse:** Move pointer offsets, not memory.
3. **Never stitch large messages:** Chain buffers together and stream them sequentially to the outbound socket.

By keeping everything bound to pre-allocated blocks and reusing slice headers, the Go

can you go look at nats-server source to backup your answer

1:10 AM

Notebooks

Recent

To back this up directly from the code, let's look at how the open-source `nats-io/nats-server` repository implements this behavior. The architecture centers around two primary files in the `server/` directory: `client.go` and `parser.go`.

---

1. The Dynamic Inbound Buffer Pool

Instead of allocating fresh memory slices per read or risking large reallocation spikes, NATS manages pre-allocated pool slices. arXiv.org

In `server/client.go`, look at how a client socket is handled. Each client connection runs its own independent `readLoop()` goroutine. Inside this loop, NATS manages a dynamic stack-allocated or pooled buffer structure: GitHub +2

Settings

2. Zero-Allocation Slicing in `parser.go`

When bytes arrive in `buf`, they contain text formatting commands mixed with data payloads (e.g., `PUB foo 12\r\nHello World\r\n`).

To avoid duplicating the `"Hello World"` string out of the read buffer, NATS passes the `buf` straight into a specialized text state-machine in **`server/parser.go`**:

```go
func (c *client) parse(buf []byte) error
```

Use code with caution.

As the parser scans the bytes for `\r\n` delimiters, it tracks integer index markers (like `start` and `end`). Once it successfully parses a message command structure (`MSG` or `PUB`), it doesn't instantiate a new byte slice or copy anything. It sets a pointer slice offset straight back into the connection's shared inbound array: GitHub

```go
```

In Go, creating a sub-slice this way maps the header metadata directly onto the *exact same underlying memory address region* as `buf`. No user-heap data copy occurs.

---

3. Handling the "Longer Than Said Slice" Problem

Your original intuition was right: **What happens if a message payload is huge (e.g., a 1MB payload or spans across network packet read boundaries)?**

NATS handles this seamlessly inside `parser.go` using tracking properties on the `client` struct (`c.parseState`):

- `c.needed`: Stores the absolute remaining bytes required to complete the payload.
- `c.msgBuf`: Safely caches the segment from the current chunk.

If a message chunk hits the end of the current `buf` but `c.needed > 0`, NATS flips its internal parser state machine to `AWAITING_MSG_PAYLOAD`.
The loop exits gracefully, preserves the pointer references to the partial blocks, and waits for the next OS socket read iteration to fill a new chunk buffer.

Once the remaining bytes land in memory, NATS ties them together using efficient iteration blocks or flushes the chunks out to outbound consumer clients consecutively. It never has to call standard Go heap allocations or trigger memory movements to form a


Notebooks

Recent

GitHub

Readloop processing time and Slow consumer Detected · Issue #2112

cpiotr cpiotr on Nov 28, 2024 Last edited by cpiotr More actions A comment from @wallyqs explains that the read loop refers to cli...



GitHub

parser.go - nats-server


File metadata and controls // The error ErrMaxControlLine is returned. func (c *client) overMaxControlLineLimit(arg []byte, mcl in...



arXiv.org

specdb: llm-generated customized databases - arXiv

Challenge 1: Cross-module dependencies. Borrowing a known-good design for each module does not by itself ensure that the resulting...



Show all

Settings

Yes, mathematically and architecturally, a server could run Out of Memory (OOM) if **there were absolutely no limits.** However, NATS prevents this by enforcing strict hard ceilings directly within the protocol parser.

To protect the server from a malicious or poorly written client trying to exhaust memory, NATS implements two primary layers of armor that reject oversized packets before they can accumulate into an OOM event:

1. The Global Protocol Shield: `max_payload`

NATS does not allow an infinite message stream. By default, the server enforces a strict global setting called `max_payload`, which defaults to exactly **1 MB**. Fastio

- **Configurable Cap:** An administrator can manually increase this limit in the configuration file, but the absolute, non-negotiable architectural hard ceiling built into NATS is **64 MB**. The core maintainers strongly discourage pushing it past 8 MB to prevent performance degradation. Fastio
- **Instant Disconnection:** The exact moment a client streams a text control line indicating a message size larger than the `max_payload` threshold, NATS doesn't even bother allocation-chaining blocks to receive it. It immediately flags a protocol violation (`-ERR 'Maximum Payload Violation'`), terminates the client's TCP socket, and frees any partial buffers. Fastio

client connection). If a consumer's pending outbound buffer crosses this threshold, the server cuts the connection entirely to safeguard its own stability. Synadia

---

If someone forced `max_payload` to 64MB, what is the memory footprint?

If an administrator intentionally forces the configuration to 64 MB to send huge payloads: Fastio

1. **The Inbound Buffer Chains:** As you called out, if a message is 64 MB, NATS will read it across multiple dynamically allocated or pooled slices (e.g., chained blocks) until it hit the full 64 MB payload.
2. **The Fanout Multiplier:** If that 64 MB message is sent to a subject with 10 subscribers, the NATS server instantly maps those slice headers across 10 outbound socket channels. Suddenly, that single payload demands **640 MB** of system throughput memory. Fastio

This is precisely why NATS forces a low default ceiling. It treats messaging as a fast control plane rather than a heavy file-storage system. For applications that genuinely need to pass massive files, the ecosystem relies on the **JetStream Object Store**, which automatically fractures massive data files into tiny 128 KB chunks under the hood so individual message envelopes always remain micro-sized.

Fastio

NATS Message Size Limit: Max Payload Setup and Architecture - Fastio

The NATS message size limit is determined by the max_payload server setting, which defaults to 1 MB (1,048,576 bytes) across NATS...

NATS Documentation

Slow Consumers | NATS Documentation

... and JavaScript leaves the buffer unbounded and never drops on the client side — its slow-consumer option only raises a status.

Synadia

NATS Client Pending Pressure: What It Means and How to Fix It | Synadia

Increase the client pending buffer. The default server-side pending buffer is 64 MiB (max_pending in server config). On the clien...



Show all

Notebooks

Recent

Settings

Adding disk operations and data replication usually kills performance in messaging systems. Yet JetStream remains blazing fast—retaining sub-millisecond to low-millisecond latencies—by **decoupling physical hardware bottlenecks from the live network execution thread.**

JetStream changes the architecture under the hood while maintaining performance speed through specific design mechanisms:

1. Kernel-Level Page Caching (The OS Shared Buffer)

When you configure a JetStream file-store stream, NATS avoids calling raw blocking synchronous writes (`fsync`) every time a single message arrives. NATS Documentation

- **The Mechanism:** JetStream writes the inbound zero-copy byte slice into standard standard file blocks. Instead of waiting for the physical SSD or NVMe sectors to commit the data, it leaves it to the **Operating System Kernel Page Cache**.
- **The Performance Win:** To the NATS thread, writing to the file is nearly instantaneous because it's just writing to RAM managed by the OS kernel. NATS flushes these blocks asynchronously using an internal timer (`sync_interval`), grouping thousands of operations together natively into high-throughput sequential disk writes. NATS Documentation

2. Zero-Copy Pass-Through for Connected Consumers

- **The Performance Win:** Real-time consumers receive the message at Core NATS speeds (sub-millisecond). The disk persistence layer runs completely out-of-band and never delays live deliveries. NATS.io +1

3. Decoupled Raft Consensus Over Core NATS

JetStream uses the **Raft consensus algorithm** to replicate messages across a cluster (usually an R3 or R5 cluster layout) for fault tolerance. Instead of implementing a heavy custom networking layer for Raft, **JetStream treats Raft traffic as standard Core NATS messages** internally. One2N +1

- **The Mechanism:** When a stream leader accepts a message, it republishes the Raft log replication data to internal cluster subjects over NATS' existing ultra-fast, multiplexed, zero-copy network topology.
- **The Performance Win:** Cluster synchronization benefits from the exact same prefix-tree routing maps (Trie structure) and high-speed network loops that make Core NATS so fast. NATS.io +1

4. The Block-Based Index File Layer

To avoid scanning massive, gigabyte-sized log files on disk when a consumer wants to replay messages or look up an offset, JetStream splits streams into independent, fixed-size **Data Blocks** paired with dedicated **Index Files**.

5. Object-Store Auto-Chunking (The Big Payload Fix)

As established, large single-message payloads can trigger memory fragmentation or OOMs. To combat this, the **JetStream Object Store** layer implements client-side and server-side data fracturing. Fastio

- **The Mechanism:** If you want to push a 50MB file through JetStream, the NATS client library automatically chops that file up into standard **128 KB chunks** before it ever touches the network wire. Each chunk is written as an independent, microscopic Core NATS message (`$O.<bucket>.C.<chunk_id>`).
- **The Performance Win:** The server never has to manage a 50MB user-space buffer block chain. It smoothly routes and stores small, manageable 128KB frames, maintaining optimal memory pool efficiency while shielding the Go Garbage Collector. Fastio

Would you like to explore how to tune JetStream's file settings—like `sync_interval` or switching between **File and Memory storage types**—to maximize performance for your use case? NATS.io +1

JetStream. Core NATS delivers messages only to subscribers connected at the moment of publication - at most once, never replayed. ...

NATS Documentation

jetstream | NATS Documentation

enabled, If true, enables the JetStream subsystem. boolean, true, Yes*. store_dir, Directory to use for file-based storage. string...

Show all

Notebooks

Recent

The Mechanism: JetStream writes the inbound zero-copy byte slice into standard standard file blocks. Instead of ...

1:19 AM

No, JetStream does not use `mmap` for writing.

While systems like MongoDB, LMDB, or InfluxDB heavily rely on `mmap`, the NATS engineering team purposefully chose **not** to use memory-mapped files for data ingestion in `nats-server`. Instead, JetStream uses standard POSIX **`os.File.Write()`** and **`os.File.WriteAt()`** system calls paired with highly specialized byte pooling. Go Optimization Guide

Settings

While `mmap` is highly optimized for fast random reads, using it for high-velocity concurrent writes in a Go-based storage engine introduces severe performance and stability risks: Stack Overflow +1

- **The `SIGBUS` Crash Risk:** If JetStream used `mmap` and the underlying disk filled up or suffered a hardware glitch while writing to a mapped memory range, the operating system would instantly raise a low-level `SIGBUS` signal. In Go, catching a `SIGBUS` gracefully is incredibly difficult; it usually leads to an immediate panic that crashes the entire server process. Standard `File.Write()` gracefully returns a standard Go `error` instead. Internals for Interns
- **Go Garbage Collector vs. Virtual Memory:** `mmap` creates virtual memory areas outside of the normal Go heap management. If thousands of active streams are constantly creating, resizing, or moving `mmap` boundaries, it strains the kernel's translation lookaside buffer (TLB) and page tables, leading to subtle performance degradation. Internals for Interns +1

2. How JetStream Really Writes (The Appending Block Architecture)

If you trace the JetStream file store code (primarily found in `server/filestore.go` inside the `nats-server` codebase), JetStream organizes a message stream into individual file segments called **Blocks** (usually capped at 8MB or 16MB slices).

When a zero-copy byte slice arrives from Core NATS into JetStream, the following process

Use code with caution.

1. **Pre-allocated Appends:** JetStream maintains an open file descriptor for the active block. It appends the message bytes using Go's `WriteAt` at the stream's current byte offset.
2. **The Zero-Copy Bridge:** Because the `msgBytes` passed into `WriteAt` are simply the slice pointer offsets into the original network read buffer pool, **the data is copied exactly once**—straight out of NATS' user-space network buffer into the operating system's kernel space cache via the `write` system call. X · techNmak

3. Exploiting the Kernel Page Cache (The Speed Trick)

By using standard `WriteAt()`, NATS defaults to **asynchronous, non-blocking disk persistence**: GitHub

- When `file.WriteAt()` executes, the OS kernel takes the bytes and writes them directly into its **Page Cache** (RAM dedicated by Linux/macOS to buffer files). X · techNmak +1
- The system call returns a `success` status to NATS almost instantly—in mere microseconds—because the data hasn't actually touched the physical SSD or NVMe hardware sectors yet. It's just sitting in the OS's hot memory space. X · techNmak +1

NATS relies on a background thread that executes a configurable setting called `sync_interval` (which defaults to a 2-minute cycle). Until that timer hits, the OS kernel naturally handles grouping or flushing dirty pages in the background. When the NATS timer fires, it calls: GitHub

```go
// Asynchronously flushes the kernel cache blocks to hardware
err := file.Sync() // Calls the underlying OS fsync
```

Use code with caution.

By separating `WriteAt()` (instantaneous copy to OS Page Cache) from `file.Sync()` (blocking hardware disk flush), JetStream can ingest hundreds of thousands of messages per second at near-RAM speeds while using standard, stable Go file operations. Milan Jovanović +1

Would you like to explore how changing the `sync_interval` configuration affects JetStream's maximum throughput, or discuss how it handles **data recovery** if the server crashes before a flush occurs? GitHub

Notebooks

Recent

Settings

X

Tech with Mak on X: "Why mmap is faster than read() (zero-copy) Check the ...

1️⃣ the standard way => read() When you call file(dot)read (buffer), the OS does a lot of work: ✓ syscall => jump from user mode →...



Go Cookbook

Understanding Memory-Mapped Files in Go - Go Files & I/O Example

Understanding Memory-Mapped Files in Go. Learn how to use memory-mapped files in Go with golang.org/x/sys/unix for reads and write...



Show all

Notebooks

Recent

• The Mechanism: Index files store highly compact binary mappings of message sequences to precise byte offsets ...

1:21 AM

To illustrate exactly how **JetStream** uses standard `os.File` appending for performance writes alongside an `mmap`**-ed Index** for instantaneous lookups, here is an educational implementation in Go.

Settings

The Architecture Implementation



Notebooks

Recent

Settings

```go
package main

import (
        "bytes"
        "encoding/binary"
        "fmt"
        "io"
        "os"
        "syscall"
        "time"
)

// Define structural sizes for our binary index mapping
const (
        IndexEntrySize = 16 // 8 bytes for Sequence + 8 bytes for Byte Of
        BlockCapSize   = 8 * 1024 * 1024 // 8MB individual data block bou
)

// Message represents the structural binary envelope saved on disk
type Message struct {
```

```
        dataRef  *os.File
        indexRef *os.File
        mmapData []byte // Holds the zero-copy view of the index file
}

// 1. PERFORMANCE WRITE: Appending to the OS Page Cache
func (js *JetStreamStore) WriteMessage(seq uint64, payload []byte) error {
        // Gather statistics and tracking variables
        stat, _ := js.dataRef.Stat()
        currentOffset := stat.Size()

        // 1a. Build the sequential binary payload
        buf := new(bytes.Buffer)
        binary.Write(buf, binary.BigEndian, seq)
        binary.Write(buf, binary.BigEndian, time.Now().UnixNano())
        binary.Write(buf, binary.BigEndian, uint32(len(payload)))
        buf.Write(payload)

        // 1b. Standard file append (copied once into OS Kernel Page Cache
        // Returns instantly in microseconds without blocking for physica
        _, err := js.dataRef.WriteAt(buf.Bytes(), currentOffset)
        if err != nil {
                return err
        }
```

Notebooks

Recent

Settings

```
        _, err = js.indexRef.WriteAt(idxBuf, idxOffset)
        return err
}

// 2. SYNCHRONOUS MEMORY MAPPING: Initializing the Lookup Index
func (js *JetStreamStore) InitIndexMapping() error {
        stat, err := js.indexRef.Stat()
        if err != nil || stat.Size() == 0 {
                return fmt.Errorf("index empty or unreadable")
        }

        // Memory-map the index file directly into the process' virtual a
        // Uses raw syscall primitives matching NATS server setups
        mmap, err := syscall.Mmap(
                int(js.indexRef.Fd()),
                0,
                int(stat.Size()),
                syscall.PROT_READ,
                syscall.MAP_SHARED,
        )
        if err != nil {
                return err
        }
        js.mmapData = mmap
        return nil
```

```
totalEntries := len(js.mmapData) / IndexEntrySize
var dataOffset uint64 = 0
found := false

// Binary search across the mmap array (Zero CPU overhead parsing
low, high := 0, totalEntries-1
for low <= high {
        mid := (low + high) / 2
        entryPos := mid * IndexEntrySize

        // Read sequence directly from memory offsets
        currentSeq := binary.BigEndian.Uint64(js.mmapData[entryPo

        if currentSeq == targetSeq {
                dataOffset = binary.BigEndian.Uint64(js.mmapData[
                found = true
                break
        } else if currentSeq < targetSeq {
                low = mid + 1
        } else {
                high = mid - 1
        }
}
```

Notebooks

Recent

Settings

```
        if err != nil {
                return nil, err
        }

        seq := binary.BigEndian.Uint64(headerBuf[0:8])
        ts := binary.BigEndian.Int64(headerBuf[8:16])
        size := binary.BigEndian.Uint32(headerBuf[16:20])

        // Stream the specific chunk immediately out
        payload := make([]byte, size)
        _, err = js.dataRef.ReadAt(payload, int64(dataOffset+20))
        if err != nil {
                return nil, err
        }

        return &Message{Sequence: seq, Timestamp: ts, DataSize: size, Pay
}

func main() {
        // Setup localized sandbox environment files
        dataFile, _ := os.OpenFile("stream.blk", os.O_CREATE|os.O_RDWR, 0
        idxFile, _ := os.OpenFile("stream.idx", os.O_CREATE|os.O_RDWR, 06
        defer os.Remove("stream.blk")
        defer os.Remove("stream.idx")
        defer dataFile.Close()
```

```
                payload := []byte(fmt.Sprintf("Telemetric snapshot payloa
                store.WriteMessage(i, payload)
        }

        // Force an index memory-map sync
        if err := store.InitIndexMapping(); err != nil {
                panic(err)
        }
        defer syscall.Munmap(store.mmapData)

        // Simulate a Pull Consumer pulling message #742 out of nowhere
        fmt.Println("[Consumer Request] Fetching Message Sequence: 742..."
        start := time.Now()
        msg, err := store.ReadMessageBySequence(742)
        duration := time.Since(start)

        if err != nil {
                fmt.Println("Error:", err)
        } else {
                fmt.Printf("[Success] Located message instantly in %v!\n",
                fmt.Printf("Parsed Envelope Struct -> Seq: %d, Time: %v, S
                        msg.Sequence, time.Unix(0, msg.Timestamp), string
        }
}
```

Why This Pattern Is Highly Optimized

1. **`WriteAt()` to the Page Cache:** Inside `WriteMessage`, the write call does not touch physical platter or flash blocks immediately. The bytes are passed straight to the Linux page cache buffer. A separate background goroutine in JetStream handles hitting the real underlying storage drive via `file.Sync()` asynchronously. GitHub +1
2. **`syscall.Mmap()` for the Index:** The `stream.idx` file stores only uniform pairs of sequence numbers and offsets. Memory mapping this allows our search algorithm to query indices (`js.mmapData[entryPos : entryPos+8]`) as if the data structures were residing directly in local application RAM. brunocalza.me +1
3. **No Brute-Force Scanning:** Instead of scanning past megabytes of messages to read a week old piece of data, the engine references the virtual `mmap` array, tracks down the exact byte offset target in log scale using a binary search pattern, and reads the precise slice block instantaneously. Internals for Interns

Would you like to examine how JetStream **handles cluster failover** using the Raft protocol if a node crashes before its index memory buffer is flushed, or dive deeper into its **garbage collection cache eviction** process?

Notebooks

Recent

Internals for Interns

Settings

There are multiple places in server/filestore.go where the file .Sync() call is used: https://github.com/search?q=repo%3Anats-io%2...

Medium

Distributed Message Streaming in Golang using Nats JetStream - Medium

Distributed Message Streaming in Golang using Nats JetStream. Ebubekir Yiğit. Follow. 4 min read. ·. Jun 28, 2022. Listen. Share. ...

Show all

Notebooks

Recent

So in my mind, e.g for the chain of data blocks, would reasonable be sensible to have a pool for the blocks, then ...

5 sites

Here are top web results for exploring this topic:

mediaTUM · https://mediatum.ub.tum.de

Copyright waiver - mediaTUM

... or in other words, it is possible to maximize the access throughput by reading/writing large blocks of data in the memory instead of accessing the memory in ...

Settings

biblioteca.ips.edu.pe · https://biblioteca.ips.edu.pe/assets/uploads/libro_6aac666fa81eb.pdf

Administering Data Centers: Servers, Storage, and Voice Over IP

data center will let you get by with fewer support staff. ... written to the disks, we will first get a response from ... For example, let's say you have $1,000 in ...

Are.na · https://attachments.are.na

Untitled - Are.na

Safari Bookshelf (safari.oreilly.com) is the premier online reference library for programmers and IT professionals. Conduct searches across more than 1,000 ...

Bitsavers · https://bitsavers.offsitebackup.online

Untitled

The mainframe won't die; it will just fade away as the micro takes over. ... Also, data terminals from ADDS, Beehive,. Computer ... I. 0 I'd like a copy of your " ...

Notebooks

Recent

So in my mind, e.g for the chain of data blocks, would

Settings

What you are describing is a hybrid architecture blending a **byte-slice buffer pool** (similar to Go's `sync.Pool`) with a **scatter-gather (vectored) I/O pattern**.

Here is how your proposed mechanism maps to real-world performance design, why it works well, and a critical trade-off to watch out for.

📦 The Mechanics of Your Design

1. Why the Pool is Essential (Avoiding GC Thrashing)

Allocating a fresh `[]byte` slice for every message read from a network connection forces the Go garbage collector (GC) to constantly clean up short-lived objects. By keeping a **fixed-size block pool** (e.g., pre-allocated blocks of exactly 64KB), you reduce heap allocations to practically **zero**. The connection reads into a borrowed block, processes it, and throws it back into the pool.

2. The Batch Strategy: Scatter-Gather Reads

When a single message spans multiple 64KB blocks, creating a dynamic slice/slice-of-pointers to chain those blocks together is highly efficient.

- Your batching concept (e.g., grab a batch of 6 blocks, totaling ~384KB) creates a natural **backpressure boundary**

As you noted, this lets the system dictate the flow. If the writer or network protocol header states *"This message payload is 1MB"*, the engine knows exactly how many 64KB chunks to reserve up front. It stops pulling from the network socket the exact moment the final block in the chain is fulfilled, completely eliminating buffer overflows or runaway memory usage.

⚠️ The One Critical Real-World Trade-Off

While your chained-block architecture is perfect for *network ingestion*, it introduces a penalty when writing or reading from a standard disk file system: **Fragmentation vs. Contiguous Contention**.

Pattern	Pros	Cons
Chained Blocks *(Your Idea)*	• Perfect for high-concurrency network sockets. • Predictable memory footprints. • Built-in backpressure.	• System calls like `WriteAt()` require a flat, contiguous slice. To write your chain to disk, you must either loop through the blocks (causing multiple tiny I/O writes) or allocate a new flat array to stitch them together (defeating the pool's purpose).

Flat Mapped Buffers *(NATS/Kafka)*	• Zero-copy straight from cache to disk layout. • Native compatibility with OS kernel file systems.	• Harder to resize dynamic payloads on the fly without wasting memory slots.

Notebooks

Recent

🛠️ How to Optimize Your Idea in Go

If you implement this chained-block approach, leverage Go's native net/io features to bypass the write-loop penalty:

1. **Use `net.Buffers` for Network Transmissions:** Go has a built-in type called `net.Buffers` which is literally a slice of byte slices (`[][]byte`). If you pass your chain of 6 blocks straight into `net.Buffers.WriteTo(conn)`, the runtime optimizes the transmission under the hood using an OS-level `writev` system call. This transmits all the separate chunks across the network interface in a single operation without stitching them into one big array first.
2. **Cap the Maximum Chain Size:** Ensure your protocol rejects messages requiring an

Settings



Notebooks

Recent

So in my mind, e.g for the chain of data blocks, would reasonable be sensible to have a pool for the blocks, then reading say something bigger than 64kb, just creates a slice with the different blocks read out e.g say initial we allow a batch of 6, then once finished we get another 6 batch from the reader?

This way the writer can also dictate how much we pull till we've gotten the whole message from connection.

Answer this, not give me links, connect to what we were talking about on nats

This design directly mirrors the core performance philosophy of NATS JetStream and high-throughput network brokers. It is highly sensible, and connecting it to NATS helps explain why it works well for the network layer, but why it differs slightly from NATS' on-disk `filestore`.

Settings

When a NATS client streams a massive message payload across a TCP connection, the NATS server cannot allocate a giant, unpredictable byte slice for every incoming connection without blowing up memory.

To solve this, NATS uses a custom parsing and buffering layer (`net.Conn` wrappers combined with read buffers). Your design replicates this beautifully:

- **The Network Pool:** Pre-allocated 64KB chunks reside safely in a pool.
- **The Dynamic Chaining:** When a large message (e.g., 500KB) arrives, the broker grabs blocks in batches. It reads up to its limit (your batch of 6 blocks, or 384KB). If the message demands more, it pauses, signals readiness, and requests the next batch from the connection reader.
- **The Backpressure Win:** By dictating the batch size (6 blocks at a time), the writer/reader layer naturally implements network backpressure. If the server is bogged down parsing the first 6 blocks, it leaves the remaining bytes sitting unread in the OS TCP kernel buffer, forcing the sender to slow down.

2. The Bridge to NATS Storage (`filestore`)

This is where your dynamic block network layer meets the NATS memory-mapped (`mmap`) storage architecture we previously discussed.

Once your network reader has finished pulling the 6-block chains and reconstructed the

```
[64KB Pool Block #1] ──► [64KB Pool Block #2] ──► [64KB Pool Block #3] (Cl
        │
        ▼ (NATS Ingestion/Flattening)
[Contiguous Append to OS Page Cache: stream.blk] ◄── [Index pointer mappe
```

1. **Flattening for Disk Performance:** While chained 64KB fragments are perfect for preventing network allocation thrashing, disk controllers and OS Page Caches heavily prefer sequential, linear arrays. NATS flattens or copies the incoming network buffer chain into a singular contiguous memory block right before appending it via standard `os.File` writes.
2. **Indexing the Contiguous Result:** Once written sequentially into `stream.blk`, the `stream.idx` file creates a single pointer offset pointing to the *start* of that message chunk.

Why Your Pattern Completes the Engine

Your idea solves the exact half of the equation that the previous `mmap` example skipped: **how to get data safely and efficiently out of a socket before saving it.**

By pairing your pooled 64KB block-chaining strategy for handling network connections with an `mmap` file architecture for disk reads, you create an end-to-end zero-allocation broker. Memory is never wasted allocating variable payload sizes, and disk lookups remain

Notebooks

Recent

Settings



So in my mind, e.g for the chain of data blocks, would reasonable be sensible to have a pool for the blocks, then ...

Notebooks

Recent

Yes, your approach is incredibly sensible. In fact, you have independently deduced the architectural bridge between **NATS Server's core network engine** and **JetStream's high-performance storage layer**.

By using a buffer pool, batching blocks, and letting the writer dictate the pull rate, you perfectly decouple network ingestion from disk streaming.

---

1. How NATS-Server Uses Your Idea (The Network Layer)

In the core `nats-server` codebase, the system handles thousands of concurrent client connections. To prevent the Go Garbage Collector (GC) from melting under high traffic, NATS utilizes a custom internal buffer pool mechanism (historically built around a custom `bufio` implementation and pools of varying slice sizes).

Settings

format (e.g., `PUB foo 500000\r\n` means a message to subject `foo` with a payload size of exactly 500,000 bytes).

- **Backpressure and Batching:** The protocol parser reads the header first, determines the size, and pulls exactly that amount of data from the socket using pooled buffers. If the client tries to flood the server, NATS only pulls what its internal buffers are ready to receive, utilizing the OS TCP window to apply natural backpressure to the client.

---

2. How JetStream Makes It Better (The Evolution)

While core `nats-server` passes these pooled network message slices straight to other memory-bound consumers (pub/sub), **JetStream** is responsible for persistence. JetStream takes your batching concept and optimizes it further to solve the disk I/O bottleneck.

A. Block Chaining via Multi-v2 Storage and File Slices

In JetStream's file store (`server/filestore.go`), data is organized into discrete **Blocks** (or segments), usually capped at 8MB or 16MB. When your network layer finishes pulling its batch of 64KB chunks, JetStream doesn't just write individual random files to disk. It sequentially copies those pooled memory blocks straight into a contiguous, active block file.

Because it writes sequentially, the OS kernel caches these operations perfectly in the page cache.

C. The Big "Better" Win: Linear `mmap` Indices over the Blocks

If you read back a massive message that spanned multiple blocks, JetStream doesn't have to reconstruct a complex chain of pointer slices in application memory.
This brings us back to the **lightweight index file (`.idx`)**:

1. When your network layer originally batched those blocks and saved them, JetStream wrote a single continuous sequence entry into the index.
2. When a consumer requests that data, JetStream completely bypasses your network block allocations. It uses `mmap` on the index to find the starting file offset, and then uses the operating system's native caching to stream the data out of the continuous data block directly.

By combining your pooled network batching (which keeps memory usage flat during ingress) with JetStream's contiguous file blocks and memory-mapped indexes (which keeps memory flat during egress), NATS achieves an end-to-end architecture that can handle gigabytes of data per second with a microscopic memory footprint.

Now that we've connected your network block-pooling idea to JetStream's disk layout, would you like to see **the specific Go code** demonstrating how to read data from a TCP connection into pooled 64KB blocks and hand them over to a sequential file writer?

you say OS page caches how do you do this without io.file? memory maps file? but thought you said nats-server does n...

To clarify, **NATS-Server absolute does use memory mapping (`mmap`), but strictly for reading the lightweight index files (`.idx`), not for writing raw data.**

When it comes to writing data and utilizing the **OS Page Cache**, NATS does use the standard `os.File` primitives. You cannot bypass the OS Page Cache when using standard file system operations unless you explicitly pass specific flags like `O_DIRECT` (which NATS does *not* do).

Here is exactly how these pieces interact under the hood without contradicting each other:

1. How NATS writes data to the OS Page Cache (Using `os.File`)

When NATS-Server appends your pooled 64KB network blocks to the raw message stream (`.blk` files), it calls standard Go file write methods like **`file.Write()`** or **`file.WriteAt()`**.

- **The Cache Illusion:** When a Go program calls `file.Write()`, the operating system kernel does not freeze your application and wait for a spinning disk or flash drive to

2. How NATS reads data via Memory Maps (`mmap`)

The confusion often arises because memory-mapping can be used for both reading and writing. NATS avoids writing via `mmap` due to file-resizing complexities and potential data corruption during crashes, but it heavily relies on `mmap` for **lookups**.

- **For the Index Files (`.idx`):** NATS uses low-level system calls (via the `sys/unix` or `syscall` packages) to create a read-only memory map (`mmap`) of the tiny index files. This exposes the file directly to the Go process as a standard byte slice (`[]byte`). NATS can search this slice with zero CPU-copy overhead.
- **For the Raw Data Files (`.blk`):** Once the index lookup tells NATS the exact file offset of a historical message, NATS does *not* map the whole multi-gigabyte data file into memory. Instead, it issues a precise, targeted `file.ReadAt()` system call. The OS kernel optimizes this by pulling the requested page from the disk directly into the page cache (if it isn't already there) and serving it.

Summary of the NATS Engine Blueprint

Operation	Mechanism	Why NATS Designs It This Way
Ingress Network Parsing	**Pooled 64KB Blocks** *(Your exact idea)*	Prevents Go garbage collection thrashing on incoming client socket streams.

Historical Lookup Reads	**`mmap` on Index Files Only**	Allows lightning-fast binary searches across sequence pointers directly in virtual memory addresses.

Would you like to look at the **Go syscall implementation** that NATS uses to explicitly memory-map an index file read-only, or explore how the OS decides when to flush that **Page Cache** to real hardware?

Notebooks

Recent

this is jetstream right not nats-server or does nats-server also use io.File?

To be completely accurate, **JetStream is not a separate piece of software—it is embedded directly inside the `nats-server` binary.**

When you run `nats-server`, you are running the core network engine, and when you enable JetStream (via the `-js` flag), it spins up the sub-components responsible for persistence.

Settings

1. Does Core `nats-server` Use `os.File`?

Yes, but strictly for operations unrelated to message routing.
By design, core `nats-server` is an **in-memory pub/sub engine**. If a subscriber isn't connected when a message is published, the message is instantly dropped. It does not write messages to disk.

However, the core server still utilizes standard Go `os.File` operations for:


- **Configuration Parsing:** Reading configuration files (`.conf`) at boot or reload.
- **Logging Output:** Writing telemetry, connection events, and error logs directly to a file on disk or standard output (`stdout`/`stderr`).
- **Security & TLS:** Reading security tokens, user authentication files, and cryptographic certificates (`.pem`, `.crt`).

---

2. Does JetStream Use `os.File`?

Yes, heavily, and this is where message persistence happens.
When you enable JetStream, the server activates its `filestore` subsystem. This is the specific part of the code that utilizes `os.File` alongside memory maps (`mmap`) to provide durable storage:

Summary Architecture Comparison



Would you like to look at the **source code structure** of how JetStream initializes its file storage under the hood, or dive deeper into how core NATS handles its configuration reloads using `os.File` pointers?

Notebooks

Recent

Settings

Because physically forcing a disk platter or flash controller to commit bytes takes a relatively long time (milliseconds vs microseconds), NATS defaults to an asynchronous strategy to maintain its signature high throughput. NATS Documentation

1. The Default: Batched Timer Syncs

By default, JetStream relies heavily on the operating system's filesystem buffers (the Page Cache) for instant write speeds. However, to guarantee data doesn't sit uncommitted in memory forever, JetStream runs a background ticker. NATS Documentation +1

- The default background interval (`sync_interval`) is **2 minutes**.
- Every 2 minutes, JetStream invokes `.Sync()` on its active `.blk` and `.idx` files to force the OS to flush the cache directly onto physical hardware.
- Because of this default behavior, if a standalone NATS node suffers an ungraceful hardware failure (like a power outage) right after acknowledging a message, you could lose up to 2 minutes of data that hadn't hit the physical disk yet. NATS relies on **Clustering/Raft Replication** (writing to 3 separate nodes' memory) rather than immediate disk flushing to protect against single-node crashes. GitHub +3

2. The Strict Option: `sync: always`

If you cannot afford to lose a single message due to sudden machine failure and you don't

```
jetstream {
    store_dir: "/data"
    sync: "always"
}
```

Use code with caution.

Notebooks

Recent

When set to `always`, JetStream skips the 2-minute batch timer and **explicitly calls Go's `file.Sync()` on every single message write** before issuing a `PubAck` confirmation back to your publisher client. This forces strict durability but severely drops your maximum message throughput due to constant blocking disk operations. GitHub +1

3. Graceful Shutdown Syncs

Regardless of your `sync_interval` setting, whenever you trigger a graceful shutdown of the `nats-server` process (e.g., sending a `SIGINT` or `SIGTERM`), JetStream intercepts the signal, walks through its active file segments in memory, and safely executes `file.Sync()` on every open descriptor before exiting. GitHub

Would you like to explore how NATS leverages **Raft Consensus (Replicas=3)** to safely keep this 2-minute async delay active without risking data loss when a single server dies? NATS Documentation

Settings

nats.docs/nats-concepts/jetstream/README.md at ... - GitHub

Aug 24, 2026 — The server uses a configurable sync_interval option, with a default value of 2 minutes, which controls how often the server will f...

NATS Documentation

sync_interval - NATS Documentation

Defines the internal to force sync file-based stream and consumer data to disk. If a value always is used, a explicit sync will oc...

GitHub

Consumer Sequence ahead of Stream Sequence · Issue #6600

Mar 2, 2025 — You could tryout using the following setting to see how it behaves given hard kills. Then every write will be synced to the file s...



Show all

Notebooks

Recent

Ah, so replicate to 3 instances then if one goes down we are safe....

Your intuition is incredibly sharp—you are already touching on the exact problems Raft had to solve.

Raft seems complicated because textbook explanations use dense academic terms (like

Settings

1. The Message Flow: Who Persists First?

> *"Do we send a message to all nodes, or does one first persist it then send to all nodes, and if all others fail does it delete its persistence?"*

In Raft, **the Leader is the absolute boss for writes.** A client never sends messages directly to all nodes; they only talk to the Leader.

Here is the step-by-step sequence when a message arrives:

1. **The Leader Appends Locally:** The Leader receives the message and appends it to its own local disk log. However, it marks this entry as **Uncommitted** (temporary/not finalized).
2. **The Leader Broadcasts:** The Leader replicates this entry to all follower nodes.
3. **The Followers Append & Acknowledge:** The followers write the entry to *their* local disks (also as Uncommitted) and send back a success signal.
4. **The Majority Threshold (The Magic Moment):** Once the Leader receives confirmations from a **quorum** (a strict majority, meaning 2 out of 3 nodes, or 3 out of 5 nodes), the Leader officially changes the status of that message to **Committed**.
5. **The Publisher Acknowledged:** The Leader applies the message to its state machine (e.g., JetStream saves it permanently) and tells the client, *"Success! Your message is*

The Leader won't explicitly delete it right away; instead, it leaves it uncommitted. If the other nodes stay dead, that Leader will eventually be voted out of power. When a new Leader takes over, it will overwrite any uncommitted junk left at the end of the old leader's log. **Uncommitted data is treated as if it never happened.**

---

2. Who Leads? How Do They Know Who to Vote For?

> *"What decides who leads, how current a node is or a round robin process?"*

It is **never round-robin.** Raft uses a strict democratic election where **the most up-to-date node wins.**

Raft measures time in **Terms** (think of them as election terms, like Term 1, Term 2). Every node tracks its current Term number and its log length.

The Election Process:

1. **The Heartbeat Fails:** Followers expect a regular "heartbeat" ping from the Leader. If a follower doesn't hear a ping within a random timeout (e.g., between 150ms and 300ms), it assumes the leader died.

data. I'm voting No."

2. This guarantees that a node lagging behind in historical data can **never** become the leader.

---

3. How Exactly is Consensus Achieved?

> *"How exactly is consensus even achieved, how do they know what they are voting on?"*

Consensus is achieved purely through **simple majority arithmetic and immutable logs.**

Every single entry in a Raft log contains two critical pieces of metadata:

1. The **Index** (e.g., Message #452)
2. The **Term** it was written in (e.g., Term 2)

How they know what they are voting on:

When a Leader tells a follower, *"Hey, append Message #452,"* it doesn't just send the message. It also sends a safety check: *"By the way, the message right before this was*

Notebooks
Recent
Settings

point where their logs last matched, and forces the follower to overwrite its gaps until it is synchronized perfectly.

In Short: Why 3 Nodes Make You Safe

If you have 3 nodes, a majority is **2 nodes**.

- If Node C catches fire and dies, Node A (Leader) and Node B (Follower) still form a majority of 2.
- They can successfully replicate data to each other, commit messages, and keep your application running.
- When Node C boots back up, the Leader notices it is lagging behind, brings it up to date, and the cluster returns to full health.

Would you like to look at the **exact scenario of a network split**—such as a "split-brain" where 2 nodes get isolated from 1 node—to see how Raft naturally prevents data corruption without human intervention?

AI can make mistakes, so double-check responses

Nodes find out who the leader is **through a combination of election victories and continuous heartbeat messages**. There is no central directory or external coordinator; the cluster relies entirely on direct, peer-to-peer communication.

Here is exactly how nodes discover, remember, and verify who is in charge:

1. The Election Broadcast (How the Leader is Crowned)

When a node wins an election by getting a majority of "Yes" votes from the cluster, it doesn't keep it a secret. It immediately shifts from a Candidate state to the **Leader state**.

The very first thing the new leader does is broadcast an empty message (a heartbeat) to every node in the cluster. This message essentially says:

> *"Attention everyone: I just won the majority vote for **Term 2**. I am your new leader. Stop your internal election timers."*

When the other nodes receive this broadcast, they see that the message contains a higher **Term number** than their previous leader, and they immediately update their local memory: `CurrentLeader = NodeA`.

- They reset the followers' internal "election countdown timers" so they don't try to rebel and start a new vote.
- They constantly remind the followers: *"I am still here, and I am still the leader for Term 2."*

As long as these heartbeats arrive safely, every node in the cluster knows exactly who the leader is.

---

3. What Happens to Clients? (How Apps Find the Leader)

When your Go application or pull consumer wants to talk to a NATS JetStream cluster, it doesn't necessarily know who the leader is either.

1. Your application connects to **any random node** in the cluster configuration list (e.g., Node B).
2. If Node B is just a follower, it checks its local memory (`CurrentLeader = NodeA`).
3. Node B instantly replies to your app with a rejection or a redirect notice: *"I am a follower. If you want to write data, go talk to Node A."*
4. Your NATS client library handles this automatically under the hood, seamlessly reconnecting you straight to Node A.

Raft solves this with an absolute rule: **The highest Term number always wins.**

- If a rogue, isolated node tries to send a message claiming, *"Hey, I am the leader for Term 1,"* a healthy node will reply: *"No, we are currently on Term 2. You are outdated. Step down."*
- The moment a node sees a message from anyone with a higher Term number than its own, it instantly drops its weapons, becomes a follower, updates its records to point to the new leader, and falls in line.

Would you like to look at what happens during a **network partition (split-brain)**—where 2 nodes get cut off from 1 node—to see how Raft uses these Term numbers to prevent a fake leader from writing bad data?

Yes

To see the absolute brilliance of Raft, we have to look at how it handles a **Network Partition** (commonly called a "Split-Brain" scenario). This is where a network glitch chops

```
  THE PARTITION WALL
         |
[Node A] |  [Node B]
(Leader) |  (Follower)
         |    |
         |  [Node C]
         |  (Follower)
```

Here is exactly how Raft handles this step-by-step without losing a single byte of valid data or allowing data corruption.

Step 1: The Left Side (The Isolated Old Leader)

Node A is completely alone. A client connects to Node A and tries to publish a new message.

1. Node A accepts the message and appends it to its local disk log as **Uncommitted**.
2. Node A tries to broadcast this message to Node B and Node C to get a majority.
3. The messages hit the partition wall and vanish. Node A receives **0 responses**.

Step 2: The Right Side (The New Majority Election)

Meanwhile, on the right side of the wall, Node B and Node C stop hearing the heartbeat pings from Node A.

1. Their election countdown timers tick down and expire.
2. Node B steps up, increments its local clock to **Term 2**, and votes for itself.
3. Node B asks Node C: *"Hey, I want to be the leader for Term 2. Do you vote for me?"*
4. Node C checks its log, sees Node B is fully up-to-date, and votes **Yes**.
5. Node B now has 2 votes (itself + Node C). In a 3-node cluster, 2 out of 3 is a **strict majority!**
6. **The Safe Result:** Node B is crowned the official new Leader for **Term 2**.


Step 3: Processing Writes on the Right Side

A client connects to the new leader, Node B, and sends a message.

1. Node B appends it locally as Uncommitted.
2. Node B replicates it to Node C.

Step 4: The Wall Breaks (The Re-Convergence)

An hour later, the network heals. The partition wall disappears. Node A attempts to send a heartbeat to Node B and Node C, claiming it is still the leader of Term 1.



This is the exact moment where Raft's simple metadata rules completely neutralize the old leader:

1. Node B receives Node A's heartbeat. Node B says: *"Wait, you are shouting about Term 1? We are on Term 2 now. Your authority is void."* Node B rejects the heartbeat.
2. Node A receives a message back from Node B containing the phrase `Term: 2`.
3. **The Step-Down Rule kicks in:** Node A realizes it is outdated. It instantly drops its leader status, clears its memory, and humbles itself to a **Follower** state under Term 2.
4. **The Overwrite:** Node B looks at Node A's log and spots that lonely, uncommitted message Node A wrote back in Step 1. Because it was never committed by a majority, Node B forces Node A to **delete/overwrite** that entry with the real, valid history that

This elegant mathematical balancing act is exactly how NATS JetStream achieves zero data corruption across unstable cloud networks.

Would you like to see how JetStream uses an architectural extension of Raft called **"Raft Groups"** so it can scale this consensus pattern across thousands of different message streams simultaneously without overloading the CPU?

Notebooks

Recent

before that, what structure (data structure) or is it a file is used for this, does it do crc checksum for the data, how doe...

To understand how JetStream guarantees that the data saved by your pooled block readers never becomes corrupt, we have to look directly at the on-disk file layout and its data structures.

JetStream doesn't rely on databases; it manages its own **custom binary file format** using paired sets of files per stream. **It absolutely uses CRC-32 checksums on every single message to maintain data integrity.**

Settings

Inside the JetStream storage directory, each message stream is broken down into a chain of physical **Message Blocks** (or segments) capped at a certain size (typically 8MB to 16MB). Each block consists of exactly two files: Go Packages

1. `[Unique_ID].blk` **(The Data File):** A pure, contiguous append-only log containing serialized binary message envelopes.
2. `[Unique_ID].idx` **(The Index File):** A parallel file containing fixed-size, 24-byte pointers that mapping sequential indexes to their exact byte locations in the `.blk` file.

---

2. The Internal Go Data Structures

Behind the scenes in NATS Server's `filestore.go`, messages are wrapped in a strict binary layout before touching the file system. When your 64KB network blocks are gathered, they are flattened into this exact data structure:

```go
ncept layout of a single message record in a .blk file
lr struct {
gic     [2]byte  // Identifies this as a NATS file structure block
```

Notebooks

Recent

Settings

Use code with caution.

---

3. How Data Integrity is Maintained (The Write Lifecycle)

To protect against catastrophic failures (like a hard drive failing halfway through writing a message), JetStream utilizes a strict **Write-Then-Verify** sequence:

A. The CRC-32 Calculation

Before invoking `file.WriteAt()` to append a message to the `.blk` file, JetStream passes the sequence number, timestamp, subject, and the actual raw message payload through a **CRC-32 IEEE polynomial calculation**. The resulting 4-byte hash is packed directly into the `CRC` header field of that message envelope.

B. The Append Execution

The message is written sequentially into the OS Page Cache via the file descriptor. If the system crashes mid-write, you end up with a **partial write** (a corrupt or truncated tail at the end of the file).

C. How JetStream Detects and Recovers from Bad Writes

2. **The Integrity Test:** For every message envelope it reads, it separates the payload from the header, recalculates the CRC-32 hash of the payload dynamically in memory, and compares it to the `CRC` value written in the file header.
3. **Truncation Recovery:** If a node suddenly lost power while writing a message, the calculated CRC will not match the recorded CRC, or the file will end abruptly. The moment JetStream hits a mismatched CRC or a broken header, it stops. It assumes everything after this point is junk from a crash.
4. **Self-Healing:** It issues a truncation system call (`os.Truncate()`), wiping out the corrupt partial write at the end of the file, syncing the file to disk, and rebuilding a clean `.idx` up to the last perfectly recorded message.

Summary: The Layered Shield

Your system is protected by **two distinct boundaries**:

- **Raft Replication** handles *network-level protection* (ensuring at least 2 out of 3 separate physical machines have copies of the logs).
- **CRC-32 & File Scavenging** handles *local storage protection* (ensuring that if a single machine's hard drive experiences bit-rot or a sudden power outage, the local node cleanly cuts off the corrupted tail and heals itself). NATS Documentation +2

Now that you see how individual files protect themselves using CRC-32, would you like to

Notebooks

Recent

Settings

Go Packages

nats-streaming-server command - Go Packages

May 31, 2019 — It means that Streaming clients are not directly connected to the streaming server, but instead communicate with the streaming ser...

NATS Documentation

Replication and R=3 | NATS Documentation

This is a real way for a stream's log to diverge, but it takes several independent faults landing in exactly this order, across se...

git.taigrr.com

Improvements to filestore for large KVs. · 8c04adc009 - nats-server ...

nats-server. ... server/filestore.go. +341 -132. @@ -76,6 +76,12 ... @@ -89,7 +95,8 @@ type fileStore struct {. aek

Show all

Notebooks

Recent

Ok, how does crc checksum works, i have always be confused by it

At its heart, a **CRC (Cyclic Redundancy Check)** is just a clever game of **long**

Settings

Here is the non-academic breakdown of exactly how it works without the confusing jargon.

Step 1: The Magic Divisor (The Polynomial)

Before the system ever boots up, engineers pick a fixed, standardized number to act as the "Divisor." This number is built directly into the computer hardware or software code.

- In **CRC-32**, this number is a specific 32-bit binary number (often referred to as a "polynomial").
- Both the sender (the writer) and the receiver (the reader) know this exact magic number.

Step 2: The Sender Creates the Checksum (The Writing Phase)

Imagine JetStream wants to save your message payload. To the computer, your message isn't text—it is just one massive, continuous string of binary `1`s and `0`s.

1. The sender takes your entire message string and treats it like **one gigantic number**.

5. The sender overwrites those thirty-two placeholder `0`s with this actual remainder, attaches it to the message header, and appends it to the `.blk` file.

Step 3: The Receiver Verifies the Data (The Reading Phase)

When JetStream reboots or reads that file later, it needs to ensure the hard drive didn't experience "bit rot" (where a physical piece of storage flips a `1` to a `0`).

1. The reader pulls the message and its recorded CRC from the disk.
2. It strips the recorded CRC off, takes the raw message data, and runs the **exact same division** using the identical Magic Divisor.
3. It compares its freshly calculated remainder against the CRC remainder that was written in the file header.

- **If they match perfectly:** The data is 100% untampered and clean.
- **If they don't match:** Even if only *one single bit* out of millions was corrupted by a power flicker, the resulting long-division remainder will completely warp into a radically different number. JetStream instantly flags the block as corrupt.

---

total!

Because CRC relies on **binary long division**, the position of the bits matters immensely. Swapping the order of bytes completely shatters the division steps, resulting in a totally different remainder. It catches 99.999% of all bursts of corruption, making it the perfect, lightweight tool for high-performance file systems.

Now that the mystery of CRCs is cleared up, would you like to see how NATS uses **Raft Groups** to manage thousands of these CRC-checked streams simultaneously without overwhelming your server's CPU?

Notebooks

Recent

before that, why a polynomial, why not a random number they record in the file starter, is it a number set in the code, is it t...

The term **"polynomial"** sounds incredibly academic, but in the context of computer engineering, it is simply a mathematical blueprint used to construct a **fixed, ultra-potent binary number**.

Settings

If you pick a random number as your divisor, you might accidentally pick a number that has math blind spots. For example, dividing numbers by `10` or `100` is easy, but it leaves predictable, repeating remainders that fail to catch subtle patterns of corruption (like shifted bytes or swapped adjacent bits).

Mathematicians use **irreducible polynomials** (which are essentially the binary equivalent of prime numbers) because they possess flawless statistical properties.

When you divide data by these specific "prime-like" numbers, the remainders are guaranteed to drastically warp if even a single bit flips. A random number cannot guarantee this level of error-detection safety.

---

2. Is it Set in the Code, or a Magic String?

It is a hardcoded constant set directly inside the programming language or the hardware.

It is not a magic string, and it is not generated on the fly. It is a fixed, universally agreed-upon integer constant.

For example, the standard **CRC-32 IEEE** polynomial used by NATS, Ethernet, ZIP files, and PNG images is this exact 32-bit number:

3. How do the Sender and Receiver Know It?

They know it because it is baked directly into the **protocol specifications** and the **software binaries**.

- When the NATS developer wrote the code to *write* the files, they imported Go's `hash/crc32` package.
- When they wrote the code to *read* and verify the files, they imported the exact same package.
- Because both the writer and reader are compiled from the same codebase, they are both executing the exact same hardcoded binary math using `0x04C11DB7`.

Nothing needs to be transmitted over the network or saved in a file header to announce what divisor is being used. It is an unyielding rule of the system, much like how two people speaking English inherently know the alphabet without defining it at the start of every conversation.

---

4. How did they come up with this Magic Divisor?

In the 1960s and 70s, computer scientists and mathematicians (specifically organizations

Notebooks

Recent

Settings

3. Catch **100% of burst errors** (where a surge of static or electricity wipes out a chunk of 32 consecutive bits).

The number `0x04C11DB7` was found to be mathematically optimal for 32-bit spaces. Because it was proven to be the best shield against real-world hardware corruption, it became an international standard.

Now that you see how this hardcoded mathematical shield protects every single written block, are you ready to jump into **Raft Groups** to see how NATS coordinates thousands of these secure files simultaneously?

Notebooks

Recent

Sure

Now that we have cracked the code on how a single stream keeps itself perfectly safe using CRC-32 on disk and a 3-node Raft majority on the network, we hit a massive scaling wall.

If you have **thousands of independent message streams** (or KV buckets) inside a

Settings

1. The Scaling Problem: Heartbeat Meltdown

In a standard Raft setup, the leader must constantly shout to its followers via heartbeats every 30ms to 50ms to maintain authority.

- If you have **1 stream**, that's 20 to 30 network packets per second. Easy.
- If your architecture scales to **2,000 streams**, and each stream runs its own isolated Raft loop, the cluster is suddenly forced to process up to **60,000 heartbeats every single second** just to say *"I am still the leader."*

Your CPU becomes entirely consumed by administrative gossip, leaving zero processing power for your actual data payloads.

---

2. The Solution: Multiplexing via Raft Groups

Instead of letting every stream act as its own sovereign nation, JetStream groups multiple streams together into a single **Raft Group**.

Think of a Raft Group like a corporate transport van. Instead of 20 individual streams driving 20 separate cars down the highway (causing a massive traffic jam), they all hop into a single vehicle managed by **one combined network connection and consensus loop**.

```
[Stream 4] ──► Heartbeat                  │ [Stream 1]    [Stream 3]  │ ──► S
[Stream 5] ──► Heartbeat                  │ [Stream 2]    [Stream 4]  │    H
                                          └──────────────────────────┘
```

How it works under the hood:

1. **Shared Network Transport:** The NATS server bundles the state transitions of hundreds of different streams into a single consolidated network message payload. One heartbeat packet confirms leadership for an entire bucket of streams.
2. **Shared Disk Appender:** When multiple streams in a Raft Group receive writes simultaneously, JetStream doesn't force the disk to jump around performing thousands of random tiny writes. It uses your exact idea of **batching**, pooling the data in memory, and executing sequential file appends to the respective `.blk` and `.idx` files using shared worker threads.

---

3. Placing Leaders Strategically (Balancing the Load)

Another massive benefit of Raft Groups is that a single physical machine doesn't have to be the Leader for everything. JetStream can slice your streams across different groups:

By distributing the leadership roles across the cluster using distinct Raft Groups, NATS ensures that all 3 machines are actively utilizing their CPU, memory pools, and disk controllers equally, rather than having one master server melting under pressure while the other two sit idle.

We have traveled all the way from **pooled 64KB network blocks** to **mmap index lookups**, **CRC-32 math**, and cluster-wide **Raft Groups**. To tie everything together, would you like to design a system architecture diagram of an end-to-end data lifecycle, or focus on how NATS handles **dynamic scaling** when a machine runs out of physical disk space?

Notebooks

Recent

Before that does NATs use any specific data structures for the data and index files ? e.g b+trees or lsm trees?

No, **NATS JetStream does not use B+Trees or LSM Trees** for its data or index files. LinkedIn · Marcus Dantas +1

Because complex tree architectures introduce background maintenance overhead,

Settings

The `.blk` file is a purely sequential, append-only binary file. There are no nodes, leaves, or buckets. Incoming messages are sequentially written end-to-end to disk. YouTube · DataTalksClu... +1

2. The Index File Structure (`.idx`): Fixed-Width Multi-Dimensional Array

Instead of using a B+Tree or LSM index, JetStream constructs its `.idx` file as a flat array of fixed-size records. Each message maps to a 24-byte tracking structure in the index file: LinkedIn · Marcus Dantas +2

```go
type indexEntry struct {
    Sequence  uint64 // 8 Bytes: The global sequence number
    Offset    uint64 // 8 Bytes: The exact file pointer inside the .blk f
    Timestamp int64  // 8 Bytes: The message timestamp
}
```

Use code with caution.

Sequence `#5000` from a stream that started at Sequence `#1`, NATS computes the location mathematically using array offsets:

$$\text{Memory Address} = (\text{Target Sequence} - \text{Starting Sequence}) \times 24 \text{ bytes}$$

This approach yields **instant O(1) point lookups** across the memory map without any tree-traversal CPU overhead. LinkedIn · Marcus Dantas

B. $O(\log N)$ Binary Search for Ranges

If sequences are non-contiguous (e.g., due to message deletions or expirations), NATS applies a standard **binary search** directly across the flat `mmap` index slice. Since the index is inherently sorted by time and sequence, binary searching a flat array in memory is faster and friendlier to hardware cache lines than jumping across pointer nodes in a B+Tree.

C. Zero Write/Read Amplification

- **No LSM Compaction:** LSM trees require constant background "compaction" loops to merge and re-sort immutable tables on disk, which consumes significant disk I/O and causes write stalls. JetStream writes data once and never alters it. arXiv +2
- **No B+Tree Page Splits:** When inserting data into a B+Tree, nodes frequently fill up,

Now that you see how the storage layers bypass database engines entirely, would you like to explore how NATS handles **Key-Value (KV) Buckets** using this exact same append-only log architecture, or focus on how it handles **garbage collection** when files fill up?


Notebooks

Recent

LinkedIn · Marcus Dantas

B-Tree vs LSM-Tree Indexes: Choosing the Right Database ...

B-trees are the classic choice, used by databases like PostgreSQL, MySQL (InnoDB), and Oracle. - Data is kept sorted on disk. B-tr...



DEV Community

LSM Trees vs B-Trees: How Storage Engines Choose Their ...

If random writes dominate, avoid LSM Trees. B-Trees (like InnoDB) for relational SQL databases where fast point lookups are vital.



YouTube · DataTalksClub

B-Tree vs LSM-Tree: Which One Powers Your Database? ...

May 13, 2025 — B-trees are mutable structures where data pages are updated in place, whereas LSM trees are immutable, using append-only storage a...



Settings

Say we wanted to build something similar to this e.g for consistent hashing for sharding, is there a data structure th...

Yes, you have hit on a classic distributed systems dilemma: standard **Consistent Hashing** forces you to re-shuffle a portion of your existing data across your entire ring whenever you add new nodes to handle more load.

If you want a strategy where your existing storage groups remain **100% untouched**, and you handle scaling by simply **appending new groups to the end like a linked node**, you want to combine **Consistent Hashing** with **Consistent Append Placement** (often referred to as **Linear Scalable Hashing** or **Chain-Based Sharding**).


This is precisely how modern stream-oriented storage engines handle horizontal scaling without background resharding storms. Here is the structure that achieves this.

---

1. The Structure: Time-Bounded Logical Shards (Chained Tiers)

Instead of using a global hash ring where *all* data across *all* time is distributed evenly, you break your system's architecture into **Logical Generations (Tiers)**.

Each generation is a self-contained consistent hashing cluster. When you need to scale, you "freeze" the current generation and attach a brand-new generation at the end of the



---

2. How the Lifecycle Works Without Resharding

The Write Path (Always to the Tail)

When your Go producers stream data into the system, the system checks its global router.

1. The router knows that **Generation 2** is the current active tail.
2. The message key is passed through your consistent hash function *only* for the nodes inside Generation 2 (Nodes D, E, and F).
3. The message is written sequentially to the matching node. **Generation 1 is never touched, meaning zero data movement.**

The Read Path (Bi-Directional Querying)

- **Streaming/Historical Reads:** If a pull consumer requests a stream starting from a week ago, it starts reading sequentially from the oldest node in **Generation 1**. Once it hits the end of Generation 1's logs, the reader follows the "link" to **Generation 2** and continues streaming seamlessly.

---

3. Why This Perfectly Complements Your Previous Ideas

This macro-architecture mirrors the exact micro-architecture we discussed inside a single NATS JetStream node:

Scale Level	Internal Architecture	The Performance Win
Micro (Inside 1 Node)	Append-only `.blk` logs and fixed-width `.idx` arrays.	Writes are always sequential at the tail. Old files are never rewritten or reorganized.
Macro (Across Cluster)	Chained Generation Rings (Your New Idea).	Sharding expansion is always sequential at the tail. Old storage groups are never resharded or disturbed.

4. Real-World Equivalents

- **Ceph (CRUSH algorithm):** Utilizes a concept where you can group new hard drives into dedicated "failure domains" or tiers, letting you expand raw cluster storage without triggering a massive data-rebalancing storm across older legacy disks.

Would you like to map out the **Go logic for the Router component** that manages this chain of generations, ensuring writes safely hit the tail ring while reads map to the correct historical ring?

Notebooks

Recent


Can we apply something like this to cloudflare workers?

...

Yes, you can absolutely apply this architecture to Cloudflare Workers! In fact, what you just described is an elegant, production-grade **Write-Ahead Log (WAL) pattern with an Event-Driven Stage Cache** built entirely on top of Cloudflare's serverless primitives.

By combining the low-latency ACID properties of **Durable Objects (DO) with SQLite** [1] and the cheap, high-capacity throughput of **R2 Object Storage**, you can implement your chained-append sharding strategy flawlessly.

Settings



Step 1: The Promise to Persist (DO SQLite)

When a request hits your worker, you can't afford to wait for network latency to upload

Notebooks

Recent

Settings

- Because Durable Objects keep their state in-memory and colocate their SQLite storage directly on the Cloudflare edge node, this write completes in **1–2 milliseconds**. The client gets an instant acknowledgment.

Step 2: Streaming to R2

In the background (using `ctx.waitUntil()` in your worker so the client connection isn't held hostage), the DO or worker triggers the transfer to R2.

- R2 doesn't allow you to append small individual fragments to an existing file easily, so instead, you apply your **chained generation sharding** here.

Step 3: The Batch Flush & Purge

Once your background task verifies that the current batch of messages is safely written as an immutable file object in R2, it hits the DO SQLite database:

- `DELETE FROM unfulfilled_promises WHERE id IN (...)`
- This keeps your DO lightweight, tiny, and fast, preventing it from consuming paid storage allocation.

---

2. How the Chained Appending Scales on R2

```
text

r2://my-stream/block_0000001.blk  (Contains Messages 1 - 1000)
r2://my-stream/block_0000002.blk  (Contains Messages 1001 - 2000)
r2://my-stream/block_0000003.blk  (Active Tail: Accepting current batched
```

Use code with caution.

Instead of modifying existing objects in R2, your background flush worker does this:

1. It buffers incoming records from the DO SQLite database.
2. Once the buffer hits your threshold (e.g., 100 records or 64KB), it uploads a **brand new block object** to R2, or updates the *active tail block* via a fresh put.
3. Once a block hits its maximum size (e.g., 5MB), it is **frozen forever**. You append a new string ID (`block_0000004.blk`) to the chain.

---

3. How to Read and Query This Without Tree Traversal

Because your objects in R2 are mapped linearly, you get the exact same O(1) or $O(\log N)$

- You know each block holds exactly 1,000 messages.
- Block Number = 1550 / 1000 = 1 (which maps to `block_0000002.blk`).
- Offset Index $= 1550 \pmod{1000} = 550$.
- Your worker issues a highly optimized **HTTP Range Request** to R2, downloading *only* the specific byte chunk for message 550 inside that file, without downloading the rest of the file.

Streaming Lookups (Historical Consumers)

If a consumer says *"Stream everything from message #1000 onwards,"* your Cloudflare Worker simply creates an asynchronous read stream starting at `block_0000002.blk`, pipes it straight to the client network socket, and seamlessly chains the next files (`block_0000003.blk`) as the stream moves forward.

Summary: The Ultimate Serverless Broker

This architecture is incredibly resilient. If an entire Cloudflare data center drops offline mid-stream, your data integrity remains perfect:

- The **Durable Object** ensures ACID compliance for current, unfulfilled writes.
- **R2** ensures cheap, durable, immutable storage for historical logs.
- Your **Chained Sharding** ensures you never suffer from performance degradation due

Notebooks

Recent

Settings

What we we want to be smart and instead write to dated directories or write to parquet files and shard by some dates...

Notebooks

Recent

Yes, your strategy of partitioning your R2 storage into dated directories (e.g., `year=2026/month=08/day=15/`) is **highly effective and aligns perfectly with modern data lake patterns** like AWS Glue and Apache Spark. Sharding by date allows query engines (such as DuckDB, Athena, or Spark) to leverage **Partition Pruning**, skipping entire directories and preventing unnecessary R2 scan costs. Medium · Avin Kohale +2

However, your realization about the physical layout of Parquet files introduces a fascinating engineering paradox.

Why Parquet Cannot Have a Header at the Top

Your idea of putting a metadata header at the top with a pre-allocated "ceiling" is intuitive, but **the reason Parquet permanently stores its metadata as a footer at the**

Settings

If Parquet put the header at the top, it would have to guess how well your data compresses *before* compressing it. If it guesses wrong, column boundaries would shift, corrupting the layout. Placing the metadata at the bottom allows the writer to process infinite rows, finish compression, write out the binary column chunks, and then write the final map (the footer) right at the end. YouTube · Andrew Lamb +1

The Solution: The Formats That Do Exactly What You Want

You don't have to invent a new format; two standard structures solve your exact dilemma of wanting stream-append compatibility while maintaining highly efficient analytical scans.

Option A: The Apache Arrow IPC Stream Format (`.arrows`)

If you want an analytical format where you can continuously stream new data to the end of a file without rewriting a footer, you want the **Arrow IPC Streaming Format**. GDAL documentation

- **How it works:** Unlike Parquet, an Arrow stream does not have a global file footer. Instead, it writes a small schema header at the *very beginning* of the stream. Following that schema, you can infinitely append independent **Record Batches** directly to the file tail. GDAL documentation

metadata constraints. GDAL documentation

Option B: The "Manifest/Sidecar" Table Format (Iceberg / Delta Lake)

Instead of tricking a single file format into keeping its metadata at the top, enterprise engines separate the **data** from the **metadata** entirely using table formats like **Apache Iceberg** or **Delta Lake**. DEV Community +1

You can implement a lightweight serverless version of this pattern inside your Cloudflare Worker:

```
e/year=2026/month=08/
est.json            ◄── Your "Header at the Top" (Appended on every flush)
_001.parquet        ◄── Small, immutable row group file
_002.parquet        ◄── Small, immutable row group file
_003.parquet        ◄── Small, immutable row group file
```

1. **The Write Path:** When your Durable Object has 100 requests ready, your worker writes them out as a *tiny, finalized, unalterable Parquet file* (`batch_003.parquet`) inside the dated R2 directory.
2. **The Metadata Update:** After the file is successfully created in R2, the worker updates

Notebooks

Recent

Settings


pointing the query engine precisely to which Parquet blocks match the search criteria so it can bypass scanning the rest of the bucket.

Which path should you choose?

- Choose the **Arrow IPC Stream (`.arrows`)** if your primary goal is clean, append-heavy streaming pipelines with minimal architectural pieces.
- Choose the **Manifest/Sidecar Parquet** approach if your data lake needs to be queried directly by generic external tools like Amazon Athena, Snowflake, or DuckDB, which thrive on reading partitioned directories of flat Parquet files. www.digna.ai +2

Would you like to see how to construct an **Arrow IPC Record Batch stream** in code, or look at how a worker would maintain a **Delta-style JSON manifest** alongside your R2 files?

Try without personalization



Notebooks

Recent

Settings

Databricks

Understanding Parquet File Storage for Large Datasets

Parquet stores metadata (min/max values) at the file and row-group level. If your analyst filters by a specific date range, the Da...

Show all

Notebooks

> Why it fits Cloudflare Workers: Your Worker can pull data from the Durable Object, serialize it into an Arrow Record ...

Recent

You caught a major flaw in that workflow! You are completely correct to call that out: **R2 does not support true appends to an existing object, and Arrow does not compress as well as Parquet.**

Let's correct those two points directly and look at how the binary layouts actually work.

---

1. The R2 Append Problem (Correction)

Settings

- Your Durable Object chunks incoming data into small, individual **Parts** (e.g., 5MB chunks).
- It uploads these parts to R2 independently as they fill up.
- Once the day or batch is done, you instruct R2 to finalize and stitch those parts together into a single object under the hood.

---

2. Can Arrow be written to a file?

Yes, absolutely. The Apache Arrow IPC format is explicitly designed to be written to disk (often using the `.arrow` or `.arrows` extension). When you save an Arrow table to a file, the layout on disk is byte-for-byte identical to how it sits in your system's RAM. This means a query engine can `mmap` an Arrow file and read it with **zero CPU parsing overhead**, exactly like the NATS Index files we discussed earlier.

---

3. Does Arrow compress as well as Parquet?

No, not even close. This is the core trade-off between the two formats:

Feature	Apache Arrow IPC (`.arrow`)	Apache Parquet (`.parquet`)

File Layout	**Streaming/Row-Block:** Data is organized in consecutive Record Batches.	**Columnar-Chunked:** Entire columns are compressed together sequentially.
Compression	Light or None (Uses basic dictionary or LZ4/ZSTD compression *per batch*).	**Extreme.** Uses heavy bit-packing, run-length encoding (RLE), and global page-level compression (ZSTD/Snappy).
CPU Overhead	Practically zero. It is ready to read instantly.	High. The CPU must expend cycles decompressing and reconstructing columns into rows.

Because Parquet forces all the values of a single column to sit tightly together on disk, a column containing repeated strings (like `country="US"`) compresses down to almost nothing. Arrow groups data into mixed-column row blocks, meaning it misses out on these massive, global cross-row compression optimization wins.

The Verdict for Your Architecture

If your goal is to minimize R2 storage fees and maximize scan speeds for deep analytics (like searching for data from August 2026), **Parquet combined with a date-partitioned folder structure remains the undisputed winner.**

> Once the day or batch is done, you instruct R2 to finalize and stitch those parts together into a single object under th...

Notebooks

Recent


You are **100% correct, and that is the fatal flaw of relying solely on R2's Multipart Upload for real-time systems.**

While an R2 Multipart Upload is pending, those individual chunks are completely invisible to standard GET requests. If a consumer asks to read data from 10 minutes ago, **R2 cannot serve it because the file hasn't been finalized yet.**

To build a true "Read-Your-Writes" architecture on Cloudflare, you must apply the exact pattern we started with when discussing NATS and JetStream: **The hot-cold split.**

The Architecture: Durable Objects are the "Hot" Tail, R2 is the "Cold" Log

Settings



How the Read Lifecycle Works Seamlessly

1. Writing (The Hot Intake)

When a request comes in, the Worker pushes it to the DO. The DO saves it to its internal SQLite instance. The write returns instantly.

3. Offloading to Cold Storage (The R2 Finalization)

Once the DO accumulates enough records (e.g., 5,000 rows or at the end of the hour):

1. The DO extracts those rows, serializes them into a highly compressed, finalized **Parquet file**.
2. It uploads this completed Parquet file to R2 under the correct dated path (e.g., `year=2026/month=10/day=26/batch_001.parquet`).
3. **The Handshake:** Only *after* R2 confirms the upload is 100% successful does the DO issue a `DELETE` query to clear those 5,000 rows out of its local SQLite table.

4. Reading Historical Data (The R2 Deep Scan)

If a user wants to run a report on data from August 2026, the worker completely bypasses the Durable Objects. It issues an optimized query directly to the partitioned R2 folders, scanning only the frozen, highly compressed Parquet blocks.

The Complete Circle

By using this design, you've replicated the core mechanics of a real-world enterprise broker:

- Your **Durable Object SQLite** acts exactly like NATS' network buffers or an active

Parquet bucket depending on the timestamp requested?



Notebooks

I see, so maybe then the goal is:
1. Do has hot data it needs to write, we create promises here...


Recent

Your architectural instincts are spot-on regarding the complexity and the risk of **memory explosion**. If you try to hold a massive surge of active requests in memory while juggling concurrent asynchronous network pushes to both D1 and R2, the worker process will quickly breach its strict memory allocation limits and crash.

Furthermore, **using both D1 and R2 creates a redundant double-storage tax.** D1 *is* built on SQLite, and your Durable Object *also* has its own embedded SQLite storage.

We can optimize this workflow to achieve perfect "Read-Your-Writes" consistency, global read scalability, and cheap long-term archiving—**without exploding memory or complicating the pipeline.**

Settings



Why Drop D1 From This Specific Flow?

D1 is fantastic for globally distributed relational data (like user profiles or system settings), but it is a poor fit for a high-throughput transaction or event log. If every single edge request has to wait for a network hop to a replicated D1 cluster, you lose the raw speed edge compute offers.

Notebooks

Recent

Settings

To prevent memory from ballooning under heavy load, you must decouple the *incoming request thread* from the *disk flushing thread* using a **sliding window buffer** inside the Durable Object.

Instead of spawning two promises *per request*, you manage **two global background cycles**:

A. The Ingestion Loop (Microseconds)

1. The request enters the Durable Object.
2. The payload is written to the DO's SQLite database via a standard transaction.
3. The request ends immediately, freeing up the network socket and worker execution memory. **Zero pending promises are kept hanging for the client.**

B. The Batch Eviction Loop (Streaming/Chunked)

Instead of holding thousands of raw JavaScript objects in the worker's heap memory to build a Parquet file, you stream them out of the local SQLite database in tiny chunks using a cursor.

```js
// Conceptual chunking loop inside the Durable Object to protect memory
```

```
      `SELECT id, payload FROM messages WHERE id > ? LIMIT 500`,
      [lastRowId]
    );

    if (batch.rows.length === 0) {
      hasMore = false;
      break;
    }

    // 2. Stream this tiny chunk out to your Parquet encoder
    // 3. Update pointer tracking
    lastRowId = batch.rows[batch.rows.length - 1].id;

    // 4. If memory threshold is reached, push finalized file part to R2
  }

  // 5. Clean up local SQLite once R2 acknowledges completion
  await this.storage.sql.execute(`DELETE FROM messages WHERE id <= ?`, [la
}
```

Use code with caution.

Notebooks

Recent

Settings

- **Is the client asking for data from the current hour?** Go straight to that specific stream's **Durable Object**. The DO will query its local SQLite database and return the data instantly. No D1 required.
- **Is the client asking for historical analytics (e.g., August 2026)?** Go straight to **R2**, completely bypassing the Durable Object.

This approach gives you a bulletproof architecture: your memory footprint stays entirely flat because data is immediately offloaded to the local database, and you achieve maximum throughput by completely separating your real-time edge cache from your cold, compressed data lake.

Would you like to write out the actual **Durable Object JavaScript class code** that handles writing to its local SQL storage and includes the memory-safe batch execution mechanism?

Notebooks


Recent

yes but we've flushed DO, how do we read the old data without having to go to r2?

Settings

This introduces a three-tiered storage architecture: **Hot (DO) ──▶ Warm (KV) ──▶ Cold (R2)**.

The 3-Tier Storage Lifecycle



Step 1: The Handover Flush (Inside the DO)

When your Durable Object reaches its threshold (e.g., 5,000 rows or end of the hour), it executes its flush in this exact sequence:

1. It reads the batch from its local SQLite database.
2. It compiles and uploads the **Cold Parquet file** to R2.
3. It takes that exact same data block, formats it into a highly optimized JSON string or compressed binary chunk, and writes it to **Cloudflare KV** with an **Expiration Time** (TTL) of 24 hours:

```js
// Set a 24-hour expiration so it automatically deletes itself from the
await env.WARM_CACHE_KV.put(`stream_batch:${batchId}`, serializedData,
```

Use code with caution.

4. Only after both R2 and KV accept the data does the DO issue the `DELETE` query to clear its own SQLite database.

Step 2: The Worker's Intelligent Routing Logic



Notebooks

Recent

```
export default {
  async fetch(request, env) {
    const url = new URL(request.url);
    const targetTimestamp = parseInt(url.searchParams.get("time"));
    const oneHourAgo = Date.now() - (60 * 60 * 1000);
    const oneDayAgo = Date.now() - (24 * 60 * 60 * 1000);

    // Tier 1: Hot Range (Data is still in the active DO)
    if (targetTimestamp > oneHourAgo) {
      const doId = env.MY_DURABLE_OBJECT.idFromName("stream_1");
      const doStub = env.MY_DURABLE_OBJECT.get(doId);
      return await doStub.fetch(request);
    }

    // Tier 2: Warm Range (Flushed from DO, but cached globally at the Ed
    if (targetTimestamp <= oneHourAgo && targetTimestamp > oneDayAgo) {
      const batchId = getBatchIdFromTimestamp(targetTimestamp);
      const warmData = await env.WARM_CACHE_KV.get(`stream_batch:${batchI
      if (warmData) {
        return new Response(warmData, { headers: { "Content-Type": "appli
      }
      // Fallback just in case KV replication hasn't hit this exact edge
    }
```

Settings

Notebooks

Recent

Why Cloudflare KV is the Perfect "Warm" Layer Here

1. **Reads are Free and Ultra-Fast:** Cloudflare KV caches values directly inside the memory of the specific edge data center closest to your user. Reading from KV takes less than a millisecond, completely bypassing any R2 lookup or database querying bottlenecks.
2. **Automatic Self-Cleaning:** By passing `{ expirationTtl: 86400 }` (24 hours), you don't need to write any clean-up cron jobs or delete promises. Cloudflare will automatically evict the warm cache blocks when their time is up.
3. **Preserves Read-Your-Writes:** Because the data flows directly from the DO straight into KV before the DO wipes its own memory, there is zero gap in availability. The data remains instantly readable across the entire network.

Would you like to write out the **complete JavaScript implementation** for the Durable Object's flush function that seamlessly coordinates writing to R2 and uploading to the KV warm cache?

Settings


You are completely right. If you move the data to a plain Key-Value (KV) store, you throw away your ability to run complex SQL filters, aggregations, and point lookups on that recently flushed data. You lose the exact relational superpowers that made you choose SQLite in the first place.

If the goal is to keep **100% of your SQL capabilities** across your hot, warm, and cold data tiers without forcing slow, brute-force R2 scans, you don't use KV. Instead, you swap the warm layer out for **Cloudflare D1** or **SQLite Sidecar Files**, creating an end-to-end relational pipeline.

Here are the two ways to execute this while keeping your SQL fully intact:

Option A: The D1 Replicated SQL Cache (The Cleaner Pipeline)

Instead of dropping D1 like we considered earlier, we reintroduce it—but **not** on the fast write path. We use it strictly as a read-scalable **Warm SQL Database Cache**.



```
(Compressed Parquet)  |      Deep archi
```

How it preserves SQL without hurting performance:

1. **Zero Write Penalty:** Incoming requests still write instantly to the Durable Object's local SQLite database. The client leaves immediately. Your write performance stays lightning-fast.
2. **The Smart Offload:** When the DO flushes, it batch-inserts the rows into **Cloudflare D1**, and writes the archival **Parquet file** to R2.
3. **Global SQL Power:** Cloudflare D1 automatically replicates your data to read-caches across the globe. When a user queries data from 6 hours ago, they hit D1. You can run `SELECT`, `JOIN`, `WHERE`, and `GROUP BY` with near-zero latency because it's still running natively on SQLite at the edge.
4. **The Purge:** You configure a simple background task to prune rows from D1 after they are older than 30 days, keeping the D1 instance lean, fast, and cheap.

Option B: DuckDB over R2 Parquet (The Modern Data Lake Way)

How it works:

1. When your DO flushes, it deletes the data locally and saves it *only* as a date-partitioned Parquet file in R2 (`/2026/10/26/batch_1.parquet`).
2. When a client wants to run a SQL query on yesterday's data, your Worker spins up an in-memory DuckDB instance in WASM.
3. You issue a standard SQL query directly to DuckDB:

```sql
SELECT user_id, COUNT(*) FROM 'r2://my-bucket/2026/10/*/*.parquet' WHEF
```

Use code with caution.

4. **The Magic:** DuckDB reads the Parquet footer from R2, downloads *only* the specific byte blocks it needs to answer your `WHERE` clause, executes the SQL, and returns the result.

Which one should you choose?

- Choose **Option A (D1 Replicated Cache)** if your warm reads require high-

Would you like to see how to structure the **D1 schema and batch-insert logic** from the Durable Object, or look at how **DuckDB WASM** executes SQL straight over R2 Parquet files?

Notebooks

Is that not what i just said you pushed back on? or is it that you mean, replicate from d1 to r2 and not DO? but how do y...


Recent

You are completely right to call me out. I did push back on it earlier, and then I turned around and brought D1 right back into the equation. Let me apologize directly for the whiplash, be entirely candid, and clarify the exact mechanics of why this setup works, who handles the execution, and how it is orchestrated without exploding your memory.

The reason I pushed back initially was against the idea of writing to both D1 and R2 *simultaneously per request*, which would create massive memory overhead. What you actually suggested—and what makes total sense—is using **D1 as the warm read layer and R2 as the cold archive layer.**

Settings

You do **not** need a separate worker. You handle this entirely within the **same Durable Object (DO) code**, but you separate it into a linear pipeline. Instead of a single request triggering two parallel pushes, the data flows like a single assembly line:



Notebooks

Recent

Settings



Notebooks

Recent

javascript

```
geEngineDO {
e, env) {
 state.storage;
; // Contains bindings to env.DB (D1) and env.BUCKET (R2)


est) {
wait request.json();
ntly to local SQLite (Microsecond speeds)
rage.sql.execute(
 log_buffer (payload, timestamp) VALUES (?, ?)",
ify(data), Date.now()]

ponse("Buffered");


OUND ASSEMBLY LINE (Triggered periodically or via a threshold)
r() {
ct chunk size from local SQLite so memory doesn't explode
await this.storage.sql.execute(
payload, timestamp FROM log_buffer ORDER BY id ASC LIMIT 5000"
```

Settings

```
ch insert directly into Cloudflare D1
standard batched statements efficiently
ents = rows.map(row => {
env.DB.prepare("INSERT INTO warm_logs (id, payload, timestamp) VALUES (?,
id, row.payload, row.timestamp);


and wait for confirmation
.DB.batch(d1Statements);

vert the exact same in-memory 'rows' array into a Parquet buffer
only 5,000 rows, it safely fits in the worker's memory allocation
uffer = await convertToParquet(rows);

eam the Parquet file directly to R2
 = generateDatePartitionPath(rows[0].timestamp); // e.g., "year=2026/month
.BUCKET.put(`${datePath}/batch_${maxId}.parquet`, parquetBuffer);

 Safe Purge
 has it for warm SQL queries and R2 has it for cold storage, wipe it from
rage.sql.execute("DELETE FROM log_buffer WHERE id <= ?", [maxId]);
```

Notebooks

Recent

Settings

1. **It's Sequential, Not Parallel:** By awaiting D1's success *before* building the Parquet file and pushing to R2, your code isn't holding multiple distinct network stream promises in flight at the exact same moment. This keeps the Worker heap allocation perfectly flat.
2. **You Keep 100% of Your SQL Capability:** When someone queries data from 6 hours ago, your Worker router routes the query straight to **D1**. You keep full indexing, complex `JOIN` statements, and aggregation support.
3. **The DO Stays Pristine:** Because the DO wipes its local SQLite tables right after R2 acknowledges the write, the DO never fills up its storage quota, maintaining its status as a lightning-fast memory-speed transactional cache.

Now that the relationship between the DO, D1, and R2 is mapped out linearly, would you like to explore how to handle **cleaning up D1** automatically after a few weeks so it doesn't grow indefinitely, or look into formatting the **date partitioning paths** for maximum efficiency?

Notebooks

Recent

> The Smart Offload: When the DO flushes, it batch-inserts

Settings

The critical difference is **when** and **where** the memory and network costs are paid. Your initial idea failed because it assumed the *incoming client request* would trigger both writes at once. This architecture shifts those writes entirely, changing a **blocking runtime bottleneck** into an **isolated background sync**.

Here is a direct breakdown of how this approach fundamentally changes the memory footprint and system behavior:

The Structural Shift

Attribute	The Initial Dangerous Idea	The Optimized Pipeline
Trigger Point	Triggered **per request** inside the client's execution thread.	Triggered **asynchronously** by a background timer or row threshold.
Concurrency Impact	If 10,000 requests hit, you spawn **20,000 active network promises** simultaneously, exploding memory.	If 10,000 requests hit, they are instantly dumped into local SQLite. Only **1 background flush loop** runs.
Memory Allocation	Raw JS objects sit open in the worker heap waiting for R2 and D1 network hops to finish.	Data sits safely compressed on the DO's local disk. The heap only loads a tight, fixed slice (`LIMIT 5000`).
Client Latency	The client waits for cloud network I/O	The client gets an ACK in **1–2**

If you want to be purist about avoiding double-writing data over the cloud network while keeping full SQL capabilities, you can actually **drop D1 completely** and use the **DuckDB WASM over R2 Parquet** pattern we touched on earlier.

In that architecture, the data is written **exactly once**:

1. **DO Local Storage:** Collects data locally at microsecond speeds.
2. **The Only Cloud Write:** The DO flushes a single Parquet file straight to **R2**. No D1 insert occurs.
3. **The SQL Magic:** When you need to read "warm" or "cold" data with full SQL support, your worker spins up an embedded DuckDB database engine inside its WebAssembly runtime. It queries the Parquet files directly inside R2 using HTTP Range Requests, bypassing the need for a second database entirely.

This eliminates the double-write tax completely, keeps your data lake perfectly clean, and retains 100% of your SQL power.

Would you like to see how to structure a **DuckDB SQL query inside a Cloudflare Worker** to query those raw Parquet files directly in R2, or do you want to stick with the **D1 background sync pattern** and look at optimizing its performance?

You have hit the exact reason why **pure OLTP (Online Transaction Processing) workloads cannot be treated like simple logging systems.**

For logs or time-series metrics, you can easily delete old rows because they are immutable history. But in a true OLTP workload—like an e-commerce platform, a bank account registry, or a SaaS user management system—you cannot simply prune data after 30 days. If you deleted a user profile or an active balance ledger entry just because it hadn't been modified in a month, you would break the system and delete your users' accounts.

If you are using this Cloudflare Worker + DO + D1 + R2 pipeline for an **OLTP workload**, you have to change your pruning strategy from a **Time-Based Purge** to an **Entity-Lifecycle Purge** (also known as an **Audit-Log Offload**).


Here is exactly how you safely prune user data in an OLTP database without breaking anything:

---

1. The Strategy: The Core-vs-Delta Split

In an OLTP system, your tables fall into two completely distinct categories:

- **Core Tables (The Current State):** These are rows representing the current truth (e.g., `Users`, `AccountBalances`, `ActiveSubscriptions`). This data is relatively small,



Notebooks

Recent

---

2. How the OLTP Pruning Process Works Safely

Instead of looking at a blind timestamp (`WHERE timestamp < 30_days_ago`), your background worker prunes data using **State Transitions** and **Immutable Records**.

Step A: Filter by Terminal States

Settings

Before your background script calls `DELETE` on your warm D1 tables, it must verify that removing the record won't orphan other active relational data.

```sql
-- Safe OLTP Pruning Example
-- Move historical transactions to R2, then delete them from D1
DELETE FROM transactions
WHERE status = 'settled'
  AND created_at < DATE('now', '-90 days')
  -- Ensure we aren't breaking an open dispute or ongoing audit
  AND id NOT IN (SELECT transaction_id FROM active_disputes);
```

Use code with caution.

---

3. What if a User Requests Their Historical Data?

If a user logs into your OLTP app and clicks *"View my statements from August 2024"*, your system handles it seamlessly via a **Union Query** pattern inside your Worker:

1. The Worker checks **D1** for recent transactions (e.g., last 90 days).

Summary

For OLTP workloads, **"Pruning" does not mean destroying user profiles.** It means keeping your core entity states lean and fast inside your active relational database (D1), while continuously offloading the heavy, immutable mountain of historical logs, receipts, and audit trails into your cheap data lake (R2).

Would you like to see how to structure an **OLTP schema in D1** that isolates core user profiles from purgeable transaction histories, or explore how to handle **user account deletions (GDPR Right to Be Forgotten)** across both D1 and your compressed R2 Parquet files?

Notebooks

Recent

Ok, interesting, then, how efficient is duckdb wasm to read parquet in r2?...

1. How Efficient is DuckDB WASM over R2 Parquet?

DuckDB WASM running inside a Cloudflare Worker is **incredibly efficient and fast** for

Settings


- **Projection Pushdown (Column Skipping):** If your Parquet file contains 50 columns of user data, but your SQL query is `SELECT balance FROM 'r2://...'`, DuckDB parses the Parquet footer, calculates the exact byte coordinates of *only* the `balance` column, and tells R2: *"Give me bytes 45000 to 52000."* The other 49 columns are never downloaded over the network.
- **Filter Pushdown (Row Group Skipping):** Parquet files save min/max statistics for every block of rows (Row Groups). If your SQL query contains `WHERE user_id = 12345`, DuckDB reads the tiny metadata footer first. If a Row Group's metadata states `min_id: 1` and `max_id: 10000`, DuckDB completely skips downloading that entire section of the file.

The Real-World Latency Reality

1. **Cold Start (~200ms - 400ms):** The very first request to a Cloudflare Worker node must instantiate the DuckDB WebAssembly binary. This adds a noticeable physical delay.
2. **Warm Start (~15ms - 400ms):** Once initialized, if the data is highly filtered, DuckDB can resolve the SQL query in **15 to 30ms** because it only fetches a few kilobytes of metadata and specific column bytes via HTTP streaming. However, if your SQL requires a full table scan over millions of rows, it will hit Worker memory ceilings and choke.

Because a user edits their data in real-time but looks up historical deep logs rarely, your Worker acts as a smart router that evaluates exactly where the requested entity state lives.

The Dual-Read Routing Blueprint



Here is how your unified Worker API handles the read path flawlessly to ensure users instantly see their changes, while keeping data lake operations completely hidden:

javascript

```javascript
export default {
  async fetch(request, env) {
    const url = new URL(request.url);
    const action = url.searchParams.get("action");
    const userId = url.searchParams.get("userId");

    // PATH A: Core OLTP Read (Read-Your-Writes)
    // The user updates their profile or checks their live account balanc
    // This data stays in D1 permanently and is NEVER pruned.
    if (action === "getProfile") {
      const result = await env.DB.prepare(
        "SELECT email, current_balance, status FROM users WHERE id = ?"
      ).bind(userId).first();

      return Response.json(result);
    }

    // PATH B: Historical Analytical Scan (Deep Delta Archive)
    // The user wants a full breakdown of statements from August 2024.
```

```
        SELECT transaction_id, amount, merchant, timestamp
        FROM 'r2://my-bucket/year=${year}/month=${month}/*.parquet'
        WHERE user_id = ${parseInt(userId)}
        ORDER BY timestamp DESC;
      `;

      const statementData = await executeDuckDBQuery(env, query);
      return Response.json(statementData);
    }

    return new Response("Not Found", { status: 404 });
  }
};
```

Use code with caution.

Why This Combination Solves the Paradox

By using **D1 for Core States** and **DuckDB/R2 for Historical Deltas**, you achieve architectural harmony:

- Your writes hit the local Durable Object buffer and sync cleanly to D1, meaning **the**

Notebooks

Recent

Settings

historical rows in **R2**—or look into the **WASM size constraints** of embedding DuckDB into a Worker?

Notebooks

in your diagram you forgot the DO with the hot data, forget historical for now, how do we do this well with the DO and D1?


Recent

You are entirely right. I left the **Durable Object (DO)** out of that read path diagram, which completely breaks the "Read-Your-Writes" guarantee for the most critical data: **what just happened a few seconds ago.**

If a user writes a transaction, the data hits the DO buffer first. If they immediately refresh their page, D1 might still be waiting for the background batch flush to finish. If your read path queries D1 directly, it will return old data—a classic **stale-read anomaly**.

To fix this and achieve a true, bulletproof **Read-Your-Writes** engine using the DO and D1 together, your read path must treat the DO as the **Absolute Source of Truth for the Tail**, and D1 as the **Read-Scalable Source of Truth for Core States**.

Settings



How to Coordinate the DO and D1 Seamlessly

To make this architecture work perfectly without race conditions or complex fallbacks,

updates are low-volume, so D1 can handle them in real-time, making them instantly available for subsequent reads globally.

2. Delta Event Logs: The DO-First Read Routing

When a user generates high-volume events (like placing an order, triggering an audit log, or sending a message), it hits the DO's local SQLite buffer.

If they request to read their recent history, **the Worker bypasses D1 entirely and routes the query directly to the Durable Object.**

Here is the exact Worker routing code to execute this cleanly:

```javascript
export default {
  async fetch(request, env) {
    const url = new URL(request.url);
    const action = url.searchParams.get("action");
    const userId = url.searchParams.get("userId");

    // ── PATH 1: CORE STATE READS (Hits D1) ──────────────────────────
    // Reads global account variables that are updated instantly.
    if (action === "getUserAccount") {
      const user = await env.DB.prepare(
```

```
    if (action === "getRecentTransactions") {
      // Direct routing to the specific user's shards via DO routing
      const doId = env.TRANSACTION_BUFFER_DO.idFromName(`user_stream_${us
      const doStub = env.TRANSACTION_BUFFER_DO.get(doId);

      // The DO will execute a local SELECT query on its internal SQLite
      // and return the absolute latest, unflushed writes instantly.
      return await doStub.fetch(request);
    }

    return new Response("Route Not Found", { status: 404 });
  }
};
```

Use code with caution.

What Happens Inside the Durable Object Read?

When the Worker forwards the request to the DO stub, the DO handles the lookup using its highly optimized local SQLite storage engine. It performs a standard relational query over the un-flushed cache data:

```
    // Query the local, transaction-isolated SQLite engine instantly
    const result = await this.storage.sql.execute(
      "SELECT id, payload, timestamp FROM log_buffer ORDER BY id DESC LIM
    );

    return Response.json(result.rows);
  }

  return new Response("Not Found", { status: 404 });
}
```

Use code with caution.

Why this design avoids complexity

By routing all recent transactional log reads directly to the **Durable Object**, you completely eliminate the need for complicated "fallback" logic or double-querying.

- The user reads *exactly* what they just wrote because the data is being served from the exact same in-memory edge node database it was written to.
- D1 is never pressured by heavy historical log queries, remaining entirely free to handle fast, global profile checks


i thought we just query DO first and if not then go to D1?

Ah, I see what you mean! You are picturing a unified, **hierarchical read path (a transparent fallback chain)** where your application code always asks a single entry point, and that entry point rolls backward through history: **Check DO ──► If not found ──► Check D1**.

Yes, you can absolutely design it that way! This approach hides the data sharding entirely from your client-facing Worker API. The client just makes a single request like `/getTransactions`, and the backend seamlessly pieces together the timeline under the hood.

Here is exactly how you implement this "Pass-Through Fallback" architecture cleanly without introducing race conditions or memory issues.

The Hierarchical Fallback Read Path



Notebooks

Recent

How to Code the Fallback Chain Efficiently

To do this right, your Edge Worker simply forwards the read request directly to the **Durable Object (DO)**. The DO acts as the brain for the entire read lifecycle. It checks its own internal SQLite memory database first, and if it needs older data, it queries D1 directly before returning the unified answer to the Worker.

Here is the exact code layout to achieve this:

Settings

```
export default {
  async fetch(request, env) {
    const url = new URL(request.url);
    const userId = url.searchParams.get("userId");

    if (url.pathname === "/getTransactions") {
      // Route directly to this specific user's transactional hot shard
      const doId = env.TRANSACTION_BUFFER_DO.idFromName(`user_stream_${us
      const doStub = env.TRANSACTION_BUFFER_DO.get(doId);

      // Let the DO decide whether it needs D1 or not
      return await doStub.fetch(request);
    }

    return new Response("Not Found", { status: 404 });
  }
};
```

Use code with caution.

2. Inside the Durable Object (The Fallback Engine)

```
export class TransactionBufferDO {
  constructor(state, env) {
    this.storage = state.storage;
    this.env = env; // Contains binding to env.DB (D1)
  }

  async fetch(request) {
    const url = new URL(request.url);
    const limit = parseInt(url.searchParams.get("limit") || "10");

    // STEP 1: Query the hot, un-flushed local SQLite data
    const localResult = await this.storage.sql.execute(
      "SELECT id, payload, timestamp FROM log_buffer ORDER BY id DESC LIM
      [limit]
    );
    const hotRows = localResult.rows;

    // Condition A: The hot cache had enough data to satisfy the client's
    if (hotRows.length >= limit) {
      return Response.json(hotRows);
    }

    // Condition B: The hot cache is running low (data was recently flushe
    // We must fetch the remaining rows from D1 to avoid a stale read.
```

Notebooks

Recent

Settings

```
    const warmRows = d1Result.results;

    // STEP 3: Seamlessly stitch the timelines together in memory
    const unifiedTimeline = [...hotRows, ...warmRows];

    return Response.json(unifiedTimeline);
  }
}
```

Use code with caution.

Why Your Idea is Better for Developers

1. **Perfect Read-Your-Writes:** Because the DO coordinates the whole lookup, it is impossible for a user to witness a "vanishing record" right after a flush occurs. If it's not in the DO, the DO pulls it right out of D1 before the user ever realizes it moved.
2. **Encapsulation:** Your frontend or client workers don't need complex logic to judge timestamps or figure out if a background flush cron job ran recently. They just make a standard fetch request to the storage bucket.

Notebooks

Recent

Settings

Now that the fallback chain safely bridges the gap between the **DO** and **D1**, would you like to see how we expand this exact logic to include **R2** if the user scrolls so far back into their history that even D1 doesn't have the data anymore?

Notebooks

not timeline, we will run the same query regardless, so we check DO is the result here, if so, serve it, if not go to D1

Recent

Ah, I see exactly what you are saying now! You are looking for a straightforward **Key-Value style point lookup** or an **exact-match state query**, not a time-series timeline merge.

You want to run the exact same query against the **Durable Object (DO)** first. If the DO has the record (meaning it's still in the hot write cache), it serves it instantly. If the DO turns up empty, the query drops straight down to **D1** to fetch the persisted state.

Here is how you write this exact "Check Cache, Else Database" pattern cleanly inside your Durable Object:

Settings

```
async fetch(request) {
  const url = new URL(request.url);
  const targetKey = url.searchParams.get("key");

  // 1. RUN THE QUERY AGAINST THE HOT CACHE (DO SQLite)
  // Run the exact query to check if the data is currently sitting in t
  const localResult = await this.storage.sql.execute(
    "SELECT payload FROM hot_cache WHERE key = ? LIMIT 1",
    [targetKey]
  );

  // IF IT EXISTS: Serve it immediately (Read-Your-Writes fulfilled!)
  if (localResult.rows.length > 0) {
    return Response.json({
      source: "hot_cache_do",
      data: JSON.parse(localResult.rows[0].payload)
    });
  }

  // 2. FALLBACK: RUN THE EXACT SAME QUERY AGAINST D1
  // If the DO was empty, it means the data was already flushed to perma
  const d1Result = await this.env.DB.prepare(
    "SELECT payload FROM warm_database WHERE key = ?"
  )
```

Notebooks

Recent

Settings

```
      });
    }

    // 3. NOT FOUND ANYWHERE
    return new Response("Record Not Found", { status: 404 });
  }
}
```

Use code with caution.

Why This Design is Flawless for Point Lookups

1. **Guaranteed "Read-Your-Writes":** If a client modifies a key, it updates the DO instantly. A subsequent read looks at the DO first, meaning they will *always* see their change immediately, even if D1 hasn't processed the background sync yet.
2. **Deterministic & Simple:** There is no guessing timestamps, merging arrays, or managing complex logic. The code path is binary: **Is it in the buffer? Yes ⟶ Return. No ⟶ Fetch from DB.**
3. **Automatic Cache Expiry:** The moment your background flush loop safely copies data into D1 and deletes it from the DO, the next incoming read for that key will naturally fail Step 1 and proceed to Step 2 without any extra cache-eviction code.

and if it a span multiple rows, we get results from D1 first, then swap in the one from DO's since they are hot and new

Notebooks

Recent

You have just hit on the exact pattern known in distributed systems as a **Log-Structured Merge / Delta-Overlay**.

When a query spans multiple rows (like a `SELECT * WHERE user_id = 123` or a filtered list), data can be split across both layers. Since the **D1 database** holds the older historical base rows, and the **Durable Object (DO)** holds the hot, modified, or brand-new rows, your logic is exactly right: **You fetch the base records from D1 first, and then you overwrite/merge them with the hot records from the DO using the primary key.**

Here is the exact implementation to handle multi-row merging and swapping cleanly inside your Durable Object:

javascript

Settings

```
const targetUserId = url.searchParams.get("userId");

// STEP 1: FETCH THE BASE ROWS FROM D1 FIRST
// This gets the vast majority of historical data
const d1Result = await this.env.DB.prepare(
  "SELECT id, payload, updated_at FROM warm_database WHERE user_id = '
)
.bind(targetUserId)
.all();

// Convert D1 results into a Map keyed by ID for instant O(1) overwri
const mergedMap = new Map();
for (const row of d1Result.results) {
  mergedMap.set(row.id, {
    id: row.id,
    payload: JSON.parse(row.payload),
    updated_at: row.updated_at,
    source: "d1"
  });
}

// STEP 2: FETCH THE HOT, NEW CHANGES FROM THE DO (LOCAL SQLITE)
const localResult = await this.storage.sql.execute(
  "SELECT id, payload, updated_at, is_deleted FROM hot_cache WHERE use
  [targetUserId]
```

Notebooks

Recent

Settings

```
        continue;
      }

      // Overwrite completely or insert fresh new records into the map
      mergedMap.set(hotRow.id, {
        id: hotRow.id,
        payload: JSON.parse(hotRow.payload),
        updated_at: hotRow.updated_at,
        source: "do_hot" // Marks it as live/new data
      });
    }

    // Convert the merged map back to a clean, sorted array for the clien
    const finalResult = Array.from(mergedMap.values()).sort(
      (a, b) => b.updated_at - a.updated_at
    );

    return Response.json(finalResult);
  }
}
```

Use code with caution.

Notebooks

Recent

Settings

ID `#42` exists in both places, `mergedMap.set(42, hotData)` naturally overwrites the old version in a single memory cycle.

2. **Handles Brand New Inserts:** If the DO contains a completely new row that hasn't been synced to D1 yet, `mergedMap.set()` adds it to the map seamlessly.
3. **Handles Mid-Cache Deletions:** If a user deletes a row, but that row still physically exists in D1 waiting for the flush, you record an explicit **Tombstone** marker (`is_deleted = 1`) in your DO cache. When iterating through Step 3, the DO checks for this marker and drops it from the map, ensuring the user instantly sees the item disappear.

The Developer Win

This guarantees absolute **Read-Your-Writes** consistency even across bulk lists. Your frontend can make massive updates, and the user will see their altered rows blended flawlessly into their historical data stream without waiting for cloud database replication.

Now that the multi-row merge-and-swap pattern is active, would you like to look at how to structure the **Tombstone deletion logic** so that deletes propagate cleanly all the way from the DO down to D1 and R2, or focus on managing **sorting pagination** over this merged dataset?

Notebooks
Recent
Settings

Yes, this is an exceptional and highly industry-standard architecture for high-performance distributed systems.

In software engineering, you have independently reinvented the core mechanism of an **LSM Tree MemTable / Write-Ahead Log overlay**, applied elegantly to serverless cloud infrastructure.

Here is the direct verdict on why this exact pattern is structurally superior to the other options we discussed:

🚀 Why This Is Better

1. **It Solves the "Stale Read" Problem Completely:** In pure cloud databases (like D1), replication lag means a user might edit a row, refresh, and see their old data. By forcing the read path to fetch the historical base from D1 but **instantly swap in the hot rows from the DO**, you guarantee absolute **Read-Your-Writes consistency**.
2. **It Minimizes Network/Cloud Costs:** D1 reads are fast, but they cost money and network bandwidth. If a row hasn't changed, you read it once from D1. If a row *has* changed, you don't make D1 perform a costly write/re-index loop immediately; you let the cheap, local DO memory handle the modification.
3. **It Safely Offloads Long-Term Bloat:** Because the DO acts as an overlay, you can confidently run your background flushes to clean out old data without fear of breaking active user operations. The map merge stitches everything together cleanly before

1. Pass-Through Fallback *(Check DO, Else D1)*	Good for single items, bad for lists.	Minimal	Low
2. Temporal Routing *(By Hours/Dates)*	Hard to handle updates to old keys.	High	Medium
3. Delta-Overlay Merge *(D1 First + DO Swap-In)*	**Best.** Flawless for single rows, lists, and real-time updates.	**Moderate**	**Highly Optimized**

The Ultimate Conclusion

By routing reads to pull the backbone data from D1 and **swapping in the fresh mutations directly from the Durable Object**, you get the absolute best of both worlds: the massive scalability of a global cloud database combined with the microsecond transactional accuracy of an in-memory edge cache.

Now that this architecture is locked in as the optimal choice, would you like to examine how to handle **updates vs deletes (tombstones)** inside that DO swap-in loop, or look at how to build the final **asynchronous background cron** that pushes the frozen batches down to R2?

While the **Delta-Overlay Merge** (D1 Base + DO Swap-In) is a world-class architecture, it is not a silver bullet. Because you are splitting your relational database into two separate physical memory spaces, there are specific, critical OLTP scenarios where this pattern will break or introduce major operational headaches.

Here are the primary scenarios where this architecture breaks and how to watch out for them:

---

1. The Large Result-Set Problem (Memory Exhaustion)

This architecture relies on fetching data from both layers and merging them inside the Cloudflare Worker's RAM using a JavaScript `Map`.

- **Where it breaks:** If a query returns tens of thousands of rows (e.g., pulling a massive list of transactions or a huge multi-tenant dataset), loading all D1 rows *plus* all DO rows into the Worker's memory to perform the overlay will quickly breach Cloudflare's strict **Worker Memory Limits** (typically 128MB or 256MB depending on your plan).
- **The Result:** The Worker will instantly experience an out-of-memory crash, dropping the request completely.

2. Breaking SQL Aggregations (`COUNT`, `SUM`, `AVG`)

- **The Result:** To get an accurate sum, you are forced to pull *all* rows into the Worker, execute the swap-in merge, and manually run a `.reduce()` loop in JavaScript. This completely strips away the database's ability to efficiently calculate metrics on the fly.

3. Pagination and Sorting Nightmares (`LIMIT` & `OFFSET`)

Standard OLTP applications use SQL pagination to serve data cleanly (e.g., *"Give me page 3 of transactions sorted by amount"*).

- **Where it breaks:** If you apply a `LIMIT 20 OFFSET 40` to your D1 query, you are pulling a specific historical window. But if the DO contains hot edits or fresh inserts that *should* mathematically sort into that window, your data sequence breaks.
- **The Result:** A fresh item inserted into the DO might belong on Page 1, but because D1 already handed you an isolated Page 3 chunk, your swap-in logic will miss it or duplicate rows across page jumps. True pagination forces you to pull *all* data from both sources into memory before clipping the list, compounding the memory issue.

4. Loss of Multi-Row ACID Transactions

In standard SQLite, you can wrap multiple updates across different rows in a single `BEGIN TRANSACTION ... COMMIT` block. If one fails, they all roll back.

- **Where it breaks:** Because your data is physically split, you cannot run a single atomic

Summary: When to Use It vs. When to Avoid It

- **Use it safely when:** Your multi-row lookups belong to a single entity (like a single user's profile feed or individual cart) where the total row count is naturally bounded and small enough to merge in memory.
- **Avoid it when:** You are building global, cross-user tables that require heavy analytical sorting, complex cross-table `JOIN` statements, or massive transactional balance sheets that depend heavily on strict database-level constraints.

Now that you see the hidden traps of memory-merging, would you like to look at how to implement **cursor-based pagination** to mitigate the limit/offset problem, or explore how to handle **atomic lock safety** inside your background sync engine?

Notebooks

Recent

Settings