

WIZARPOS International Co., Ltd.

EMV Kernel Interface

version 1.0

control info

version	Date	Description	who
1.00	2013-12-20	create	Michael Li

1. IC READER	5
1.1 OPEN READER AND WAIT CARD.....	5
1.2 CLOSE READER.....	5
1.3 GET CURRENT CARD TYPE	5
1.4 GET CARD ATR.....	5
1.5 APDU COMMAND	5
2. STORE AND SET EMV DATA	6
2.1 CHECK THE EXISTENCE OF DATA FOR THE TAG	6
2.2 GET THE DATA FOR THE TAG	6
2.3 GET THE DATA FOR THE TAG LIST	6
2.4 SET THE DATA FOR THE TAG.....	7
3. EMV TRANSACTION PROCESSING.....	7
3.1 EMVKERNEL INITIALIZE	7
3.2 INITIALIZE EMV TRANSACTION DATA.....	8
3.3 EMV PROCESSING FUNCTION	8
4. OTHERS FUNCTIONS.....	9
4.1 GET EMV KERNEL VERSION	9
4.2 SET TRANSACTION AMOUNT	9
4.3 SET OTHER AMOUNT	9
4.4 SET TRANSACTION TYPE	9
4.5 SET EMV KERNEL TYPE.....	9
4.6 IS NEEDED ADVICE THE TRANSACTION	10
4.7 IS NEEDED SIGN THE TRANSACTION	10
4.8 SET THE PARAMETER FOR FORCE ONLINE	10
4.9 READ TRANSACTION RECORD FROM THE CARD	10
4.10 GET APPLICATION LIST	10
4.11 SET THE SELECTED INDEX FOR APPLICATION SELECTION	11
4.12 SET THE RESULT FOR CARDHOLDER ID CHECK	11
4.13 SET THE RESULT FOR ONLINE PIN	11
4.14 SET ACCEPTANCE FOR BYPASS PIN	11
4.15 SET THE RESULT FOR ONLINE CERTIFICATION.....	11
5. SETUP EMVPARAMETERS.....	12
5.1 CLEAR AID INFO	12

5.2 ADD AID INFO	12
5.3 CLEAR CAPK INFO	13
5.4 ADD CAPK INFO	13
5.5 SET EMV TERMINAL PARAMETERS	14
5.6 CLEAR EXCEPTION FILE	14
5.8 ADD EXCEPTION FILE	14
5.9 CLEAR REVOKED CERTICATES.....	14
5.10 ADD REVOKED CERTIFICATE	15

1. IC Reader

1.1 open reader and wait card

```

/*
 * @param[in] reader : reader type      : 0   all of readers
 *                                     : 1   only contact reader
 *                                     : 2   only contactless reader
 * return value      : < 0   Fail
 *                   : >= 0   Success
 *   (If select open all of readers, any open success return success)
 */
int open_reader(int reader)

```

1.2 close reader

```

/*
 * @param[in] reader:  reader type  : 0 all of readers
 *                   : 1 only contact reader
 *                   : 2 only contactless reader
 */
void close_reader(int reader)

```

1.3 get current card type

```

/*
 * return value  : 1   contact card
 *               : 2   contactless card
 *               : -1  no card
 */
int get_card_type(void)

```

1.4 get card ATR

```

/*
 * @param[out] pATR : the value of ATR
 * return value  : the length of ATR
 */
int get_card_atr(unsigned char *pATR)

```

1.5 APDU command

```

/*
 * @param[in] cmd      :APDU command
 * @param[in] cmdLength : the length of APDU command

```

```

* @param[out] respData : the value of card response
* @param[in]  respDataLength : accepted max length of card response
* return value : >= 0 : the length of card response
*              < 0 : Fail
*/
int transmit_card( unsigned char *cmd,
                  int cmdLength,
                  unsigned char *respData,
                  int respDataLength)

```

2. store and set EMV data

2.1 check the existence of data for the tag

```

/*
* @param[in] tag : tag name
* return value : < 0 the data not exist
*              >= 0 the length of data
*/
int emv_is_tag_present(int tag)

```

2.2 get the data for the tag

```

/*
* @param[in] tag : tag name
* @param[out] data : the value of the data
* @param[in] dataLength : accepted max length of the data
* return value : < 0 : Fail
*              >= 0: the length of the data
*/
int emv_get_tag_data(int tag, unsigned char *data, int dataLength)

```

2.3 get the data for the tag list

```

/*
* @param[in] tagNames : the list of the tags
* @param[in] tagCount : the count of the tags
* @param[out] pTagsValue : the values of the data (TLV format)
* @param[in] pTagsValueLength : accepted max length of the data
* return value : < 0 : Fail
*              : >= 0: the length of the data
*/
int emv_get_tag_list_data(int *tagNames, int tagCount,
                        unsigned char *pTagsValue,
                        int pTagsValueLength);

```

2.4 set the data for the tag

```

/*
 * @param[in] tag    : tag name
 * @param[in] data    : the value of the data
 * @param[in] length : the length of the data
 * return value      : < 0 : Fail
 *                   : >= 0 : the tag的长度
 */
int emv_set_tag_data(int tag, unsigned char *data, int length)

```

3. EMV transaction processing

3.1 EMVKernel initialize

typedef struct

```

{
    // callback function for card event
    CARD_EVENT_OCCURED pCafEventOccurred;
    // callback function for EVM processing
    EMV_PROCESS_CALLBACK pEVMProcessCallback;
}EMV_INIT_DATA;
void emv_kernel_initialize(unsigned char *pInitData)

```

1) typedef void (*CARD_EVENT_OCCURED) (int eventType)

```

// any card event occurred, this function will be revoked
// @param[in] eventType : SMART_CARD_EVENT_INSERT_CARD = 0;
//                  : SMART_CARD_EVENT_REMOVE_CARD = 1;
//                  : SMART_CARD_EVENT_POWERON_ERROR = 9;
//                  : SMART_CARD_EVENT_CONTALESS_HAVE_MORE_CARD = 10;

```

2) typedef void (*EMV_PROCESS_CALLBACK)(unsigned char *pData);

```

// callback function for EVM processing, pData have 2 bytes
// unsigned char status = pData[0];
// unsigned char desc = pData[1];

```

* status:

```

* STATUS_ERROR = 0; //ERROR
* STATUS_CONTINUE = 1; // not completed, need to continue
* STATUS_COMPLETION = 2; // completed

```

* desc

```

* when status = STATUS_COMPLETION, desc means:
* APPROVE_OFFLINE = 1; //Transaction approved Offline
* APPROVE_ONLINE = 2; //Transaction approved Online
* DECLINE_OFFLINE = 3; //Transaction declined Offline
* DECLINE_ONLINE = 4; //Transaction declined Online

```

```

*
*   when status = STATUS_ERROR, desc means:
*       SUCCESS = 0; //SUCCESS
*       ERROR_NO_APP = 1; //No Application Selected when Application Select
*       ERROR_APP_BLOCKED = 2; //card return 6A81 when Application Select
*       ERROR_APP_SELECT = 3; //Error when Application Select
*       ERROR_INIT_APP = 4; //Error when Initialize Application Data
*       ERROR_EXPIRED_CARD = 5; // Card Expired
*       ERROR_APP_DATA = 6; //Error when Read Application Data
*       ERROR_DATA_INVALID = 7; // have invalid data
*       ERROR_DATA_AUTH = 8; // Fail in offline authentication
*       ERROR_GEN_AC = 9; //Generate AC error when Transaction Process
*       ERROR_PROCESS_CMD = 10; //Process Command ERROR
*       ERROR_SERVICE_NOT_ALLOWED = 11; //Service not Allowed
*       ERROR_PINENTRY_TIMEOUT = 12; //PIN Entry timeout
*       ERROR_OFFLINE_VERIFY = 13; //Check Offline PIN Error when Cardholder Verify
*       ERROR_NEED_ADVICE = 14; //Communication Error with Host, but the card need
advice, halted the transaction
*       ERROR_USER_CANCELLED = 15;
*       ERROR_AMOUNT_OVER_LIMIT = 16; // amount over limit
*       ERROR_AMOUNT_ZERO = 17; // amount can not be zero
*       ERROR_OTHER_CARD = 18; // Please try other card
*
*   when status = STATUS_CONTINUE, desc means:
*       EMV_CANDIDATE_LIST = 1; //notify Application show Application Candidate List
*       EMV_APP_SELECTED = 2; //Application Select Completed
*       EMV_READ_APP_DATA = 3; //Read Application Data Completed
*       EMV_DATA_AUTH = 4; //Data Authentication Completed
*       EMV_OFFLINE_PIN = 5; // notify Application prompt Caldholder enter offline PIN,
*       EMV_ONLINE_ENC_PIN = 6; //notify Application prompt Caldholder enter Online
PIN
*       EMV_PIN_BYPASS_CONFIRM = 7; //notify Application confirm to Accepted PIN
Bypass or not
*       EMV_PROCESS_ONLINE = 8; //notify Application to Process Online
*       EMV_ID_CHECK = 9; //notify Application Check Cardholder's Identification
*/

```

3.2 Initialize EMV transaction data

```
void emv_trans_initialize(void)
```

3.3 EMV processing function

```

/*
* return value: >=0 SUCCESS, <0 Fail
*/

```



```
int emv_process_next(void)
```

4. Others functions

4.1 Get EMV Kernel version

```
/**
 * @param[out] buffer: the value of emv kernel version
 * @param[in] bufferLength: accepted max length of emv kernel version
 * return value: the length of emv kernel version
 */
int emv_get_version_string(unsigned char *buffer, int bufferLength)
```

4.2 Set transaction amount

```
/**
 * @param[in] amount: '\0' as ending mark
 * return value: >=0 Success; < 0 Fail
 */
int emv_set_trans_amount(unsigned char *amount)
```

4.3 Set other amount

```
/**
 * @param[in] amount: '\0' as ending mark
 * return value: >=0 Success; < 0 Fail
 */
int emv_set_other_amount(unsigned char *amount)
```

4.4 Set transaction type

```
int emv_set_trans_type(unsigned char transType)
```

```
#define TRANS_GOODS_SERVICE    0x00
#define TRANS_CASH              0x01
#define TRANS_INQUIRY          0x04
#define TRANS_TRANSFER         0x05
#define TRANS_PAYMENT          0x06
#define TRANS_ADMIN            0x07
#define TRANS_CASHBACK         0x09
#define TRANS_CARD_RECORD      0x0A
```

4.5 set emv kernel type

```
/**
```

```

* @param[in] kernelType:  1    EMV KERNAL
*                        2    QPBOC KERNAL for China
*                        3    UPCASH_KERNAL for China
*/
int emv_set_kernel_type(unsigned char kernelType)

```

4.6 Is needed advice the transaction

```

/**
* return value:  1 need advice
*              0 not need advice
*/
int emv_is_need_advice(void)

```

4.7 Is needed sign the transaction

```

/**
* return value:  1 need sign
*              0 not need sign
*/
int emv_is_need_signature(void)

```

4.8 Set the parameter for force online

```

/**
* @param[in] flag:  flag=1 Yes,  flag = 0 No
*/
int emv_set_force_online(int flag)

```

4.9 Read transaction record from the card

```

/**
* @param[out] data      : transaction record
* @param[in]  dataLength : accepted max length for the transaction record
* return value          : < 0 : Fail
*                      : >= 0: record count
*/
int emv_get_card_record(uint8_t *data, int dataLength)

```

4.10 Get application list

```

/**
* @param[out] data : application list as "LV" format
* @param[in]  dataLength : accepted max length for application list
* return value          : < 0 : Fail
*                      : >= 0: application count
*/
int emv_get_candidate_list(uint8_t *data, int dataLength)

```

4.11 Set the selected index for application selection

```
/**
 * @param[in] index : the selected index (started by 0)
 * return value : < 0 : Fail
 *              : >= 0: Success
 */
int emv_set_candidate_list_result(int index)
```

4.12 Set the result for cardholder ID check

```
/* ID Type (9F62) 、ID Number(9F61)
 * @param[in] result : 0: check Fail, 1:check success
 * return value : < 0 : Fail
 *              : >= 0: Success
 */
int emv_set_id_check_result(int result)
```

4.13 Set the result for Online PIN

```
/**
 * @param[in] result : 0: Online PIN not input, 1:Online PIN inputted
 * return value : < 0 : Fail
 *              : >= 0: Success
 */
int emv_set_online_pin_entered(int result)
```

4.14 Set acceptance for Bypass PIN

```
/**
 * @param[in] result : 0: refused bypass pin
 *                  1: accepted bypass pin
 * return value : < 0 : Fail
 *              : >= 0: Success
 */
int emv_set_pin_bypass_confirmed(int result)
```

4.15 Set the result for online certification

```
/**
 * @param[in] result : -1:communication failed; 0: host refused; 1: host accepted
 * @param[in] respCode : 2 bytes response code from the host
 * @param[in] issuerRespData : the emv data from the host
 * @param[in] issuerRespDataLength : the length of the emv data from the host
 * return value : < 0 : Fail
 *              : >= 0: Success
 */
int emv_set_online_result(int result,
```

```

        unsigned char *respCode,
        unsigned char *issuerRespData,
        int issuerRespDataLength)

```

5. Setup EMVparameters

5.1 Clear AID info

```

/**
 * return value: >=0: Success; < 0: Fail
 */
int emv_aidparam_clear(void)

```

5.2 Add AID info

```

/*
 * @param[in] data : see form below, format is TLV
 * @param[in] dataLength : the length of the data
 * return value      : < 0 : Fail
 *                   : >= 0: Success
 */
int emv_aidparam_add( uint8_t *data, int dataLength)

```

name	Format	length (byte)	tag
AID	b	5—16	9F06
Application selection Indicator (ASI)	b	1	DF01
Application version number	b	2	9F08
TAC—Default	b	5	DF11
TAC—Online	b	5	DF12
TAC—Denial	b	5	DF13
Terminal floor limit	b	4	9F1B
Threshold value for Biased Random Selection	b	4	DF15
Maximum Target Percentage to be used for Biased Random Selection	cn	1	DF16
Target Percentage to be used for Random Selection	cn	1	DF17
Default DDOL	b	Var.	DF14

name	Format	length (byte)	tag
Ability for Online PIN	b	1	DF18
Application Label	an	1-16	50
Application Preferred Name	an	1-16	9F12
Application Priority Indicator	b	1	87
Merchant Identifier	an	15	9F16
Acquirer Identifier	n	6-11	9F01
MCC	n	4	9F15
POS Entry Mode	n	2	9F39
Transaction Reference Currency Code	n	3	9F3C
Transaction Reference Currency Exponent	n	1	9F3D
Default TDOL	b	Var.	DF22

5.3 Clear CAPK info

```
/**
 * return value: >=0 Success; < 0 Fail
 */
int emv_capkparam_clear(void)
```

5.4 Add CAPK info

```
/*
 * @param[in] data : see form below, format is TLV
 * @param[in] dataLength : the length of the data
 * return value : < 0 : Fail
 * : >= 0: Success
 */
int emv_capkparam_add( uint8_t *data, int dataLength)
```

Name	Format	length (byte)	tag
RID	b	5	9F06
Certification Authority Public Key Index	b	1	9F22
Certification Authority Public Key Expiration Date	n8	8	DF05
Certification Authority Public Key hash Algorithm Indicator	b	1	DF06

Name	Format	length (byte)	tag
Certification Authority Public Key Algorithm Indicator	b	1	DF07
Certification Authority Public Key Modulus	b	Var.	DF02
Certification Authority Public Key Exponent	b	1 or 3	DF04
Certification Authority Public Key Checksum	b	Var.	DF03

5.5 Set EMV terminal parameters

```
typedef struct{
    unsigned char  terminal_country_code[2];          // 9F1A [BCD] : Terminal Country Code
    unsigned char  TID[8];                          // 9F1C [ASC]
    unsigned char  IFD[8];                          // 9F1E [ASC] : IFD Serial Number
    unsigned char  transaction_currency_code[2];     // 5F2A [BCD]
    unsigned char  terminal_capabilities[3];         // 9F33 [BIN]
    unsigned char  terminal_type[1];                // 9F35 [BCD]
    unsigned char  transaction_currency_exponent[1]; // 5F36 [BCD]
    unsigned char  additional_terminal_capabilities[5]; // 9F40 [BIN]
    unsigned char  merchantNameLength;
    unsigned char  merchantName[20];                // 9F4E [ASC]
    unsigned char  rev[2];
}TERMINAL_INFO;

int emv_terminal_param_set( uint8_t *TerminalParam)
```

5.6 Clear Exception File

```
/**
 * return value:  >=0 Success; < 0 Fail
 */
int emv_exception_file_clear(void)
```

5.8 Add Exception File

```
typedef struct{
    unsigned char cardNo[19];          // PAN
    unsigned char panSequence;         // PAN Sequence Number
}ExceptionFile
int emv_exception_file_add( unsigned char *exceptFile)
```

5.9 Clear Revoked Certificates

```
/**
 * return value:  >=0 Success; < 0 Fail
 */
```

```
int emv_revoked_cert_clear(void)
```

5.10 Add revoked Certificate

```
Typedef struct{  
    unsigned char rid[5];  
    unsigned char capki;  
}RevokedCert  
int emv_revoked_cert_add( uint8_t *revokedCert)
```