

Code Review Report

Repository: AZANIR/cypressAllure | Cypress + TypeScript + Allure

#1 myAccount.test.ts does not test My Account functionality

Severity: **Critical**

Location: cypress/e2e/tests/myAccount.test.ts, lines 1-10

Description: The test only logs to console and performs no real actions or checks.

Impact: The suite always passes and gives false coverage.

Recommendation: Implement a real scenario or remove the placeholder test.

#2 Allure results path is inconsistent across configuration

Severity: **High**

Location: config/config.config.ts and package.json

Description: Three different paths are used for the same Allure results data.

Impact: Report generation is likely to find no data and fail silently.

Recommendation: Use one consistent results folder everywhere.

#3 Typo in expected error text breaks the assertion

Severity: **High**

Location: cypress/e2e/tests/login.test.ts, line 35

Description: Expected text reads "addresssssss" instead of "address".

Impact: The assertion fails against the real application text.

Recommendation: Fix the typo to match the actual UI message.

#4 Duplicate test case with hardcoded credentials

Severity: **Medium**

Location: cypress/e2e/tests/login.test.ts, lines 11-22

Description: Two tests verify the same valid-login scenario, one hardcoded and one from fixture.

Impact: Extra maintenance without extra coverage.

Recommendation: Keep only the fixture-driven test.

#5 No URL assertions after navigation

Severity: **Medium**

Location: loginPage.ts and myAccountPage.ts

Description: Login/logout checks rely only on element text, never the URL.

Impact: Can produce false positives during unexpected redirects.

Recommendation: Add cy.url() checks alongside the existing assertions.

#6 Generated report committed to master via docs/

Severity: Medium

Location: docs/ (repository root)

Description: CI commits the full generated report to master on every run.

Impact: Bloats repository history with build artifacts.

Recommendation: Deploy to a dedicated gh-pages branch instead.

#7 Configuration file is not located in project root

Severity: Low

Location: config/config.config.ts

Description: The Cypress config file sits in a subfolder instead of the project root.

Impact: Harder to find and run the config file.

Recommendation: Move the file to the repository root.

#8 Deprecated CI action versions and end-of-life Node runtime

Severity: Medium

Location: .github/workflows/cyAllureRun.yml

Description: Workflow uses ubuntu-20.04, old action versions, and Node 14.

Impact: Pipeline can fail outright as these get retired.

Recommendation: Upgrade to current actions and a supported Node LTS.

#9 Outdated core dependencies

Severity: Medium

Location: package.json

Description: Cypress and TypeScript are several major versions behind.

Impact: Every fork starts from an outdated baseline.

Recommendation: Bump dependencies periodically and re-test.

#10 Assertions implemented inside Page Objects

Severity: Medium

Location: loginPage.ts and myAccountPage.ts

Description: Page Object methods call .should() directly instead of only exposing elements.

Impact: Mixes page abstraction with test verification logic.

Recommendation: Keep assertions in the test spec files.

#11 README setup instructions are vague

Severity: Low

Location: README.md, "Steps to run"

Description: Instructions don't name the fixture file or list prerequisites.

Impact: Adds friction for new contributors.

Recommendation: Name the file explicitly and list prerequisites.

#12 Unused default boilerplate left in commands.js

Severity: Low

Location: cypress/support/commands.js

Description: File still contains only default Cypress scaffold comments.

Impact: Missed opportunity to demonstrate a custom command.

Recommendation: Add an example command or trim the comments.

#13 Inconsistent use of the public modifier

Severity: Low

Location: loginPage.ts and myAccountPage.ts

Description: Methods are marked public but getters are not.

Impact: Minor readability inconsistency.

Recommendation: Pick one convention project-wide.

#14 Inconsistent formatting (missing semicolons)

Severity: Low

Location: cypress/e2e/pages/*.ts and cypress/e2e/tests/*.ts

Description: Some files end statements with semicolons, others don't.

Impact: Code may break if there's missing semicolon

Recommendation: Review the code and add missing semicolons.

#15 Hardcoded baseUrl with no environment override example

Severity: Low

Location: config/config.config.ts, line 22

Description: baseUrl points to one fixed public demo site.

Impact: No example of targeting another environment.

Recommendation: Source baseUrl from an environment variable.