
aws re:Invent



SEC 305

The busy manager's guide to encryption

Spencer Janyk Senior Product Manager, Tech AWS



Agenda

Security and defense in depth

Envelope encryption

Asymmetric permissions

Client-side encryption

Building an application



Related session



https://www.youtube.com/watch?v=-ObImxw1PmI

What is security?

Goal

Reduce risk

- Data exposure
- Loss of control

What is security?


Goal


Reduce risk

- Data exposure
- Loss of control


Risk types


- Inadvertent
- Malicious












Why encrypt?

- Keep data confidential
- Demonstrate compliance
- Improve agility




Paving the trusted path



Paving a trusted path

You need to access data (often)


- Read path
- Write path





Paving a trusted path

You need to access data (often)

- Read path
- Write path









| | Permission model | Logging | Complexity |
|--------|------------------|---------|------------|
| SSE-S3 | S3 | S3 | Low |









Which key was used to encrypt this key?











Metadata

Encrypted key

Encrypted data

(Not to scale)

Key hierarchy






Key hierarchy








User



S3 bucket



User \$3 bucket

| | Permission model | Logging | Complexity |
|---------|------------------|----------|------------|
| SSE-S3 | S3 | S3 | Low |
| SSE-KMS | S3 + KMS | S3 + KMS | Medium |

Asymmetric permissions



IAM policy

```
"version": "2012-10-17",
"Statement": {
    "Effect": "Allow",
    "Action": [
        "kms:ListKeys",
        "kms:ListAliases"
        ],
    "Resource": "*"
    }
}
```

Key policy

IAM policy

```
"Version": "2012-10-17",
"Statement": {
    "Effect": "Allow",
    "Action": [
        "kms:ListKeys",
        "kms:ListAliases"
        ],
    "Resource": "*"
    }
}
```

Key policy

Administer

```
"Action": [
          "kms:ListAliases",
          "kms:Create*",
          "kms:Describe*",
          "kms:Enable*",
          "kms:List*",
          "kms:Put*",
          "kms:Update*",
          "kms:Revoke*",
          "kms:Disable*",
          "kms:Get*",
          "kms:Delete*",
          "kms:TagResource",
          "kms:UntagResource",
          "kms:ScheduleKeyDeletion",
          "kms:CancelKeyDeletion"
```

Use

```
"Action": [
     "kms:Encrypt",
     "kms:Decrypt",
     "kms:ReEncrypt*",
     "kms:GenerateDataKey*",
     "kms:DescribeKey"
"Sid": "Allow attachment of
persistent resources",
"Action": [
     "kms:CreateGrant",
     "kms:ListGrants",
     "kms:RevokeGrant"
```

Encrypt

```
"Effect": "Allow",
"Action": [
    "kms:Encrypt",
    "kms:Decrypt",
    "kms:ReEncrypt*",
    "kms:GenerateDataKey*",
    "kms:DescribeKey"
]
```


Decrypt

```
"Effect": "Allow",
"Action": [
     "kms:Decrypt",
     "kms:DescribeKey"
]
```


Client-side encryption





Client-side encryption





User




























| | Permission model | Logging | Complexity |
|---------------|---------------------|---------------------|------------|
| SSE-S3 | S3 | S3 | Low |
| SSE-KMS | S3 + KMS | S3 + KMS | Medium |
| SSE-KMS + CSE | S3 + KMS + your app | S3 + KMS + your app | High |


Building an application








(PWs, OAuth tokens, etc.)
































"Nothing is wholly obvious without becoming enigmatic."

Jean Baudrillard EGS



Thank you.





Please complete the session survey

