

ExaModels

Sungho Shin

August 15, 2023

Contents

Contents	ii
I Introduction	1
1 Overview	2
1.1 What is ExaModels.jl?	2
1.2 When should I use ExaModels.jl?	2
1.3 New to Julia?	3
1.4 Supported Solvers	3
1.5 Documentation Structure	3
1.6 Citing ExaModels.jl	3
1.7 Supporting ExaModels.jl	3
2 Highlights	4
2.1 Key differences from other algebraic modeling tools	4
2.2 Performance	4
II Mathematical Abstraction	7
3 SIMD Abstraction	8
3.1 What is SIMD abstraction?	8
3.2 Why SIMD abstraction?	8
III Tutorial	10
4 Getting Started	11
5 Performance Tips	15
5.1 Use a function to create a model	15
5.2 Make sure your array's eltype is concrete	16
6 Accelerations	38
7 Developing Extensions	41
8 Example: Quadrotor	44
9 Example: Distillation Column	46
10 Example: Optimal Power Flow	48
IV API Manual	54
11 ExaModels	55
V References	60
12 References	61

Part I

Introduction

Chapter 1

Overview

Welcome to the documentation of [ExaModels.jl](#)

Note

This documentation is also available in PDF format: [ExaModels.pdf](#).

Warning

This documentation page is currently under construction. Please help us improve ExaModels.jl and this documentation! ExaModels.jl is in the early stage of development, and you may encounter unintended behaviors or missing documentations. If you find anything is not working as intended or documentation is missing, please [open issues](#) or [pull requests](#) or start [discussions](#).

1.1 What is ExaModels.jl?

ExaModels.jl is an [algebraic modeling](#) and [automatic differentiation](#) tool in [Julia Language](#), specialized for [SIMD](#) abstraction of [nonlinear programs](#). ExaModels.jl employs what we call [SIMD](#) abstraction for [nonlinear programs](#) (NLPs), which allows for the preservation of the parallelizable structure within the model equations, facilitating efficient [automatic differentiation](#) either on the single-thread CPUs, multi-threaded CPUs, as well as [GPU accelerators](#). More details about SIMD abstraction can be found [here](#).

1.2 When should I use ExaModels.jl?

ExaModels.jl shines when your model has

- nonlinear objective and constraints;
- a large number of variables and constraints;
- highly repetitive structure;
- sparse Hessian and Jacobian.

These features are often exhibited in optimization problems associated with first-principle physics-based models. Primary examples include optimal control problems formulated with direct subscription method [\[1\]](#) and network system optimization problems, such as optimal power flow [\[2\]](#) and gas network control/estimation problems.

1.3 New to Julia?

Welcome to Julia community! Below is the helpful link to start using Julia.

- [juliaup](#): julia installer and version multiplexer.
- Julia tutorial in [Julia's official documentation](#).

1.4 Supported Solvers

ExaModels can be used with any solver that can handle `NLPModel` data type, but several callbacks are not currently implemented, and cause some errors. Currently, it is tested with the following solvers:

- [Ipopt](#) (via `NLPModelsIpopt.jl`)
- [MadNLP.jl](#)

1.5 Documentation Structure

This documentation is structured in the following way.

- The remainder of [this page](#) highlights several key aspects of `ExaModels.jl`.
- The mathematical abstraction—SIMD abstraction of nonlinear programming—of `ExaModels.jl` is discussed in [Mathematical Abstraction page](#).
- The step-by-step tutorial of using `ExaModels.jl` can be found in [Tutorial page](#).
- This documentation does not intend to discuss the engineering behind the implementation of `ExaModels.jl`. Some high-level idea is discussed in [a recent publication](#), but the full details of the engineering behind it will be discussed in the future publications.

1.6 Citing ExaModels.jl

If you use `ExaModels.jl` in your research, we would greatly appreciate your citing this [preprint](#).

```
@misc{shin2023accelerating,
  title={Accelerating Optimal Power Flow with {GPU}s: {SIMD} Abstraction of Nonlinear Programs and Condensed-Space Interior-Point Methods},
  author={Sungho Shin and Fran{\c{c}}ois Pacaud and Mihai Anitescu},
  year={2023},
  eprint={2307.16830},
  archivePrefix={arXiv},
  primaryClass={math.OC}
}
```

1.7 Supporting ExaModels.jl

- Please report issues and feature requests via the [GitHub issue tracker](#).
- Questions are welcome at [GitHub discussion forum](#).

Chapter 2

Highlights

2.1 Key differences from other algebraic modeling tools

ExaModels.jl is different from other algebraic modeling tools, such as [JuMP](#) or [AMPL](#), in the following ways:

- **Modeling Interface:** ExaModels.jl enforces users to specify the model equations always in the form of Generator. This allows ExaModels.jl to preserve the SIMD-compatible structure in the model equations.
- **Performance:** ExaModels.jl compiles (via Julia's compiler) derivative evaluation codes that are specific to each computation pattern, based on reverse-mode automatic differentiation. This makes the speed of derivative evaluation (even on the CPU) significantly faster than other existing tools.
- **Portability:** ExaModels.jl can evaluate derivatives on GPU accelerators. The code is currently only tested for NVIDIA GPUs, but GPU code is implemented mostly based on the portable programming paradigm, [KernelAbstractions.jl](#). In the future, we are interested in supporting Intel, AMD, and Apple GPUs.

2.2 Performance

For the nonlinear optimization problems that are suitable for SIMD abstraction, ExaModels.jl greatly accelerate the performance of derivative evaluations. The following is a recent benchmark result. Remarkably, for the AC OPF problem for a 9241 bus system, derivative evaluation using ExaModels.jl on GPUs can be up to 2 orders of magnitudes faster than JuMP or AMPL.

Evaluation Wall Time (sec)								
ExaModels (single)								
case	nvar	ncon	obj	con	grad	jac	hess	
LV1	100	98	6.3e-06	7.6e-06	6.3e-06	1.2e-05	9.3e-05	
LV2	1k	998	2.8e-05	3.0e-05	2.4e-05	5.5e-05	6.7e-04	
LV3	10k	10k	2.8e-04	2.9e-04	2.3e-04	5.4e-04	2.5e-03	
QR1	659	459	8.9e-06	1.0e-05	6.2e-06	1.9e-05	3.1e-05	
QR2	7k	5k	5.7e-05	5.1e-05	4.1e-05	1.0e-04	2.1e-04	
QR3	65k	45k	5.9e-04	5.4e-04	4.6e-04	1.2e-03	6.4e-03	
DC1	402	396	1.4e-06	4.9e-06	2.6e-06	6.4e-06	3.5e-05	
DC2	3k	3k	2.0e-06	2.6e-05	6.2e-06	5.4e-05	9.7e-05	
DC3	34k	33k	1.1e-05	2.4e-04	6.3e-05	5.3e-04	2.0e-03	
PF1	1k	2k	2.0e-06	3.5e-05	2.3e-06	3.7e-05	3.4e-04	

	PF2	11k	17k	5.3e-06	3.1e-04	9.7e-06	3.2e-04	3.6e-03	
	PF3	86k	131k	1.9e-05	2.8e-03	1.2e-04	2.7e-03	2.0e-02	
=====									
				ExaModels (multli)					
	case	nvar	ncon	obj	con	grad	jac	hess	
=====									
	LV1	100	98	1.3e-05	1.5e-05	1.7e-05	1.6e-05	1.0e-04	
	LV2	1k	998	4.3e-05	4.1e-05	4.8e-05	7.5e-05	2.4e-04	
	LV3	10k	10k	2.5e-04	2.2e-04	3.6e-04	5.1e-04	2.7e-03	
	QR1	659	459	2.2e-05	4.8e-05	2.4e-05	5.8e-05	8.4e-05	
	QR2	7k	5k	2.5e-04	9.7e-05	2.6e-04	1.4e-04	6.5e-04	
	QR3	65k	45k	5.0e-04	1.2e-03	7.7e-04	2.0e-03	6.9e-03	
	DC1	402	396	1.0e-05	3.7e-05	1.3e-05	3.9e-05	1.2e-04	
	DC2	3k	3k	9.0e-06	1.8e-04	2.0e-05	2.0e-04	2.7e-04	
	DC3	34k	33k	2.3e-05	4.3e-04	8.6e-05	8.2e-04	2.6e-03	
	PF1	1k	2k	7.1e-06	7.8e-05	9.7e-06	8.7e-05	4.0e-04	
	PF2	11k	17k	8.7e-06	1.5e-03	1.8e-05	1.4e-03	7.6e-03	
	PF3	86k	131k	1.3e-04	1.9e-03	2.2e-04	2.3e-03	9.2e-03	
=====									
				ExaModels (gpu)					
	case	nvar	ncon	obj	con	grad	jac	hess	
=====									
	LV1	100	98	8.3e-05	4.8e-05	8.9e-05	5.3e-05	1.1e-04	
	LV2	1k	998	5.1e-05	2.6e-05	5.4e-05	3.7e-05	6.6e-05	
	LV3	10k	10k	6.4e-05	2.8e-05	5.7e-05	3.5e-05	6.8e-05	
	QR1	659	459	1.1e-04	2.2e-04	1.0e-04	2.3e-04	3.2e-04	
	QR2	7k	5k	9.1e-05	1.5e-04	8.3e-05	1.6e-04	2.3e-04	
	QR3	65k	45k	1.0e-04	1.7e-04	9.0e-05	1.8e-04	2.6e-04	
	DC1	402	396	8.3e-05	2.0e-04	7.9e-05	2.0e-04	2.6e-04	
	DC2	3k	3k	6.6e-05	1.6e-04	6.7e-05	1.6e-04	2.1e-04	
	DC3	34k	33k	7.3e-05	1.6e-04	7.0e-05	1.7e-04	2.5e-04	
	PF1	1k	2k	5.7e-05	3.4e-04	5.2e-05	2.8e-04	3.5e-04	
	PF2	11k	17k	5.6e-05	3.2e-04	5.6e-05	3.1e-04	3.1e-04	
	PF3	86k	131k	9.9e-05	3.6e-04	5.0e-05	2.9e-04	3.8e-04	
=====									
				JuMP					
	case	nvar	ncon	obj	con	grad	jac	hess	
=====									
	LV1	100	98	5.5e-06	2.8e-05	8.6e-06	3.1e-05	3.5e-04	
	LV2	1k	998	4.6e-05	2.9e-04	1.1e-04	4.9e-04	2.9e-03	
	LV3	10k	10k	9.1e-04	4.8e-03	2.1e-03	7.0e-03	2.5e-02	
	QR1	659	459	9.2e-06	3.1e-05	8.3e-06	5.1e-05	1.0e-04	
	QR2	7k	5k	1.2e-04	3.7e-04	1.1e-04	7.0e-04	3.8e-03	
	QR3	65k	45k	2.1e-03	8.2e-03	2.1e-03	1.6e-02	4.0e-02	
	DC1	402	396	2.5e-06	2.0e-05	4.1e-06	3.9e-05	3.5e-04	
	DC2	3k	3k	2.7e-05	2.9e-04	6.0e-05	6.0e-04	1.2e-03	
	DC3	34k	33k	4.8e-04	7.7e-03	1.9e-03	1.5e-02	4.2e-02	
	PF1	1k	2k	3.5e-06	1.1e-04	4.0e-06	2.3e-04	1.9e-03	
	PF2	11k	17k	3.8e-05	2.1e-03	5.0e-05	4.4e-03	1.7e-02	
	PF3	86k	131k	6.9e-04	3.5e-02	1.1e-03	7.2e-02	1.1e-01	
=====									
				AMPL					
	case	nvar	ncon	obj	con	grad	jac	hess	
=====									
	LV1	100	98	1.2e-06	1.7e-06	9.1e-06	1.3e-05	2.1e-04	
	LV2	1k	998	1.5e-06	8.5e-06	2.6e-05	1.7e-04	1.6e-03	

LV3	10k	10k	8.9e-06	2.3e-04	3.1e-04	3.4e-03	2.2e-02
QR1	659	459	1.5e-06	3.4e-06	1.4e-06	2.7e-05	2.9e-04
QR2	7k	5k	1.2e-05	4.5e-05	1.2e-05	3.5e-04	4.4e-03
QR3	65k	45k	1.4e-04	1.1e-03	1.2e-04	7.9e-03	5.4e-02
DC1	402	396	5.3e-07	4.8e-06	1.2e-06	5.2e-06	3.5e-05
DC2	3k	3k	8.6e-07	3.9e-05	5.5e-06	6.2e-05	2.6e-05
DC3	34k	33k	4.8e-06	4.1e-04	2.5e-05	4.1e-04	3.3e-03
PF1	1k	2k	9.5e-07	2.4e-04	2.8e-06	1.3e-04	1.6e-03
PF2	11k	17k	1.1e-06	5.1e-03	7.7e-06	3.5e-03	2.6e-02
PF3	86k	131k	3.5e-06	4.1e-02	5.4e-05	3.6e-02	2.3e-01

=====

```

* commit : 8a396718b7f7632d239e9edb18f6177fedf4e2a0
* CPU    : Intel(R) Xeon(R) Gold 6140 CPU @ 2.30GHz (nthreads = 20)
* GPU    : Quadro GV100

```


Part II

Mathematical Abstraction

Chapter 3

SIMD Abstraction

In this page, we explain what SIMD abstraction of nonlinear program is, and why it can be beneficial for scalable optimization of large-scale optimization problems. More discussion can be found in our [paper](#).

3.1 What is SIMD abstraction?

The mathematical statement of the problem formulation is as follows.

$$\begin{aligned} \min_{x^b \leq x \leq x^\#} \quad & \sum_{l \in [L]} \sum_{i \in [I_l]} f^{(l)}(x; p_i^{(l)}) \\ \text{s.t.} \quad & \left[g^{(m)}(x; q_j) \right]_{j \in [J_m]} + \sum_{n \in [N_m]} \sum_{k \in [K_n]} h^{(n)}(x; s_k^{(n)}) = 0, \quad \forall m \in [M] \end{aligned}$$

where $f^{(\ell)}(\cdot, \cdot)$, $g^{(m)}(\cdot, \cdot)$, and $h^{(n)}(\cdot, \cdot)$ are twice differentiable functions with respect to the first argument, whereas $\{\{p_i^{(k)}\}_{i \in [N_k]}\}_{k \in [K]}$, $\{\{q_i^{(k)}\}_{i \in [M_l]}\}_{m \in [M]}$, and $\{\{\{s_k^{(n)}\}_{k \in [K_n]}\}_{n \in [N_m]}\}_{m \in [M]}$ are problem data, which can either be discrete or continuous. It is also assumed that our functions $f^{(l)}(\cdot, \cdot)$, $g^{(m)}(\cdot, \cdot)$, and $h^{(n)}(\cdot, \cdot)$ can be expressed with computational graphs of moderate length.

3.2 Why SIMD abstraction?

Many physics-based models, such as AC OPF, have a highly repetitive structure. One of the manifestations of it is that the mathematical statement of the model is concise, even if the practical model may contain millions of variables and constraints. This is possible due to the use of repetition over a certain index and data sets. For example, it suffices to use 15 computational patterns to fully specify the AC OPF model. These patterns arise from (1) generation cost, (2) reference bus voltage angle constraint, (3-6) active and reactive power flow (from and to), (7) voltage angle difference constraint, (8-9) apparent power flow limits (from and to), (10-11) power balance equations, (12-13) generators' contributions to the power balance equations, and (14-15) in/out flows contributions to the power balance equations. However, such repetitive structure is not well exploited in the standard NLP modeling paradigms. In fact, without the SIMD abstraction, it is difficult for the AD package to detect the parallelizable structure within the model, as it will require the full inspection of the computational graph over all expressions. By preserving the repetitive structures in the model, the repetitive structure can be directly available in AD implementation.

Using the multiple dispatch feature of Julia, ExaModels.jl generates highly efficient derivative computation code, specifically compiled for each computational pattern in the model. These derivative evaluation codes can be run over the data in various GPU array formats, and implemented via array and kernel programming in

Julia Language. In turn, ExaModels.jl has the capability to efficiently evaluate first and second-order derivatives using GPU accelerators.

Part III

Tutorial

Chapter 4

Getting Started

ExaModels can create nonlinear programming models and allows solving the created models using NLP solvers (in particular, those that are interfaced with NLPModels, such as [NLPModelsIpopt](#) and [MadNLP](#). This documentation page will describe how to use ExaModels to model and solve nonlinear optimization problems.

We will first consider the following simple nonlinear program [3]:

$$\begin{aligned} \min_{\{x_i\}_{i=0}^N} \quad & \sum_{i=2}^N 100(x_{i-1}^2 - x_i)^2 + (x_{i-1} - 1)^2 \\ \text{s.t.} \quad & 3x_{i+1}^3 + 2x_{i+2} - 5 + \sin(x_{i+1} - x_{i+2}) \sin(x_{i+1} + x_{i+2}) + 4x_{i+1} - x_i e^{x_i - x_{i+1}} - 3 = 0 \end{aligned}$$

We will follow the following Steps to create the model/solve this optimization problem.

- Step 0: import ExaModels.jl
- Step 1: create a [ExaCore](#) object, wherein we can progressively build an optimization model.
- Step 2: create optimization variables with [variable](#), while attaching it to previously created ExaCore.
- Step 3 (interchangeable with Step 2): create objective function with [objective](#), while attaching it to previously created ExaCore.
- Step 4 (interchangeable with Step 2): create constraints with [constraint](#), while attaching it to previously created ExaCore.
- Step 5: create an [ExaModel](#) based on the ExaCore.

Now, let's jump right in. We import ExaModels via (Step 0):

```
| using ExaModels
```

Now, all the functions that are necessary for creating model are imported to into Main.

An ExaCore object can be created simply by (Step 1):

```
| c = ExaCore()
```

```
An ExaCore
```

```
Float type: ..... Float64
Array type: ..... Vector{Float64}
Backend: ..... Nothing

number of objective patterns: .... 0
number of constraint patterns: ... 0
```

This is where our optimization model information will be progressively stored. This object is not yet an `NLPModel`, but it will essentially store all the necessary information.

Now, let's create the optimization variables. From the problem definition, we can see that we will need N scalar variables. We will choose $N = 10$, and create the variable $x \in \mathbb{R}^N$ with the following command:

```
N = 10
x = variable(c, N; start = (mod(i, 2) == 1 ? -1.2 : 1.0 for i = 1:N))
```

```
Variable
```

```
x ∈ ℝ10
```

This creates the variable x , which we will be able to refer to when we create constraints/objective constraints. Also, this modifies the information in the `ExaCore` object properly so that later an optimization model can be properly created with the necessary information. Observe that we have used the keyword argument `start` to specify the initial guess for the solution. The variable upper and lower bounds can be specified in a similar manner.

The objective can be set as follows:

```
objective(c, 100 * (x[i-1]^2 - x[i])^2 + (x[i-1] - 1)^2 for i = 2:N)
```

```
Objective
```

```
min (...) + ∑_{p ∈ P} f(x,p)

where |P| = 9
```

The constraints can be set as follows:

```
constraint(
    c,
    3x[i+1]^3 + 2 * x[i+2] - 5 + sin(x[i+1] - x[i+2])sin(x[i+1] + x[i+2]) + 4x[i+1] -
    x[i]exp(x[i] - x[i+1]) - 3 for i = 1:N-2
)
```

```
Constraint
```

```
s.t. (...)
    b_g ≤ [g(x,p)]_{p ∈ P} ≤ #g

where |P| = 8
```

Finally, we are ready to create an `ExaModel` from the data we have collected in `ExaCore`. Since `ExaCore` includes all the necessary information, we can do this simply by:

```
| m = ExaModel(c)

| An ExaModel
|
| Problem name: Generic
| All variables: ██████████ 10      All constraints: ██████████ 8
|   free: ██████████ 10          free: ..... 0
|   lower: ..... 0              lower: ..... 0
|   upper: ..... 0              upper: ..... 0
| low/upp: ..... 0              low/upp: ..... 0
|   fixed: ..... 0              fixed: ██████████ 8
|   infeas: ..... 0             infeas: ..... 0
|   nnz: (-36.36% sparsity) 75    linear: ..... 0
|                                   nonlinear: ██████████ 8
|                                   nnz: ( 70.00% sparsity) 24
```

Now, we got an optimization model ready to be solved. This problem can be solved with for example, with the `Ipopt` solver, as follows.

```
| using NLPModelsIpopt
| result = ipopt(m)

| "Execution stats: first-order stationary"

| Here, result is an AbstractExecutionStats, which typically contains the solution information. We can check
| several information as follows.

| println("Status: $(result.status)")
| println("Number of iterations: $(result.iter)")
```

```
| Status: first_order
| Number of iterations: 6
```

The solution values for variable `x` can be inquired by:

```
| sol = solution(result, x)

| 10-element view(::Vector{Float64}, 1:10) with eltype Float64:
| -0.9505563573613093
|  0.9139008176388945
|  0.9890905176644905
|  0.9985592422681151
|  0.9998087408802769
|  0.9999745932450963
|  0.9999966246997642
|  0.9999995512524277
|  0.999999944919307
|  0.999999930070643
```

ExaModels provide several APIs similar to this:

- `solution` inquires the primal solution.
- `multiplier` inquires the dual solution.
- `multiplier_L` inquires the lower bound dual solution.
- `multiplier_U` inquires the upper bound dual solution.

This concludes a short tutorial on how to use ExaModels to model and solve optimization problems. Want to learn more? Take a look at the following examples, which provide further tutorial on how to use ExaModels.jl. Each of the examples are designed to instruct a few additional techniques.

- Example: Quadrotor: modeling multiple types of objective values and constraints.
- Example: Distillation Column: using two-dimensional index sets for variables.
- Example: Optimal Power Flow: handling complex data and using constraint augmentation.

This page was generated using [Literate.jl](#).

Chapter 5

Performance Tips

5.1 Use a function to create a model

It is always better to use functions to create ExaModels. This in this way, the functions used for specifying objective/constraint functions are not recreated over all over, and thus, we can take advantage of the previously compiled model creation code. Let's consider the following example.

```
using ExaModels

t = @elapsed begin
    c = ExaCore()
    N = 10
    x = variable(c, N; start = (mod(i, 2) == 1 ? -1.2 : 1.0 for i = 1:N))
    objective(c, 100 * (x[i-1]^2 - x[i])^2 + (x[i-1] - 1)^2 for i = 2:N)
    constraint(
        c,
        3x[i+1]^3 + 2 * x[i+2] - 5 + sin(x[i+1] - x[i+2])sin(x[i+1] + x[i+2]) + 4x[i+1] -
        x[i]exp(x[i] - x[i+1]) - 3 for i = 1:N-2
    )
    m = ExaModel(c)
end

println("$t seconds elapsed")
```

```
| 0.116776726 seconds elapsed
```

Even at the second call,

```
t = @elapsed begin
    c = ExaCore()
    N = 10
    x = variable(c, N; start = (mod(i, 2) == 1 ? -1.2 : 1.0 for i = 1:N))
    objective(c, 100 * (x[i-1]^2 - x[i])^2 + (x[i-1] - 1)^2 for i = 2:N)
    constraint(
        c,
        3x[i+1]^3 + 2 * x[i+2] - 5 + sin(x[i+1] - x[i+2])sin(x[i+1] + x[i+2]) + 4x[i+1] -
        x[i]exp(x[i] - x[i+1]) - 3 for i = 1:N-2
    )
    m = ExaModel(c)
end
```

```
println("$t seconds elapsed")
```

```
0.117271018 seconds elapsed
```

the model creation time can be slightly reduced but the compilation time is still quite significant.

But instead, if you create a function, we can significantly reduce the model creation time.

```
function luksan_vlcek_model(N)
    c = ExaCore()
    x = variable(c, N; start = (mod(i, 2) == 1 ? -1.2 : 1.0 for i = 1:N))
    objective(c, 100 * (x[i-1]^2 - x[i])^2 + (x[i-1] - 1)^2 for i = 2:N)
    constraint(
        c,
        3x[i+1]^3 + 2 * x[i+2] - 5 + sin(x[i+1] - x[i+2])sin(x[i+1] + x[i+2]) + 4x[i+1] -
        x[i]exp(x[i] - x[i+1]) - 3 for i = 1:N-2
    )
    m = ExaModel(c)
end

t = @elapsed luksan_vlcek_model(N)
println("$t seconds elapsed")
```

```
0.201202923 seconds elapsed
```

```
t = @elapsed luksan_vlcek_model(N)
println("$t seconds elapsed")
```

```
7.052e-5 seconds elapsed
```

So, the model creation time can be essentially nothing. Thus, if you care about the model creation time, always make sure to write a function for creating the model, and do not directly create a model from the REPL.

5.2 Make sure your array's eltype is concrete

In order for ExaModels to run for loops over the array you provided without any overhead caused by type inference, the eltype of the data array should always be a concrete type. Furthermore, this is **required** if you want to run ExaModels on GPU accelerators.

Let's take an example.

```
using ExaModels

N = 1000

function luksan_vlcek_model_concrete(N)
    c = ExaCore()

    arr1 = Array{2:N}
    arr2 = Array{1:N-2}

    x = variable(c, N; start = (mod(i, 2) == 1 ? -1.2 : 1.0 for i = 1:N))
```

```

objective(c, 100 * (x[i-1]^2 - x[i])^2 + (x[i-1] - 1)^2 for i = arr1)
constraint(
    c,
    3x[i+1]^3 + 2 * x[i+2] - 5 + sin(x[i+1] - x[i+2])sin(x[i+1] + x[i+2]) + 4x[i+1] -
    x[i]exp(x[i] - x[i+1]) - 3 for i = arr2
)
m = ExaModel(c)
end

function luksan_vlcek_model_non_concrete(N)
    c = ExaCore()

    arr1 = Array{Any}(2:N)
    arr2 = Array{Any}(1:N-2)

    x = variable(c, N; start = (mod(i, 2) == 1 ? -1.2 : 1.0 for i = 1:N))
    objective(c, 100 * (x[i-1]^2 - x[i])^2 + (x[i-1] - 1)^2 for i = arr1)
    constraint(
        c,
        3x[i+1]^3 + 2 * x[i+2] - 5 + sin(x[i+1] - x[i+2])sin(x[i+1] + x[i+2]) + 4x[i+1] -
        x[i]exp(x[i] - x[i+1]) - 3 for i = arr2
    )
    m = ExaModel(c)
end

```

```
| luksan_vlcek_model_non_concrete (generic function with 1 method)
```

Here, observe that

```
| isconcretetype(eltype(Array{2:N}))
```

```
| true
```

```
| isconcretetype(eltype(Array{Any}(2:N)))
```

```
| false
```

As you can see, the first array type has concrete eltypes, whereas the second array type has non concrete eltypes. Due to this, the array stored in the model created by `luksan_vlcek_model_non_concrete` will have non-concrete eltypes.

Now let's compare the performance. We will use the following benchmark function here.

```

using NLPModels

function benchmark_callbacks(m; N = 100)
    nvar = m.meta.nvar
    ncon = m.meta.ncon
    nnzj = m.meta.nnzj
    nnzh = m.meta.nnzh

    x = copy(m.meta.x0)
    y = similar(m.meta.x0, ncon)

```

```

c = similar(m.meta.x0, ncon)
g = similar(m.meta.x0, nvar)
jac = similar(m.meta.x0, nnzj)
hess = similar(m.meta.x0, nnzh)
jrows = similar(m.meta.x0, Int, nnzj)
jcols = similar(m.meta.x0, Int, nnzj)
hrows = similar(m.meta.x0, Int, nnzh)
hcols = similar(m.meta.x0, Int, nnzh)

GC.enable(false)

NLPModels.obj(m, x) # to compile

tobj = (1 / N) * @elapsed for t = 1:N
    NLPModels.obj(m, x)
end

NLPModels.cons!(m, x, c) # to compile
tcon = (1 / N) * @elapsed for t = 1:N
    NLPModels.cons!(m, x, c)
end

NLPModels.grad!(m, x, g) # to compile
tgrad = (1 / N) * @elapsed for t = 1:N
    NLPModels.grad!(m, x, g)
end

NLPModels.jac_coord!(m, x, jac) # to compile
tjac = (1 / N) * @elapsed for t = 1:N
    NLPModels.jac_coord!(m, x, jac)
end

NLPModels.hess_coord!(m, x, y, hess) # to compile
thess = (1 / N) * @elapsed for t = 1:N
    NLPModels.hess_coord!(m, x, y, hess)
end

NLPModels.jac_structure!(m, jrows, jcols) # to compile
tjacs = (1 / N) * @elapsed for t = 1:N
    NLPModels.jac_structure!(m, jrows, jcols)
end

NLPModels.hess_structure!(m, hrows, hcols) # to compile
thesss = (1 / N) * @elapsed for t = 1:N
    NLPModels.hess_structure!(m, hrows, hcols)
end

GC.enable(true)

return (
    tobj = tobj,
    tcon = tcon,
    tgrad = tgrad,
    tjac = tjac,
    thess = thess,
    tjacs = tjacs,

```

```

        thesss = thesss,
    )
end

```

```
benchmark_callbacks (generic function with 1 method)
```

The performance comparison is here:

```

m1 = luksan_vlcek_model_concrete(N)
m2 = luksan_vlcek_model_non_concrete(N)

benchmark_callbacks(m1)

```

```

(tobj = 1.572299e-5, tcon = 2.6152030000000002e-5, tgrad = 1.868329e-5, tjac = 4.884695e-5, thess =
0.000417949160000000004, tjacs = 1.68763e-5, thesss = 1.958946e-5)

```

```
benchmark_callbacks(m2)
```

```

(tobj = 0.00018287400999999998, tcon = 0.00025873918, tgrad = 0.00025151023000000004, tjac =
0.00144025575, thess = 0.00345549689, tjacs = 0.0005031359, thesss = 0.00203735337)

```

As can be seen here, having concrete eltype dramatically improves the performance. This is because when all the data arrays' eltypes are concrete, the AD evaluations can be performed without any type inference, and this should be as fast as highly optimized C/C++/Fortran code.

When you're using GPU accelerators, the eltype of the array should always be concrete. In fact, non-concrete eltype will already cause an error when creating the array. For example,

```

using CUDA

try
    arr1 = CuArray{2:N}
catch e
    showerror(stdout,e)
end

```

```

999-element CUDA.CuArray{Int64, 1, CUDA.Mem.DeviceBuffer}:
 2
 3
 4
 5
 6
 7
 8
 9
10
11
12
13
14
15
16
17

```

18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73

74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129

130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185

186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241

242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297

298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353

354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409

410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465

466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521

522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577

578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633

634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689

690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745

746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801

802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857

858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913

914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969

```
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000
```

Chapter 6

Accelerations

One of the key features of ExaModels.jl is being able to evaluate derivatives either on multi-threaded CPUs or GPU accelerators. Currently, GPU acceleration is only tested for NVIDIA GPUs. If you'd like to use multi-threaded CPU acceleration, start julia with

```
$ julia -t 4 # using 4 threads
```

Also, if you're using NVIDIA GPUs, make sure to have installed appropriate drivers.

Let's say that our CPU code is as follows.

```
function luksan_vlcek_obj(x,i)
    return 100*(x[i-1]^2-x[i])^2+(x[i-1]-1)^2
end

function luksan_vlcek_con(x,i)
    return 3x[i+1]^3+2*x[i+2]-5+sin(x[i+1]-x[i+2])sin(x[i+1]+x[i+2])+4x[i+1]-x[i]exp(x[i]-x[i+1])-3
end

function luksan_vlcek_x0(i)
    return mod(i,2)==1 ? -1.2 : 1.0
end

function luksan_vlcek_model(N)

    c = ExaCore()
    x = variable(
        c, N;
        start = (luksan_vlcek_x0(i) for i=1:N)
    )
    constraint(
        c,
        luksan_vlcek_con(x,i)
        for i in 1:N-2)
    objective(
        c,
        luksan_vlcek_obj(x,i)
        for i in 2:N)

    return ExaModel(c)
end
```


| luksan_vlcek_model (generic function with 1 method)

Now we simply modify this by

```
function luksan_vlcek_model(N, backend = nothing)

    c = ExaCore(backend) # specify the backend
    x = variable(
        c, N;
        start = (luksan_vlcek_x0(i) for i=1:N)
    )
    constraint(
        c,
        luksan_vlcek_con(x,i)
        for i in 1:N-2)
    objective(
        c,
        luksan_vlcek_obj(x,i)
        for i in 2:N)

    return ExaModel(c)
end
```

| luksan_vlcek_model (generic function with 2 methods)

The acceleration can be done simply by specifying the backend. In particular, for multi-threaded CPUs,

```
using ExaModels, NLPModelsIpopt, KernelAbstractions

m = luksan_vlcek_model(10, CPU())
ipopt(m)
```

| "Execution stats: first-order stationary"

For NVIDIA GPUs, we can use CUDABackend. However, currently, there are not many optimization solvers that are capable of solving problems on GPUs. The only option right now is using [a development branch in MadNLP.jl](#). To use this, first install

```
import Pkg; Pkg.add("MadNLP"; rev="sparse_condensed_2")
```

Then, we can run:

```
using CUDA, MadNLP, MadNLPGPU

m = luksan_vlcek_model(10, CUDABackend())
madnlp(m)
```

In the case we have arrays for the data, what we need to do is to simply convert the array types to the corresponding device array types. In particular,

```
function cuda_luksan_vlcek_model(N)
    c = ExaCore(CUDABackend())
    d1 = CuArray(1:N-2)
    d2 = CuArray(2:N)
    d3 = CuArray([luksan_vlcek_x0(i) for i=1:N])

    x = variable(
        c, N;
        start = d3
    )
    constraint(
        c,
        luksan_vlcek_con(x,i)
        for i in d1
    )
    objective(
        c,
        luksan_vlcek_obj(x,i)
        for i in d2
    )

    return ExaModel(c)
end
```

```
| cuda_luksan_vlcek_model (generic function with 1 method)
```

```
| m = cuda_luksan_vlcek_model(10)
| madnlp(m)
```

Chapter 7

Developing Extensions

ExaModels.jl's API only uses simple julia functions, and thus, implementing the extensions is straightforward. Below, we suggest a good practice for implementing an extension package.

Let's say that we want to implement an extension package for the example problem in [Getting Started](#). An extension package may look like:

```
Root|—
Project.toml|—
src|
  └─ LuksanVlcekModels.jl ─
test
  └─ runtest.jl
```

Each of the files containing

```
# Project.toml

name = "LuksanVlcekModels"
uuid = "0c5951a0-f777-487f-ad29-fac2b9a21bf1"
authors = ["Sungho Shin <sshin@anl.gov>"]
version = "0.1.0"

[deps]
ExaModels = "1037b233-b668-4ce9-9b63-f9f681f55dd2"

[extras]
NLPMoelsIpopt = "f4238b75-b362-5c4c-b852-0801c9a21d71"
Test = "8dfed614-e22c-5e08-85e1-65c5234f0b40"

[targets]
test = ["Test", "NLPMoelsIpopt"]
```

```
# src/LuksanVlcekModels.jl

module LuksanVlcekModels

import ExaModels

function luksan_vlcek_obj(x,i)
    return 100*(x[i-1]^2-x[i])^2+(x[i-1]-1)^2
end
```

```

function luksan_vlcek_con(x,i)
    return 3x[i+1]^3+2*x[i+2]-5+sin(x[i+1]-x[i+2])sin(x[i+1]+x[i+2])+4x[i+1]-x[i]exp(x[i]-x[i+1])-3
end

function luksan_vlcek_x0(i)
    return mod(i,2)==1 ? -1.2 : 1.0
end

function luksan_vlcek_model(N; backend = nothing)

    c = ExaModels.ExaCore(backend)
    x = ExaModels.variable(
        c, N;
        start = (luksan_vlcek_x0(i) for i=1:N)
    )
    ExaModels.constraint(
        c,
        luksan_vlcek_con(x,i)
        for i in 1:N-2)
    ExaModels.objective(c, luksan_vlcek_obj(x,i) for i in 2:N)

    return ExaModels.ExaModel(c) # returns the model
end

export luksan_vlcek_model

end # module LuksanVlcekModels

# test/runtest.jl

using Test, LuksanVlcekModels, NLPModelsIpopt

@testset "LuksanVlcekModelsTest" begin
    m = luksan_vlcek_model(10)
    result = ipopt(m)

    @test result.status == :first_order
    @test result.solution ≈ [
        -0.9505563573613093
        0.9139008176388945
        0.9890905176644905
        0.9985592422681151
        0.9998087408802769
        0.9999745932450963
        0.9999966246997642
        0.9999995512524277
        0.999999944919307
        0.999999930070643
    ]
    @test result.multipliers ≈ [
        4.1358568305002255
        -1.876494903703342
        -0.06556333356358675
        -0.021931863018312875
        -0.0019537261317119302
    ]
end

```

```
|      -0.00032910445671233547  
|      -3.8788212776372465e-5  
|      -7.376592164341867e-6  
|    ]  
|  end
```

Chapter 8

Example: Quadrotor

```
function quadrotor_model(N = 3; backend = nothing)

    n = 9
    p = 4
    nd = 9
    d(i,j,N) = (j==1 ? 1*sin(2*pi/N*i) : 0.) + (j==3 ? 2*sin(4*pi/N*i) : 0.) + (j==5 ? 2*i/N : 0.)
    dt = .01
    R = fill(1/10,4)
    Q = [1,0,1,0,1,0,1,1,1]
    Qf = [1,0,1,0,1,0,1,1,1]/dt

    x0s = [(i,0.) for i=1:n]
    itr0 = [(i,j,R[j]) for (i,j) in Base.product(1:N,1:p)]
    itr1 = [(i,j,Q[j],d(i,j,N)) for (i,j) in Base.product(1:N,1:n)]
    itr2 = [(j,Qf[j],d(N+1,j,N)) for j in 1:n]

    c = ExaCore(backend)

    x = variable(c,1:N+1,1:n)
    u = variable(c,1:N,1:p);

    constraint(c, x[1,i]-x0 for (i,x0) in x0s)
    constraint(c, -x[i+1,1] + x[i,1] + (x[i,2])*dt for i=1:N)
    constraint(c, -x[i+1,2] + x[i,2] +
        ↪ (u[i,1]*cos(x[i,7])*sin(x[i,8])*cos(x[i,9])+u[i,1]*sin(x[i,7])*sin(x[i,9]))*dt for i=1:N)
    constraint(c, -x[i+1,3] + x[i,3] + (x[i,4])*dt for i=1:N)
    constraint(c, -x[i+1,4] + x[i,4] +
        ↪ (u[i,1]*cos(x[i,7])*sin(x[i,8])*sin(x[i,9])-u[i,1]*sin(x[i,7])*cos(x[i,9]))*dt for i=1:N)
    constraint(c, -x[i+1,5] + x[i,5] + (x[i,6])*dt for i=1:N)
    constraint(c, -x[i+1,6] + x[i,6] + (u[i,1]*cos(x[i,7])*cos(x[i,8])-9.8)*dt for i=1:N)
    constraint(c, -x[i+1,7] + x[i,7] +
        ↪ (u[i,2]*cos(x[i,7])/cos(x[i,8])+u[i,3]*sin(x[i,7])/cos(x[i,8]))*dt for i=1:N)
    constraint(c, -x[i+1,8] + x[i,8] + (-u[i,2]*sin(x[i,7])+u[i,3]*cos(x[i,7]))*dt for i=1:N)
    constraint(c, -x[i+1,9] + x[i,9] +
        ↪ (u[i,2]*cos(x[i,7])*tan(x[i,8])+u[i,3]*sin(x[i,7])*tan(x[i,8])+u[i,4])*dt for i=1:N)

    objective(c, .5*R*(u[i,j]^2) for (i,j,R) in itr0)
    objective(c, .5*Q*(x[i,j]-d)^2 for (i,j,Q,d) in itr1)
    objective(c, .5*Qf*(x[N+1,j]-d)^2 for (j,Qf,d) in itr2)
```

```
|      m = ExaModel(c)
|
|  end
|
|  quadrotor_model (generic function with 2 methods)
|
|  using ExaModels, NLPModelsIpopt
|
|  m = quadrotor_model(100)
|  result = ipopt(m)
|
|  "Execution stats: first-order stationary"
```

This page was generated using [Literate.jl](#).

Chapter 9

Example: Distillation Column

```
function distillation_column_model(T = 3; backend = nothing)

    NT = 30
    FT = 17
    Ac = 0.5
    At = 0.25
    Ar = 1.0
    D = 0.2
    F = 0.4
    ybar = 0.8958
    ubar = 2.0
    alpha = 1.6
    dt = 10 / T
    xAf = 0.5
    xA0s = ExaModels.convert_array([(i, 0.5) for i = 0:NT+1], backend)

    itr0 = ExaModels.convert_array(collect(Iterators.product(1:T, 1:FT-1)), backend)
    itr1 = ExaModels.convert_array(collect(Iterators.product(1:T, FT+1:NT)), backend)
    itr2 = ExaModels.convert_array(collect(Iterators.product(0:T, 0:NT+1)), backend)

    c = ExaCore(backend)

    xA = variable(c, 0:T, 0:NT+1; start = 0.5)
    yA = variable(c, 0:T, 0:NT+1; start = 0.5)
    u = variable(c, 0:T; start = 1.0)
    V = variable(c, 0:T; start = 1.0)
    L2 = variable(c, 0:T; start = 1.0)

    objective(c, (yA[t, 1] - ybar)^2 for t = 0:T)
    objective(c, (u[t] - ubar)^2 for t = 0:T)

    constraint(c, xA[0, i] - xA0 for (i, xA0) in xA0s)
    constraint(
        c,
        (xA[t, 0] - xA[t-1, 0]) / dt - (1 / Ac) * (yA[t, 1] - xA[t, 0]) for t = 1:T
    )
    constraint(
        c,
        (xA[t, i] - xA[t-1, i]) / dt -
        (1 / At) * (u[t] * D * (yA[t, i-1] - xA[t, i]) - V[t] * (yA[t, i] - yA[t, i+1])) for
```



```

        (t, i) in itr0
    )
    constraint(
        c,
        (xA[t, FT] - xA[t-1, FT]) / dt -
        (1 / At) * (
            F * xAf + u[t] * D * xA[t, FT-1] - L2[t] * xA[t, FT] -
            V[t] * (yA[t, FT] - yA[t, FT+1])
        ) for t = 1:T
    )
    constraint(
        c,
        (xA[t, i] - xA[t-1, i]) / dt -
        (1 / At) * (L2[t] * (yA[t, i-1] - xA[t, i]) - V[t] * (yA[t, i] - yA[t, i+1])) for
        (t, i) in itr1
    )
    constraint(
        c,
        (xA[t, NT+1] - xA[t-1, NT+1]) / dt -
        (1 / Ar) * (L2[t] * xA[t, NT] - (F - D) * xA[t, NT+1] - V[t] * yA[t, NT+1]) for
        t = 1:T
    )
    constraint(c, V[t] - u[t] * D - D for t = 0:T)
    constraint(c, L2[t] - u[t] * D - F for t = 0:T)
    constraint(
        c,
        yA[t, i] * (1 - xA[t, i]) - alpha * xA[t, i] * (1 - yA[t, i]) for (t, i) in itr2
    )

    return ExaModel(c)
end

```

```
distillation_column_model (generic function with 2 methods)
```

```

using ExaModels, NLPModelsIpopt

m = distillation_column_model(10)
ipopt(m)

```

```
"Execution stats: first-order stationary"
```

Chapter 10

Example: Optimal Power Flow

```
function parse_ac_power_data(filename)
    data = PowerModels.parse_file(filename)
    PowerModels.standardize_cost_terms!(data, order=2)
    PowerModels.calc_thermal_limits!(data)
    ref = PowerModels.build_ref(data)[:it][:pm][:nw][0]

    arcdict = Dict{
        a=>k
        for (k,a) in enumerate(ref[:arcs])
    }
    busdict = Dict{
        k=>i
        for (i,(k,v)) in enumerate(ref[:bus])
    }
    gendict = Dict{
        k=>i
        for (i,(k,v)) in enumerate(ref[:gen])
    }
    branchdict = Dict{
        k=>i
        for (i,(k,v)) in enumerate(ref[:branch])
    }

    return (
        bus = [
            begin
                bus_loads = [ref[:load][l] for l in ref[:bus_loads][k]]
                bus_shunts = [ref[:shunt][s] for s in ref[:bus_shunts][k]]
                pd = sum(load["pd"] for load in bus_loads; init = 0.)
                gs = sum(shunt["gs"] for shunt in bus_shunts; init = 0.)
                qd = sum(load["qd"] for load in bus_loads; init = 0.)
                bs = sum(shunt["bs"] for shunt in bus_shunts; init = 0.)
                (
                    i = busdict[k],
                    pd = pd, gs = gs, qd = qd, bs = bs
                )
            end
            for (k,v) in ref[:bus]],
        gen = [
            (i = gendict[k],
             cost1 = v["cost"][1], cost2 = v["cost"][2], cost3 = v["cost"][3], bus =
             ↪ busdict[v["gen_bus"]])
            for (k,v) in ref[:gen]],
        arc = [
```

```

        (i=k, rate_a = ref[:branch][l]["rate_a"], bus = busdict[i])
    for (k,(l,i,j)) in enumerate(ref[:arcs]),
branch = [
    begin
        f_idx = arcdict[i, branch["f_bus"], branch["t_bus"]]
        t_idx = arcdict[i, branch["t_bus"], branch["f_bus"]]
        g, b = PowerModels.calc_branch_y(branch)
        tr, ti = PowerModels.calc_branch_t(branch)
        ttm = tr^2 + ti^2
        g_fr = branch["g_fr"]
        b_fr = branch["b_fr"]
        g_to = branch["g_to"]
        b_to = branch["b_to"]
        c1 = (-g*tr-b*ti)/ttm
        c2 = (-b*tr+g*ti)/ttm
        c3 = (-g*tr+b*ti)/ttm
        c4 = (-b*tr-g*ti)/ttm
        c5 = (g+g_fr)/ttm
        c6 = (b+b_fr)/ttm
        c7 = (g+g_to)
        c8 = (b+b_to)
        (
            i = branchdict[i],
            j = 1,
            f_idx = f_idx,
            t_idx = t_idx,
            f_bus = busdict[branch["f_bus"]],
            t_bus = busdict[branch["t_bus"]],
            c1 = c1,
            c2 = c2,
            c3 = c3,
            c4 = c4,
            c5 = c5,
            c6 = c6,
            c7 = c7,
            c8 = c8,
            rate_a_sq = branch["rate_a"]^2,
        )
    end
    for (i,branch) in ref[:branch]],
ref_buses = [busdict[i] for (i,k) in ref[:ref_buses]],
vmax = [
    v["vmax"] for (k,v) in ref[:bus]],
vmin = [
    v["vmin"] for (k,v) in ref[:bus]],
pmax = [
    v["pmax"] for (k,v) in ref[:gen]],
pmin = [
    v["pmin"] for (k,v) in ref[:gen]],
qmax = [
    v["qmax"] for (k,v) in ref[:gen]],
qmin = [
    v["qmin"] for (k,v) in ref[:gen]],
rate_a = [
    ref[:branch][l]["rate_a"]
    for (k,(l,i,j)) in enumerate(ref[:arcs])],

```

```

        angmax = [b["angmax"] for (i,b) in ref[:branch]],
        angmin = [b["angmin"] for (i,b) in ref[:branch]],
    )
end

convert_data(data::N, backend) where {names, N <: NamedTuple{names}} =
↳ NamedTuple{names}(ExaModels.convert_array(d,backend) for d in data)

parse_ac_power_data(filename, backend) = convert_data(parse_ac_power_data(filename), backend)

function ac_power_model(
    filename;
    backend = nothing,
    T = Float64
)

    data = parse_ac_power_data(filename, backend)

    w = ExaCore(T, backend)

    va = variable(
        w, length(data.bus);
    )

    vm = variable(
        w,
        length(data.bus);
        start = fill!(similar(data.bus,Float64),1.),
        lvar = data.vmin,
        uvar = data.vmax
    )

    pg = variable(
        w,
        length(data.gen);
        lvar = data.pmin,
        uvar = data.pmax
    )

    qg = variable(
        w,
        length(data.gen);
        lvar = data.qmin,
        uvar = data.qmax
    )

    p = variable(
        w,
        length(data.arc);
        lvar = -data.rate_a,
        uvar = data.rate_a
    )

    q = variable(
        w,
        length(data.arc);
        lvar = -data.rate_a,

```

```

    uvar = data.rate_a
)

o = objective(
    w,
    g.cost1 * pg[g.i]^2 + g.cost2 * pg[g.i] + g.cost3
    for g in data.gen)

c1 = constraint(
    w,
    va[i] for i in data.ref_buses)

c2 = constraint(
    w,
    p[b.f_idx]
    - b.c5*vm[b.f_bus]^2
    - b.c3*(vm[b.f_bus]*vm[b.t_bus]*cos(va[b.f_bus]-va[b.t_bus]))
    - b.c4*(vm[b.f_bus]*vm[b.t_bus]*sin(va[b.f_bus]-va[b.t_bus]))
    for b in data.branch)

c3 = constraint(
    w,
    q[b.f_idx]
    + b.c6*vm[b.f_bus]^2
    + b.c4*(vm[b.f_bus]*vm[b.t_bus]*cos(va[b.f_bus]-va[b.t_bus]))
    - b.c3*(vm[b.f_bus]*vm[b.t_bus]*sin(va[b.f_bus]-va[b.t_bus]))
    for b in data.branch)

c4 = constraint(
    w,
    p[b.t_idx]
    - b.c7*vm[b.t_bus]^2
    - b.c1*(vm[b.t_bus]*vm[b.f_bus]*cos(va[b.t_bus]-va[b.f_bus]))
    - b.c2*(vm[b.t_bus]*vm[b.f_bus]*sin(va[b.t_bus]-va[b.f_bus]))
    for b in data.branch)

c5 = constraint(
    w,
    q[b.t_idx]
    + b.c8*vm[b.t_bus]^2
    + b.c2*(vm[b.t_bus]*vm[b.f_bus]*cos(va[b.t_bus]-va[b.f_bus]))
    - b.c1*(vm[b.t_bus]*vm[b.f_bus]*sin(va[b.t_bus]-va[b.f_bus]))
    for b in data.branch)

c6 = constraint(
    w,
    va[b.f_bus] - va[b.t_bus] for b in data.branch;
    lcon = data.angmin,
    ucon = data.angmax
)

c7 = constraint(
    w,
    p[b.f_idx]^2 + q[b.f_idx]^2 - b.rate_a_sq for b in data.branch;
    lcon = fill!(similar(data.branch,Float64,length(data.branch)), -Inf)
)

c8 = constraint(

```

```

        w,
        p[b.t_idx]^2 + q[b.t_idx]^2 - b.rate_a_sq for b in data.branch;
        lcon = fill!(similar(data.branch,Float64,length(data.branch)), -Inf)
    )

    c9 = constraint(
        w,
        + b.pd
        + b.gs * vm[b.i]^2
        for b in data.bus)

    c10 = constraint(
        w,
        + b.qd
        - b.bs * vm[b.i]^2
        for b in data.bus)

    c11 = constraint!(
        w,
        c9,
        a.bus => p[a.i]
        for a in data.arc)
    c12 = constraint!(
        w,
        c10,
        a.bus => q[a.i]
        for a in data.arc)

    c13 = constraint!(
        w,
        c9,
        g.bus => -pg[g.i]
        for g in data.gen)
    c14 = constraint!(
        w,
        c10,
        g.bus => -qg[g.i]
        for g in data.gen)

    return ExaModel(w)

end

```

```
| ac_power_model (generic function with 1 method)
```

We first download the case file.

```

using Downloads

case = tempname() * ".m"

Downloads.download(
    "https://raw.githubusercontent.com/power-grid-lib/pglib-
    ↪ opf/dc6be4b2f85ca0e776952ec22cbd4c22396ea5a3/pglib_opf_case3_lmbd.m",
    case
)

```

```
| "/tmp/jl_qpi5CNgfAz.m"
```

Then, we can model/sovle the problem.

```
| using PowerModels, ExaModels, NLPModelsIpopt  
|  
| m = ac_power_model(case)  
| ipopt(m)
```

```
| "Execution stats: first-order stationary"
```

This page was generated using [Literate.jl](#).

Part IV

API Manual

Chapter 11

ExaModels

ExaModels.ExaModels – Module.

| ExaModels

An algebraic modeling and automatic differentiation tool in Julia Language, specialized for SIMD abstraction of nonlinear programs.

For more information, please visit <https://github.com/sshin23/ExaModels.jl>

[source](#)

ExaModels.ExaModel – Method.

| ExaModel(core)

Returns an ExaModel object, which can be solved by nonlinear optimization solvers within JuliaSmoothOptimizer ecosystem, such as NLPModelsIpopt or MadNLP.

Example

```
julia> using ExaModels

julia> c = ExaCore();           # create an ExaCore object

julia> x = variable(c, 1:10);   # create variables

julia> objective(c, x[i]^2 for i in 1:10); # set objective function

julia> m = ExaModel(c)          # creat an ExaModel object
An ExaModel

Problem name: Generic
All variables: ██████████ 10    All constraints: ..... 0
    free: ██████████ 10        free: ..... 0
    lower: ..... 0            lower: ..... 0
    upper: ..... 0            upper: ..... 0
    low/upp: ..... 0          low/upp: ..... 0
    fixed: ..... 0            fixed: ..... 0
    infeas: ..... 0           infeas: ..... 0
    nnzh: ( 81.82% sparsity) 10 linear: ..... 0
                                nonlinear: ..... 0
                                nnzj: (-----% sparsity)
```

```
julia> using NLPModelsIpopt

julia> result = ipopt(m; print_level=0)    # solve the problem
"Execution stats: first-order stationary"
```

[source](#)

ExaModels.constraint - Method.

```
constraint(core, generator; start = 0, lcon = 0, ucon = 0)
```

Adds constraints specified by a generator to core, and returns an Constraint object.

Keyword Arguments

- start: The initial guess of the solution. Can either be Number, AbstractArray, or Generator.
- lcon : The constraint lower bound. Can either be Number, AbstractArray, or Generator.
- ucon : The constraint upper bound. Can either be Number, AbstractArray, or Generator.

Example

```
julia> using ExaModels

julia> c = ExaCore();

julia> x = variable(c, 10);

julia> constraint(c, x[i] + x[i+1] for i=1:9; lcon = -1, ucon = (1+i for i=1:9))
Constraint

s.t. (...)
      gᵇ ≤ [g(x,p)]_{p ∈ P} ≤ gᵃ
where |P| = 9
```

[source](#)

ExaModels.multipliers - Method.

```
multipliers(result, y)
```

Returns the multipliers for constraints y associated with result, obtained by solving the model.

Example

```
julia> using ExaModels, NLPModelsIpopt

julia> c = ExaCore();

julia> x = variable(c, 1:10, lvar = -1, uvar = 1);

julia> objective(c, (x[i]-2)^2 for i in 1:10);

julia> y = constraint(c, x[i] + x[i+1] for i=1:9; lcon = -1, ucon = (1+i for i=1:9));
```

```
julia> m = ExaModel(c);

julia> result = ipopt(m; print_level=0);

julia> val = multipliers(result, y);

julia> val[1] ≈ 0.81933930
true
```

[source](#)

ExaModels.multipliers_L - Method.

```
| multipliers_L(result, x)
```

Returns the multipliers_L for variable x associated with result, obtained by solving the model.

Example

```
julia> using ExaModels, NLPModelsIpopt

julia> c = ExaCore();

julia> x = variable(c, 1:10, lvar = -1, uvar = 1);

julia> objective(c, (x[i]-2)^2 for i in 1:10);

julia> m = ExaModel(c);

julia> result = ipopt(m; print_level=0);

julia> val = multipliers_L(result, x);

julia> isapprox(val, fill(0, 10), atol=sqrt(eps(Float64)), rtol=Inf)
true
```

[source](#)

ExaModels.multipliers_U - Method.

```
| multipliers_U(result, x)
```

Returns the multipliers_U for variable x associated with result, obtained by solving the model.

Example

```
julia> using ExaModels, NLPModelsIpopt

julia> c = ExaCore();

julia> x = variable(c, 1:10, lvar = -1, uvar = 1);

julia> objective(c, (x[i]-2)^2 for i in 1:10);

julia> m = ExaModel(c);
```

```
julia> result = ipopt(m; print_level=0);

julia> val = multipliers_U(result, x);

julia> isapprox(val, fill(2, 10), atol=sqrt(eps(Float64)), rtol=Inf)
true
```

[source](#)

ExaModels.objective – Method.

```
| objective(core::ExaCore, generator)
```

Adds objective terms specified by a generator to core, and returns an Objective object.

Example

```
julia> using ExaModels

julia> c = ExaCore();

julia> x = variable(c, 10);

julia> objective(c, x[i]^2 for i=1:10)
Objective

    min (...) +  $\sum_{\{p \in P\}} f(x,p)$ 

    where |P| = 10
```

[source](#)

ExaModels.solution – Method.

```
| solution(result, x)
```

Returns the solution for variable x associated with result, obtained by solving the model.

Example

```
julia> using ExaModels, NLPModelsIpopt

julia> c = ExaCore();

julia> x = variable(c, 1:10, lvar = -1, uvar = 1);

julia> objective(c, (x[i]-2)^2 for i in 1:10);

julia> m = ExaModel(c);

julia> result = ipopt(m; print_level=0);

julia> val = solution(result, x);

julia> isapprox(val, fill(1, 10), atol=sqrt(eps(Float64)), rtol=Inf)
true
```

[source](#)

ExaModels.variable - Method.

```
| variable(core, dims...; start = 0, lvar = -Inf, uvar = Inf)
```

Adds variables with dimensions specified by `dims` to `core`, and returns `Variable` object. `dims` can be either `Integer` or `UnitRange`.

Keyword Arguments

- `start`: The initial guess of the solution. Can either be `Number`, `AbstractArray`, or `Generator`.
- `lvar`: The variable lower bound. Can either be `Number`, `AbstractArray`, or `Generator`.
- `uvar`: The variable upper bound. Can either be `Number`, `AbstractArray`, or `Generator`.

Example

```
julia> using ExaModels

julia> c = ExaCore();

julia> x = variable(c, 10; start = (sin(i) for i=1:10))
Variable
  x ∈ R^{10}

julia> y = variable(c, 2:10, 3:5; lvar = zeros(9,3), uvar = ones(9,3))
Variable
  x ∈ R^{9 × 3}
```

[source](#)

Part V

References

Chapter 12

References