

## 1 Basic Concurrency Primitives, Ch1

topics: interior mutability, threadsafety, runtime borrow check

### 1.1 single thread interior mutability

RefCell: borrow at runtime

Cell: value replacement, not borrow; limited to word size

### 1.2 threadsafe interior mutability

Mutex: exclusive borrow at runtime

RwLock: differentiates borrow type: exclusive vs. shared read only

Atomics: value replacement, not borrow; limited to word size

UnsafeCell: express raw pointer to wrapped data via unsafe block; in practice wrapped by a safer interface to user

Traits for threadsafety: Send, Sync

T: Send  $\iff$  T can be transferred to another thread

T: Sync  $\iff$  T can be shared with  $> 1$  threads; &T: Send  
all primitive types are Send + Sync

auto traits:

- automatically opt-in
- manually opt-out
- recursively deduced on fields of structs

un-implemented types:

```
Cell<T>: Send + Sync!
* const T / * mut T: !Send + !Sync
Rc<T>: !Send + !Sync
std::marker::PhantomData<T> where T: !Send / !Sync
```

force opt-in for un-implemented type:

```
unsafe impl Send/Sync for T {}
```

### 1.3 Mutex

T is usually Send(not required) in which case the Mutex gives Sync:

T: Send  $\impl$  Mutex<T>: Sync

logical states: unlocked, locked

owning wrapper over T

interface makes access to T safer

MutexGuard as proof of exclusive access; drop automatically triggers unlock at the end of its lifetime

efficient usage: make locked interval as short as possible

lock poisoning: when thread panics while holding the lock

- lock is released
- the invoking method call errors
- further invoking a poisoned mutex returns error and also a locked MutexGuard in case user can correct it to some consistent state

unnamed guard may not be immediately dropped in certain statements:

```
if ... /*dropped here; only boolean value needed*/ {
    ...
}

if let ... = ... {
    ... /*dropped here; may borrow from let expression*/
}
```

### 1.4 ReaderWriterLock

requires T: Send + Sync:

T: Send + Sync  $\impl$  RwLock<T>: Send + Sync

logical states: uncoked, locked by 1 exclusive accessor, locked by any number of shared readers

differentiating lock guards:

read()  $\impl$  ReLockReadGuard: Deref

write()  $\impl$  ReLockWriteGuard: DerefMut

writer starvation issue to consider for fairness of access

### 1.5 Thread Signaling

#### 1.6 park/unpark

park: current thread put itself to sleep

unpark: another thread wakes sleeping thread; needs handle of the sleep read from spawn() method or thread::current()

spurious wakeup due to false sharing, etc.  $\impl$  user provide a check upon wakeup

request to unpark recorded if unpark happens before park in order to avoid lost notification, but does not stack up (max of 1 unpark recorded)

## 1.7 Condition Variable

signaling events related to protected data of mutex

methods: wait, notify

atomically unlock mutex and start waiting (to avoid lost notification)

### 1.7.1 Communication

waiting thread:

takes MutexGuard as input unlocks mutex thread put to sleep  
thread wakes (via a notify of CondVar or spurious wakeup)  
relocks mutex and returns MutexGuard

notifying thread:

invoke notify on CondVar

### 1.7.2 Spurious Wakeup

need additional memory to check actual event: can add this  
along with the original value wrapped by mutex  
use a loop with wait to put thread back to sleep if condition  
not met

usage: 1 CondVar for 1 mutex

optionally can wait with timeout parameter to unconditionally  
wakeup thread after timeout

## 1.8 Comparison of Interior Mutability Primitives

	value replacement	reference / borrow
1 thread	Cell	RefCell
threadsafe	Atomic	Mutex/RwLock

## 1.9 Comparison of Shared Ownership Primitives

Rc/Arc: act similar to Box / smart pointer but with dropping  
logic to take care of deallocation for shared data

1 thread	Rc
threadsafe	Arc

## 1.10 Traits for Interior Mutability Primitives

$T: \text{Send} \implies \text{Cell}\langle T \rangle: \text{Send} + !\text{Sync}$  (usual practical case)

$T: !\text{Send} \implies \text{Cell}\langle T \rangle: !\text{Send} + !\text{Sync}$

$T: \text{Send} \implies \text{RefCell}\langle T \rangle: \text{Send} + !\text{Sync}$  (usual)

$T: !\text{Send} \implies \text{RefCell}\langle T \rangle: !\text{Send} + !\text{Sync}$

$T: \text{Send} \implies \text{Mutex}\langle T \rangle: \text{Send} + \text{Sync}$  (usual)

$T: !\text{Send} \implies \text{Mutex}\langle T \rangle: !\text{Send} + !\text{Sync}$

$T: \text{Send} + \text{Sync} \implies \text{RwLock}\langle T \rangle: \text{Send} + \text{Sync}$  (usual)

$T: !\text{Send} / !\text{Sync} \implies \text{RwLock}\langle T \rangle: !\text{Send} + !\text{Sync}$

## 1.11 Traits for Shared Ownership Primitives

$\text{Rc}\langle T \rangle: !\text{Send} + !\text{Sync}$

$T: \text{Send} + \text{Sync} \implies \text{Arc}\langle T \rangle: \text{Send} + \text{Sync}$

## 1.12 Typical Usage Pattern

$\text{Arc}\langle \text{Mutex}\langle T \rangle \rangle$

where:

Arc allows threadsafe immutable sharing

Mutex allows interior mutability using references across  $\geq 1$  threads

$\text{Rc}\langle \text{RefCell}\langle T \rangle \rangle$

where:

Rc allows single thread immutable sharing

RefCell allows interior mutability using references in single thread

$\text{Rc}\langle \text{Cell}\langle T \rangle \rangle$

where:

Rc allows single thread immutable sharing

Cell allows interior mutability using value in single thread

$\text{Arc}\langle \text{Atomic}\langle T \rangle \rangle$

where:

Arc allows threadsafe immutable sharing

Atomic allows interior mutability using value across  $\geq 1$  threads

## 2 Atomics

fetch\_and\_modify  
swap  
compare\_exchange:

- ABA problem for pointer algorithms
- weak version exists for more efficient impl. on some hardware at expense of spurious wakeup

fetch\_update  $\iff$  load followed by loop with compare\_exchange\_weak and user provided computation

### 2.1 Scoped Thread

regular `std::thread::spawn` requires closure to be Send  $\implies$  all captures of closure are required to be Send

`std::thread::scope`:

borrowed object of non-static lifetime that can outlive thread mutability rules apply  
threads are automatically joined at the end of the scope

### 2.2 Lazy Initialization

execute once by 1 thread, sharable afterwards  
race possible from threads, but this is different from data race which causes undefined behaviour (UB)  
can use `CondVar` / thread parking / `std::sync::Once` / `std::sync::OnceLock` to avoid wasted compute from multiple threads

### 2.3 Move Closure

transfer ownership of value  
capture variable via copying/moving instead of borrowing  
copying reference in a move closure in order to borrow from variable  
note: Atomic does not implement Copy trait

### 2.4 Data Sharing Between Threads in General

data shared need to outlive all involved threads:

- make data owned by entire program via static lifetime (static item exists even before start of the main program)
- leak an allocation and promise never to drop it from that point onward in the duration of the entire program: eg: `Box::leak(Box::new(...))`  
note: 'static means the object will exist until the end of the program but may not exist at the start of the program  
note: Copy *implies* when moved, the original value still exists
- reference counting: track ownership and drop when no owners  
eg: `std::rc::Rc`: clone increments counter only and gives reference to allocation  
eg: `std::sync::Arc`: version of `Rc` that is safe between threads

use of scope and variable shadowing to reuse identifiers when cloning:  
shadowing: original name is not obtainable anymore in current scope  
original name still obtainable in an outerscope, can clone it in another inner scope

reference counted pointers(`Rc` and `Arc`) have same restrictions as immutable reference (`&T`)

mutable borrows are guaranteed at compile time  $\implies$  mutable aliasing between 2 variables does not occur; optimization to remove impossible code blocks possible

assumptions held by the compiler:

- an immutable reference exists *implies* no other mutable references to the associated data exists
- there is at maximum 1 mutable reference to an object at anytime

if such assumptions are broken, then UB exists: more wrong conclusions may be propagated through optimizations

`unsafe` blocks are also assumed to be sound by the compiler which means compiler may apply optimizations and elide code when feasible

### 2.5 Interior Mutability

shared reference `&T`: copied and sharable (not mutable)  
exclusive reference `& mut T`: exclusive borrow of T

interior mutability provides more flexibility for shared data that needs mutation

`Cell` / `Atomic`: replace value, no borrow

`RefCell` / `Mutex`: runtime borrowing; book-keeping cost for existing borrows; failable at runtime

### 3 Memory Ordering

defining happens-before relations across threads

concurrent non-atomic stores to same variable causes data race  $\Rightarrow$  UB

lack of globally consistent order

thread spawn/join: automatically enforces happens-before relation

note: current theoretical model for formalizing memory ordering bug: cyclic reasoning / value out of thin air

#### 3.0.1 Relaxed Ordering

- per atomic variable: a total modification order in every run of the program  $\Rightarrow$  all modifications of the said atomic variable happen in 1 order that is consistent/same from views of every thread
- multiple possible orderings may exist when the program is run multiple times, but each run satisfies a total modification order
- no happens-before relation

#### 3.0.2 Release-Acquire Ordering Pair

pairing:

store operation specified with release semantics

load operation specified with acquire semantics

happens-before relation formed at runtime when load succeeds: all memory operations before release store is observable by and after acquire load

release store of an atomic variable may be modified by any number of fetch-modify / compare-exchange operations and still have a happens-before relation with an acquire load afterwards on the said atomic variable

any store of the associated atomic variable breaks the chain of a release-acquire pair (that previously starts with a release store and possibly followed with fetch-modifies/compare-exchanges)

use of non-atomic variable in different threads and borrow checker  $\Rightarrow$  may need unsafe blocks

#### 3.0.3 Release-Consume Ordering Pair

pairing:

store operation specified with release semantics

load operation specified with consume semantics

happens-before relation for associated atomic variable in the release store and the dependent expressions in the consumer thread

practically, hard to define dependent evaluation and implementation tends to fallback to acquire semantics instead

#### 3.0.4 Sequentially Consistent Ordering

pairing:

store operation specified with SeqCst semantics

load operation specified with SeqCst semantics

guarantees of:

- acquire ordering
- release ordering

- globally consistent ordering of all SeqCst operations (every SeqCst operation in a program is a part of a single total order that all threads agree on)

can replace acquire and release ordering and maintain happens-before relation

#### 3.1 Memory Fence

separate memory ordering semantics from atomic operations

it can take place of acquire / release / other memory order operations

types of fences:

- release fence
- acquire fence
- acquire-release fence
- sequentially consistent fence

##### 3.1.1 Practical Replacement

without fences	with fences
release store	fence with release ordering ... atomic store (any memory ordering)
acquire load	atomic load (any memory ordering) ... fence with acquire ordering

any atomic store following release fence is observable by any atomic load before acquire fence  $\Rightarrow$  happens-before relation is established between the release-acquire fences pairing

##### 3.1.2 Practical Usages

- can be used for multiple variables at once
- conditional fence (apply happens-before relation only after certain condition is met)  
eg: place acquire fence in conditional branch that succeeds that is relevant to the atomic variable  

```
let p = var.load(relaxed);
if p == ... {
    fence(acquire);
    do_something(...);
}
```
- may be more efficient if atomic variable is expected to fail in comparison often (let atomic variable be loaded with relaxed memory ordering)

##### 3.1.3 SeqCst Fence

- is both a release fence and an acquire fence
- is part of a single total order of sequentially consistent operations

#### 3.2 Compiler Fence

does not prevent processor from reordering instructions

Rust compiler fence: `std::sync::atomic::compiler_fence`

uses:

- process-wide memory barriers
- special cases of signal handler/interrupt

### 3.3 FAQs

memory model is not related to timing

memory model defines order of operations and affects instruction reordering

SeqCst implies the operation depends on the total order of every single SeqCst operation in the program

⇒ usually overly tall claim

⇒ more relaxed constraints may be easier to review (eg: release-acquire pairs)

release store not form happens-before relation with SeqCst store: for a part of a globally consistent order, both operations need to be SeqCst

### 3.4 Summary

each atomic variable has its own total modification order that all threads agree on

single thread: happens-before relations exist between every single operations

unlocking a mutex happens-before locking that mutex

SeqCst results in 1 globally consistent order of operations that participates in SeqCst, but it is usually overly constraining

fences allow combining memory ordering of multiple operations for efficiency or applying conditional memory ordering for efficiency

happens-before relation exist when:

- threads spawn / join
- acquire load from a release store on an atomic variable
- fetch-modifies / compare-exchanges in between a release-acquire pair on an atomic variable is still valid for that happens-before relation

## 4 Processor

## 5 OS Primitives

## 6 Primitive Implementation Examples

### 6.1 Spin Lock

release store (unlock) and acquire load (lock) pair for prevention of data race (UB)

`std::hint::spin_leap()`: possible optimization of processor

possible implementation:

- wraps actual data inside an `UnsafeCell<T>` for interior mutability
- requires `T: Send`
- locking provides exclusive access (and provides `Sync` trait)
- uses `unsafe` blocks in function, user will not have to use `unsafe`
- use lock guard (representing safe access to locked data) pattern to manage lifetime of locked access to protected data:
  - implement `Deref`, `DerefMut` to access data for user ergonomics (behave similar to reference)
  - implement `Drop`: automatic release store (unlocking) when lifetime of the guard ends
  - manual drop also possible: this consumes and ends the valid lifetime of the guard and hence access to data at compile time  $\Rightarrow$  any further reference and borrow to guard is invalid and will be flagged as error by the compiler

### 6.2 Channels

#### 6.2.1 One Shot Channel

- 1 message only from 1 thread to another thread
- `T: Send`
- use of `unsafe`:
  - may be uninitialized
  - non-copy data must not be duplicated
  - manual content drop may be necessary: leaking/forgetting is safe but sometimes undesirable
  - eg: `std::mem::MaybeUninit<T>` (unsafe version of `Option<T>`)
- can use `UnsafeCell` for interior mutability when sharing across multiple threads
- use type checking and static analysis to avoid errors: move/consume to avoid unwanted reuse of resources
- use of `Arc<T>` for sharing and resource dropping: `RX` drop and `TX` drop  $\Rightarrow$  `Arc<T>` drop  $\Rightarrow$  `T` drop
- allocation optimization: user borrowed channel instead of creating an `Arc` and managing it: use of lifetimes and mutable borrow for compile time checks
- overwriting content for fresh initialization: after 1st borrow expires, subsequent borrows are made on these newly created resources
- `TX`, `RX` take in additional lifetime parameter which is the same as the lifetime of the borrowed channel: when `TX` or `RX` is present, existing channel cannot be mutably borrowed again until `TX` and `RX` are both dropped

- channel needs to outlive TX and RX for compiler check to pass
- blocking interface:
  - make RX object not `Send`, such as using a `PhantomData<* const ()>` member field so that auto trait deduction for the wrapping struct is propagated to be `!Send`:
 

```
* const () : !Send ==>
PhantomData<* const ()> : !Send ==>
wrapping struct is !Send
```
  - use receiving thread's handle to invoke waking up a blocked thread (place this inside the sender struct)
  - call `unpark` on receiving thread's handle after release store operation is performed by the sender

### 6.3 Arc

### 6.4 Locks