
How Much of Platonic Convergence is Semantic? Measuring Alignment in the Jacobian Subspace

Anonymous Author(s)

Affiliation

Address

email

Abstract

1 The Platonic Representation Hypothesis [13] asserts that neural networks converge towards a shared representation of reality as they become more competent.
2 Current evidence for this hypothesis comes from full activation space alignment,
3 which mixes semantic content with superficial regularities like document length
4 and syntax. We instead measure alignment in the Jacobian space (J-space), the
5 privileged subspace induced by the Jacobian lens (J-lens) [11], and find it is
6 a more semantically selective measure, though a random-dictionary control attributes only part of that selectivity to the J-space itself.
7

8
9 Measuring alignment in the J-space, we still find that models converge: the text–
10 text Spearman correlation between competence and alignment is $\rho = +0.56$,
11 $p = 0.0162$, and the text–vision correlation is $\rho = +0.97$, $p < 10^{-4}$. Within
12 language, though, the J-space converges much more slowly than the full activation
13 space, so part of the apparent link between competence and convergence is
14 carried by superficial structure. Consistent with this, the gap between J-space and
15 full convergence disappears across modalities, where no such structure is shared.

16 This convergence is also legible: using the J-lens at matched layer depth, independently
17 trained models name 5.1 of 25 shared vocabulary words against 2.0 for the
18 plain logit lens. J-lens overlap rises with competence ($\rho = +0.74$, $p = 0.0020$).
19 Overall, full-space alignment is partially confounded by superficial structure, and
20 semantically selective measures like the J-space can help isolate meaningful convergence.
21 Code available at [placeholder].


22 1 Introduction

23 The Platonic Representation Hypothesis [13] asserts that “Neural networks, trained with different
24 objectives on different data and modalities, are converging to a shared statistical model of reality
25 in their representation spaces.” Concretely, the claim is that alignment between two models grows
26 with their competence. To our knowledge, alignment has thus far been computed over the full
27 representational spaces.¹ We show this method conflates semantic content with confounding surface-
28 level similarities like syntax, length, and formatting.


29 Recently, Gurnee et al. [11] introduced a new interpretability technique, the Jacobian lens (J-lens),
30 which recovers the concepts a language model is poised to verbalise at a given layer. The J-lens
31 induces the J-space, a privileged subspace of internal representations available for report and reasoning.
32 It is semantically significant, acting as a “global workspace” for the model, and privileged,
33 capturing a median of only 6–7% of a concept vector’s variance [11].

¹We say “full activation space” rather than “full representational space”, since every quantity we compare is a mean-pooled residual-stream vector at a given layer.

(a) The J-lens splits a pooled activation



(b) Retention after randomising content



(c) Slope of alignment vs. competence




Figure 1: **Measuring Platonic convergence in the J-space.** (a) The J-lens splits a pooled activation into a J-space component and a non-J remainder. The document shown above is the example found in Section 3.1. The list of words is illustrative. (b) Randomising content words retains 26.3% of J-space alignment and 54.1% of full-activation alignment. When applying the same J-space measurement with a random Gaussian dictionary rather than a J-lens, it is found that this alignment retains 34.7% (Table 1). (c) In regards to language, J-space alignment rises with competence at a rate that is approximately one third the rate that full activation alignment does. Across modalities, J-space alignment and full activation alignment converge at around equal rates (Figure 2).

Thus, we hypothesise that the J-space will provide a more semantically selective measure of convergence than the full activation space, in the sense that J-space alignment will drop more sharply when semantic content is removed.

Motivating experiment We compute alignment using “mutual κ -nearest-neighbour overlap” between pairs of models. Other metrics are reported in Appendix D. We do this once on an ordinary dataset of text documents and once on the same documents with content words randomised but sentence structure preserved. We find that over half of the full alignment is retained, compared with just over a quarter of J-space alignment. A random-dictionary control separates how much of this gap is attributable to the J-lens itself as opposed to the sparse coding effect of decomposition (Section 4.1).

We use the J-space to re-examine the Platonic Representation Hypothesis’s central claim, and find that models do indeed converge under this stricter measure.

Our three experiments (Figure 1) compare 1) J-space against full alignment for text models (including the content-ablated motivating experiment); 2) text models against vision encoders, which have no J-space of their own; and 3) the J-lens readouts of text models, where outputs are vocabulary tokens and no machinery is needed. For each case, we calculate convergence as the correlation between alignment and competence. The third experiment also compares J-lens overlap with logit lens overlap [19] as a control.

Related work Representational similarity has been measured in many ways: RSA compares dissimilarity matrices [16], SVCCA compares subspaces through canonical correlation [24], and centred kernel alignment (CKA) compares item-item kernels, with invariance to orthogonal transformation and isotropic scaling [15]. Huh et al. [13] measure convergence using mutual κ -nearest-neighbour overlap [21] and CKNN. Some work [24, 28] does restrict attention to a subspace, but always by introducing a new measure of alignment.

We instead vary only the *subspace* the metric is computed in, holding the metric itself fixed. Appendix D repeats the comparison under seven further metrics.

Platonic convergence is also contested. Gröger et al. [10] suggest model alignment is inflated, and Bangachev et al. [1] partly attribute alignment to word frequency. It is well-established that alignment measures capture non-semantic structure. We instead examine how much of the competence–convergence relationship is semantic using the J-space. To our knowledge, the J-space has not yet been used to examine convergence.

Contributions

1. We propose measuring alignment between models in the J-space rather than the full activation space, and we validate the J-space as a semantically selective measure of alignment using an intervention. We find that randomising content words removes 74% of J-space alignment but only 46% of full-activation alignment, though only about one third of this gap can be directly attributed to the J-space rather than its sparse coding.
2. We find that part of the existing competence–convergence relationship rests on structure that is shared, but not semantic. Indeed, within language, J-space alignment rises with competence at roughly a third the rate of the full activation space, while across modalities (where no such shared structure exists) the two rates are indistinguishable.
3. We show that J-space convergence is meaningful and can be read as words using the J-lens. At matched relative layer depth, independently trained models name 5.1 of 25 shared vocabulary words against 2.0 for the plain logit lens. J-lens readouts also converge as competence increases, at least as closely as the neighbour-overlap measure.

2 Formal setup

We first define the alignment measure used in Experiments 1 and 2. Our third experiment needs no machinery beyond the J-lens itself, since the readouts are in a shared vocabulary space.

For the first two experiments there is no such shared output space. For instance, two models may have different residual widths or different modalities. We therefore adapt the method of Huh et al. [13], which measures alignment by kernels rather than the representations themselves. Between language models, we compare the kernels induced by the J-spaces of the models. Across modalities, we compare the kernel induced by the J-space of the text model to the kernel built from raw pooled patch features.

Let $A, B, \dots$ denote language models with residual widths $r_A, r_B, \dots$ and layer counts $L_A, L_B, \dots$ that generally differ. We index layers by $\ell \in \{0, \dots, L_A - 1\}$ and write $\lambda = \ell / (L_A - 1) \in [0, 1]$ for the corresponding *relative depth*.

We consider alignment over input items. For text–text comparisons, item i is a document and both models receive it. For text–vision comparisons, item i is an image–caption pair, with each encoder receiving its respective input. For each model, layer ℓ , and item i , we mean-pool the residual stream over the item’s tokens or patches, giving $h_i^{A,(\ell)} \in \mathbb{R}^{r_A}$.

For each language model, we compute the fitted J-lens [11]:

$$J_\ell^A = \mathbb{E}_i \left[\mathbb{E}_{(s' \geq s)} \left[\frac{\partial h_{s',i}^{A,(\text{final})}}{\partial h_{s,i}^{A,(\ell)}} \right] \right] \in \mathbb{R}^{r_A \times r_A},$$

where s and s' index tokens with $s' \geq s$, since a token cannot affect its predecessors.

Let $W_U^A \in \mathbb{R}^{m_A \times r_A}$ be model A ’s unembedding matrix, mapping its final residual stream to m_A vocabulary logits. We preprocess W_U^A by folding in the gain w^A of model A ’s final normalisation layer and centring it over the m_A output coordinates:

$$\widetilde{W}_U^A = \left(I_{m_A} - \frac{1}{m_A} \mathbf{1} \mathbf{1}^\top \right) W_U^A \text{diag}(w^A), \quad \mathbf{1} \in \mathbb{R}^{m_A}.$$

99 The J-space dictionary for layer ℓ of model A , with rows $d_{\ell,v}^A$ that are directions in residual-stream
 100 space, is

$$D_\ell^A = \widetilde{W}_U^A J_\ell^A \in \mathbb{R}^{m_A \times r_A}.$$

101 2.1 Decomposing activations into the J-space and remainder

102 We write each pooled activation as a sparse non-negative combination of $k = 25$ J-space dictionary
 103 directions, which is how we split the activations into their J-space and non-J remainder. To select
 104 the subset $\mathcal{S}_i$ of dictionary coordinates with $|\mathcal{S}_i| = k$, we use a greedy orthogonal matching pursuit
 105 (OMP). We then refit the coefficients $\alpha_{i,v}$, where $v \in \mathcal{S}_i$, with a projected-gradient non-negative
 106 least-squares (NNLS) step.

107 Denote by $\bar{d}_{\ell,v}^A$ the normalised unit directions, and write $h_{\text{full},i}^{A,(\ell)} \equiv h_i^{A,(\ell)}$ for the full pooled activation.
 108 Then, we have

$$h_{J,i}^{A,(\ell)} = \sum_{v \in \mathcal{S}_i} \alpha_{i,v} \bar{d}_{\ell,v}^A, \quad h_{\perp,i}^{A,(\ell)} = h_{\text{full},i}^{A,(\ell)} - h_{J,i}^{A,(\ell)}.$$

109 We thus consider three components, written $h_{\omega,i}^{A,(\ell)}$ for $\omega \in \{\text{full}, J, \perp\}$: the full activation $h_{\text{full},i}^{A,(\ell)}$,
 110 the J-space component $h_{J,i}^{A,(\ell)}$, and the non-J remainder $h_{\perp,i}^{A,(\ell)}$. Our aim is to compare alignment
 111 computed from each.

112 2.2 Kernels

113 Each component is winsorised at the 95th percentile and normalised to unit magnitude, and we
 114 denote the preprocessed components by $\hat{h}_{\omega,i}^{A,(\ell)}$. The kernel for model A , layer ℓ , and component ω
 115 is the $n \times n$ matrix of cosine similarities between items,

$$K_\ell^{A,\omega}(i, j) = \left\langle \hat{h}_{\omega,i}^{A,(\ell)}, \hat{h}_{\omega,j}^{A,(\ell)} \right\rangle.$$

116 The dictionaries of text models have one row per vocabulary token [3, 8], but a vision analogue
 117 would not be as easily interpretable: MAE [12] decodes to raw pixels, and DINOv2 [20] decodes
 118 to abstract prototypes. We thus apply the J-lens only to the caption side, building image kernels
 119 from raw pooled patch features, so on the image side, only $\omega = \text{full}$ is defined. The image kernel
 120 $K_\ell^{\text{img}, \text{full}}$ is formed by the same cosine-similarity expression from the preprocessed² mean-pooled
 121 patch activations.

122 2.3 Mutual κ -nearest-neighbour alignment

123 We compare two kernels through mutual κ -nearest-neighbour overlap [21]. Taking each item's
 124 κ nearest neighbours under each kernel (the κ largest off-diagonal entries of its row), we define
 125 $\text{m-NN}(K_\ell^{A,\omega}, K_{\ell'}^{B,\omega'})$ between layer ℓ of model A and layer ℓ' of model B as the average fraction
 126 of neighbours shared by the two kernels, over all n items.

127 For a text–text comparison, both sides carry the same component, $\omega' = \omega$. For a text–vision com-
 128 parison, the caption side varies over $\omega \in \{\text{full}, J, \perp\}$ while the image side is fixed at $\omega' = \text{full}$.

129 Finally, we define the alignment between A and B for component ω as the mean over layer pairs
 130 $(\ell, \ell') \in \mathcal{B}_A \times \mathcal{B}_B$, where $\mathcal{B}_A = \{\ell : 0.35 \leq \ell/(L_A - 1) \leq 0.90\}$ is the relative layer depth band:

$$\mathcal{A}^\omega(A, B) = \text{mean}_{\ell, \ell'} \text{m-NN}(K_\ell^{A,\omega}, K_{\ell'}^{B,\omega'}).$$

²The image side is winsorised per coordinate at the 0.5th and 99.5th percentiles, then normalised to unit magnitude.

3 Experiment setup

3.1 Text–text alignment and motivating experiment

We compare the following 11 text models of varying size and architecture: Pythia-70M [2], GPT-2 [22], Gemma-3-270M [7], Qwen3.5-0.8B [26], Gemma-3-1B, Qwen3-1.7B [27], Qwen3.5-2B, Gemma-2-2B [6], Qwen3-4B, Qwen3.5-4B, and Gemma-3-4B.

For the first experiment, we use the prefitted J-lenses on Neuronpedia [17], and compute alignment across all $\binom{11}{2} = 55$ text–text pairs on 1,000 documents from pile-10k [18], a subset of the Pile [5]. We take the first 1,000 rows, truncate each to at most 1,500 characters, then to at most 300 tokens, and mean-pool over token positions. Any difference in tokeniser efficiency is quite marginal, from 3.79 to 4.19 characters per token. Measured over the corpus, the least efficient tokeniser still ingests 94.8% as many characters per document as the most efficient. Neighbourhoods are taken at $\kappa = 10$.

Following the procedure described in the previous section, we evaluate shared semantic content for the J-space, the non-J remainder, and the full activation space over the original corpus. We then repeat the measurement on a content-ablated variant of the same 1,000 documents. We preserve syntactic structure, replacing each non-stopword alphabetic token (i.e. each content word) with another drawn from the same log-frequency bin. For example, “Remember that children each progress at their own rate.” becomes “Reduce that self each rates at their own special.” Comparing these two results isolates how much of each component’s alignment is semantic.

To assess how much of the retention drop comes from the sparse coding of the J-space, we run a Gaussian dictionary through the same content-ablation test and compute its retention rate.

Finally, we relate alignment to competence, measuring competence³ using the HellaSwag benchmark [29]. Appendix B repeats the analysis with different competence axes.

3.2 Text–vision alignment

For our second experiment, we compare DINOv2, MAE, CLIP [23], and SigLIP [30] against the 11 language models for a total of $4 \times 11 = 44$ text–vision model pairs. All four are ViT-Base encoders [4] with different pretraining objectives. Alignment is computed as in Section 2 over 1,024 image–caption pairs from the Wikipedia-based Image Text (WIT) dataset [25].

For tractability, we compute mean alignment over a subset of the layers. On the text side, we consider at most⁴ five evenly spaced layers from the band $\mathcal{B}_A$. On the vision side, we consider the final hidden state along with five evenly spaced blocks from index 2 to final $- 2$. For a model pair, this gives at most $5 \times 6 = 30$ layer pairs.

We consider a competence axis only on the text side, using the same HellaSwag benchmark.

3.3 Text–text shared J-lens output

For our third experiment, we apply the prefitted J-lenses per model and per layer over 200 documents in the pile-10k dataset [18]. Each document is first truncated to at most 1,500 characters, then to at most 300 tokens. We read the lens out as words, keeping the top $t = 25$ entries.

$$\text{lens}_\ell^A(h) = \text{softmax}(W_U^A \text{norm}^A(J_\ell^A h)).$$

Since the 11 models do not share a tokeniser, we restrict the J-lens to the 31,548 strings that are a single token in all 11 vocabularies. We also index positions by character rather than by token, evaluating at 6,000 character positions that fall at a token-end word boundary in all 11 tokenisers.

We then measure how many of the $t = 25$ words are shared between model pairs as a function of relative layer depth $\lambda = \ell/(L_A - 1)$. We compare against the logit lens [19], which outputs the next-token prediction if the model stopped at a given layer by reading the residual stream directly: $\text{softmax}(W_U^A \text{norm}^A(h))$.

We then relate J-lens overlap to mean HellaSwag accuracy for each model pair to re-evaluate the convergence trend measured in Experiment 1.

³All benchmark results were self-computed to ensure consistency.

⁴The layer band for Pythia-70M contains only two layers. All other text models use five layers.

Table 1: Alignment on real versus content-ablated documents over 55 model pairs. Retention is the mean over all pairs of content-ablated alignment divided by the original alignment, and is substantially lower for the J-space than for the full space. The lower block repeats the ablation with the J-lens dictionary replaced by a Gaussian dictionary. Bracketed intervals are 95% percentile bootstrap confidence intervals over the 55 model pairs (2,000 resamples).

	Real alignment	Content-ablated alignment	Retention
<i>Components, J-lens dictionary</i>			
full	0.5577 [0.539, 0.579]	0.3009 [0.290, 0.312]	54.1% [53.01, 55.14]
non-J	0.5057 [0.484, 0.529]	0.2609 [0.252, 0.271]	52.0% [50.73, 53.30]
J	0.4202 [0.409, 0.432]	0.1099 [0.108, 0.112]	26.3% [25.63, 27.02]
<i>J-space under a substituted dictionary</i>			
Gaussian	0.2103 [0.202, 0.220]	0.0719 [0.071, 0.073]	34.7% [33.66, 35.85]

176 All experiments were run on a single RTX 3080 (10 GB) GPU, taking a total of around 40 hours.

177 4 Results

178 4.1 Text–text alignment and motivating experiment

179 When we randomise all content words, the full alignment retains a mean of 54.1% of its original
180 value, while J-space alignment retains only 26.3% (Table 1). To test how much of this drop comes
181 from the sparse coding itself, we repeat the ablation experiment with a randomised Gaussian dictio-
182 nary instead of the J-space dictionary. Under this control, retention is 34.7%, meaning sparse coding
183 accounts for 69.7% of the drop between full and J-space retention. However, the remaining third is
184 still attributable to the J-space itself.

185 J-space alignment therefore depends more heavily on content than the full activation space.

186 Mean alignment for the J-space (0.420), the non-J remainder (0.506), and the full activation space
187 (0.558) is significant, between $42.0\times$ and $55.7\times$ the chance level.

188 For each model pair, we compare alignment and the mean of their competences. We find a positive
189 correlation across the J-space (Spearman correlation $\rho = +0.56$, $p = 0.0162$), full activation ($\rho =$
190 $+0.77$, $p = 0.0008$), and remainder ($\rho = +0.87$, $p < 0.0001$) (Figure 2(a)). Since pairs are not
191 independent, p -values come from permuting competence across models while holding alignment
192 values fixed.

193 The rate of convergence in the J-space is about a third of that in the full activation space. Alignment
194 rises with pair competence at $+0.76 \pm 0.09$ per unit HellaSwag accuracy in the full activation space
195 against $+0.23 \pm 0.07$ in the J-space.

196 4.2 Text–vision alignment

197 Alignment between text models and vision encoders for each component is significant, between
198 $6.8\times$ and $7.4\times$ the chance level. It correlates strongly and positively with competence across the J-
199 space ($\rho = +0.97$, $p < 10^{-4}$), the full activation space ($\rho = +0.93$, $p = 0.0001$), and the remainder
200 ($\rho = +0.92$, $p = 0.0002$) (Figure 2(b)).

201 Unlike the text–text comparison, we do not correlate competence with alignment across all 44 text–
202 vision pairs—since the four encoders differ from one another far more than the text models do, this
203 would obscure the actual trend. Indeed, mean J-space alignment ranges from 0.053 for MAE to
204 0.087 for SigLIP, a spread well in excess of the standard deviation of cross-modal alignment across
205 the 11 text models (0.0134).

206 We instead average alignment within each encoder, then average these four values. We report the
207 four within-encoder J-space correlations, which range from $+0.95$ to $+0.97$, in Appendix A.

208 Cross-modally, there is no shared superficial structure for a full-space metric to capture, so intu-
209 itively, J-space and full alignment should match, and they do. This is further evidence that the gap




Figure 2: Alignment graphed against HellaSwag accuracy for full activation, J-space, and non-J remainder, with a line of best fit. **(a)** Text–text alignment against competence; p -values are model-label permutation values. The J-space converges much more slowly than the full activation space. **(b)** Alignment averaged over the four vision encoders; error bars show standard error of this mean across the four encoders. Alignment rises with competence for every component in both settings.

210 between these components within language is explained by superficial structure rather than by a
 211 property of the J-space.

212 Results for other metrics are reported in Appendix D.

213 4.3 Text–text shared J-lens output

214 We find that at matched relative layer depth, about 5.1 of 25 words are shared, against 2.0 of 25 for
 215 the plain logit lens. In particular, for middle layers $\lambda \in [0.2, 0.5]$, J-lens alignment beats logit lens
 216 alignment by 4–5 $\times$. The logit lens comparison rules out the explanation that J-lens alignment arises
 217 because models might agree on next-token predictions.

218 We also find that across the 38 cross-family model pairs, a model’s best-matching counterpart layer
 219 sits, on average, 11.1% of the layer stack away, consistent with Figure 3.

220 Finally, J-lens overlap rises with competence, further validating the results of Section 4.1. Over the
 221 same 55 pairs, overlap and competence correlate at $\rho = +0.74$ ($p = 0.0020$), shown in Figure 4.
 222 The plain logit lens gives $\rho = +0.41$, which does not reach significance ($p = 0.11$).

223 This readable form of alignment correlates with competence at least as strongly as the kernel form,
 224 corroborating the convergence claim.

225 4.4 Controls

226 In addition to the random-dictionary control above, we run five further controls:

227 **Random-unembedding-row null** When we replace the J-lens dictionary with random unembed-
 228 ding rows, J-space alignment exceeds the strongest of five seeded draws in all 55 pairs (mean mar-
 229 gin +0.167). This shows that J-space alignment captures information that arbitrary directions do
 230 not. The null dictionaries use a random subset of 20,000 unembedding rows rather than the full
 231 dictionary due to computational constraints.

232 **Lens-fitting corpus** To rule out the possibility that J-space alignment emerges from the shared
 233 fitting corpus, we refit so that no two compared models share one. The effect is immaterial (Ap-
 234 pendix C.1).




Figure 3: **(a)** Mean J-lens top-25 word agreement between language models as a function of each model’s relative layer depth $\lambda = \ell / (L_A - 1)$. Grids are symmetrised before averaging. **(b)** The difference between J-lens and logit lens overlap, against relative layer depth. $\lambda = 0$ is omitted as the logit lens reads the embedding matrix directly, and so dominates by construction. Lines are shown for same-family and cross-family pairs. The shaded region is ± 1 standard deviation across the model pairs in each family group. The mean difference is positive at every depth shown, and peaks in the middle layers.




Figure 4: J-lens top-25 median overlap over all matched relative layer depths, against the pair’s mean HellaSwag accuracy. Points are coloured by family composition, and p is a model-label permutation value. Agreement rises with competence.

235 **Shuffling image–caption pairs** Shuffling image–caption pairings in the text–vision alignment ex-
 236 periments reduces alignment to an average of 0.0096, against a chance level of 0.0098. Since shuf-
 237 fled pairs share no image–caption relationships, the alignment we measure on the actual pairings is
 238 not simply a result of the metric.

239 **Lens degradation** The J-lens is fitted on ordinary text, so the reduced alignment on the content-
 240 ablated documents in the first experiment may be a result of the J-lens simply working less well on
 241 such documents. We find that degrading the lens cannot reproduce the effect of removing semantic
 242 meaning (Appendix C.2).

Position-shuffled floor In Experiment 3, some of the top-25 lens overlap is coincidental, since both models naturally rank common tokens highly. We compare each model’s top-25 list against the other model’s list at a randomly chosen position in the corpus, which preserves the marginal distributions over words while destroying the correspondence between them. Under this control, overlap is 0.1 of 25 words for both the J-lens and logit lens, which is negligible.

5 Conclusion and limitations

We propose measuring Platonic convergence in the J-space to isolate shared semantic content. Our results suggest that full-space convergence is inflated by surface-level agreement. Within language (where models share superficial regularities), restricting the comparison to the J-space slows convergence to a third of the full-space rate. Across modalities, where no such regularities exist, the J-space and full components converge at rates that are indistinguishable within standard error. Nevertheless, the original convergence claimed by the Platonic Representation Hypothesis still stands, as the J-spaces and J-lenses still align more at higher competence.

This alignment is meaningful and can be read out as actual words. At the same relative layer depth, language models’ J-lenses have significant overlap, and this overlap is greater than with the plain logit lens. Measuring convergence with the J-lens reproduces the result of the first experiment, finding that more competent models share a greater J-lens overlap.

Limitations First, we use limited compute for experiments, testing only 11 text models and four vision encoders. The text models span 70M–4.3B parameters, and all four vision encoders are ViT-Base, so we have no competence axis on the vision side. HellaSwag is near its floor for our smallest models: Pythia-70M scores 30.8% and GPT-2 scores 38.5% against 25% chance. Thus, competence differences at the bottom of the range are highly compressed. We also compute alignment only on about 1,000 documents, a scale that Koepke et al. [14] argue inflates alignment, though our claim is relative.

Second, we show the semantic weight of the J-space through only the retention statistic and a single random-dictionary control.

Third, our cross-modal measurement is asymmetric, as for a given image–caption pair, we compare the J-space of a text model to the raw visual representation of the vision encoder.

Fourth, the J-space is a small part of the full activation space, accounting for an average of 18.3% of the pooled activation’s squared norm across the 11 models. The non-J remainder therefore carries the other 81.7% of the squared norm. Our results concern a minority component of the full activation space, albeit a privileged one, and the remainder is close enough to the full activation that the two behave nearly identically.

Fifth, our main results use the mutual κ -nearest-neighbour measure of kernel alignment. Appendix D repeats the first two experiments under seven new metrics, keeping all else the same. The claim about within-language J-space convergence only holds under neighbourhood-based measures, but not global subspace measures; cross-modal results hold under all measures. In the appendix we explain this result and justify why we believe global subspace metrics are not appropriate measures of alignment in the J-space.

Finally, the J-lens is fitted per token position, but we apply it to mean-pooled document vectors. This means we are assuming that the dictionary’s validity transfers to those vectors.

Next steps We would like to strengthen our key claim about the J-space’s semantic weight with more tests on larger and more varied model types.

We believe that by leveraging the semantically selective properties of the J-space, we can re-examine many other questions in mechanistic interpretability. We would also welcome a theoretical account of why the J-space should be more semantically selective.

Finally, our third experiment compares word overlap rather than activation geometry, a comparison that is more functional than representational. Since this paper mostly compares representations, we would welcome future research that uses the J-space to measure functional convergence.

References

- [1] Kiril Bangachev, Guy Bresler, and Yury Polyanskiy. Representation alignment rests on linear structure, 2026. URL <https://arxiv.org/abs/2605.28870>.
- [2] Stella Biderman, Hailey Schoelkopf, Quentin Gregory Anthony, Herbie Bradley, Kyle O’Brien, Eric Hallahan, Mohammad Aflah Khan, Shivanshu Purohit, Usven Sai Prashanth, Edward Raff, Aviya Skowron, Lintang Sutawika, and Oskar Van Der Wal. Pythia: A suite for analyzing large language models across training and scaling. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 2397–2430. PMLR, 2023.
- [3] Guy Dar, Mor Geva, Ankit Gupta, and Jonathan Berant. Analyzing transformers in embedding space. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 16124–16170, 2023. doi: 10.18653/v1/2023.acl-long.893.
- [4] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021. URL <https://arxiv.org/abs/2010.11929>.
- [5] Leo Gao, Stella Biderman, Sid Black, et al. The Pile: An 800GB dataset of diverse text for language modeling, 2020. URL <https://arxiv.org/abs/2101.00027>.
- [6] Gemma Team. Gemma 2: Improving open language models at a practical size, 2024. URL <https://arxiv.org/abs/2408.00118>.
- [7] Gemma Team. Gemma 3 technical report, 2025. URL <https://arxiv.org/abs/2503.19786>.
- [8] Mor Geva, Avi Caciularu, Kevin Wang, and Yoav Goldberg. Transformer feed-forward layers build predictions by promoting concepts in the vocabulary space. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 30–45, 2022. doi: 10.18653/v1/2022.emnlp-main.3.
- [9] Aaron Gokaslan and Vanya Cohen. OpenWebText corpus. <http://Skylion007.github.io/OpenWebTextCorpus>, 2019.
- [10] Fabian Gröger, Shuo Wen, and Maria Brbic. Revisiting the platonic representation hypothesis: An aristotelian view. In *Forty-third International Conference on Machine Learning*, 2026. URL <https://openreview.net/forum?id=uz0gAAydl>.
- [11] Wes Gurnee, Nicholas Sofroniew, Adam Pearce, et al. Verbalizable representations form a global workspace in language models, 2026. URL <https://arxiv.org/abs/2607.15495>.
- [12] Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 15979–15988, 2022. URL <https://arxiv.org/abs/2111.06377>.
- [13] Minyoung Huh, Brian Cheung, Tongzhou Wang, and Phillip Isola. Position: The Platonic Representation Hypothesis. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 20617–20642. PMLR, 2024.
- [14] A. Sophia Koepke, Daniil Zverev, Shiry Ginosar, and Alexei A. Efros. Back into plato’s cave: Examining cross-modal representational convergence at scale, 2026. URL <https://arxiv.org/abs/2604.18572>.
- [15] Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. Similarity of neural network representations revisited. In *International Conference on Machine Learning*, 2019.
- [16] Nikolaus Kriegeskorte, Marieke Mur, and Peter Bandettini. Representational similarity analysis – connecting the branches of systems neuroscience. *Frontiers in Systems Neuroscience*, 2:4, 2008.
- [17] Johnny Lin. Neuronpedia: Interactive reference and tooling for analyzing neural networks, 2023. URL <https://www.neuronpedia.org>. Software available from neuronpedia.org.
- [18] Neel Nanda. NeelNanda/pile-10k – datasets at Hugging Face. <https://huggingface.co/datasets/NeelNanda/pile-10k>, 2022.
- [19] nostalgebraist. interpreting GPT: the logit lens. LessWrong, 2020. URL <https://www.lesswrong.com/posts/AcKRB8wDpdaN6v6ru/interpreting-gpt-the-logit-lens>.

- [20] Maxime Oquab, Timothée Darcet, Théo Moutakanni, Huy V. Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, Mahmoud Assran, Nicolas Ballas, Wojciech Galuba, Russell Howes, Po-Yao Huang, Shang-Wen Li, Ishan Misra, Michael Rabbat, Vasu Sharma, Gabriel Synnaeve, Hu Xu, Herve Jegou, Julien Mairal, Patrick Labatut, Armand Joulin, and Piotr Bojanowski. DINOv2: Learning robust visual features without supervision. *Transactions on Machine Learning Research*, 2024. URL <https://openreview.net/forum?id=a68SUt6zFt>.
- [21] Shaul Oron, Tali Dekel, Tianfan Xue, William T. Freeman, and Shai Avidan. Best-buddies similarity—robust template matching using mutual nearest neighbors. *IEEE Transactions on Pattern Analysis & Machine Intelligence*, 40(08):1799–1813, August 2018. ISSN 1939-3539. doi: 10.1109/TPAMI.2017.2737424. URL <https://doi.ieeecomputersociety.org/10.1109/TPAMI.2017.2737424>.
- [22] Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. Technical report, OpenAI, 2019.
- [23] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 8748–8763. PMLR, 2021. URL <https://arxiv.org/abs/2103.00020>.
- [24] Maithra Raghu, Justin Gilmer, Jason Yosinski, and Jascha Sohl-Dickstein. SVCCA: Singular vector canonical correlation analysis for deep learning dynamics and interpretability. In *Advances in Neural Information Processing Systems*, 2017.
- [25] Krishna Srinivasan, Karthik Raman, Jiecao Chen, Michael Bendersky, and Marc Najork. WIT: Wikipedia-based image text dataset for multimodal multilingual machine learning. In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 2443–2449, 2021. doi: 10.1145/3404835.3463257. URL <https://arxiv.org/abs/2103.01913>.
- [26] Qwen Team. Qwen3.5: Towards native multimodal agents, February 2026. URL <https://qwen.ai/blog?id=qwen3.5>.
- [27] An Yang, Anfeng Li, Baosong Yang, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.
- [28] Amirhossein Yavari and Farnaz Zamani Esfahlani. Beyond activation alignment: The geometry of neural sensitivity, 2026. URL <https://arxiv.org/abs/2605.03222>.
- [29] Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. HellaSwag: Can a machine really finish your sentence? In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4791–4800. Association for Computational Linguistics, 2019. doi: 10.18653/v1/P19-1472. URL <https://arxiv.org/abs/1905.07830>.
- [30] Xiaohua Zhai, Basil Mustafa, Alexander Kolesnikov, and Lucas Beyer. Sigmoid loss for language image pre-training. In *2023 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 11941–11952, 2023. URL <https://arxiv.org/abs/2303.15343>.

378 A Aggregation robustness

379 Table 2 gives the cross-modal correlation separately for each vision encoder. Each encoder has a
 380 different alignment level, which is why we consider correlations within encoders rather than pool
 381 across all 44 pairs. The relationship holds within every encoder, including MAE, which receives no
 382 text supervision at all.

383 B Competence axes

384 The main paper measures competence with HellaSwag exclusively. Keeping previous alignment
 385 values, we vary the competence axis and derive similar results, shown in Table 3 and Table 4.

386 Table 4 repeats the cross-modal comparison of Figure 2(b) against all three competence mea-
 387 sures. We also measured competence using language-modelling performance, computed as 1 –
 388 bits-per-byte over 4M tokens of OpenWebText [9]. We derive similar results to those in the main
 389 paper.

Table 2: Cross-modal alignment against HellaSwag accuracy, computed separately within each vision encoder over the 11 text models. The “mean J” column shows alignment for a given encoder across the 11 text models, highlighting the differences between encoders that make pooling the 44 pairs inadvisable. p -values are exact permutation values for $n = 11$.

	mean J	full	non-J	J
DINOv2	0.0742	$\rho = +0.93$ $p = 0.0001$	$\rho = +0.92$ $p = 0.0002$	$\rho = +0.97$ $p < 0.0001$
MAE	0.0535	$\rho = +0.91$ $p = 0.0003$	$\rho = +0.92$ $p = 0.0002$	$\rho = +0.95$ $p < 0.0001$
CLIP	0.0764	$\rho = +0.93$ $p = 0.0001$	$\rho = +0.92$ $p = 0.0002$	$\rho = +0.97$ $p < 0.0001$
SigLIP	0.0865	$\rho = +0.93$ $p = 0.0001$	$\rho = +0.92$ $p = 0.0002$	$\rho = +0.97$ $p < 0.0001$

Table 3: Spearman correlation between within-language alignment and mean competence of the two models, per component. We use both HellaSwag and log parameter count as competence axes. The pairs are not independent, so we use model-label permutation p -values, which hold the alignment values fixed and permute competence across models. The alignment values are the same as in Table 1, and only the competence axis varies.

	log parameters ($n = 55$)	HellaSwag ($n = 55$)
full	$\rho = +0.79$ $p = 0.0006$	$\rho = +0.77$ $p = 0.0008$
non-J	$\rho = +0.87$ $p = 0.0002$	$\rho = +0.87$ $p < 0.0001$
J	$\rho = +0.60$ $p = 0.0094$	$\rho = +0.56$ $p = 0.0162$

390 We follow Huh et al. [13] in using this measure for the cross-modal comparison only; we note that
 391 it gives a within-language J-space correlation of $\rho = +0.35$ ($p = 0.185$), which is not significant.

Table 4: Spearman rank correlation between cross-modal alignment and competence, per component. Each of the 11 text models contributes one point, its alignment averaged over the four vision encoders and each layer-pair grid reduced by its mean; p -values are exact permutation values for $n = 11$. As in Table 3, only the competence axis varies, here log parameter count, HellaSwag, and 1 – bits-per-byte.

	log parameters	HellaSwag	1 – bits-per-byte
full	$\rho = +0.84$ $p = 0.0018$	$\rho = +0.93$ $p = 0.0001$	$\rho = +0.96$ $p < 0.0001$
non-J	$\rho = +0.83$ $p = 0.0022$	$\rho = +0.92$ $p = 0.0002$	$\rho = +0.98$ $p < 0.0001$
J	$\rho = +0.89$ $p = 0.0005$	$\rho = +0.97$ $p < 0.0001$	$\rho = +0.94$ $p < 0.0001$

392 C Lens robustness controls

393 C.1 Lens-fitting control

394 In the main experiment, J-lenses were all fitted on the same corpus (WikiText-103). As a result,
 395 J-space alignment might be a result of the fact that the lenses were fitted on shared text. Figure 5
 396 recomputes text–text alignment, splitting the fitting corpus into two halves and ensuring the J-lenses
 397 of two models in a pair do not use the same half. We also repeat the experiment where two models
 398 in a pair share the same half of the fitting corpus. Due to computational constraints, we conduct the
 399 control on only 10 pairs (spanning three families) among five models: Pythia-70M, GPT-2, Gemma-
 400 3-270M, Qwen3.5-0.8B, and Gemma-3-1B.

401 We find that corpus-sharing has no measurable impact on alignment. Per-pair differences between
 402 the shared-half and crossed-half conditions have a median of +0.0002. All three alignment condi-
 403 tions remain far above the random-dictionary control for every pair.

404 C.2 Lens-degradation control

405 The J-lens was fitted only on ordinary text, not content-ablated text, so the reduced alignment on the
 406 content-ablated documents may be a result of the J-lens simply working less well on such documents.




Figure 5: Disjoint lens-fitting control over the 10 pairs among five models. Lenses are fitted on disjoint halves of WikiText-103. **Left:** crossed-half against shared-half J-component alignment; points lie on $y = x$ within the ± 0.02 materiality band fixed in advance, so refitting on disjoint halves changes nothing. **Middle:** the three fitting conditions per pair—shared-full corpus, shared-half, and crossed-half—all sit far above the per-pair random-dictionary control. **Right:** the per-pair difference Δ between shared-half and crossed-half, median $+0.0002$ against an alignment level of 0.42, every value inside the band.

Indeed, the J-space component accounts for 13.5% of the activation’s squared norm on content-ablated text against 18.3% on real text.

We construct an instrument-only null by reducing the number of dictionary directions on the original corpus until the J-space component accounts for the same fraction of the activations as it does on content-ablated text. This gives a J-space that is degraded but computed on documents with intact meaning. Alignment between model pairs with the degraded J-space is 0.2924 against 0.1099 for the content-ablated text. Even a five-direction J-space, which accounts for less of the activation than the 25-direction J-space on content-ablated text, gives alignment $2.1\times$ higher (0.2326 against 0.1099). Thus, the lens degradation cannot reproduce the effect of removing semantic meaning.

D Varying the alignment metric

Table 5: J-space and full alignment on different metrics, with all other parts of the experiment identical to the main paper. $\rho(J)$ is the J-space correlation between alignment and mean HellaSwag competence, J/full is the ratio of the rates of convergence. p -values are model-label permutation values. Neighbourhood metrics reproduce main results, while global metrics do not (see the paragraph below).

Metric	Within language ($n = 55$)				Cross-modal ($n = 11$)		
	full	J	$\rho(J)$	J/full slope	full	J	$\rho(J)$
<i>Neighbourhood-based</i>							
mutual κ -NN (ours)	0.5577	0.4202	$+0.56 \ p = 0.016$	$+0.30$	0.0719	0.0726	$+0.97 \ p < 0.0001$
CKNNA	0.5975	0.4615	$+0.63 \ p = 0.011$	$+0.43$	0.0761	0.0763	$+0.96 \ p < 0.0001$
cycle κ -NN	0.9358	0.9122	$+0.63 \ p = 0.011$	$+0.68$	0.3672	0.3712	$+0.95 \ p < 0.0001$
edit-distance κ -NN	0.1609	0.0936	$+0.62 \ p = 0.011$	$+0.23$	0.0106	0.0106	$+0.95 \ p < 0.0001$
LCS κ -NN	3.5457	2.6809	$+0.60 \ p = 0.012$	$+0.28$	0.5712	0.5762	$+0.97 \ p < 0.0001$
<i>Global subspace</i>							
CKA	0.8036	0.6892	$+0.09 \ p = 0.651$	-0.00	0.2001	0.2038	$+0.97 \ p < 0.0001$
unbiased CKA	0.7938	0.6615	$-0.19 \ p = 0.475$	-0.31	0.1687	0.1677	$+0.94 \ p = 0.0001$
SVCCA	0.6846	0.5869	$-0.30 \ p = 0.267$	-0.55	0.3070	0.3029	$+0.94 \ p < 0.0001$

The main text measures alignment through mutual κ -nearest-neighbour overlap. We vary our choice of metric, changing only the function for alignment between two layer pairs (Table 5). Implementations follow Huh et al. [13].

Table 6: Retention after the content-ablation experiment, by metric. Retention for the random-Gaussian dictionary is also shown, as well as the percent drop explained by the J-space. (Gaussian – J)/(full – J).

Metric	Retention			Explained by J-space
	full	J	Gaussian	
<i>Neighbourhood-based</i>				
mutual κ -NN (ours)	54.1%	26.3%	34.7%	30.3%
CKNNA	49.8%	20.2%	19.3%	−3.0%
cycle κ -NN	64.4%	45.0%	44.7%	−1.8%
edit-distance κ -NN	37.7%	18.5%	27.7%	47.9%
LCS κ -NN	57.0%	31.5%	39.3%	30.6%
<i>Global subspace</i>				
CKA	100.8%	88.1%	82.7%	−42.1%
unbiased CKA	101.4%	85.4%	117.9%	203.5%
SVCCA	96.9%	77.6%	79.2%	8.7%

We note that within language, regardless of metric, full alignment is always greater than J-space alignment. Cross-modally the two are near-indistinguishable, with J-space marginally ahead for six of the eight metrics, and the cross-modal correlation result is similarly strong ($+0.94 \leq \rho \leq +0.97$).

Within-language, we find that there is a split along two metrics. The metrics which compare *local neighbourhood structure* (e.g. κ -NN) follow our main paper’s results, and the metrics which compare *global subspace geometry*, i.e. how variance is distributed, do not. As well, the competence-alignment correlations for neighbourhood-based metrics all reach significance with $p < 0.02$, but the correlations for global subspace metrics are not significant (the smallest is $p = 0.267$).

Global subspace metrics are insensitive to semantic content We repeat the content-ablation experiment of Section 4.1, again only varying the metric. Results are shown in Table 6. Under the three global metrics, we find that full-space alignment is essentially unchanged by the ablation: each metric retains at least 96.9%. Notably, ablating semantic content nominally increased these metrics’ alignment as shown by CKA and unbiased CKA both measuring retention values above 100%. For J-space ablation, the same metrics retain 88.1%, 85.4%, and 77.6%. In other words, under a quarter of J-space alignment is attributable to semantic content. For neighbourhood-based measures, the opposite is true. Thus, since this paper seeks to measure semantically-significant convergence, global subspace metrics are not appropriate.

Furthermore, we argue that such metrics are not an accurate measure of J-space alignment, since we compute the J-space as a sparse combination of only 25 vocabulary directions. Thus, its coarse geometry is quite generic, and every model’s J-space points in broadly similar directions. As a result, global measures see all J-spaces as similar. For example, GPT-2 and Pythia-70M, our two smallest models, have the highest J-space alignment under CKA.

Since neighbourhood-based metrics and global metrics are two ends of a spectrum, we can find at what locality the correlations begin to decay. CKNNA restricts the kernel to an item’s k nearest neighbours before computing CKA, so for $k = n - 1$, it is simply unbiased CKA. As we vary k across the spectrum, we find that J-space correlation decays monotonically, from $\rho = +0.68$ at $k = 2$ to $\rho = -0.19$ at $k = 999$. The correlation loses significance for k around 50–100. Thus, the within-language claim in our main paper holds for neighbourhoods up to roughly 5% of the corpus.

The percentage of the drop in retention explained by the J-space matches our main results only for the neighbour-identity metrics (mutual κ -NN, LCS, and edit-distance). We note that the global subspace metrics are immaterial as they capture very limited semantic content.

NeurIPS Paper Checklist

1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper’s contributions and scope?

Answer: [Yes]

Justification: The claims in the abstract and introduction are supported by our analysis, figures, and results.

Guidelines:

- The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. Limitations

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer: [Yes]

Justification: Key limitations are discussed in the conclusion.

Guidelines:

- The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
- The authors are encouraged to create a separate “Limitations” section in their paper.
- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
- The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren’t acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. Theory assumptions and proofs

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [N/A]

Justification: Our paper does not include any theoretical results. Our formal setup section defines a procedure for comparing models, but does not derive any new theoretical results.

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. Experimental result reproducibility

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [Yes]

Justification: Detailed steps of the experiment procedure are included in the Formal Setup and Experiment Setup sections of our paper. In addition, code will be released upon acceptance.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general, releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
 - (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
 - (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
 - (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
 - (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. Open access to data and code

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [Yes]

Justification: We include a detailed procedure for replication and will release code upon acceptance.

Guidelines:

- The answer [N/A] means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. Experimental setting/details

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

Answer: [Yes]

Justification: Training and test details are all provided in the Experiment Setup sections.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

7. Experiment statistical significance

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [Yes]

Justification: Our experimental section includes confidence intervals, p -values, etc., and figures report error bars. Controls are reported against explicit floors, and are detailed in the controls section.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.

- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. Experiments compute resources

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: [Yes]

Justification: We report our compute usage in the paper.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. Code of ethics

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics <https://neurips.cc/public/EthicsGuidelines>?

Answer: [Yes]

Justification: We have read the code of ethics, and our research conforms to it. Our work involves no human subjects or personal data, and releases no new model.

Guidelines:

- The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
- If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. Broader impacts

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [N/A]

Justification: Our work has no direct societal impact. This is a foundational measurement paper on how the internal representations of existing models relate to one another, and we see no path from a more semantically selective alignment to any societal harm.

Guidelines:

- The answer [N/A] means that there is no societal impact of the work performed.
- If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. Safeguards

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

Answer: [N/A]

Justification: No models or data are released, and the only code we use operates on preexisting models and public datasets. There is no risk of misuse.

Guidelines:

- The answer [N/A] means that the paper poses no such risks.
- Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
- Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. Licenses for existing assets

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [Yes]

Justification: All models, datasets, and prefitted J-lenses are properly cited, and each is used within the terms of its public release.

Guidelines:

- The answer [N/A] means that the paper does not use existing assets.
- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.

- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, paperswithcode.com/datasets has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset’s creators.

13. New assets

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [Yes]

Justification: Our only new assets are the experimental code and design, released upon acceptance with a README documenting them.

Guidelines:

- The answer [N/A] means that the paper does not release new assets.
- Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
- The paper should discuss whether and how consent was obtained from people whose asset is used.
- At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. Crowdsourcing and research with human subjects

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [N/A]

Justification: No crowdsourcing was used.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. Institutional review board (IRB) approvals or equivalent for research with human subjects

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer: [N/A]

Justification: No research with human subjects was conducted.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.

- 763 • Depending on the country in which research is conducted, IRB approval (or equivalent)
764 may be required for any human subjects research. If you obtained IRB approval,
765 you should clearly state this in the paper.
- 766 • We recognize that the procedures for this may vary significantly between institutions
767 and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the
768 guidelines for their institution.
- 769 • For initial submissions, do not include any information that would break anonymity
770 (if applicable), such as the institution conducting the review.

771 16. Declaration of LLM usage

772 Question: Does the paper describe the usage of LLMs if it is an important, original, or
773 non-standard component of the core methods in this research? Note that if the LLM is used
774 only for writing, editing, or formatting purposes and does *not* impact the core methodology,
775 scientific rigor, or originality of the research, declaration is not required.

776 Answer: [N/A]

777 Justification: This paper studies LLMs and does not use them as a component of the exper-
778 imental method.

779 Guidelines:

- 780 • The answer [N/A] means that the core method development in this research does not
781 involve LLMs as any important, original, or non-standard components.
- 782 • Please refer to our LLM policy in the NeurIPS handbook for what should or should
783 not be described.