

VPS Setup:

1. Login CMD: (ssh -p 4443 cruvzadmin@103.160.153.115)
2. Password : (EXCERPIT001@+91)
3. After login you will see two folders (Deployment and Testing)
4. Select the related Folder accordingly like Production or Testing site
5. Clone the production copy of the application into that folder
6. Install the node modules for the node applications using (npm install --omit=dev)
7. Test the application state by running using PORT=some port number (node index or node server) according your code (you can access the application in the 103.160.153.115:{PORT} (your port number)
8. Once you are ok the application then stop the application
9. Start the application with pm2 (Process manager we are using)
 - a. PORT=0000 pm2 start "root file name" --name "name of application"
 - b. Using the command PORT=(next port based on the previous port (the used port number are recorded in the [Google Sheet](#))
10. Go to /etc/nginx/ sites-available folder
11. Create a file with the domain name of the application

```
server {
    server_name "domain name";
    location / {
        proxy_pass http://localhost: "PORT of your application";
        proxy_http_version 1.1;
        proxy_set_header Upgrade $http_upgrade;
        proxy_set_header Connection 'upgrade';
        proxy_set_header Host $host;
        proxy_cache_bypass $http_upgrade;
    }
}
```
12. Create link using ln -s /etc/nginx/sites-available/example.com /etc/nginx/sites-enabled/
13. Reload the nginx using sudo systemctl reload nginx
14. Create a (A) record in the domain and add the name as the domain name and value is the ip address

```
C:\Users\Admin>ssh -p 4443 cruvzadmin@103.160.153.115
cruvzadmin@103.160.153.115's password:
Welcome to Ubuntu 24.04.3 LTS (GNU/Linux 6.8.0-84-generic x86_64)
```

- * Documentation: <https://help.ubuntu.com>
- * Management: <https://landscape.canonical.com>
- * Support: <https://ubuntu.com/pro>

System information as of Wed Oct 8 12:45:24 PM UTC 2025

```
System load: 0.26      Processes:      166
Usage of /: 23.5% of 97.00GB Users logged in: 1
Memory usage: 42%      IPv4 address for enX0: 103.160.153.115
Swap usage: 0%
```

- * Strictly confined Kubernetes makes edge and IoT secure. Learn how MicroK8s just raised the bar for easy, resilient and secure K8s cluster deployment.

<https://ubuntu.com/engage/secure-kubernetes-at-the-edge>

Expanded Security Maintenance for Applications is not enabled.

2 updates can be applied immediately.

To see these additional updates run: `apt list --upgradable`

Enable ESM Apps to receive additional future security updates.

See <https://ubuntu.com/esm> or run: `sudo pro status`

*** System restart required ***

Last login: Wed Oct 8 12:36:32 2025 from 49.207.195.202

```
cruvzadmin@excerpit001:~$ cd Testing/
```

```
cruvzadmin@excerpit001:~/Testing$ ls
```

```
dummy  geekychat_testing  pie_electronics
```

```
cruvzadmin@excerpit001:~/Testing$ git clone
```

```
https://github.com/excerpttechnologies/demowebwebsite.git
```

```
Cloning into 'demowebwebsite'...
```

```
remote: Enumerating objects: 6, done.
```

```
remote: Counting objects: 100% (6/6), done.
```

```
remote: Compressing objects: 100% (5/5), done.
```

```
remote: Total 6 (delta 0), reused 6 (delta 0), pack-reused 0 (from 0)
```

Receiving objects: 100% (6/6), 8.77 KiB | 8.77 MiB/s, done.

cruvzadmin@excerpit001:~/Testing\$ cd demowebsite/

cruvzadmin@excerpit001:~/Testing/demowebsite\$ ls

index.js package.json package-lock.json

cruvzadmin@excerpit001:~/Testing/demowebsite\$ npm i --omit=dev

added 71 packages, and audited 72 packages in 2s

17 packages are looking for funding

run `npm fund` for details

found 0 vulnerabilities

npm notice

npm notice New patch version of npm available! 11.6.0 -> 11.6.1

npm notice Changelog: <https://github.com/npm/cli/releases/tag/v11.6.1>

npm notice To update run: npm install -g npm@11.6.1

npm notice

cruvzadmin@excerpit001:~/Testing/demowebsite\$ PORT=7002 node index

[dotenv@17.2.3] injecting env (0) from .env -- tip: 🔒 encrypt with Dotenvx:

<https://dotenvx.com>

✓ Server is running on http://localhost:7002

cruvzadmin@excerpit001:~/Testing/demowebsite\$ pm2 l

6	Geeky Bot	default	N/A	fork	34825	6D	0	online	
0%	552.5mb	cru...	disabled						
8	GeekyChat	default	N/A	fork	72006	20h	208	online	
0%	77.8mb	cru...	disabled						
10	Geekychat_Testing	default	1.0.0	fork	77408	51m	1	online	
0%	143.4mb	cru...	disabled						
9	PIE Electronics	default	1.0.0	fork	49272	5D	0	online	
0%	95.8mb	cru...	disabled						
5	Terra Bot	default	N/A	fork	34824	6D	0	online	0%
1.3gb	cru...	disabled							

```
cruvzadmin@excerpit001:~/Testing/demowebiste$ PORT=7002 pm2 start index.js --name "DEMO"
```

```
[PM2] Starting /home/cruvzadmin/Testing/demowebiste/index.js in fork_mode (1 instance)
```

```
(node:77827) [DEP0176] DeprecationWarning: fs.R_OK is deprecated, use fs.constants.R_OK instead
```

```
(Use `node --trace-deprecation ...` to show where the warning was created)
```

```
[PM2] Done.
```

id	name	namespace	version	mode	pid	uptime	U	status	
cpu	mem	user	watching						
11	DEMO	default	1.0.0	fork	77834	0s	0	online	0%
19.6mb	cru...	disabled							
4	Demo ERP	default	1.0.0	fork	34811	6D	0	online	
0%	120.5mb	cru...	disabled						
7	ERP	default	1.0.0	fork	34827	6D	0	online	0%
117.3mb	cru...	disabled							
3	Excerpt ERP	default	1.0.0	fork	34804	6D	0	online	
0%	130.0mb	cru...	disabled						
0	Excerpt Trainings	default	1.0.0	fork	54396	4D	99	online	
0%	119.9mb	cru...	disabled						
2	Excerptech	default	1.0.0	fork	54722	4D	1	online	
0%	132.7mb	cru...	disabled						

6	Geeky Bot	default	N/A	fork	34825	6D	0	online	
0%	552.5mb	cru...	disabled						
8	GeekyChat	default	N/A	fork	72006	20h	208	online	
0%	77.8mb	cru...	disabled						
10	Geekychat_Testing	default	1.0.0	fork	77408	52m	1	online	
0%	143.4mb	cru...	disabled						
9	PIE Electronics	default	1.0.0	fork	49272	5D	0	online	
0%	95.8mb	cru...	disabled						
5	Terra Bot	default	N/A	fork	34824	6D	0	online	0%
1.3gb	cru...	disabled							

```

cruvzadmin@excerpit001:~/Testing/demoweb$ cd /
cruvzadmin@excerpit001:/$ sudo su
root@excerpit001:/# cd /etc
root@excerpit001:/etc# cd nginx
root@excerpit001:/etc/nginx# ls
conf.d      fastcgi_params koi-win  modules-available nginx.conf  scgi_params
sites-e     snippets      win-utf
fastcgi.conf koi-utf       mime.types modules-enabled proxy_params sites-available
sites-enabled uwsgi_params
root@excerpit001:/etc/nginx# cd sites-available/
root@excerpit001:/etc/nginx/sites-available# ls
api.etpl.ai demoerp.etpl.ai erp.etpl.ai erp.excerptech.com excerpt.etpl.ai
geekychat.in site1.etpl.ai site2.etpl.ai trainings.excerptech.com
root@excerpit001:/etc/nginx/sites-available# cat site1.etpl.ai
server {
    server_name site1.etpl.ai;

    location / {
        proxy_pass http://localhost:7000;
        proxy_http_version 1.1;
        proxy_set_header Upgrade $http_upgrade;
        proxy_set_header Connection 'upgrade';
        proxy_set_header Host $host;
        proxy_set_header X-Real-IP $remote_addr;
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
        proxy_set_header X-Forwarded-Proto $scheme;
        proxy_cache_bypass $http_upgrade;
        proxy_read_timeout 86400;
    }
}

```

```

}}
root@excerpit001:/etc/nginx/sites-available# vim site3.etpl.ai
root@excerpit001:/etc/nginx/sites-available# cat site3.etpl.ai
server {
    server_name site3.etpl.ai;

    location / {
        proxy_pass http://localhost:7002;;
        proxy_http_version 1.1;
        proxy_set_header Upgrade $http_upgrade;
        proxy_set_header Connection 'upgrade';
        proxy_set_header Host $host;
        proxy_set_header X-Real-IP $remote_addr;
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
        proxy_set_header X-Forwarded-Proto $scheme;
        proxy_cache_bypass $http_upgrade;
        proxy_read_timeout 86400;
    }
}
root@excerpit001:/etc/nginx/sites-available# ln -s /etc/nginx/sites-
available/site3.etpl.ai /etc/nginx/sites-enabled/
root@excerpit001:/etc/nginx/sites-available# cd ../sites-enabled/
root@excerpit001:/etc/nginx/sites-enabled# ls
api.etpl.ai    erp.etpl.ai    excerpt.etpl.ai site1.etpl.ai site3.etpl.ai
demoerp.etpl.ai erp.excerptech.com geekychat.in  site2.etpl.ai
trainings.excerptech.com
root@excerpit001:/etc/nginx/sites-available# ln -s /etc/nginx/sites-
available/site3.etpl.ai /etc/nginx/sites-enabled/
root@excerpit001:/etc/nginx/sites-available# systemctl reload nginx
root@excerpit001:/etc/nginx/sites-available# certbot
Saving debug log to /var/log/letsencrypt/letsencrypt.log

```

Which names would you like to activate HTTPS for?

We recommend selecting either all domains, or all domains in a VirtualHost/server block.

- 1: api.etpl.ai
- 2: demoerp.etpl.ai
- 3: erp.etpl.ai
- 4: excerpt.etpl.ai
- 5: site1.etpl.ai
- 6: site2.etpl.ai

7: site3.etpl.ai
8: erp.excerptech.com
9: trainings.excerptech.com
10: geekychat.in
11: www.geekychat.in

Select the appropriate numbers separated by commas and/or spaces, or leave input blank to select all options shown (Enter 'c' to cancel): 7

Requesting a certificate for site3.etpl.ai

Successfully received certificate.

Certificate is saved at: /etc/letsencrypt/live/site3.etpl.ai/fullchain.pem

Key is saved at: /etc/letsencrypt/live/site3.etpl.ai/privkey.pem

This certificate expires on 2026-01-06.

These files will be updated when the certificate renews.

Certbot has set up a scheduled task to automatically renew this certificate in the background.

Deploying certificate

Successfully deployed certificate for site3.etpl.ai to /etc/nginx/sites-enabled/site3.etpl.ai

Congratulations! You have successfully enabled HTTPS on https://site3.etpl.ai

If you like Certbot, please consider supporting our work by:

* Donating to ISRG / Let's Encrypt: <https://letsencrypt.org/donate>

* Donating to EFF: <https://eff.org/donate-le>

Git commands

C:\Users\Admin\Documents\GitHub\dummy>git init

Initialized empty Git repository in C:/Users/Admin/Documents/GitHub/dummy/.git/

C:\Users\Admin\Documents\GitHub\dummy>git add .

warning: in the working copy of 'package-lock.json', LF will be replaced by CRLF the next time Git touches it

warning: in the working copy of 'package.json', LF will be replaced by CRLF the next time Git touches it

```
C:\Users\Admin\Documents\GitHub\dummy>git commit -m "new"
[master (root-commit) c000b31] new
4 files changed, 938 insertions(+)
create mode 100644 .gitignore
create mode 100644 index.js
create mode 100644 package-lock.json
create mode 100644 package.json
```

```
C:\Users\Admin\Documents\GitHub\dummy>git branch -M main
```

```
C:\Users\Admin\Documents\GitHub\dummy>git remote add origin
https://github.com/excerpttechnologies/demowebsite.git
```

```
C:\Users\Admin\Documents\GitHub\dummy>git push -u origin main
Enumerating objects: 6, done.
Counting objects: 100% (6/6), done.
Delta compression using up to 8 threads
Compressing objects: 100% (5/5), done.
Writing objects: 100% (6/6), 8.77 KiB | 1.25 MiB/s, done.
Total 6 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/excerpttechnologies/demowebsite.git
 * [new branch]    main -> main
branch 'main' set up to track 'origin/main'.
```

```
C:\Users\Admin\Documents\GitHub\dummy>
```