

API Documentation

This collection documents the **Vehicle Booking System API** — a RESTful backend service for managing users, vehicles, and bookings.

Overview

The API is organized into two main groups:

- **User:** Authentication and registration endpoints.
- **Collections > User Calls:** Endpoints for authenticated users to manage vehicle bookings.
- **Collections > Admin Calls:** Endpoints for admin users to manage vehicles and view platform data.

Base URL

localhost:8080

Authentication

Protected routes are prefixed with `/auth/`. Include a valid JWT token (obtained from the login endpoint) in the `Authorization` header as a Bearer token for all protected requests.

Folders

Folder	Description
User	Registration and login
Collections > Admin Calls	Vehicle and user management (admin only)
Collections > User Calls	Booking management (authenticated users)
Collections> Global Calls	Global data that can be shown without any authentication

Authorization

API Key

Key

X-API-Key

Value

{{token}}

Authentication Calls

Contains authentication endpoints for user registration and login. These endpoints are public and do not require a JWT token.

AuthorizationAPI Key

This folder is using an authorization helper from collection

POSTGet authenticated user

localhost:8080/login

Authenticates an existing user and returns a JWT token.

Authentication: None (public endpoint)

Request Body (JSON):

JSON

```
{  
  
  "email": "user@example.com",  
  
  "password": "yourpassword"  
}
```

Response: Returns a JWT Bearer token to be used in the `Authorization` header for protected routes.

AuthorizationAPI Key

This request is using an authorization helper from collection

Bodyraw (json)

json

```
{  
  
  "email": "rampra484@gmail.com",  
  
  "password": "123456"  
}
```

Example

Successful Response

Request

Postman CLI

```
postman request 'https://api.getpostman.com/me'
```

200 OK

Response

- **Body**
- **Headers (1)**

View More

json

```
{
  "user": {
    "id": 12345678,
    "username": "taylor-lee",
    "email": "taylor.lee@example.com",
    "fullName": "Taylor Lee",
    "avatar": "https://example.com/user/r5u9qpvmujfjf61bqmgga.jpg",
    "isPublic": true
  },
  "operations": [
    {
      "name": "mock_usage",
      "limit": 1000000,
      "usage": 110276,
      "overage": 0
    },
    {
      "name": "monitor_request_runs",
      "limit": 10000000,
      "usage": 1141750,
      "overage": 0
    },
    {
      "name": "api_usage",
      "limit": 1000000,
      "usage": 16240,
```

```
    "overage": 0
  },
  {
    "name": "custom_domains",
    "limit": 25,
    "usage": 25,
    "overage": 0
  },
  {
    "name": "serverless_requests",
    "limit": 10000,
    "usage": 0,
    "overage": 0
  },
  {
    "name": "integrations",
    "limit": 5000,
    "usage": 1018,
    "overage": 0
  },
  {
    "name": "cloud_agent_requests",
    "limit": 1000000,
    "usage": 1615,
    "overage": 0
  }
]
}
```

POST Register User

localhost:8080/register

Registers a new user in the system.

Authentication: None (public endpoint)

Request Body (JSON):

JSON

```
{  
  
  "name": "John Doe",  
  
  "email": "user@example.com",  
  
  "password": "yourpassword".  
  
  "phoneNumber": "12345678"  
  
}
```

Response: Returns the newly created user object with a confirmation message.

AuthorizationAPI Key

This request is using an authorization helper from collection

Bodyraw (json)

json

```
{  
  
  "name": "Kunal Yadav",  
  
  "email": "kn484@gmail.com",  
  
  "password": "123456",  
  
  "phoneNumber": "9257839375"  
  
}
```

Example

Successful Response

Request

Postman CLI

```
postman request 'https://api.getpostman.com/me'
```

200 OK

Response

- **Body**
- **Headers (1)**

View More

json

```
{
  "user": {
    "id": 12345678,
    "username": "taylor-lee",
    "email": "taylor.lee@example.com",
    "fullName": "Taylor Lee",
    "avatar": "https://example.com/user/r5u9qpvmujfjf6lbqmgga.jpg",
    "isPublic": true
  },
  "operations": [
    {
      "name": "mock_usage",
      "limit": 1000000,
      "usage": 110276,
      "overage": 0
    },
    {
      "name": "monitor_request_runs",
      "limit": 10000000,
      "usage": 1141750,
      "overage": 0
    },
    {
      "name": "api_usage",
      "limit": 1000000,
      "usage": 16240,
      "overage": 0
    },
    {
      "name": "custom_domains",
```

```

        "limit": 25,
        "usage": 25,
        "overage": 0
    },
    {
        "name": "serverless_requests",
        "limit": 10000,
        "usage": 0,
        "overage": 0
    },
    {
        "name": "integrations",
        "limit": 5000,
        "usage": 1018,
        "overage": 0
    },
    {
        "name": "cloud_agent_requests",
        "limit": 1000000,
        "usage": 1615,
        "overage": 0
    }
]
}

```

Collections

Groups all core API call categories. Divided into Admin Calls (for platform administrators) and User Calls (for authenticated end users).

AuthorizationAPI Key

This folder is using an authorization helper from collection

Admin Calls

Endpoints restricted to admin users for managing the platform. All requests require a valid admin JWT Bearer token in the Authorization header. Admins can add or update vehicles, retrieve all users, and view all booking details.

AuthorizationAPI Key

This folder is using an authorization helper from collection

POSTAdd Vehicle

localhost:8080/auth/admin/addVehicle

Adds a new vehicle to the system.

Authentication: Required — Admin Bearer JWT token in `Authorization` header .

Request Body (JSON):

JSON

```
{
  "make": "Hero",
  "model": "HF Delux Pro",
  "year": 2026,
  "price": 99000,
  "bookingAmount": 5000,
  "imageUrl": "lfnosaf.vnoaw",
  "remainingUnits": 47
}
```

Response: Returns the newly created vehicle object with an assigned vehicle ID.

AuthorizationAPI Key

This request is using an authorization helper from collection

Bodyraw (json)

json

```
{
  "make": "Honda",
```

```
    "model": "Sp Shine 125",
    "year": 2026,
    "price": 125000,
    "bookingAmount": 5000,
    "imageUrl": "lfnosaf.vnoaw",
    "remainingUnits": 42
}
```

POST Update Vehicle

localhost:8080/auth/admin/addVehicle

Updates the details of an existing vehicle in the system.

Authentication: Required — Admin Bearer JWT token in **Authorization** header.

Request Body (JSON):

JSON

```
{
  "id": 1,
  "make": "Toyota Camry",
  "model": "Fortuner",
  "remainingUnits": 34
}
```

Response: Returns the updated vehicle object with the applied changes.

AuthorizationAPI Key

This request is using an authorization helper from collection

Bodyraw (json)

json

```
{
  "make": "Honda",
  "model": "Sp Shine 125",
  "year": 2026,
  "price": 125000,
  "bookingAmount": 5000,
```

```
    "imageUrl": "lfnosaf.vnoaw",  
    "remainingUnits": 42  
}
```

GET get all users

localhost:8080/auth/admin/users

Retrieves a list of all registered users in the system.

Authentication: Required — Admin Bearer JWT token in Authorization header.

Response: Returns an array of user objects containing user ID, name, email, and role information.

AuthorizationAPI Key

This request is using an authorization helper from collection

GET get all booking details

Retrieves all booking records across all users in the system.

Authentication: Required — Admin Bearer JWT token in Authorization header.

Response: Returns a complete list of all bookings, including user details, vehicle information, booking dates, and current status.

AuthorizationAPI Key

This request is using an authorization helper from collection

User Calls

Endpoints available to authenticated users for interacting with the vehicle booking system. All requests in this folder require a valid JWT Bearer token in the Authorization header. Users can book vehicles, cancel existing bookings, and view their booked vehicles.

AuthorizationAPI Key

This folder is using an authorization helper from collection

POST book Vehicle

localhost:8080/auth/user/bookVehicle

Books a vehicle for the authenticated user.

Authentication: Required — Bearer JWT token in Authorization header.

Request Body (JSON):

JSON

```
{  
  "vehicleId":6,  
  "deliveryDate":"2026-10-07"  
}
```

Response: Returns the booking confirmation details including booking ID, vehicle info, and dates.

AuthorizationAPI Key

This request is using an authorization helper from collection

Bodyraw (json)

```
json  
{  
  "vehicleId":2,  
  "deliveryDate":"2026-10-07"  
}
```

POSTCancel Booking

localhost:8080/auth/user/cancelBooking/3

Cancels an existing vehicle booking by its booking ID.

Authentication: Required — Bearer JWT token in Authorization header.

Path Parameter:

- {bookingId} — The ID of the booking to cancel (e.g., 3).

Response: Returns a confirmation message indicating the booking was successfully cancelled.

AuthorizationAPI Key

This request is using an authorization helper from collection

GETget my booked vehicel

localhost:8080/auth/user/bookedVehicles

Retrieves all vehicle bookings made by the currently authenticated user.

Authentication: Required — Bearer JWT token in Authorization header.

Response: Returns a list of booking objects associated with the authenticated user, including vehicle details, booking dates, and status.

AuthorizationAPI Key

This request is using an authorization helper from collection

Global calls no auth req

Add folder description...

AuthorizationAPI Key

This folder is using an authorization helper from collection

GETget All Vehicle

localhost:8080/vehicle

Retrieves a list of all available vehicles in the system.

Response: Returns an array of vehicle objects, each containing details such as vehicle ID, name, type, and availability status.

AuthorizationAPI Key

This request is using an authorization helper from collection

Bodyraw (json)

json

```
{
  "make": "Honda",
  "model": "Sp Shine 125",
  "year": 2026,
  "price": 125000,
  "bookingAmount": 5000,
  "imageUrl": "lfnosaf.vnoaw",
  "remainingUnits": 42
}
```