# 7 Segment Display

Seven-segment displays are used in common household appliances like microwave ovens, washing machines, and air conditioners. They're a simple and effective way to display numerical information like sensor readings, time, or quantities. In this tutorial, we'll see how to set up and program single seven-segment displays on the STM32F0 dev board.


Components Required

You will need the following components –

- 1 × Breadboard
- 1 × STM32F030F4P6
- 1× Single digit Seven Segment display
- 8 × 100Ω Resistor
- Some Jumper wire

Procedure

Follow the circuit diagram and hook up the components on the breadboard as shown in the image given below.

This tutorial uses a 7-segment common anode which means the **com** pin is connected to the Vcc pin and the rest of the pins are connected to GPIOs.These pins led ON when the GPIO output gave low voltage.

STM32F0 Pin Configuration:

PA0 to PA7 set as an output.

Click the mouse right button on the output pin and label or set the output name.

Hit the keyboard Enter button

CODE

```c
#include "main.h"

void SystemClock_Config(void);
static void MX_GPIO_Init(void);

uint8_t seg_table[] = {

    0b11000000,   // 0
    0b11111001,   // 1
    0b10100100,   // 2
    0b10110000,   // 3
    0b10011001,   // 4
    0b10010010,   // 5
    0b10000010,   // 6
    0b11111000,   // 7
    0b10000000,   // 8
    0b10010000    // 9
};

int length = sizeof(seg_table) / sizeof(seg_table[0]);

int main(void)
{
  HAL_Init();

  SystemClock_Config();

  MX_GPIO_Init();
  while (1)
  {

      for (uint8_t count = 0; count <length; count++) {

          GPIOA->ODR = seg_table[count];   //ODR-Output Data Register value

          HAL_Delay(1000);  // Delay 1 second
        }


  }
}
```

```
uint8_t seg_table[] = {

    0b11000000,    // 0
    0b11111001,    // 1
    0b10100100,    // 2
    0b10110000,    // 3
    0b10011001,    // 4
    0b10010010,    // 5
    0b10000010,    // 6
    0b11111000,    // 7
    0b10000000,    // 8
    0b10010000     // 9
};
```

The array **seg_table** holds binary values that represent which segments of the seven-segment display need to be lit to display a specific digit (0-9).

```
    for (uint8_t count = 0; count <length; count++) {

        GPIOA->ODR = seg_table[count];    //ODR-Output Data Register value

        HAL_Delay(1000);  // Delay 1 second
    }
```

This code creates a loop that iterates through the **seg_table**, displaying each digit (0 to 9) on the seven-segment display for one second before moving on to the next digit. This creates a continuous cycling display of all digits.