

Java Full Stack Development

2. IntelliJ Debugging and Testing




Module Topics

- Debugging in IntelliJ
- Run Configurations
- Running and Managing Tests in IntelliJ

Debugger

- Logging tells you what happened
 - But the debugger shows you why
 - Logs record output at a point in time
 - The debugger exposes the full program state at any point in execution
 - Use cases in Spring Boot
 - Understanding exactly how Spring resolves a bean dependency
 - Inspecting the state of a request as it passes through a filter chain
 - Diagnosing a data mapping failure between a JSON payload and a Java object
 - Stepping through conditional logic to verify branching behaviour



```
1 package org.example;
2
3 To Run code, press Shift F10 or click the ▶ icon in the gutter.
4
5 public class Main { new *
6     public static void main(String[] args) { new *
7
8         Press Alt Enter with your caret at the highlighted text to see how IntelliJ IDEA
          suggests fixing it.
9
10        System.out.printf("Hello and welcome!");
11
12        for (int i = 1; i <= 5; i++) {
13
14            Press Shift F9 to start debugging your code. We have set one
              breakpoint for you, but you can always add more by pressing Ctrl 8.
15            System.out.println("i = " + i);
16        }
17    }
```

Debugger and Spring Boot


- Spring Boot framework
 - Does a significant amount of work before the code runs
 - Auto-configuration
 - Bean initialization
 - Dependency injection
 - Filter registration
 - Debugger lets you step into any of this framework code when needed
 - Particularly powerful when something fails silently during context startup



```
1 package org.example;
2
3 To Run code, press Shift F10 or click the ▶ icon in the gutter.
4
5 public class Main { new *
6     public static void main(String[] args) { new *
7
8         Press Alt Enter with your caret at the highlighted text to see how IntelliJ IDEA
          suggests fixing it.
9         System.out.printf("Hello and welcome!");
10
11         for (int i = 1; i <= 5; i++) {
12
13             Press Shift F9 to start debugging your code. We have set one
              breakpoint for you, but you can always add more by pressing Ctrl 8.
14             System.out.println("i = " + i);
15         }
16     }
17 }
```


IntelliJ Debugger

- IntelliJ debugger
 - Communicates with the JVM via the Java Debug Wire Protocol (JDWP)
 - JDWP is a standard JVM protocol, not IntelliJ-specific
 - The JVM exposes a socket that the debugger attaches to
 - Two attachment modes
 - Launch mode: IntelliJ starts the JVM and attaches automatically
 - Remote mode: IntelliJ attaches to an already-running JVM over a network socket




IntelliJ Debugger

- IntelliJ debugger
 - The debugger operates on the compiled bytecode resolved against the source
 - Source mapping is automatic when source is available in the project
 - No special compiler flags are needed for standard Spring Boot projects




Breakpoints

- An instruction to suspend the JVM at a specific location
- Setting a breakpoint
 - Click the gutter (the grey margin left of line numbers) on any executable line
 - Or **Ctrl+F8** to toggle a breakpoint at the current cursor position




Breakpoints

- Breakpoint types
 - Line breakpoint
 - Suspends execution when that line is reached
 - Method breakpoint
 - Suspends on entry, exit, or both for a method
 - Field watchpoint
 - Suspends when a specific field is read or written
 - Exception breakpoint
 - Suspends when a specific exception type is thrown




Breakpoints

- Conditional breakpoints
 - Only pause when an expression evaluates to true
 - Right-click a breakpoint → set a condition
 - Example: `orderId.equals("ORD-42")` pauses only for that specific order
 - Avoids stopping on every iteration when debugging a loop
- Logging breakpoints
 - Print a message without halting execution
 - Right-click a breakpoint → uncheck "Suspend" → enable "Evaluate and log"
 - Effectively a zero-code, runtime `System.out.println`
 - Useful in production-like scenarios where stopping execution is not practical




Debug Tool Window

- The Debug tool window opens automatically when a debug session starts
- Key panels
 - Frames: the current call stack
 - Click any frame to inspect its local variables
 - Variables: all local variables and fields visible at the current stack frame
 - Watches: expressions evaluated continuously during the session
 - Console: stdout/stderr from the running JVM



Debug Tool Window

- Navigating the call stack
 - Every frame in the stack is clickable
 - Selecting a frame shows the variables in scope at that point in the call chain
 - Being able to click a frame and see the exact state of variables at that level
 - Helps answer the question "which Spring component did something unexpected before my code was called?"



Stepping Controls

- Uses
 - **Step Over** is the most common action during a debugging session
 - Move line by line through the current method without descending into calls
 - **Step Into** is used when you need to understand what a called method actually does.
 - **Force Step Into**
 - IntelliJ by default skips stepping into JDK and library code
 - If you need to trace into Spring's DispatcherServlet, a Jackson deserializer, or any framework class
 - **Force Step Into** bypasses that filter.

Action	Shortcut	Behaviour
Step Over	F8	Execute the current line; if it's a method call, run it without entering
Step Into	F7	Enter the method being called on the current line
Force Step Into	Alt+Shift+F7	Step into even when IntelliJ would normally skip it (e.g. library code)
Step Out	Shift+F8	Finish the current method and return to the caller
Run to Cursor	Alt+F9	Run until the cursor position, then suspend
Resume	F9	Continue execution until the next breakpoint

Evaluating Expressions

- Evaluate Expression: **Alt+F8**
 - Execute any valid Java expression in the context of the current stack frame
 - Calls methods, accesses fields, constructs objects
 - Results display immediately
- Inline variable values
 - IntelliJ renders current variable values directly on the source line, next to the code
 - Grey text showing the actual value, visible without opening the Variables panel
 - Quick Evaluate: hover over any expression while suspended
 - A tooltip shows the current evaluated value

Modifying State

- Variable values can be changed while the JVM is suspended
 - Right-click a variable in the [Variables panel](#) → [Set Value](#)
 - Allows testing "what if this value were different" without code changes
- Drop Frame (Rewind a method call)
 - Removes the current frame from the call stack
 - Re-executes the method from its beginning with the same entry state
 - Useful when you stepped past the point of interest
 - Not available across native frames or after side effects (DB writes, network calls)


Remote Debugging

- Remote debugging allows attaching IntelliJ to a JVM running outside the IDE
 - Docker containers, remote servers, or locally started processes
 - The target JVM must be started with JDWP enabled
 - `-agentlib:jdwp=transport=dt_socket,server=y,suspend=n,address=*:5005`
- In IntelliJ
 - `Run → Edit Configurations → Add New → Remote JVM Debug`
 - Configure host and port to match the target JVM
 - Connect using the Debug button (not Run)
- Common use cases
 - Debugging a Spring Boot app running inside a local Docker container
 - Diagnosing a startup failure in a pre-production environment

Run Configurations


Run Configuration

- Temporary configuration
 - Created when developer manually starts a Spring Boot application by clicking the green arrow on the main class
 - If they never save it, a teammate cloning the same repository will have no launch configuration at all
 - They must recreate it instead
 - Shared configurations stored in [.idea/runConfigurations/](#) solve this
 - Every developer who clones the repository gets the same set of launch instructions
 - Including the correct active profile, environment variables, JVM arguments, and working directory
 - This is a team hygiene practice, not an individual productivity feature




Run Configuration

- Named, saved execution blueprint
 - Specifies
 - What to launch
 - How to launch it
 - With what environment
 - Every execution in IntelliJ uses a Run Configuration
- The three lifecycle states
 - Temporary: auto-created, not saved, eventually discarded
 - Permanent: saved to local IDE settings, survives restarts
 - Shared: committed to [.idea/runConfigurations/](#) as XML, visible to the whole team
 - Shared configurations should be the standard on any team project




Spring Boot Run Configuration

- Standard for launching Spring applications
 - Available in IntelliJ Ultimate (not Community)
 - Community edition uses the generic Application type instead
- Key fields:
 - Main class: the `@SpringBootApplication` entry point
 - Active profiles: sets `spring.profiles.active` (e.g., dev)
 - VM options: JVM flags, including JDWP for remote debug enablement
 - Environment variables: key-value pairs injected into the process environment
 - Working directory: the directory the JVM uses as its working root




Spring Boot Run Configuration

- A properly configured team project
 - Will have three shared configurations
 - One for local (using local infrastructure)
 - One for dev (pointing at shared dev services)
 - Possibly one with a test profile for integration testing
 - The **Environment Variables** field is the right place to supply secrets and connection strings that should not be committed to source control
 - These are injected into the process at startup and accessible via Spring's **@Value** annotation or **Environment** bean.




Spring Boot Run Configuration

- VM options examples
 - `-Xmx2g` maximum heap for the application JVM (separate from IDE heap)
 - `-Dspring.datasource.url=jdbc:oracle:thin:@localhost:1521:XE` override a Spring property
 - `-agentlib:jdwp=...` enable remote debugging for a separately launched process
- Environment Variables
 - Injected into the OS environment of the process
 - Accessed in Spring via `${ENV_VAR_NAME}` in YAML or `@Value("${ENV_VAR_NAME}")`
 - Preferred for secrets because they are not visible in log output by default




Spring Boot Run Configuration

- A common mistake
 - Attempting to pass environment variables as VM options or vice versa
 - Spring's [Environment](#) abstraction resolves property values in a defined order of precedence
 - Environment variables sit higher in the precedence chain than [application.yml](#) values but lower than command-line arguments.
 - VM options set as system properties override [application.yml](#) values




Spring Boot Run Configuration

- A common mistake
 - The full order, from highest to lowest priority in a typical Spring Boot application
 - command-line args
 - OS environment variables
 - Java system properties
 - application-{profile}.yml
 - application.yml.




Compound Run Configuration

- A Compound configuration
 - Launches multiple Run Configurations simultaneously
 - Single click starts all configured services together
 - Common use cases
 - Start the Spring Boot backend and a local mock OAuth server together
 - Launch multiple microservices that the current service depends on
 - Start the backend and a local Kafka instance before running integration tests
 - Creating a Compound configuration:
 - [Run](#) → [Edit Configurations](#) → [+](#) → [Compound](#)
 - Add individual configurations to the Compound



Before Launch Actions


- Every Run Configuration supports a **Before Launch** list
 - Actions executed automatically before the main process starts
 - Common **Before Launch** actions
 - Build: compiles the project (enabled by default)
 - Run Maven Goal: execute clean package, test, or any Maven lifecycle phase
 - Run Another Configuration: start a dependency service first
 - Run External Tool: execute a shell script, Docker command, or any CLI tool
 - **Before Launch** actions run sequentially, in order



Running and Managing Tests in IntelliJ

Discovering Tests


- IntelliJ scans the `src/test/java` source root for test classes
 - Test classes annotated with `@Test` (JUnit 5) or extending `TestCase` (JUnit 4) are recognized
 - Spring Boot test classes annotated with `@SpringBootTest` are also recognized
- Test discovery is automatic
 - No registration required
 - The test source root is configured in the Project Structure (`Ctrl+Alt+Shift+S`)
 - Maven projects set this automatically from the `pom.xml` configuration



```
AppTest.java x
1 package com.mycompany.app;
2
3 > import ...
4
5
6
7 /**
8  * Unit test for simple App.
9  */
10 > public class AppTest  Rod Davison +1
11 {
12     /**
13      * Rigorous Test :-)
14      */
15     @Test  Rod Davison +1
16     > public void shouldAnswerWithTrue() { assertTrue( condition: true ); }
17
18
19
20 }
21
```

Discovering Tests

- When tests are not being discovered
 - Often because the test source folder (`src/test/java`) is not marked as a **Test Sources Root** in IntelliJ's project model
 - In an imported Maven project this is automatic
 - Maven's standard directory layout is understood by IntelliJ's Maven import
 - If tests are missing from the test runner, check
 - [Project Structure](#) → [Modules](#) → [Source Folders](#)
 - Verify the test folder has the green test icon, not the blue source icon
 - A manual Maven reload usually fixes this by re-importing the project model from the pom.xml



```
AppTest.java x
1  package com.mycompany.app;
2
3  > import ...
4
5
6
7  /**
8   * Unit test for simple App.
9   */
10 > public class AppTest  Rod Davison +1
11 {
12     /**
13      * Rigorous Test :-)
14      */
15     @Test  Rod Davison +1
16     > public void shouldAnswerWithTrue() { assertTrue( condition: true ); }
17
18
19
20 }
21
```

Running Tests


- Run options, from most specific to most general
 - Single test method
 - Click the green play icon in the gutter next to an `@Test` method
 - Single test class
 - Click the green play icon in the gutter next to the class declaration
 - All tests in a package
 - Right-click the package in the Project window → Run Tests
 - All tests in the module
 - Right-click the `src/test/java` root → Run All Tests
 - Keyboard shortcut: **Ctrl+Shift+F10**
 - Run the test at the current cursor position



```
AppTest.java x
1  package com.mycompany.app;
2
3  > import ...
4
5
6
7  /**
8   * Unit test for simple App.
9   */
10 > public class AppTest  Rod Davison +1
11 {
12     /**
13      * Rigorous Test :-)
14     */
15     @Test  Rod Davison +1
16 > public void shouldAnswerWithTrue() { assertTrue( condition: true ); }
17
18
19
20 }
21
```



The Test Run Tool Window

- Opens automatically when tests execute
 - Result structure:
 - Tests are displayed in a tree: `class` → `method`
 - Green checkmark: test passed
 - Red X: test failed (assertion failure or unexpected exception)
 - Yellow: test ignored or skipped (`@Disabled`)



The Test Run Tool Window

- Failure details
 - Click any failed test to see the assertion error message
 - The diff view shows expected vs actual values side by side for assertion failures
 - The full stack trace is available with clickable frames that navigate to source




Debugging Tests

- Can be launched in debug mode exactly like application code
 - Click the debug icon (bug) instead of the run icon next to a test method or test class
 - Or **right-click → Debug**
- Breakpoints set in test code and in production code are both honoured
 - Set a breakpoint in the test method to inspect test setup
 - Set a breakpoint in the production method under test to inspect its execution
 - Conditional breakpoints work the same as in application debugging
 - The Debug tool window shows the test execution call stack



Debugging Tests


- Debugging tests
 - Effective way to understand unexpected test behaviour
 - If a test is failing with a confusing assertion message
 - Setting a breakpoint immediately before the assertion
 - Evaluating the actual value using Alt+F8 is usually faster than adding logging and rerunning



```
9      * unit test for simple App.  
10     */  
11     public class AppTest  Rod Davison *  
12     {  
13         /**  
14          * Rigorous Test :-)  
15          */  
16         @Test  Rod Davison *  
17         public void shouldAnswerWithTrue()  
18         {  
19             // ...  
20             assertEquals(0.0, delta: .00);  
21         }  
22     }
```

Test Coverage

- IntelliJ can measure code coverage while running tests
 - Right-click a test class or package → [Run with Coverage](#)
 - Or use the [Run with Coverage](#) button in the toolbar
- Coverage results appear in
 - The editor gutter
 - Green (covered) / red (not covered) line highlighting
 - The coverage tool window
 - Class-level and method-level coverage percentages
 - A full HTML report (exportable)
- Coverage modes
 - IntelliJ coverage: faster, built-in
 - JaCoCo: the standard in CI pipelines; matches what Maven/Surefire reports



Element	Class, %	Method, %	Line, %	Branch, %
org.springframework	2% (17/764)	3% (81/2125)	3% (233/7413)	78% (63/80)
aop	0% (0/4)	0% (0/4)	0% (0/24)	100% (0/0)
boot	0% (0/617)	0% (0/1654)	0% (0/4585)	100% (0/0)
cache	0% (0/15)	0% (0/48)	0% (0/156)	100% (0/0)
context.event	0% (0/8)	0% (0/8)	0% (0/32)	100% (0/0)
data	0% (0/39)	0% (0/87)	0% (0/276)	100% (0/0)
orm.jpa	0% (0/3)	0% (0/12)	0% (0/63)	100% (0/0)
samples.petclinic	26% (17/64)	48% (81/168)	12% (233/18...)	78% (63/80)
model	100% (3/3)	100% (10/10)	100% (10/10)	100% (2/2)
BaseEntity	100% (1/1)	100% (3/3)	100% (3/3)	100% (2/2)
NamedEntity	100% (1/1)	100% (3/3)	100% (3/3)	100% (0/0)
Person	100% (1/1)	100% (4/4)	100% (4/4)	100% (0/0)
owner	40% (8/20)	71% (56/78)	63% (185/290)	77% (57/74)
service	0% (0/2)	0% (0/4)	0% (0/88)	100% (0/0)
system	12% (2/16)	8% (2/25)	0% (2/388)	100% (0/0)
vet	33% (3/9)	47% (10/21)	29% (29/97)	100% (4/4)

Questions?

