

V.I.P.E.R. — Data-Flow & Third-Party Integration Disclosure

Product: V.I.P.E.R. (Versatile Investigative Platform for Enforcement Records) **Vendor:** Intellect LE, LLC
Document Version: 1.0 **Applies to:** VIPER v4.0.8 **Companion to:** VIPER_NIST_CSF_Policy_Guide.md (ID.AM-4) · VIPER_Architecture_and_Security.md **Audience:** Agency IT / CJIS Systems Officer (CSO) / Local Agency Security Officer (LASO) / risk & audit reviewers

Purpose

This document is a complete, source-verified inventory of **every network connection VIPER can make**, exactly what data each connection transmits, and whether that data is Criminal Justice Information (CJI). It exists to answer one question precisely:

"VIPER interfaces with third-party services — does that mean our CJI leaves our control, and should this be treated as cloud/SaaS software?"

Short answer: No. VIPER is a locally-installed desktop application. **No agency case content, subject identity, evidence, warrant return, or narrative text is ever transmitted to Intellect LE (the vendor).** The third-party services officers recognize (Flock, TLOxp, Accurant, etc.) are **not data integrations** — they are the vendor's own websites displayed inside VIPER, accessed with the **agency's own existing accounts**, with traffic flowing **directly between the officer's authenticated session and that provider**, exactly as it would in a web browser.

The critical distinction: *embedded panel vs. data integration*

Most vendor-security questionnaires assume a **data integration**: your data is pushed from the vendor's servers to a third-party SaaS API, creating a chain of custody the vendor must attest to. **VIPER does not do this.** The recognizable third-party tools are **embedded browser panels**.

	Data integration (what the questionnaire assumes)	Embedded browser panel (what VIPER actually does)
Where auth happens	Vendor holds/relays credentials or API keys	Officer signs in with the agency's own account , on the provider's real login page
Traffic path	Your data → vendor servers → third-party API	Officer's session ↔ provider, directly
Does VIPER see the data?	Yes, it passes through vendor systems	No — VIPER renders the provider's site; it does not proxy, store, or parse the traffic
Session isolation	Shared vendor context	Dedicated, isolated session partition per service (separate cookies/storage)
Equivalent to	A cloud middleware/ETL connector	Opening the site in Edge/Chrome

Who owns the CJIS relationship	Ambiguous / vendor-entangled	The agency ↔ the provider (unchanged by VIPER)
--------------------------------	------------------------------	---

Consequence: The security and CJIS relationship for Flock, Accurint, TLOxp, Vigilant, etc. is the one the **agency already has** with those providers. VIPER neither expands nor alters it. There is no VIPER-controlled server anywhere in that data path.

Complete external-connection inventory (source-verified)

Grouped into four bounded categories. Hostnames, transmitted data, and classification are taken directly from the VIPER source (`electron-main.js`, `page Content-Security-Policy` headers, and the integration modules).

Category A — Vendor infrastructure (licensing & software distribution)

Endpoint	Purpose	What is transmitted	CJI?	Opt-out
<code>intellect-unified-dashboard-production.up.railway.app</code>	License validation / registration, version check	Organization name, license-key hash , product version, machine fingerprint, request IP	No	Required for licensing; contains no case data
<code>github.com/exhonorated999/project-viper</code>	Signed installer, <code>latest.yml</code> , on-demand Whisper engine download	Inbound download only (no case data sent)	No	Disable auto-update via firewall

Category B — Vendor-hosted privacy-preserving broker (opt-in)

Endpoint	Purpose	What is transmitted	CJI?	Opt-out
<code>trace-broker-production.up.railway.app</code>	Optional cross-agency deconfliction ("TRACE Network")	One-way SHA-256 token hashes only (e.g. hash of a plate/name), plus token type/tier/case-type. Never the plaintext value.	No plaintext CJI — irreversible hashes only	Off by default: requires explicit enable + registration

Design note: The broker cannot recover the original search term from the hash. Deconfliction works by matching hashes, not by sharing data. This is a privacy-preserving design, not a data feed.

Category C — Agency-authenticated embedded browser panels

VIPER renders each provider's **own website** inside an isolated `BrowserView` session partition. The officer authenticates with the **agency's existing account**. Traffic flows **directly between that session and the provider** — VIPER does not proxy, relay, store, or parse it.

Service	Hostname	Isolated partition	Notes
Flock Safety LPR	search-2.flocksafety.com	persist:flock	Agency's Flock account
TLOxp	tloxp.tlo.com	persist:tlo	Agency's TLOxp account
Accurint (LexisNexis)	secure.accurint.com	persist:accurint	Agency's Accurint account
Whooster	app.whooster.com	persist:whooster	Agency's Whooster account
Vigilant / Motorola VehicleManager	vm.motorolasolutions.com	persist:vigilant	Agency's Vigilant account
ICAC Data System	icacdatasystem.com	persist:icacDataSystem	ICAC task-force credentials
ICAC COPS	icaccops.com	dedicated partition	ICAC task-force credentials
GridCop	gridcop.com	dedicated partition	Agency account
Callyo	callyo.com	dedicated partition	Agency account

Each panel can be hidden/disabled in **Settings**. The agency's existing CJIS agreements with these providers are the controlling authority for anything exchanged with them.

Category D — Officer-initiated OSINT / enrichment lookups

Triggered explicitly by the officer; transmit only the query term, using the agency's own API credentials where applicable.

Endpoint	Purpose	What is transmitted	CJI?
api.wigle.net	Wi-Fi / BT / cell geolocation	BSSID / SSID	Investigative query term
api.genlogs.io	Commercial-vehicle sightings / FMCSA data	USDOT / MC / plate	Investigative query term
whois.arin.net	IP ownership lookup	An IP address	Public registry query
safer.fmcsa.dot.gov	Motor-carrier lookup	Carrier name / number	Public registry query
ip-api.com	IP geolocation	An IP address	Public query
nominatim.openstreetmap.org	Address geocoding	An address string	Location query

*.tile.openstreetmap.org, *.basemaps.cartocdn.com	Map tiles	Tile coordinates only	No
router.project-osrm.org	Route calculation	Coordinates only	No

What is *never* transmitted anywhere off-device

Regardless of category, the following **never** leave the agency workstation via any VIPER connection:

- Case files, case numbers, case narrative, or report text
- Evidence files or their contents
- Warrant returns (KIK, Google, Discord, Snapchat, Meta, etc.) or anything parsed from them
- Victim / suspect / witness / missing-person identities as stored in a case
- Officer notes, operations plans, custom-metric values
- Master passphrases or encryption keys (Field Security keys are derived on-device and never leave it)
- Audit-log contents

CJI created and stored in VIPER lives in %APPDATA%\viper-electron on the agency's own device, inside the agency's existing CJIS perimeter, and is optionally encrypted at rest with AES-256-GCM (Field Security).

Enforcement mechanisms (how the above is guaranteed, not just asserted)

- **Content-Security-Policy:** Every application page ships a CSP meta tag whose `connect-src` directive whitelists only the Category A/B/D endpoints. Renderer `fetch()/XHR` to any other origin is blocked by the Chromium engine.
- **Session isolation:** Each Category C service loads in a dedicated `persist:<service>` partition — cookies, storage, and auth state are isolated per service and from the main application.
- **No inbound listeners:** VIPER runs a loopback-only server on `localhost:8000` for internal page loading; it does not listen on external interfaces.
- **Opt-in by default:** Categories B, C, and D are user-initiated or explicitly enabled. A firewall/proxy allowlist can restrict VIPER to Category A only if the agency chooses.

Recommended agency controls (drop-in for an audit file)

1. **Firewall/proxy allowlist** — permit only the endpoints in the categories the agency actually uses; block the rest.
2. **Provider agreements** — confirm existing CJIS/contractual coverage for each Category C service in use (these predate VIPER).
3. **Full-disk encryption** — BitLocker on every VIPER workstation (baseline at-rest control for the local case store).

4. **Field Security** — enable VIPER's AES-256-GCM field encryption on all installations.
5. **Audit-log retention** — export/retain VIPER's tamper-evident audit log per the agency's CJIS retention schedule.
6. **TRACE Network** — leave disabled unless the agency has adopted the deconfliction program; even when enabled, only irreversible hashes are shared.

Verification

Every hostname and behavior in this document is verifiable in the published, signed source:

- **Embedded-panel hostnames & partitions:** `electron-main.js` (BrowserView definitions and `loadURL(...)` calls)
- **CSP connect-src whitelists:** `index.html`, `settings.html`, `case-detail-with-analytics.html` (`<meta http-equiv="Content-Security-Policy">`)
- **TRACE broker (hash-only transmission):** `modules/trace-search-api.js`, `modules/resource-hub.js`
- **OSINT modules:** `modules/genlogs-api.js`, **WiGLE integration**, `whois.arin.net/safer.fmcsa.dot.gov` **handlers** in `electron-main.js`

Intellect LE will demonstrate any of these live and provide packet/payload captures on request.

--	--	--