

SINGLE SPLIT BLACK OXIDE COUPLINGS

Material : Low Carbon Steel

Type : Heavy

Part Nos	Bore	O.D.	Length	Screw size	Without	wt./pc
	INCH	INCH	INCH	Socket Cap screw	Keyway	KGS
CC-025-025	1/4"	13/16"	1.1/4"	UNC 4-40 X 3/8"		0.065
CC-037-037	3/8"	1.1/16"	1.5/8"	UNC 6-32 X 3/8"		0.141
CC-050-050	1/2"	1.1/4"	1.7/8"	UNC 8-32 X 1/2"		0.219
CC-062-062	5/8"	1.1/2"	2.1/4"	UNF 10-32 X 1/2"		0.636
CC-075-075	3/4"	1.3/4"	2.5/8"	UNF 1/4-28 X 5/8"		0.595
CC-087-087	7/8"	1.7/8"	2.7/8"	UNF 1/4-28 X 5/8"		0.722
CC-100-100	1"	2"	3"	UNF 1/4-28 X 5/8"		0.825
CC-112-112	1.1/8"	2.1/8"	3.1/4"	UNF 1/4-28 X 3/4"		0.986
CC-125-125	1.1/4"	2.1/4"	3.3/8"	UNF 1/4-28 X 3/4"		1.091
CC-137-137	1.3/8"	2.3/8"	3.5/8"	UNF 1/4-28 X 3/4"		1.270
CC-150-150	1.1/2"	2.1/2"	3.3/4"	UNF 1/4-28 X 3/4"		1.407
CC-175-175	1.3/4"	3"	4.1/2"	UNF 5/16-24 X 1"		2.557
CC-200-200	2"	3.1/4"	4.7/8"	UNF 3/8-24 X 1"		3.040

SINGLE SPLIT BLACK OXIDE COUPLINGS with keyway

Material : Low Carbon Steel

Type : Heavy

Part Nos	Bore	O.D.	Length	Screw size	Keyway	wt./pc
	INCH	INCH	INCH	Socket Cap screw	dimension	KGS
CC-050-050-KW	1/2"	1.1/4"	1.7/8"	UNC 8-32 X 1/2"	1/8" X 1/16"	0.219
CC-062-062-KW	5/8"	1.1/2"	2.1/4"	UNF 10-32 X 1/2"	3/16" X 3/32"	0.636
CC-075-075-KW	3/4"	1.3/4"	2.5/8"	UNF 1/4-28 X 5/8"	3/16" X 3/32"	0.595
CC-087-087-KW	7/8"	1.7/8"	2.7/8"	UNF 1/4-28 X 5/8"	3/16" X 3/32"	0.722
CC-100-100-KW	1"	2"	3"	UNF 1/4-28 X 5/8"	1/4" X 1/8"	0.825
CC-112-112-KW	1.1/8"	2.1/8"	3.1/4"	UNF 1/4-28 X 3/4"	1/4" X 1/8"	0.986
CC-125-125-KW	1.1/4"	2.1/4"	3.3/8"	UNF 1/4-28 X 3/4"	1/4" X 1/8"	1.091
CC-137-137-KW	1.3/8"	2.3/8"	3.5/8"	UNF 1/4-28 X 3/4"	5/16" X 5/32"	1.270
CC-150-150-KW	1.1/2"	2.1/2"	3.3/4"	UNF 1/4-28 X 3/4"	3/8" X 3/16"	1.407
CC-175-175-KW	1.3/4"	3"	4.1/2"	UNF 5/16-24 X 1"	3/8" X 3/16"	2.557
CC-200-200-KW	2"	3.1/4"	4.7/8"	UNF 3/8-24 X 1"	1/2" X 1/4"	3.040

Single Split Coupling Material	: Low Carbon Steel
Surface Finsih	: Black Oxide
Hex Socket Cap Screw-Alloy Steel	: ANSI B18.3-1982
Marking	: i.d & INDIA
Packing	: Polybag, Carton boxes and in Pallets

wt./pc
oz
2.26
4.96
7.70
13.30
20.90
25.40
29.00
34.70
38.40
44.70
57.40
90.00
107.00

wt./pc
oz
7.70
13.30
20.90
25.40
29.00
34.70
38.40
44.70
57.40
90.00
107.00

--