Robustness labels follow the problem: six model signals fail on unseen problems, and a text-length control reaches the kit baseline

Anonymous Author(s)
Affiliation
Address
email

Technical report for the AIMO Interpretability Challenge writeup awards. Negative result. Tracks: Main and Small Models.

Abstract

In the organisers' training labels, robustness belongs to the problem more than to the model: 13 of the 14 problems labelled for several models carry one label for every model, against 4.8 expected under a label shuffle (none of 2,000 shuffles reaches 13). A split by row therefore rewards recognising problems, and 5 of the 10 public sample problems already have training labels. Holding out whole problems, we tested six signals read from the model: prompt-only features, ability and difficulty calibration, generation stability, counterfactual trace sensitivity, a hidden-activation probe and forced-answer flips. None beat answering "robust" everywhere. The four whose gates were committed before their results all missed them, and on 34 rows the trace, activation and prompt-capability probes have a 95 % upper bound of zero rows over that baseline. On the organisers' 141-row DeepSeek set, four text-length features reach balanced accuracy 0.64 under problem-grouped folds, against 0.63 reported for the kit's uncertainty-profiling method. Gates, intervals and code are released.

1 Summary

We ask whether robustness signals generalise to problems a model has not seen, on the small-track training labels: 34 (model, problem) configurations over 20 problems and four models (Qwen3.5-4B, Skywork-OR1-Math-7B, Olmo-3-7B-Think, DeepSeek-R1-0528-Qwen3-8B).

1. **Robustness is mostly a property of the problem** (Lesson 9). In the 2026-10-15 label file, 13 of the 14 problems labelled for several models carry one label for every model (11 of 11 at the pinned snapshot), against 4.8 expected under a label shuffle (2,000 permutations, 95 % range 2 to 8). A split by row leaks the problem, so every headline result holds out whole problems.
2. **Prevalence differs between training and public sets** (Lesson 6). 24 of the 34 configurations are robust, so always answering "robust" scores 0.706 here, against 0.48 on the public main set; the small public set is 7 of 14 robust (0.50). We report balanced accuracy beside accuracy.

None of the six signals showed transfer to unseen problems. Calibration came closest at 25/34 against a majority of 24 (balanced accuracy 0.579, interval −2 to +4 rows; −1 of 43 on the newer file). What the data exclude: the trace, activation and prompt-capability probes have a 95 % upper bound of zero rows over the majority on 34 rows (2, 0 and 0 of 43); calibration's bound is +4 of

Submitted to 40th Conference on Neural Information Processing Systems (NeurIPS 2026). Do not distribute.

34 but 0 of 43; only the prompt sensitivity and combined arms keep room on both files (+4 and +1, +4 and +5 rows). Generation stability had no gate and nearly constant agreement features, so it is a weak test (Appendix B.2). Results use the 82-row snapshot of `train-main-v2` (pinned revision `23791d9b`; Appendix B.3).

2 Data and protocol

Labels are the organisers' `is_robust` field: robust when accuracy holds across every perturbation, non-robust when one degrades it clearly; the exact criterion is unpublished and leaves a gap between the classes (FAQ 7 of the competition page). Each problem contributes up to four rows (one per model), so a split by row would leak the problem. Every result below except the family holdout holds out whole problems (outer folds). Feature standardisation is fitted on the outer training rows only. The calibration, trace and activation probes also choose their penalty (and carry per-model terms) there; the prompt-only probe uses a fixed $C = 1$, with no model term. The 34 labelled rows are Qwen3.5-4B 12, DeepSeek-R1-0528-Qwen3-8B 10, Olmo-3-7B-Think 9 and Skywork-OR1-Math-7B 3; a family holdout, which leaks problems, is in Appendix B.2. Every label comes from the organisers' `train-main-v2`; Lessons 6, 8 and 9 also read their augmented DeepSeek sets and public sample. Our only labels of our own are a transfer check on the public sample (Appendix C), and the organisers retired the rule against extra labelled data on 19 September (rules page, read 2026-10-27).

3 Methods

Each signal sees only what a deployed entry sees: the prompt, or the model's own generations on it. Details are in Appendix B.4.

- **Prompt-only features.** One forward pass over the original prompt and two perturbed copies (typos, an irrelevant sentence) gives eight features (likelihood, length, changes in both, hidden-state shift), read by a logistic probe.
- **Calibration.** A per-model ability term and a per-problem difficulty term from prompt statistics; the arm is chosen inside each training fold.
- **Generation stability.** Qwen3.5-4B samples the original and perturbed prompts; answer agreement and accuracy drop are compared with the label's `max_drop`.
- **Counterfactual trace sensitivity.** A fixed 256-token reasoning prefix is teacher-forced under answer-preserving rewrites and one answer-changing control; eleven features measure the response.
- **Hidden-activation probe.** A ridge probe on native hidden states at 25, 50 and 75 % depth, over the prompt and a 128-token reasoning prefix.
- **Forced-answer flips.** Each model answers the original and two or three perturbed copies, with the final answer forced when unfinished; the share of changed answers is the signal.

Four of the five gates (all but flips) were committed before their results (Appendix B.1); generation stability had none. "Short by" counts rows missing from the +3 margin over the gate's own baseline.




Figure 1: Correct rows minus the majority baseline, with 95 % problem-bootstrap intervals (Section 4 table).

Signal	Gate as coded (all must hold)	Commit	Short by
Prompt-only features	combined accuracy $\geq$ 0.80; correct $\geq$ better baseline + 3; margin > 0 after dropping any one problem	`8821dd5`	4 (23 vs 24)
Calibration	nested accuracy $\geq$ 0.80; correct $\geq$ prompt-probe control (23) + 3; no held-out family below its majority	`7ba8061`	1 (25 vs 23); 2 against majority 24
Generation stability	none: it prints correlations and leave-one-out accuracy	no gate	not applicable
Counterfactual trace	accuracy $\geq$ 0.80; correct $\geq$ max(majority, calibration 25) + 3; balanced $\geq$ 0.70; margin > 0 after dropping any one problem	`8f7abe9`	6 (22 vs 25)
Hidden-activation probe	coverage complete; accuracy $\geq$ 0.80; correct $\geq$ majority + 3 and $\geq$ calibration + 3; balanced $\geq$ 0.70; margin > 0 after dropping any one problem	`2c49bc8`	5 against majority 24; 6 against calibration
Forced-answer flips	held-out correct $\geq$ majority + 3	`6303f85`	2 (52 vs 51 on 86 rows)

4 Results

Signal	Correct / 34	Balanced accuracy	Wins / losses vs majority	Difference [95 %]	43 rows: correct, difference [95 %]
Always "robust"	24	0.500	—	—	31
Prompt-only: capability	23	0.479	0 / 1	−1 [−3, 0]	30, −1 [−3, 0]
Prompt-only: sensitivity	24	0.558	2 / 2	0 [−4, 4]	28, −3 [−8, 1]
Prompt-only: combined	23	0.567	3 / 4	−1 [−6, 4]	29, −2 [−9, 5]
Calibration (nested selection)	25	0.579	2 / 1	+1 [−2, 4]	30, −1 [−3, 0]
Counterfactual trace sensitivity	22	0.458	0 / 2	−2 [−5, 0]	30, −1 [−4, 2]
Hidden-activation probe	22	0.458	0 / 2	−2 [−5, 0]	29, −2 [−5, 0]

Wins are rows a signal gets right where the majority is wrong, losses the reverse. The last column refits all six on the 43 labelled rows of the 2026-10-15 file (22 problems; `report/intervals-43.json`), where every gate fails again. Intervals: 10,000 resamples of whole problems (`report/intervals.py`).

Post hoc (Appendix B.2), no signal's held-out AUC interval lies above 0.5; calibration's is 0.67 [0.45, 0.95], and at a prior-matched threshold it gets 24/34, the majority's count.

- **Generation stability** (12 labelled rows, no gate): largest Spearman with `max_drop` 0.24 (p = 0.46); the best of 13 leave-one-out rules, chosen after the fact, gets 9/12 against 8/12.
- **Forced-answer flips:** 52/86 against a majority of 51/86 (Lesson 8).

5 What we learned

1. **Sensitivity of a fixed trace is not sensitivity of the answer.** The answer-changing control moved the likelihood more in 33 of 42 traced configurations, yet the contrast did not separate labels.
2. **The label is about perturbations of solved problems, and nearly every row is solved.** In the organisers' two DeepSeek sets, 52 of 54 and 138 of 141 rows have base accuracy 1.0, and 79 % and 74 % of those are non-robust (Lesson 6).
3. **Forcing the final answer does not rescue the answer-level test.** Held out, the flip rule gets 18 of 34 train-file rows against a majority of 24, and its AUC differs by label source (0.71 against 0.40, difference 0.30 [−0.01, 0.54]; Lesson 8).
4. **Robustness behaves like a property of the problem** (Lesson 9). Holding out one row instead of the whole problem lets a same-problem lookup gain 4 of 34 rows (one problem) and 8 of 43 (three problems) over the majority, balanced accuracy +0.20 [0, 0.40] and +0.33 [0, 0.46]; the length, prompt-only and calibration fits gain at most two rows there, so the strict split does not explain their nulls (Appendix B.3).

For the next entrant. Hold out whole problems (a row-split lookup gains up to 8 of 43 rows); report balanced accuracy (labels 71 % robust, public sets about half); check the public sample against the training file (5 of its 10 problems carry labels); report a text-length control; give answer-level signals more than 4,096 tokens (DeepSeek-R1-0528-Qwen3-8B finished none of 36 samples within it; Lesson 7).

A text-length control. On the organisers' 141-row DeepSeek set (137 problems), a logistic regression on four counts of the problem text (log characters, words, digits, $) reaches balanced accuracy 0.644 (0.592 to 0.677 over 20 seeds) under five-fold problem-grouped folds; the 95th percentile of its label-shuffle null is 0.592. The kit's uncertainty-profiling README reports 0.626 on the same rows with its own folds (its accuracy, 0.6879, is 97 of 141), so the comparison is indicative. Run once on our 10 DeepSeek rows, that artifact gets 2 of 10, too few to measure (Appendix C).

6 Reproduction

Code, saved features and commands: the supplementary ZIP (the public repository link is withheld for anonymous review), `supplementary.zip` with `MANIFEST.sha256`, under Apache-2.0. `REPRODUCE.md` recomputes Sections 1 to 4 on a CPU in about seven minutes on two CPU threads from the saved features and the data files of Appendix D. The scored entries are the v3 uploads of 2026-10-27, a per-configuration prior fitted on the training file alone whose posteriors all exceed 0.5, so both answer "robust" for every problem, the decision these results support (Appendix A). Our v1 entries of 2026-10-19 picked the configurations to call robust from ten single-configuration public-board uploads, which is public-board feedback; we raised this with the organisers on 2026-10-24 and replaced them.

Related work

Our signals follow work on a model's own reliability: self-evaluation (Kadavath et al., 2022), semantic entropy (Kuhn, Gal and Farquhar, 2023) and hidden-state probes (Azaria and Mitchell, 2023; Burns et al., 2023); our perturbations follow Shi et al. (2023) and Mirzadeh et al. (2024). Written chain-of-thought can misreport what drove an answer (Turpin et al., 2023; Lanham et al., 2023), so our trace signal scores how a fixed prefix responds to edits. Rows from one subject inflate predictions in small samples (Kapoor and Narayanan, 2023; Rosenblatt et al., 2024); our repeated problems are such subjects.

Limitations

Generation stability (12 rows) and forced-answer flips (86 rows) were scored on their own row sets, not in the Section 4 table. The 34-row sample gives about 20 independent problems. Local models are a proxy for the official deployments (Lesson 4). No white-box ablation was run, so the entry makes no White-Box claim. The Olmo-3-7B-Think forced-answer run was stopped (Appendix B.1).

No signal was tested for transfer without problem leakage: the family holdout shares problems, and neither the main track nor the public sample was scored with any of the six signals. Calibration's interval on 34 rows leaves a true gain of up to four rows (12 points) unexcluded.

AI Use Statement

In this work, we used generative AI tools for ideation, coding, analysis and writing. Claude (Anthropic, through Claude Code) proposed methods, wrote the code, ran the experiments and analyses and drafted this report; OpenAI Codex (through the Codex CLI) helped plan experiment rounds and reviewed code and claims. We did not use generative AI tools to create or change any label (all labels are the organisers'), to decide which entries were uploaded to Codabench, or to submit this report. We have reviewed all AI-assisted work and take full responsibility for the final content of this report, including AI-assisted text, claims, code and other artifacts. Every number was rerun from the scripts named in this report, except Lesson 7 (36 of 36 samples without a final answer), whose outputs were not kept, the Olmo progress count read from its log, and the Codabench scores, IDs and board ranks of Appendices A and D, which were read from the competition pages and our submission log and have no script.

References

- Azaria, A., Mitchell, T. (2023). The Internal State of an LLM Knows When It's Lying. Findings of EMNLP 2023.
- Burns, C., Ye, H., Klein, D., Steinhardt, J. (2023). Discovering Latent Knowledge in Language Models Without Supervision. ICLR 2023.
- Kadavath, S., et al. (2022). Language Models (Mostly) Know What They Know. arXiv:2207.05221.
- Kapoor, S., Narayanan, A. (2023). Leakage and the Reproducibility Crisis in Machine-Learning-Based Science. Patterns, doi:10.1016/j.patter.2023.100804.
- Kuhn, L., Gal, Y., Farquhar, S. (2023). Semantic Uncertainty: Linguistic Invariances for Uncertainty Estimation in Natural Language Generation. ICLR 2023.
- Lanham, T., et al. (2023). Measuring Faithfulness in Chain-of-Thought Reasoning. arXiv:2307.13702.
- Mirzadeh, I., et al. (2024). GSM-Symbolic: Understanding the Limitations of Mathematical Reasoning in Large Language Models. arXiv:2410.05229.
- Rosenblatt, M., et al. (2024). Data Leakage Inflates Prediction Performance in Connectome-Based Machine Learning Models. Nature Communications, doi:10.1038/s41467-024-46150-w.
- Shi, F., et al. (2023). Large Language Models Can Be Easily Distracted by Irrelevant Context. ICML 2023.
- Turpin, M., Michael, J., Perez, E., Bowman, S. R. (2023). Language Models Don't Always Say What They Think: Unfaithful Explanations in Chain-of-Thought Prompting. NeurIPS 2023, arXiv:2305.04388.
- AIMO Interpretability Challenge organisers. getting-started kit, github.com/aimo-interp/getting-started, commit `de79405`.

A Submission history

Every upload to the competition, in order. Hashes are of the zips in the lane's `dist/`, all of which the archive ships (`dist/entry/`, `dist/probe/`, and the two constant baselines); full hashes are in `REPRODUCE.md`.

File	sha256 (first 16)	Uploaded	Task	Id	Public score
`always-true-main.zip`	`ba38cb0e7b55dd3a`	2026-10-11	main	977178	0.48
`always-true-small.zip`	`a3748c648a5a0d9a`	2026-10-11	small	977183	not recorded
ten single-configuration probes, `probe/*.zip` (nine zips kept)	see `REPRODUCE.md`	2026-10-18	both	not recorded	main best 0.57, small best 0.57
`main-hybrid-v1.zip`	`d2df7dc8a0daaf85`	2026-10-19	main	1002314	0.57
`small-groups-v1.zip`	`82344d44e9b9d86e`	2026-10-19	small	1002316	0.64
`small-hybrid-v1.zip`	`376c170a05b963c8`	2026-10-19	small	1002317	0.57
`main-training-v3.zip`	`c315e32fc6392fb3`	2026-10-27	main	1014009	0.48
`small-training-v3.zip`	`470ceba57ca85278`	2026-10-27	small	1014010	0.50

The two constant baselines answer "robust" for every configuration. Our submission log notes that the first `always-true-small` upload had gone to the main task and was rejected at ingestion, so its small-task score is not recorded; the log counts the small public set as 7 of 14 robust (0.50).

The probes each answered "robust" for one model configuration and non-robust for the rest. Their net robust counts on the public sets (score times problems, minus the all-non-robust score) were, main: Qwen3.5-4B 0, Olmo-3-7B-Think 0, DeepSeek-R1-0528-Qwen3-8B -1, gpt-oss-120b low -1, gpt-oss-120b medium +1 (0.57), Skywork pending (cancelled); small: Qwen3.5-4B +1 (0.57), Skywork -1, Olmo -1, DeepSeek +1. The small-track DeepSeek +1 is derived from the log's total, not a measured score. The log lists the main-track DeepSeek probe as -1 on 2026-10-18 and as cancelled on 2026-10-19; the public board holds five scored main-track probe rows from 2026-10-18 whose nets (0, 0, -1, -1, +1) match the five values above, but which id is which probe was not recorded. `small-hybrid-v1` scored 0.57 (8 of 14; public board, read 2026-10-27). The public sets are 21 main and 14 small problems, so counts of +/-1 are noise-sized, as the log notes itself; the v1 groups were chosen by those counts and can be overfit to the public sets. `small-groups-v1` answers "robust" for Qwen3.5-4B and DeepSeek (public 9/14 = 0.64, the sum of the two probes' counts, one of them derived). `main-hybrid-v1` answers "robust" for gpt-oss-120b at medium effort only. Both hybrids replace DeepSeek's answer by the prediction of the organisers' bundled uncertainty-profiling artifact (`uncertainty_profile/`, run on DeepSeek's own greedy trace); the small hybrid also keeps Qwen3.5-4B robust. That artifact is not one of the six signals tested above; scored afterwards on 10 of our rows, it got 2 against a majority of 7 (Section 5). On the public main set the hybrid scored 0.57, the same as the gpt-oss-medium probe alone. None of these v1 entries uses a signal that cleared its gate; they used public-board feedback and are withdrawn. The v3 entries use no public-set signal: their prior is fitted on the organisers' training file alone. Guarded v2 hybrids (`entry/`, built by `entry/build.sh`) were built and not uploaded.

Submission bundle (v3 training-only entries)

Each zip holds a `solution.py` and `training-prior.json`; the small-track zip also holds the root-level `small.txt` marker the competition requires there and forbids in a main-track one (kit README). There is no artifact and the code reads no clock. `entry/fit_training_prior.py` fits a beta-binomial prior (strength 64, chosen by leave-one-problem-out log loss inside the training data) on the 2026-10-15 training file (94 rows, sha256 `e18eb442...`) and writes `entry/training-prior.json`. A configuration with at least five labelled rows takes its posterior robust rate, any other configuration the track's global rate, and a rate of 0.5 or more answers "robust" for every problem of that configuration:

Track	zip sha256 (first 16)	Training rows	Global posterior	Answers	
main	`c315e32fc6392fb3`	37 (gpt-oss-120b only)	0.757	"robust"	everywhere
small	`470ceba57ca85278`	43	0.721	"robust"	everywhere

Every configuration's posterior is at least 0.5, so both entries make the same predictions as the constant baselines; a configuration missing from the training file takes the global rate. The prior is refitted with `entry/fit_training_prior.py\-\/-train\data/train-main-v2/train-2026-10-15.parquet\-\/-pinned\data/train-main-v2/`

train-00000-of-00001.parquet (REPRODUCE.md section 6). The v2 hybrids were built and not uploaded. entry/build.sh v3 fixes the file timestamps and the file order, so two builds give the same bytes (entry/test_entry_v3.py, line 175).

B Methods, results and gates in full

B.1 Gates

The gates are in the table in Section 3. Commit and result times: prompt-only 8821dd5 2026-10-11 14:36, results 17:49; calibration 7ba8061 2026-10-11 19:53, results 21:22; trace 8f7abe9 2026-10-13 12:04, rows 14:16; activation 2c49bc8 2026-10-14 11:16, result 14:50; flips 6303f85 2026-10-14 15:10, rows file 15:10.

"Set before it ran" rests on git commit times against file times of untracked, unsigned run files, and holds only for the prompt, calibration, trace and activation gates. For the first flips run it cannot be shown: its rows file is stamped 25 s before the gate's commit (the gate line is unchanged since). That run was unforced and gave no result: DeepSeek-R1-0528-Qwen3-8B produced no final answer within 4,096 tokens on 36 of 36 samples (Lesson 7), and it was stopped. The reported 52/86 run came three days later with the final answer forced. Its Olmo-3-7B-Think job was stopped at 24 of 108 prompts (runs/force-r4/Olmo-3-7B-Think.log), so no Olmo row enters the flip test; Olmo has 9 labelled rows. Calibration's control of 23 was the prompt probe's own result, already known when its gate was committed.

Prevalence. A count that beats a 71 %-robust majority says little about a near-balanced private set, so the table reports balanced accuracy (any constant answer scores 0.500). The trace and hidden-activation gates also required balanced accuracy of at least 0.70; those two probes reached 0.458, and no nested-selection result in the table exceeds 0.579 (the descriptive arm in B.2 reaches 0.60). report/balanced_gates.py prints these values from the saved reports. The forced-answer test saved no held-out predictions; its majority class is non-robust (rows are 40.7 % robust), and it was 52/86 against 51/86.

B.2 Results

- **Prompt-only features:** capability features 23/34 (balanced 0.479), sensitivity 24/34 (0.558), combined 23/34 (0.567). The gate needed at least three more correct than majority; the margin was -1, and -2 after dropping the worst problem group.

- **Calibration:** 25/34 (0.735, balanced 0.579) under nested problem holdout, one more than majority; the family holdout fell to 22/34 (balanced 0.604). The family holdout is not a held-out-problem test: the problems in the held-out family appear in training under the other models, and Lesson 9 shows their labels are nearly identical across models. The leak favours the method, and the figure still does not beat the majority of 24. The descriptive arm ability + difficulty + sensitivity, fitted as a fixed arm, reached 26/34 (balanced 0.60) and was chosen in 12 of 20 outer folds, but the pre-set nested selection gave 25/34.

- **Post hoc ranking** (not part of any gate; report/posthoc_auc.py, report/posthoc_auc.json). For each gated signal except forced-answer flips, the held-out score behind the table's prediction (same model, same training rows, same inner selection; each score cut at the model's own threshold reproduces the reported correct count). AUC has robust as positive, with a 95 % interval from 10,000 resamples of whole problems. The prior-matched cut predicts robust for the highest scores so that the predicted share equals the mean training-fold robust share (0.706, 24 of 34 rows); ties at the cut all count as robust.

Signal	Held-out AUC, 95 % interval	Correct / 34 at the prior-matched cut	Correct / 34 reported
Prompt-only: capability	0.43 [0.14, 0.89]	22	23
Prompt-only: sensitivity	0.57 [0.36, 0.82]	18	24
Prompt-only: combined	0.59 [0.32, 0.93]	22	23
Calibration (nested selection)	0.67 [0.45, 0.95]	24	25
Counterfactual trace sensitivity	0.39 [0.14, 0.64]	20	22
Hidden-activation probe	0.35 [0.17, 0.66]	18	22

Every interval includes 0.5. The pooled cut mixes scores from different folds, so it is descriptive only; the always-"robust" majority gets 24/34.

- **Generation stability:** on the 12 labelled Qwen3.5-4B rows, the largest rank correlation of any stability statistic with `max_drop` is Spearman 0.24 (p = 0.46, 12 rows; change in mean log-probability under the distractor; the 14 rows including the two unlabelled give 0.30, p = 0.30). The best leave-one-out threshold rule gets 9/12 (change in log-probability under typos, a different feature, the best of 13 chosen after the fact) against a majority of 8/12. In 10 of the 12 rows none of the four original samples reached a final answer within the 8,192-token cap, and the other two had one of four unanswered, so the agreement statistics are nearly constant. This signal had no predeclared gate.
- **Counterfactual trace sensitivity:** the pilot traced 37 configurations, the 34 labelled ones and 3 from the unlabelled band; the 43-row refit appended 12 Skywork rows, so `runs/trace-pilot/rows.jsonl` now holds 49. Of the 34 labelled rows the probe is scored on, 31 had two or more verified variant families and 29 had the negative control; rows with a missing family or control enter with imputed values and a missing indicator. The probe reached 22/34 (balanced 0.458), wrong on two rows the majority gets right and right on none it gets wrong; the family holdout reached 24/34, equal to its majority; the same leak applies to it.
- **Refit on 43 rows** (2026-10-15 file; `report/intervals-43.json`, `report/posthoc_auc-43.json`). Gates fail again: prompt-only margin −2; calibration out-of-fold accuracy 0.698, net −1 against the majority, one row above its control (30 against 29 correct); trace and hidden-activation probes do not pass. Balanced accuracy: 0.484, 0.477, 0.544 (prompt-only), 0.484 (calibration), 0.509 (trace), 0.468 (activation). Post hoc AUC [95 %]: capability 0.468 [0.16, 0.87], sensitivity 0.570 [0.34, 0.81], combined 0.629 [0.34, 0.93], calibration 0.460 [0.22, 0.76], trace 0.513 [0.35, 0.69].

B.3 Row split and data snapshot

Row split against problem split (`report/split_audit.py`; `report/split-audit.json` for the 34 pinned rows, `report/split-audit-1015.json` for the 43 rows of the newer file). Split A holds out one (model, problem) row and keeps that problem's other rows in training; split B holds out the whole problem, as every headline result does. Features, train-only preprocessing and arms were fixed before the run. The same-problem lookup predicts a row from the training rows with the same problem text, else the fold majority; it demonstrates the leak and is not a method. Intervals come from 10,000 whole-problem bootstrap draws (seed 0), both splits rescored on each draw.

Arm	34 rows: correct A / B	balanced A − B	43 rows: correct A / B	balanced A − B
Majority	24 / 24	0	31 / 31	0
Four length features	24 / 24	0	31 / 31	0
Prompt-only combined	23 / 23	0	31 / 29	+0.03 [0, 0.07]
Calibration (nested)	26 / 25	+0.05 [0, 0.10]	29 / 30	−0.02 [−0.05, 0]
Same-problem lookup	28 / 24	+0.20 [0, 0.40]	39 / 31	+0.33 [0, 0.46]

Under split A, 23 of 34 and 32 of 43 test rows have their problem in training. The lookup never loses a row to the majority; every gain is a non-robust row, from one problem (34 rows) and three

problems (43 rows), so the lower bound sits at zero: a resample is positive whenever it draws one of those problems, 1 − (19/20)^20 = 64 % of draws on 34 rows and 1 − (19/22)^22 = 96 % on 43, and none is negative. On 34 rows the length and prompt-only predictions are identical under both splits. Calibration under split A keeps its inner search unchanged, which still holds out whole problems. A label shuffle within each model, which keeps every model's robust rate, expects 3.9 agreeing problems against 11 observed (34-row snapshot, all labelled models) and 4.9 against 11 on the small track of the newer file; the pooled shuffle expects 3.8 and 4.7, and no shuffle of 2,000 reaches the observed count in either. Model prevalence does not explain the agreement of Lesson 9.

The table keeps the 82-row snapshot of `train-main-v2` (pinned revision `23791d9b`), because gates and features were frozen on it before the 2026-10-15 file existed. The newer file (94 rows) has 49 small-track rows, 43 of them labelled, over 22 problems, 31 robust; the 43-row refit uses it.

B.4 Method details

Prompt-only features. One forward pass of the original prompt and of two surface perturbations (typos, an irrelevant distractor sentence): prompt NLL and length, the change in NLL under each perturbation, and the cosine change of hidden states at 50 % and 75 % depth. A logistic probe over these eight features.

Ability and difficulty calibration. A per-model ability term and a per-problem difficulty term estimated from prompt statistics, with covariates offered as arms (ability; +difficulty; +covariates; +sensitivity) and the arm chosen inside the outer folds by inner leave-one-problem-out.

Generation stability. Qwen3.5-4B sampled on the originals and perturbed prompts; agreement and accuracy drop between them, compared with the labels' `max_drop`.

Counterfactual trace sensitivity. A deterministic 256-token reasoning prefix is generated from the original prompt. It is then teacher-forced after the original prompt and after verified answer-preserving variants: variable renaming (with the rename applied inside the trace), equivalent numeric expressions, equation-side swaps and reordering of independent givens. A condition change that alters the answer (one integer constant raised by one) is the negative control. Eleven predeclared features: the prefix's mean log-probability under the original prompt, the per-token log-likelihood change (mean, worst family, variance, concentration in the least likely 20 % of tokens), hidden-state cosine change at 50 % and 75 % depth (also near renamed entities), the ratio of answer-preserving to answer-changing sensitivity, and indicators for missing families and a missing control. Only trace positions are captured, and activations are released per problem.

C Lessons in full

1. **The sample is smaller than it looks.** 34 rows from 20 problems give about 20 independent units. The Section 4 intervals are 3 to 10 configurations wide, so a real gain of one or two configurations could not be seen here.
2. **Prompt features did not beat the majority.** Capability features reached 23/34, sensitivity 24/34 and the combined arm 23/34 against a majority of 24 (Section 4). One possible reason is that the label is a difference between two accuracies and a feature of one prompt sees only one side of it; we did not test this.
3. **Sensitivity of a fixed trace is not sensitivity of the answer.** The trace features measure a likelihood response, not whether the final answer survives the perturbation: teacher-forcing one reasoning prefix under a renamed or reordered problem measures surprise at the edit. The control that changes the answer moved the likelihood more in 33 of the 42 traced configurations that have one (49 traced, 7 without a control; median ratio of answer-preserving to answer-changing change 0.62; on the 29 labelled rows with a control, 22 of 29, median 0.62; `report/trace_control.py`), so the features see the edits; the contrast still did not separate the labels.
4. **Local models are a proxy for the official deployments.** Qwen3.5-4B ran in BF16; Olmo-3-7B-Think, DeepSeek-R1-0528-Qwen3-8B and Skywork-OR1-Math-7B ran in 4-bit NF4. Neither matches the organisers' serving setup, and the NF4 rows may carry quantisation effects in the trace features. We report this as a limitation, not as an explanation of the null result.

5. **Hidden states did not help either.** A linear ridge probe on each model's native hidden states (prompt and a 128-token reasoning prefix, pooled at 25, 50 and 75 % depth, families kept in separate coordinates) reached 22/34 under the same nested problem holdout, two below the majority (`fit_activation_probe.py`, `run_activation_probe.py`).
6. **The label is about perturbations of solved problems.** In the organisers' augmented sets, problems whose every base sample was correct are still mostly non-robust. The two sets are the same model, DeepSeek-R1-0528-Qwen3-8B (the kit's `uncertainty_profile/config.py` maps the id `qwen3-8b:low` to it), and all 52 problems of `augmented-sample-math-agg-filtered` also appear in `augmented-sample-math-agg` (137 problems), so the two figures are not two models. Rows are per permutation type, so a problem can appear in several rows: the filtered set has 54 rows over 52 unique `problem_id`, the larger set 141 rows over 137. Rows with `base_accuracy` = 1.0 (any number of base samples, 1 to 60) are 52 of 54 and 138 of 141, nearly all rows, so the non-robust share among them (41 of 52, 79 %; 102 of 138, 74 %) matches the unconditional share (43 of 54, 80 %; 105 of 141, 74 %). Restricted to rows with exactly ten base samples: 34 of 40 (85 %) and 63 of 82 (77 %). `report/lesson6_counts.py` computes all of these. Answer consistency on the original cannot be tested in these sets. The public evaluation sets are near balance (always "robust" scores 0.48 on the main task, and the small-model set is 7 of 14 robust) while our 34 labelled rows are 71 % robust (Section 1), so a majority vote learned on the training rows is not a safe default.
7. **Answer-level tests run out of token budget.** We started an answer-flip test (each model answers the original, typo and distractor copies, and a renamed copy where the problem has a name). DeepSeek-R1-0528-Qwen3-8B produced no final answer within 4,096 tokens on 36 of 36 samples of the olympiad problems. This check is not reproducible from the archive: its outputs were not kept. We did not run the unforced test further; Lesson 8 forces the final answer instead.
8. **Forcing the final answer does not rescue the answer-level test.** We reran the answer-flip test with the final answer forced: each unfinished sample is continued from its reasoning with `</think>` and `The final answer is \boxed{` appended, greedy, 24 tokens. Rows: the 2026-10-15 `train-main-v2` small-track labels (Qwen3.5-4B 12, Skywork-OR1-Math-7B 12, DeepSeek-R1-0528-Qwen3-8B 10; 34 rows, 24 robust) plus the 52 DeepSeek rows of the organisers' aggregated set `augmented-sample-math-agg-filtered` (11 robust); four samples per variant at 2,048 tokens, Skywork and DeepSeek with FP8 weights. Under the same problem-held-out protocol the best rule reached 52/86 against a majority of 51/86, short of the gate.

   The sign of the signal differs between the two row sets, and the data do not tell label source from model apart: the two sets share no model except DeepSeek, and the DeepSeek train-file rows alone are 10 rows. `report/flips_by_source.py` joins the rows to their source and prints, for the AUC of the mean flip rate (above 0.5 means robust rows flip less) with a 95 % interval from 4,000 bootstrap resamples of problem ids (seed 0):

Label source	Rows (robust)	Mean-flip AUC	95 % interval	Problem-held-out rule, correct / majority
2026-10-15 train file, Qwen3.5-4B	12 (8)	0.703		
2026-10-15 train file, Skywork-OR1-Math-7B	12 (9)	0.685		
2026-10-15 train file, DeepSeek-R1-0528-Qwen3-8B	10 (7)	0.738	[0.12, 1.00]	
2026-10-15 train file, all	34 (24)	0.706	[0.44, 0.87]	18 / 24
Organisers' per-permutation set, DeepSeek	52 (11)	0.402	[0.22, 0.59]	41 / 41

   The difference, train file all minus organisers' set, is 0.304 [−0.01, 0.54].

   The train file labels a model on a problem by the largest accuracy drop over the perturbation families (Section 2). In the organisers' `augmented-sample-math-agg-filtered` (54

rows), `permutation_type` is a single type for 43 rows (32 `domain`, 59 % of all 54) and a list for 11 rows (3 one-element `["distract"]`, 8 with two to five types). All 34 `domain` and `rephrase` rows are non-robust, so the 11 robust rows are among the other 20, while our typo, distractor and rename copies include neither permutation. Restricted to the 12 rows whose problem has only typos, distract or rename permutations in every one of its source rows (8 single-type rows, 4 list rows; 4 robust), the mean-flip AUC is 0.547 [0.10, 0.89] (same 4,000-draw problem bootstrap, `--permutations`). With fewer than 5 robust rows the restricted test is underpowered and cannot say whether the sign reverses. The earlier pooled DeepSeek figure (0.348 on 62 rows) mixed both sources. On the competition-style labels the in-sample AUC is 0.71, but the held-out rule gets 18 of 34 against a majority of 24, so the null stands. The 52 augmented rows give 41 against 41, again no gain.

9. **Robustness behaves like a property of the problem, which makes public scores easy to inflate.** `report/lesson9_counts.py` computes these counts from the organisers' parquet files, and `report/lesson9_shuffle.py` the shuffle null. `train-main-v2` labels 33 problems. At the pinned revision (82 rows, `23791d9b`), 11 of them are labelled for more than one model and all 11 carry the same label for every model; counting each reasoning effort of gpt-oss-120b as its own configuration, 15 problems are labelled for more than one configuration and 14 of those agree. In the 2026-10-15 file used for the forced-answer test (94 rows), the figures are 14 of 33 with 13 agreeing by model, and 16 with 15 agreeing by configuration. The rule that any model counts as a repeat is the loose one; the counts are small either way. On the small track alone the shuffle expects 4.7 agreeing problems (range 2 to 7). The one disagreement mixes a Skywork row with gpt-oss-120b rows, so it crosses tracks. Five of the ten problems in the public challenge sample appear in `train-main-v2` with labels (same count in both files). A lookup over labelled problems can therefore score well on public problems that overlap the training labels; we did not measure it on unseen private problems, and we read public scores far above the majority with that overlap in mind. Appendix B.3 measures the same lookup on our labels under a row split and a shuffle that keeps each model's robust rate.

The organisers' artifact, scored once on our labels. The uncertainty-profiling example is not one of the six signals; both v1 hybrids shipped it (Appendix A); the v3 entries ship no artifact. `report/artifact_gate.py` generated greedily with DeepSeek-R1-0528-Qwen3-8B on the 10 DeepSeek rows of the 2026-10-15 train file (10 problems, 7 robust; 4,096 new tokens; the kit's pinned library versions; most layers offloaded to the CPU on a 12 GB card, which changes speed, and greedy tokens only through floating-point differences) and applied the artifact's estimator and decision threshold unchanged (`runs/artifact-gate/score.json`). It scores 2/10 against a majority of 7/10: balanced accuracy 0.333, difference −5 rows with a 95 % whole-problem bootstrap interval of [−10, 0]. It predicts non-robust for 9 of 10 rows; both correct calls are non-robust rows, and the probability that a robust row scores below a non-robust one is 0.14. Ten rows with three non-robust cannot measure its accuracy. They are consistent with a threshold set where 74.5 % of rows are non-robust and applied to labels that are 70 % robust.

Its README documents a grouped out-of-fold balanced accuracy of 0.6262 and plain accuracy 0.6879 (`kit/solutions/uncertainty-profiling/README.md`, lines 127-128; DeepSeek only, on the organisers' aggregated set). That is below this report's own 0.70 balanced bar, so by our standard it would not clear a gate either. A constant "non-robust" scores 105/141 = 0.745 on that set, above the artifact's 97/141. Our ten rows count against it, and the v2 bundles that use it were not entered.

A length baseline (`report/length_baseline.py`) tests the 0.626 against problem length. On the same 141 rows (137 problems), five-fold problem-grouped folds, seeds 0 to 19, a standardized logistic regression with balanced class weights on four features of the problem text (log character count, word count, digit count, $ count) reaches balanced accuracy 0.644 (0.592 to 0.677) and accuracy 0.664; log character count alone reaches 0.698 (accuracy 0.702). A label-shuffle null (200 shuffles that permute labels across problems, rows of one problem kept together, one seed each) has median 0.498, 95th percentile 0.592 and maximum 0.647. The artifact's 0.6262 is not shown to beat problem length; its own folds and threshold differ from these, so the comparison is indicative.

Transfer to the organisers' public sample (`report/sample_transfer.py`): labelling the 558-row sample by the proposal paper's outline, which the organisers say differs from the official rule (largest

absolute_accuracy_decay per model and problem, robust at most 0.10, non-robust from 0.25), gives 69 labelled (model, problem) pairs of 80 over 10 problems, 38 robust. Five of the 10 problems are also in train-main-v2, and only gpt-oss-120b:low and qwen3-8b:low (taken to be DeepSeek-R1-0528-Qwen3-8B) match a training configuration; the per-configuration prior predicts robust for both, so it scores 8 of 15 labelled pairs, the same as the pooled majority. The pooled per-problem arm needs features that do not exist for these problems (a GPU run), so it was not tested there.

D Reproduction details

Code, saved features and exact commands: the supplementary ZIP (the public repository link is withheld for anonymous review), supplementary.zip with MANIFEST.sha256, released under Apache-2.0 (LICENSE in the tree). REPRODUCE.md recomputes the numbers in Sections 1 to 4 on a CPU in about seven minutes on two CPU threads from the saved features and the data files below, and lists the data file, script and run folder behind each section; regenerating the hidden-activation features needs a GPU. Data, all Hugging Face datasets of the organisation aimo-interp, none redistributed:

- aimo-interp/train-main-v2 at revision 23791d9b120132087877b0459f953d5959fc8455, data/train-00000-of-00001.parquet, sha256 bedfb551ea0f4d95d5e70e1df7cf61395ce2d36eeba2869aba6a90fc3c198824.
- aimo-interp/train-main-v2 as of 2026-10-15 (data/train-main-v2/train-2026-10-15.parquet, 94 rows), sha256 e18eb44207e7987781ec2ff214793196038442bdc1466fdf5498f3e87ec58285. At revision fa8af758c6519fc97a9d0bd9017feb6f12232b52, downloaded 2026-10-17.
- aimo-interp/aimo-interp-challenge-sample-full (the public sample of Lesson 9), validation-00000-of-00001.parquet, sha256 2989ab6a018f2779a821209f414bd0049c9ef1c2488f589ff2d3bf4ed16942ff. File dated 2026-10-11 in the data folder; no revision recorded.
- aimo-interp/augmented-sample-math-agg (Lesson 6), validation-00000-of-00001.parquet, sha256 b785750259a3f4524cbaf988f51660197cbdfca19d8f45cc35347d4ef29aa4db. The organisers' kit pins revision f972ced0705096f8d7ca7fac30825900b8b7fb6a; we did not record the revision of our copy (file dated 2026-10-11), so the match is not verified.
- aimo-interp/augmented-sample-math-agg-filtered (Lessons 6 and 8), same file name, sha256 b8a485868ce5a14d0c961e009e30bc61f850ad2d2224a01ae1ada401fb73ed3d. File dated 2026-10-11 in the data folder; no revision recorded. Training code: this repository (fit_probe.py, sub/calibration.py, fit_trace_probe.py, fit_activation_probe.py). Organisers' kit: github.com/aimo-interp/getting-started at commit de79405. Competition: https://www.codabench.org/competitions/16180/.

The v1 uploads, replaced by the v3 entries on 2026-10-27, and their scores (Appendix A; board position on 2026-10-19): small-groups-v1 (static groups, no artifact) scored 0.64, rank 29 of 60 on the small task; main-hybrid-v1 scored 0.57, rank 22 of 47 on the main task; small-hybrid-v1 scored 0.57. The hybrids run the organisers' artifact for DeepSeek; none of the three uses a signal tested here. The v2 bundles were built and not uploaded. Codabench IDs of the v1 uploads are in Appendix A. The leaderboard lists eight probe rows, IDs 1000868, 1000873, 1000876, 1000878, 1000884, 1000887, 1000891 and 1000892; REPRODUCE.md lists the zip hashes of the nine kept. Appendix A describes the shipped v3 bundle (main id 1014009, score 0.48; small id 1014010, score 0.50).