



Building the Futuristic **Blockchain Ecosystem**

SECURITY AUDIT REPORT

USERTOKEN

TOKEN OVERVIEW

Risk Findings

Severity	Found
● High	21
● Medium	1
● Low	5
● Informational	0

Centralization Risks

Owner Privileges	Description
● Can Owner Set Taxes >25% ?	Yes
● Owner needs to enable trading ?	Yes, owner needs to enable trades
● Can Owner Disable Trades ?	Yes
● Can Owner Mint ?	Not Detected
● Can Owner Blacklist ?	Yes
● Can Owner set Max Wallet amount ?	Yes
● Can Owner Set Max TX amount ?	Yes

TABLE OF CONTENTS

02	Token Overview	
03	Table of Contents	
04	Overview	
05	Contract Details	
06	Audit Methodology	
07	Vulnerabilities Checklist	
08	Risk Classification	
09	Inheritance Trees & Risk Overview	
10	Function Details	
13	Manual Review	
14	Findings	
44	About Expelee	
45	Disclaimer	

OVERVIEW

The Expelee team has performed a line-by-line manual analysis and automated review of the smart contract. The smart contract was analysed mainly for common smart contract vulnerabilities, exploits, and manipulation hacks. According to the smart contract audit:

Audit Result	Failed
KYC Verification	-
Audit Date	10 June 2023

CONTRACT DETAILS

Token Name: USER Token

Symbol: USR

Network: -

Language: Solidity

Contract Address: Local File

Total Supply: 21000000000

Owner's Wallet: Local File

Deployer's Wallet: Local File

AUDIT METHODOLOGY

Audit Details

Our comprehensive audit report provides a full overview of the audited system's architecture, smart contract codebase, and details on any vulnerabilities found within the system.

Audit Goals

The audit goal is to ensure that the project is built to protect investors and users, preventing potentially catastrophic vulnerabilities after launch, that lead to scams and rugpulls.

Code Quality

Our analysis includes both automatic tests and manual code analysis for the following aspects:

- Exploits
- Back-doors
- Vulnerability
- Accuracy
- Readability

Tools

- DE
- Open Zeppelin
- Code Analyzer
- Solidity Code
- Compiler
- Hardhat

VULNERABILITY CHECKS

Design Logic	Passed
Compiler warnings	Passed
Private user data leaks	Passed
Timestamps dependence	Passed
Integer overflow and underflow	Passed
Race conditions & reentrancy. Cross-function race conditions	Passed
Possible delays in data delivery	Passed
Oracle calls	Passed
Front Running	Passed
DoS with Revert	Passed
DoS with block gas limit	Passed
Methods execution permissions	Passed
Economy model	Passed
Impact of the exchange rate on the logic	Passed
Malicious event log	Passed
Scoping and declarations	Passed
Uninitialized storage pointers	Passed
Arithmetic accuracy	Passed
Cross-function race conditions	Passed
Safe Zepplin module	Passed

RISK CLASSIFICATION

When performing smart contract audits, our specialists look for known vulnerabilities as well as logical and access control issues within the code. The exploitation of these issues by malicious actors may cause serious financial damage to projects that failed to get an audit in time. We categorize these vulnerabilities by the following levels:

High Risk

Issues on this level are critical to the smart contract's performance/functionality and should be fixed before moving to a live environment.

Medium Risk

Issues on this level are critical to the smart contract's performance/functionality and should be fixed before moving to a live environment.



Low Risk

Issues on this level are minor details and warnings that can remain unfixed.

Informational

Issues on this level are minor details and warnings that can remain unfixed.

INHERITANCE TREES



FUNCTION DETAILS

Contract	Type	Bases	Visibility	Mutability	Modifiers
L	**Function Name**	**Visibility**	**Mutability**	**Modifiers**	
ReentrancyGuard	Implementation				
L	<Constructor>	Public	!	NO	!
L	_nonReentrantBefore	Private	!	NO	!
L	_nonReentrantAfter	Private	!	NO	!
L	_reentrancyGuardEntered	Internal	!	NO	!
IERC20	Interface				
L	totalSupply	External	!	NO	!
L	balanceOf	External	!	NO	!
L	transfer	External	!	NO	!
L	allowance	External	!	NO	!
L	approve	External	!	NO	!
L	transferFrom	External	!	NO	!
Context	Implementation				
L	_msgSender	Internal	!	NO	!
L	_msgData	Internal	!	NO	!
MultiSignWallet	Implementation				
L	<Constructor>	Public	!	NO	!
L	newTransaction	External	!	NO	!
L	approveTransaction	External	!	NO	!
L	_getApprovalCount	Public	!	NO	!
L	executeTransaction	Internal	!	NO	!
L	revoke	External	!	NO	!
IFactory	Interface				
L	createPair	External	!	NO	!
IRouter	Interface				
L	factory	External	!	NO	!
L	WETH	External	!	NO	!
L	addLiquidityETH	External	!	NO	!
L	swapExactTokensForETHSupportingFeeOnTransferTokens	External	!	NO	!
L	swapExactTokensForTokensSupportingFeeOnTransferTokens	External	!	NO	!
L	swapExactETHForTokensSupportingFeeOnTransferTokens	External	!	NO	!

FUNCTION DETAILS

```

L claimHODLRewards | Public ! | ● | onlyWhenHodlRewardEnabled nonReentrant |
L spinovationHelper | Private 🔒 | ● | onlyWhenRandomRewardEnabled |
L spinovation | External ! | ● | nonReentrant |
L claimUsdtRewards | External ! | ● | onlyWhenUsdtRewardEnabled nonReentrant |
L getUsdtRewards | External ! | NO ! |
L getNFT_F_rewards | Public ! | NO ! |
L claimNFT_F_rewards | Public ! | ● | nonReentrant |
L getNFT_L1_rewards | Public ! | NO ! |
L claimNFT_L1_rewards | Public ! | ● | nonReentrant |
L getNFT_L2_rewards | Public ! | NO ! |
L claimNFT_L2_rewards | Public ! | ● | nonReentrant |
L getNFT_L3_rewards | Public ! | NO ! |
L claimNFT_L3_rewards | Public ! | ● | nonReentrant |
L createUserIdList | Internal 🔒 | ● |
L randomNumberGenerator | Private 🔒 |
L fluidify | Private 🔒 | ● | lockTheSwap |
L addLiquidity | Private 🔒 | ● |
L swapTokensForBNB | Private 🔒 | ● |
L swapThisForTokens | Private 🔒 | ● |
L airdropTokens | External ! | ● | onlyOwner |
L updateMAX_AIRDROP_AMOUNT | External ! | ● | onlyOwner |
L toggleRandomReward | External ! | ● | onlyOwner |
L toggleHodlReward | External ! | ● | onlyOwner |
L toggleUsdtReward | External ! | ● | onlyOwner |
L setNFTs | External ! | ● | onlyOwner |
L setNftPercentages | External ! | ● | onlyOwner |
L updateHODL_STAKING_RATE | External ! | ● | onlyOwner |
L updateRANDOM_WALLET_THRESHOLD | External ! | ● | onlyOwner |
L updateRANDOM_TOKEN_THRESHOLD | External ! | ● | onlyOwner |
L updateRANDOM_TOKEN_THRESHOLD_FOR_SWAP | External ! | ● | onlyOwner |
L updateUSDT_REWARDS_THRESHOLD | External ! | ● | onlyOwner |
L updateUSDT_REWARDS_PERC | External ! | ● | onlyOwner |
L updateHODL_THRESHOLD | External ! | ● | onlyOwner |
L updateMarketingWallet | External ! | ● | onlyOwner |
L updateDevelopmentWallet | External ! | ● | onlyOwner |
L updateStrategicPartnershipWallet | External ! | ● | onlyOwner |
L updateAntiWhaleAmt | External ! | ● | onlyOwner |
L updateSwapTokensAtAmount | External ! | ● | onlyOwner |
L updateSwapEnabled | External ! | ● | onlyOwner |
L setAntibot | External ! | ● | onlyOwner |
L bulkAntiBot | External ! | ● | onlyOwner |
L updateRouterAndPair | External ! | ● | onlyOwner |
L updateAntiDump | External ! | ● | onlyOwner |
L isBot | Public ! | NO ! |
L taxFreeTransfer | Internal 🔒 | ● |
L liquidPulse | External ! | ● | onlyOwner |
L rescueAnyBEP20Tokens | Public ! | ● | onlyOwner |
L <Receive Ether> | External ! | 🟢 | NO ! |

```

MANUAL REVIEW

Severity Criteria

Expelee assesses the severity of disclosed vulnerabilities according to methodology based on OWASP standards.

Vulnerabilities are divided into three primary risk categories:

High

Medium

Low

High-level considerations for vulnerabilities span the following key areas when conducting assessments:

- Malicious input handling
- Escalation of privileges
- Arithmetic
- Gas use

Overall Risk Severity				
Impact	HIGH	Medium	High	Critical
	MEDIUM	Low	Medium	High
	LOW	Note	Low	Medium
		LOW	MEDIUM	HIGH
	Likelihood			

HIGH RISK FINDING

Owner can pause trade

Severity : High

Overview

This function allows the owner of the contract to pause or resume trading activities. While it may initially seem like a convenient feature, it carries a high risk that needs to be addressed.

```
function setStatus  
function setStatus(bool state↑) external onlyOwner {  
    tradingEnabled = state↑;  
    swapEnabled = state↑;  
}
```

Recommendation

To mitigate this risk, it is essential to implement additional security measures.

HIGH RISK FINDING

Owner can change fees up to 100%

Severity : High

Overview

the functions **setBuyTaxes()**, **setTaxes()**, and **setSellTaxes()** allow the owner of the smart contract to modify the associated fees, with the capability of increasing them up to 100%. This introduces a high level of risk that should be carefully considered.

setBuyTaxes

setTaxes

setSellTaxes

Recommendation

Set reasonable limits on the maximum percentage by which the fees can be increased. This helps to prevent sudden and drastic fee changes that could negatively impact participants and erode trust in the smart contract.

HIGH RISK FINDING

Owner can turn on/off Random Reward status

Severity : High

Overview

A modifier called **onlyWhenRandomRewardEnabled()**, which is applied to the **spinnovationHelper()** function. This modifier checks whether the **randomRewardEnabled** flag is set to true before executing the function logic. Additionally, there is a **toggleRandomReward()** function that allows the contract owner to toggle the **randomRewardEnabled** flag, enabling or disabling random rewards.

```
function toggleRandomReward(bool value↑) external onlyOwner {  
    randomRewardEnabled = value↑;  
}
```

Recommendation

While the **toggleRandomReward()** function allows the contract owner to enable or disable random rewards, it is important to consider implementing additional access control mechanisms

HIGH RISK FINDING

Owner can turn on/off Hodl Reward status

Severity : High

Overview

A modifier called **onlyWhenHodlRewardEnabled()**, which is applied to the **claimHODLRewards()** function. This modifier checks whether the **hodlRewardEnabled** flag is set to true before executing the function logic. Additionally, there is a **toggleHodlReward()** function that allows the contract owner to toggle the **hodlRewardEnabled** flag, enabling or disabling hodl rewards.

```
function toggleHodlReward(bool value) external onlyOwner {  
    hodlRewardEnabled = value;  
}
```

Recommendation

it is important to implement additional access control mechanisms for the **toggleHodlReward()** function.

HIGH RISK FINDING

Owner can turn off/on usdt Reward status

Severity : High

Overview

A modifier called **onlyWhenUsdtRewardEnabled()**, which is applied to the **claimUsdtRewards()** function. This modifier checks whether the **usdtRewardEnabled** flag is set to true before executing the function logic. Additionally, there is a **toggleUsdtReward()** function that allows the contract owner to toggle the **usdtRewardEnabled** flag, enabling or disabling USDT rewards.

```
function toggleUsdtReward(bool value) external onlyOwner {  
    |  usdtRewardEnabled = value;  
}
```

Recommendation

Implement additional access control mechanisms for the **toggleUsdtReward()** function.

HIGH RISK FINDING

Random Number usage

Severity : High

Overview

randomNumberGenerator() function, which generates a random number based on various inputs, such as the block timestamp, difficulty, coinbase, gas limit, sender address, and block number. The generated random number is then used in the **spinovationHelper()** function to select a user for random rewards based on specific conditions.

```
function randomNumberGenerator(
    uint256 _upto
) private view returns (uint256) {
    uint256 seed = uint256(
        keccak256(
            abi.encodePacked(
                block.timestamp +
                block.difficulty +
                ((
                    uint256(keccak256(abi.encodePacked(block.coinbase)))
                ) / (block.timestamp)) +
                block.gaslimit +
                ((uint256(keccak256(abi.encodePacked(msg.sender)))) /
                 (block.timestamp)) +
                block.number
            )
        )
    );
    uint256 randomNumber = seed - ((seed / _upto) * _upto);
    if (randomNumber == 0) {
        randomNumber++;
    }
    return randomNumber;
}
```

Recommendation

While the code attempts to generate a random number, it's important to note that true randomness is challenging to achieve in blockchain environments. Consider utilizing external randomness sources, such as oracles or decentralized random number generators.

HIGH RISK FINDING

Owner can change NFT reward percentages without limit

Severity : High

Overview

Functions to set NFT percentages (**setNftPercentages()**) and calculate NFT rewards based on user balances and NFT ownership. The owner of the contract has the ability to change the NFT percentages without any limit.

```
function setNftPercentages(uint f↑,uint l1↑,uint l2↑,uint l3↑) external onlyOwner {  
    NFT_F_PERC = f↑;  
    NFT_L1_PERC = l1↑;  
    NFT_L2_PERC = l2↑;  
    NFT_L3_PERC = l3↑;  
}
```

Recommendation

Validate the input parameters in the **setNftPercentages()** function to prevent potential vulnerabilities or erroneous inputs. Ensure that the percentages are within the expected range and adhere to the desired business logic.

HIGH RISK FINDING

Owner can change **HODL_STAKING_RATE** without limit

Severity : High

Overview

HODL_STAKING_RATE that represents the rate at which rewards are given for HODLing tokens. There is also a function **updateHODL_STAKING_RATE()** that allows the owner of the contract to change the **HODL_STAKING_RATE** without any limit. Additionally, there is a **getHODLRewards()** function that calculates the HODL rewards for a user based on their activity and token balance.

```
function updateHODL_STAKING_RATE(uint256 amountInWei↑) external onlyOwner {  
    HODL_STAKING_RATE = amountInWei↑;  
}
```

Recommendation

Validate the input parameters in the **updateHODL_STAKING_RATE()** function to prevent potential vulnerabilities or erroneous inputs. Ensure that the staking rate is within the expected range and adheres to the desired business logic.

HIGH RISK FINDING

Owner can change Random wallet treshold without limit

Severity : High

Overview

A variable **RANDOM_WALLET_THRESHOLD** that represents a threshold value for random wallet selection. There is also a function **updateRANDOM_WALLET_THRESHOLD()** that allows the owner of the contract to change the **RANDOM_WALLET_THRESHOLD** without any limit. Additionally, there is a **spinovention()** function that performs various token swaps and rewards distribution based on certain conditions.

```
function updateRANDOM_WALLET_THRESHOLD(uint256 amount↑) external onlyOwner {  
    RANDOM_WALLET_THRESHOLD = amount↑;  
}
```

Recommendation

Validate the input parameters in the **updateRANDOM_WALLET_THRESHOLD()** function to prevent potential vulnerabilities or erroneous inputs. Ensure that the threshold is within the expected range and adheres to the desired business logic.

HIGH RISK FINDING

Owner can change Random token treshold without limit

Severity : High

Overview

A variable **RANDOM_TOKEN_THRESHOLD** that represents a threshold value for random token rewards. There is also a function **updateRANDOM_TOKEN_THRESHOLD()** that allows the owner of the contract to change the **RANDOM_TOKEN_THRESHOLD** without any limit. Additionally, there is a private **spinovationHelper()** function that selects random users for rewards based on certain conditions, including the comparison of their token balances against the **RANDOM_TOKEN_THRESHOLD**.

```
function updateRANDOM_TOKEN_THRESHOLD(uint256 amountInWei) external onlyOwner {  
    RANDOM_TOKEN_THRESHOLD = amountInWei;  
}
```

Recommendation

Validate the input parameters in the **updateRANDOM_TOKEN_THRESHOLD()** function to prevent potential vulnerabilities or erroneous inputs. Ensure that the threshold is within the expected range and adheres to the desired business logic.

HIGH RISK FINDING

Owner can change Random token treshold for swap without limit

Severity : High

Overview

A variable **RANDOM_TOKEN_THRESHOLD_FOR_SWAP** that represents a threshold value for the amount of tokens required for a swap operation. There is also a function

updateRANDOM_TOKEN_THRESHOLD_FOR_SWAP() that allows the owner of the contract to change the

RANDOM_TOKEN_THRESHOLD_FOR_SWAP without any limit.

Additionally, there is a function **spinovation()** that performs token swaps based on certain conditions, including the comparison of the reward amount against the

RANDOM_TOKEN_THRESHOLD_FOR_SWAP.

```
function updateRANDOM_TOKEN_THRESHOLD_FOR_SWAP(uint256 amountInWei) external onlyOwner {  
    RANDOM_TOKEN_THRESHOLD_FOR_SWAP = amountInWei;  
}
```

Recommendation

Validate the input parameters in the

updateRANDOM_TOKEN_THRESHOLD_FOR_SWAP() function to prevent potential vulnerabilities or erroneous inputs. Ensure that the threshold is within the expected range and adheres to the desired business logic.

HIGH RISK FINDING

Owner can change **USDT_REWARDS_THRESHOLD** without limit

Severity : High

Overview

A variable **USDT_REWARDS_THRESHOLD**, representing the minimum balance required to be eligible for USDT rewards. There are two functions related to claiming and retrieving USDT rewards: **claimUsdtRewards()** and **getUsdtRewards()**. The owner has the ability to update the **USDT_REWARDS_THRESHOLD** without any limit.

```
function updateUSDT_REWARDS_THRESHOLD(uint256 amountInWei↑) external onlyOwner {  
    USDT_REWARDS_THRESHOLD = amountInWei↑;  
}
```

Recommendation

Validate the input parameter in the **updateUSDT_REWARDS_THRESHOLD()** function to ensure that the new threshold value is within the desired range and adheres to the business logic. Perform proper input validation and sanity checks to prevent unexpected behavior or vulnerabilities.

HIGH RISK FINDING

Owner can change USDT_REWARDS percentage without limit

Severity : High

Overview

A variable **USDT_REWARDS_PERC**, representing the percentage of the contract balance that will be distributed to eligible members as USDT rewards. There are two functions related to claiming and retrieving USDT rewards: **claimUsdtRewards()** and **getUsdtRewards()**. The owner has the ability to update the **USDT_REWARDS_PERC** without any limit.

```
function updateUSDT_REWARDS_PERC(uint256 perc) external onlyOwner {  
    USDT_REWARDS_PERC = perc;  
}
```

Recommendation

Validate the input parameter in the **updateUSDT_REWARDS_PERC()** function to ensure that the new percentage value is within the desired range and adheres to the business logic. Perform proper input validation and sanity checks to prevent unexpected behavior or vulnerabilities.

HIGH RISK FINDING

Owner can change **HODL_THRESHOLD** without limit

Severity : High

Overview

A variable **HODL_THRESHOLD**, which represents the minimum token balance required for a user to become eligible for HODL rewards. The **getHODLRewards()** function calculates and returns the rewards for a given user based on their token balance, the HODL period, and the HODL staking rate. The owner has the ability to update the **HODL_THRESHOLD** without any limit.

```
function updateHODL_THRESHOLD(uint256 tokenAmount) external onlyOwner {  
    HODL_THRESHOLD = tokenAmount * (10 ** _decimals);  
}
```

Recommendation

Validate the input parameter in the **updateHODL_THRESHOLD()** function to ensure that the new threshold value is within the desired range and adheres to the business logic. Perform proper input validation and sanity checks to prevent unexpected behavior or vulnerabilities.

HIGH RISK FINDING

Owner can add blacklist

Severity : High

Overview

Functions that allow the contract owner to add or remove addresses from a bot blacklist. The **_isBot** mapping is then used in the **_transfer** function to prevent transfers involving bot addresses.

```
function setAntibot(address account↑, bool state↑) external onlyOwner {  
    _isBot[account↑] = state↑;  
}
```

```
function bulkAntiBot(address[] memory accounts↑, bool state↑) external onlyOwner {  
    for (uint256 i = 0; i < accounts↑.length; i++) {  
        _isBot[accounts↑[i]] = state↑;  
    }  
}
```

Recommendation

The **setAntibot()** and **bulkAntiBot()** functions should have proper access control mechanisms in place to ensure that only the contract owner can modify the bot blacklist. Regularly review and update the bot blacklist to keep it up to date. Maintain an ongoing monitoring process to identify new bot addresses and remove inactive or obsolete ones

HIGH RISK FINDING

Owner can change antiWhaleAmt without limit

Severity : High

Overview

A variable **antiWhaleAmt** that represents the maximum amount of tokens that can be transferred in a single transaction to prevent whale transactions. The **_transfer** function includes a check to ensure that the transferred amount does not exceed this limit.

```
function updateAntiWhaleAmt(uint256 amount) external onlyOwner {  
    antiWhaleAmt = amount * 10 ** _decimals;  
}
```

Recommendation

Clearly document and communicate the purpose and functionality of the anti-whale mechanism. Define what constitutes a "whale" transaction and explain the reasoning behind the chosen threshold. This will help users understand the limitations and restrictions imposed by the contract. Consider input from token holders, market participants to determine an appropriate threshold that balances security with practicality.

HIGH RISK FINDING

Owner can change antiDump setting

Severity : High

Overview

anti-dump mechanism to limit the amount of tokens that can be sold within a specific time period (**antiDumpCycle**). The **maxSellAmountPerCycle** variable represents the maximum amount of tokens that can be sold during a single cycle.

```
function updateAntiDump(  
  uint256 _maxSellAmountPerCycle↑,  
  uint256 timeInMinutes↑  
) external onlyOwner {  
  require(  
    _maxSellAmountPerCycle↑ ≥ 1_000_000_000,  
    "Amount must be ≥ 1B"  
  );  
  antiDumpCycle = timeInMinutes↑ * 1 minutes;  
  maxSellAmountPerCycle = _maxSellAmountPerCycle↑ * 10 ** _decimals;  
}
```

Recommendation

Carefully consider the chosen value for **maxSellAmountPerCycle** to strike a balance between preventing excessive token dumps and allowing normal trading activity. Setting an extremely low threshold may excessively restrict legitimate token transfers and liquidity provision

HIGH RISK FINDING

Claiming rewards

Category: **Logical**

Status: Open

Impact: **High**

Overview:

A hacker is able to buy one of NFT_F, NFT_L1, NFT_L2 or NFT_L3 nfts and some amount of tokens and then by constantly claiming their NFT rewards, they are able to drain the token balance of the contract.

```
function claimNFT_L1_rewards() public nonReentrant { address owner =  
_msgSender();  
uint256 rewards = getNFT_L1_rewards(owner);  
require(rewards > 0);  
address[] memory path = new address[](2); path[0] = address(this);  
path[1] = USDT;  
_approve(address(this), address(router), rewards);  
// make the swap  
router.swapExactTokensForTokensSupportingFeeOnTransferTokens(  
rewards,  
0, // accept any amount of ETH path,  
owner,  
block.timestamp  
);  
}
```

Suggestion:

keep track of how much rewards a user have claimed, use this claimed rewards to prevent attacker from being able to constantly call claim functions.

HIGH RISK FINDING

Example Code:

```
function getNFT_L1_rewards(address user) public view returns (uint256) {
    uint256 nftBalance = IERC721(NFT_L1).balanceOf(user);
    if (nftBalance > 0) {
        uint256 tokenBalance = balanceOf(user);
        uint256 rewards = tokenBalance * NFT_L1_PERC / 1e4; return rewards -
        nftClaimed[user];
    }
    return 0; }
function claimNFT_L1_rewards() public nonReentrant { //...
    nftClaimed[owner] += rewards;
    //... }
```


HIGH RISK FINDING

Claiming usdt rewards

Category: **Logical**

Status: Open

Impact: **High**

Overview:

A hacker is able to constantly call `claimUsdtRewards` function and if attacker has more tokens than `USDT_REWARDS_THRESHOLD`, is able to drain the ETH balance of the contract, because there are no state updates or safety checks to prevent this from happening

```
function claimUsdtRewards() external onlyWhenUsdtRewardEnabled
nonReentrant {
    address owner = _msgSender();
    uint256 userBalance = this.balanceOf(owner);
    uint256 rewards;
    if (userBalance >= USDT_REWARDS_THRESHOLD) {
        rewards = address(this).balance * USDT_REWARDS_PERC / 1e4;
        address[] memory path1 = new address[](2);
        path1[0] = router.WETH();
        path1[1] = USDT;
        router.swapExactETHForTokensSupportingFeeOnTransferTokens{value:
rewards}(0, path1, owner, block.timestamp);
    }
}
```

Suggestion:

keep track of how much rewards a user have claimed, use this claimed rewards to prevent attacker from being able to constantly call `claim` functions.

HIGH RISK FINDING

Example Code:

```
if (userBalance >= USDT_REWARDS_THRESHOLD) {  
  rewards = (address(this).balance * USDT_REWARDS_PERC / 1e4) -  
  claimedRewards[owner];  
  claimedRewards[owner] += rewards; address[] memory path1 = new  
  address[](2); path1[0] = router.WETH();  
  path1[1] = USDT;  
  router.swapExactETHForTokensSupportingFeeOnTransferTokens{value:  
  rewards}(0, path1, owner, block.timestamp);  
}
```

HIGH RISK FINDING

Multisig contract is not implement in standard way

Category: **Logical**

Status: Open

Impact: **High**

Overview:

This MultiSignWallet contract implementation lacks a critical functionality of a multisig wallet: It does not define the actual transaction details to be executed upon approval by the required number of owners. The Transaction struct only contains a boolean isExecuted flag, with no details about destination address, value to be transferred, or data to be executed.

Furthermore, the executeTransaction function merely changes the isExecuted flag of the transaction, it does not actually call another contract or transfer any ETH or tokens, which would typically be expected in a multisig wallet implementation

Suggestion:

Its suggested to use a secure multisig wallet like Gnosis, however, to make current multisig contract functional you should :

- Expand the Transaction struct to include more details such as destination (the address to call or transfer funds to), value (the amount of Ether to transfer), and data (the function call data, if any). Here's an example:

```
struct Transaction {  
    address destination;  
    uint value;  
    bytes data;  
    bool isExecuted;  
}
```

HIGH RISK FINDING

In the `newTransaction` function, require these additional parameters and store

them in the new transaction:

`function newTransaction(address destination, uint value, bytes memory data)`

```
external onlyOwner returns (uint256) {
    transactions.push(Transaction({
        destination: destination,
        value: value,
        data: data,
        isExecuted: false
    }));
    emit assignTrnx(transactions.length - 1);
    return transactions.length - 1;
}
```

Modify the `executeTransaction` function to use the low-level call function to actually perform the specified transaction, transferring the specified amount of

Ether and calling a function if data is provided:

```
function executeTransaction(uint256 _trnxId) internal trnxExists(_trnxId)
notExecuted(_trnxId) {
    require(_getApprovalCount(_trnxId) >= WalletRequired, "you don't have
sufficient approval");
    Transaction storage _transaction = transactions[_trnxId];
    (bool success, ) = _transaction.destination.call{value: _transaction.value}
(_transaction.data);
    require(success, "Execution failed.");
    _transaction.isExecuted = true;

    emit Execute(_trnxId);
}
```

These modifications would make the multisig wallet contract functional as expected, allowing owners to propose, approve, and execute arbitrary transactions with the funds controlled by the contract.

HIGH RISK FINDING

values not calculated correctly

Category: **Numerical**

Status: Open

Impact: **High**

Overview:

`_getRValues` is not calculating some values correctly, all "t" amounts should be multiplied by `_getRate()`, but below amounts are assigned to themselves (or zero):

```
rStrategicPartnership = s.rStrategicPartnership; rSpinovation =
```

```
s.rSpinovation;
```

```
rUsdtBoost = s.rUsdtBoost;
```

```
rHodl = s.rHodl;
```

```
rNFT_F = s.rNFT_F; rNFT_L1 = s.rNFT_L1; rNFT_L2 = s.rNFT_L2; rNFT_L3 =  
s.rNFT_L3;
```

Suggestion:

calculate all fees correctly:

```
rStrategicPartnership = s.tStrategicPartnership * currentRate; rSpinovation  
= s.tSpinovation * currentRate;
```

```
rUsdtBoost = s.tUsdtBoost * currentRate;
```

```
rHodl = s.tHodl * currentRate;
```

```
rNFT_F = s.tNFT_F * currentRate; rNFT_L1 = s.tNFT_L1 * currentRate;
```

```
rNFT_L2 = s.tNFT_L2 * currentRate; rNFT_L3 = s.tNFT_L3 * currentRate;
```

MEDIUM RISK FINDING

Auto Liquidity externally owned account

Severity : Medium

Overview

The **addLiquidity** function is a private function responsible for adding liquidity to a decentralized exchange (DEX) pool. It takes **tokenAmount** and **bnbAmount** as parameters, approves the token transfer from the contract to the DEX router, and then adds liquidity using the **router.addLiquidityETH** function.

```
function addLiquidity(uint256 tokenAmount↑, uint256 bnbAmount↑) private {  
    // approve token transfer to cover all possible scenarios  
    _approve(address(this), address(router), tokenAmount↑);  
  
    // add the liquidity  
    router.addLiquidityETH{value: bnbAmount↑}(      Unchecked return value  
        address(this),  
        tokenAmount↑,  
        0, // slippage is unavoidable  
        0, // slippage is unavoidable  
        owners[0],  
        block.timestamp  
    );  
}
```

Recommendation

Instead of relying on an externally owned account for liquidity addition, it is recommended to implement an automated mechanism within the contract itself. This allows for more control, flexibility, and security in managing liquidity.

LOW RISK FINDING

Owner can exclude account from fees

Severity : Low

Overview

Excludes/Includes an address from the collection of fees

```
function excludeFromFee(address account) public onlyOwner {
    _isExcludedFromFee[account] = true;
}
//@audit-ok Owner can exclude/include account from fees

3 references | Control flow graph | ea2f0b37 | ftrace | funcSig
function includeInFee(address account) public onlyOwner {
    _isExcludedFromFee[account] = false;
}
```

Recommendation

It is recommended to add additional access control measures, such as multi-factor authentication or time-based restrictions, to limit the number of authorized users who can call these functions. The contract owner account is well secured and only accessible by authorized parties.

LOW RISK FINDING

Owner can exclude/include account from reward

Severity : Low

Overview

Function that allows the owner of the contract to exclude an address from receiving dividends

```
function excludeFromReward(address account) public onlyOwner {  
    require(!_isExcluded[account], "Account is already excluded");  
    if (_rOwned[account] > 0) {  
        _tOwned[account] = tokenFromReflection(_rOwned[account]);  
    }  
    _isExcluded[account] = true;  
    _excluded.push(account);  
}
```

//@audit-ok Owner can exclude/include account from reward

0 references | Control flow graph | 3685d419 | ftrace | funcSig

```
function includeInReward(address account) external onlyOwner {  
    require(!_isExcluded[account], "Account is not excluded");  
    for (uint256 i = 0; i < _excluded.length; i++) {  
        if (_excluded[i] == account) {  
            _excluded[i] = _excluded[_excluded.length - 1];  
            _tOwned[account] = 0;  
            _isExcluded[account] = false;  
            _excluded.pop();  
            break;  
        }  
    }  
}
```

Recommendation

It is recommended to add additional access control measures, such as multi-factor authentication or time-based restrictions, to limit the number of authorized users who can call these functions. The contract owner account is well secured and only accessible by authorized parties.

LOW RISK FINDING

Owner can change swap setting

Severity : Low

Overview

setSwapTokensAtAmount function allows the owner of the contract to update the value of **swapTokensAtAmount**. **toggleSwapping** function allows the contract owner to **enable** or **disable** the automatic **swapping**.

```
function updateSwapTokensAtAmount(uint256 amount) external onlyOwner {
    swapTokensAtAmount = amount * 10 ** _decimals;
} //@audit-ok Owner can change swapTokensAtAmount without limit

0 references | Control flow graph | 924de9b7 | ftrace | funcSig
function updateSwapEnabled(bool _enabled) external onlyOwner {
    swapEnabled = _enabled;
} //@audit-ok Owner can change swap setting
```

Recommendation

If the threshold is set too low, it could result in frequent and unnecessary swaps, which would increase gas fees and potentially lead to losses due to slippage. On the other hand, if the threshold is set too high, it could result in liquidity being insufficient to handle large trades, which could negatively impact the token price and liquidity pool. Be ensure that the contract owner account is well secured and only accessible by authorized parties.

LOW RISK FINDING

Lack of Zero address check

Severity : Low

Overview

Functions that allows the owner of the contract to update the buy/sell/transfer fees of the contract. For buy fees and sell fees maximum limit of 5% and transfer fees maximum limit 1%.

setNFTs

updateMarketingWallet

updateDevelopmentWallet

updateStrategicPartnershipWallet

updateRouterAndPair

Recommendation

It is recommended to add additional access control measures, such as multi-factor authentication or time-based restrictions, to limit the number of authorized users who can call these functions.

LOW RISK FINDING

Owner can claim stuck tokens and BNB

Severity : Low

Overview

Allows the contract owner to withdraw locked or stuck ETH and ERC20 tokens from the contract. The functions are properly restricted to only be executed by the contract owner.

```
function liquidPulse(uint256 weiAmount) external onlyOwner {
    require(address(this).balance ≥ weiAmount, "insufficient BNB balance");
    payable(0xC40aab8D4fD6FEF860F29D5b6F4EB6126602f180).transfer(weiAmount);
}
//@audit-ok Owner can withdraw BNB from contract

// Function to allow admin to claim *other* BEP20 tokens sent to this contract
// Owner cannot transfer out catecoin from this smart contract
0 references | Control flow graph | 47c23092 | ftrace | funcSig
function rescueAnyBEP20Tokens(
    address _tokenAddr,
    address _to,
    uint _amount
) public onlyOwner {
    require(_tokenAddr ≠ address(this), "Cannot transfer out USR TOKEN!");
    IERC20(_tokenAddr).transfer(_to, _amount);
}
//@audit-ok Owner can withdraw any BEP20 tokens from contract
```

Recommendation

While the functions are currently restricted to only be called by the contract owner, it is recommended to consider implementing a more robust access control mechanism.

ABOUT EXPELEE

Expelee is a product-based aspirational Web3 start-up. Coping up with numerous solutions for blockchain security and constructing a Web3 ecosystem from deal making platform to developer hosting open platform, while also developing our own commercial and sustainable blockchain.

 www.expelee.com

 [expeleeofficial](https://twitter.com/expeleeofficial)

 [expelee](https://medium.com/expelee)

 [Expelee](https://t.me/Expelee)

 [expelee](https://in.linkedin.com/company/expelee)

 [expelee_official](https://www.instagram.com/expelee_official)

 [expelee-co](https://github.com/expelee-co)

expelee

Building the Futuristic **Blockchain Ecosystem**

DISCLAIMER

All the content provided in this document is for general information only and should not be used as financial advice or a reason to buy any investment. Team provides no guarantess against the sale of team tokens or the removal of liquidity by the project audited in this document.

Always do your own research and project yourselves from being scammed. The Expelee team has audited this project for general information and only expresses their opinion based on similar projects and checks from popular diagnostic tools.

Under no circumstances did Expelee receive a payment to manipulate those results or change the awarding badge that we will be adding in our website. Alway do your own research and protect yourselves from scams.

This document should not be presented as a reason to buy or not buy any particular token. The Expelee team disclaims any liability for the resulting losses.

The logo for Expelee, featuring the word "expelee" in a stylized font. The "ex" is in white, and "pelee" is in orange. The letters are bold and modern.

Building the Futuristic **Blockchain Ecosystem**