

801 T-USB testing board


This testing board hosts the 801 T-USB daughter board.

The 801 is a bridge board that connects daughter boards. 801 T-USB is one such daughter board.

The T-USB daughterboard has two functions

- Supply the system with power
- Provide data signals in the system over two USB-C connectors

The T-USB board exposes two vertical USB-C sockets and connects to the carrier board through two 50 pin B2B connectors. These are routed ultimately through two USB-C connectors on testing board



Board Components

- 2 * [Hirose DF40-50DS-0.4V](#) mated height 1.5mm [Mouser](#) - [JLCPCB](#) socket
- 2 * [HD3SS3220 10-Gbps USB 3.1 Type-C 2:1 mux with DRP Controller](#) [Mouser](#)
- 2 * USB-C connectors [DX07S024JA1R1300](#) or [DX07S024JJ2R1300](#) - [Mouser](#) -
- 3 * [Samtec TSW-116-14-T-S Header 16 pin](#) - [Mouser](#)

Open notes

Step up voltage 3.5V -> 5V

Testing staged power and data enable when plugging in the module.


Chip enable when plugged in. 100ms delay.

Testing with the board

Testing cases

- Routing UART over breakout connectors
- VSOM load test
- Interrupt triggering
- Requesting system standby
- Detecting system standby
- Triggering system reset
- Detecting system reset
- Powering dev board from T-USB power output
- Simulating CONN_EN signal
- High voltage USB-C (20V / 12V / 9V) power supplies never produces more than 5V SYS_PWR when connected.
- If one USB port receives power (5V) the other port can deliver power (5V).
- VSOM is 3.45V to 4.4V regardless of charger
- If a Apple Dedicated Charger 5V(1A BC1.2) is connected the board can draw 1A
- If a CDP(5V, 1A) compatible charger is connected the board can draw 1A
- If a CDP(5V, 3A) compatible charger is connected the board can draw 3A
- If power is connected to USB the battery can charge
- If no power is connected the system is battery powered
- USB 3.0 data signal can be passed through from T-USB OTG to testing board OTG, and reverse min. 250MB/sec
- USB 3.0 data signal can be passed through from T-USB Host to testing board Host, and reverse min. 250MB/sec
- USB 2.0 data signal can be passed through from T-USB OTG to testing board OTG, and reverse min. 35MB/sec
- USB 2.0 data signal can be passed through from T-USB Host to testing board Host, and reverse min. 35MB/sec
- Power and Data works through T-USB ports with 300 cm cable length.
- USB signal jitter within accepted range (see USB 3.0 Electrical Compliance Methodology)

Sample USB 3.0 data rates



Ideal testing equipment for USB 3.0 are [Loopback Plugs](#).

DIP switches

To test cases a bank of 8 DIP switches allow enabling features

- 4 * CONN_EN high/low/disconnected
- BAT_CE# - Disable or disconnected
- PD_VIN_EN - Enabled or disconnected
- SPI_3V3 - Enable power to SPI memory, connect to LDO_3V3

LEDs


LEDs will test specific situations and test cases

- Battery STAT (BAT_STAT - BAT_LDO)
- Battery power good (PWR_CHARGE above 4.3V)
- VSOM power on
- VSOM voltage >4.5V
- VCC_RTC power on
- Power on Reset POR_B_3P3
- System reset mode
- System powering down

Connecting the Board

Signals passed to USB-C connectors

The signals from the USB-C connectors are routed through a Ti HD3SS3220 to handle polarity of the plug.



50 pins for PD Controller -> Dev Board P20

Pin	Code	Type	Details	Voltage	Misc
-----	------	------	---------	---------	------

Pin	Code	Type	Details	Voltage	Misc
48	UART1_TXD	UART	P1.72 UART1 Tx		P20.9
47	UART1_RXD	UART	P1.19 UART1 Rx		P20.11
46	UART2_TXD	UART	UART2 Tx		P20.1
45	UART2_RXD	UART	UART2 Rx		P20.3
44	UART3_TXD	UART	P1.61 UART3 Tx		P20.2
43	UART3_RXD	UART	P1.21 UART3 Rx		P20.4
42	UART4_TXD	UART	UART4 Tx		P20.8
41	UART4_RXD	UART	UART4 Rx		P20.10
38	I2C3_SCL	I2C	Stem SCL		P21.2 ?
37	I2C3_SDA	I2C	Stem SDA		P21.4 ?
13	EX_OH_nINT	IRQ	Interrupt signal (GPIO1_IO0)		P20.12
14	EX_T_nINT	IRQ	Interrupt signal (GPIO1_IO1).		P20.14
	GND	Power	Ground		

50 pins for PD Controller -> Dev Board P21 + direct connects

Pin	Code	Type	Details	Voltage	Misc
40	I2C_SCL	I2C	P1.99 SYS SCL		P21.7
39	I2C_SDA	I2C	P1.97 SYS SDA		P21.5
12	EX0_nINT	IRQ	Interrupt signal (GPIO4_IO19)		P21.30
20	VCC_RTC	Power	Low power mode supply		
21	PWRBTN	Boot	Power button trigger		
22	ALT_BOOT	Boot	Alternate boot		
23	QSPI_BOOT_EN_3P3	Boot	SPI boot		P21.18
	GND	Power	Ground		

50 pins for PD Controller -> Dev Board P10

Pin	Code	Type	Details	Voltage	Misc
16	SYS_RST_PMIC	Reset	PMIC reset input pin. Internally pulled up with LDO1 power rail. Once low, PMIC performs reset.		P10.9
17	POR_B_3P3	Reset	Power On reset output pin. Open drain output requiring external pull up resistor.		P10.7

Pin	Code	Type	Details	Voltage	Misc
18	PMIC_ON_REQ	Reset	PMIC ON input from Application processor. When high, the device starts power on sequence.		P10.5
19	PMIC_STBY_REQ	Reset	Standby mode input from Application processor. When high, device enters STANDBY mode.		P10.3
	GND	Power	Ground		

These pins are from both 50 pins connectors reflecting the connector insertion corner pins

Pin	Code	Type	Details	Voltage	Misc
1	CONN_EN	Enable	Signal + / GND to inform the T-USB board of being connected		
1	CONN_EN	Enable	Signal + / GND to inform the T-USB board of being connected		
26	CONN_EN	Enable	Signal + / GND to inform the T-USB board of being connected		
26	CONN_EN	Enable	Signal + / GND to inform the T-USB board of being connected		
11	VSOM	Power	Main power for board 3.45V - 4.5V		
49	GND	Power	Ground		

Breakout of Charging Signals

From 50 pins for PD Controller as a 16 pins header

Pin	Code	Type	Details	Voltage	Misc
9	SWD_CLK	Debug	PD Controller GPIO12		
10	SWD_DAT	Debug	PD Controller GPIO13		
33	SPI_CS	PD	Programming/External flash directly	3.3V	
32	SPI_CLK	PD	Programming/External flash directly	3.3V	
31	SPI_MISO	PD	Programming/External flash directly	3.3V	
30	SPI_MOSI	PD	Programming/External flash directly	3.3V	
24	BAT_CE#	Charger	Charge Enable Active-Low Input. Connect to a high logic level to place the battery charger in standby mode.		
24	PWR_CHARGE	Power	Internal charging power		

Pin	Code	Type	Details	Voltage	Misc
25	PD_VIN_EN		Enable VIN_5V/3V3 from PWR_SYS (TBD)		
29	VIN_3V3		Supply for TPS64988 circuitry and I/O. Current 50 mA	3.3V	
34	SPI_3V3	Power	Power to the flash chip. Bridge connects to VIN_3V3	3.3V	
28	VIN_5V	Power	System 5V power source (PPHV1, PPHV2, PP1_CABLE, PP2_CABLE). 500 mA.	5V	
29	VSOM	Power	Main power for board 3.45V - 4.5V		
50	VSOM	Power	Main power for board 3.45V - 4.5V		
49	GND	Power	Ground		
49	GND	Power	Ground		

Signals **NOT** connected on 50 pin connectors

Pin	Code	Type	Details	Voltage
50	LVCLK+	LVDS	LVDS CLK+	
49	LVCLK-	LVDS	LVDS CLK-	
47	LVD0+	LVDS	LVDS D0+	
46	LVD0-	LVDS	LVDS D0-	
44	LVD1+	LVDS	LVDS D1+	
43	LVD1-	LVDS	LVDS D1-	
41	LVD2+	LVDS	LVDS D2+	
40	LVD2-	LVDS	LVDS D2-	
38	LVD3+	LVDS	LVDS D3+	
37	LVD3-	LVDS	LVDS D3-	

Yet to plan ...

One side

| 14 | T_USB_O_ALT_EN | AltMode | Exposed EX3 || | 15 | T_USB_O_ALT_POL | AltMode | Exposed EX3 || | 16 | T_USB_O_ALT_AMSEL | AltMode | Exposed EX3 || | 17 | T_USB_H_ALT_EN | AltMode | Exposed EX3 || | 18 | T_USB_H_ALT_POL | AltMode | Exposed EX3 || | 19 | T_USB_H_ALT_AMSEL | AltMode | Exposed EX3 || | 20 | GND | Power | Ground || | 21 | || || || | 23 | || || || | 24 | || || |

TODO remove EX3 exposure