

Infected Ip address: 10.1.17.255

Reason: I was able to find this out by filtering out the IP address of the one our lan range and our domain controller which helped filter out the result making it so there aren't many repeating IP from our own domain

No.	Time	Source	Destination	Protocol	Length	Info
1560	29.683215	10.1.17.215	224.0.0.251	MDNS	82	Standard query 0x0000 PTR _googlecast._tcp.local, "QM" question
1648	30.683998	10.1.17.215	224.0.0.251	MDNS	82	Standard query 0x0000 PTR _googlecast._tcp.local, "QM" question
2230	32.686785	10.1.17.215	224.0.0.251	MDNS	82	Standard query 0x0000 PTR _googlecast._tcp.local, "QM" question
2340	33.697475	10.1.17.215	224.0.0.251	MDNS	82	Standard query 0x0000 PTR _googlecast._tcp.local, "QM" question
7097	66.666714	10.1.17.212	142.250.116.155	TLSv1.3	432	Client Hello (SNI=googlecast.berleson-appliance.net)
7164	67.004764	10.1.17.215	142.250.186.106	TLSv1.3	431	Client Hello (SNI=www.google.com)
22236	901.281347	10.1.17.215	142.250.115.101	TLSv1.3	423	Client Hello (SNI=clients2.google.com)
22571	902.192295	10.1.17.215	142.250.115.139	TLSv1.3	423	Client Hello (SNI=clients2.google.com)

Mac Address: 00:d0:b7:26:4a:74

Reason: I was able to find this through a packet between the infected ip address trying to communicate with another IP.


```

▼ Ethernet II, Src: Intel_26:4a:74 (00:d0:b7:26:4a:74), Dst: Cisco_c2:3a:46 (08:d0:9f:c2:3a:46)
  ▼ Destination: Cisco_c2:3a:46 (08:d0:9f:c2:3a:46)
    .... ..0. .... = LG bit: Globally unique address (factory default)
    .... ..0. .... = IG bit: Individual address (unicast)
  ▼ Source: Intel_26:4a:74 (00:d0:b7:26:4a:74)
    .... ..0. .... = LG bit: Globally unique address (factory default)
    .... ..0. .... = IG bit: Individual address (unicast)

```

Host name: DESKTOP-L8C5GSJ


Reason: I found a query providing the information for the host name



No.	Time	Source	Destination	Protocol	Length	Info
9	0.015595	10.1.17.215	224.0.0.252	LLMNR	75	Standard query 0xceec ANY DESKTOP-L8C5GSJ
19	0.079719	10.1.17.215	10.1.17.255	NBNS	110	Registration NB DESKTOP-L8C5GSJ<00>
20	0.079719	10.1.17.215	10.1.17.255	NBNS	110	Registration NB DESKTOP-L8C5GSJ<20>
21	0.079896	10.1.17.215	10.1.17.255	NBNS	110	Registration NB BLUEMOONTUESDAY<00>
36	0.425427	10.1.17.215	224.0.0.252	LLMNR	75	Standard query 0xceec ANY DESKTOP-L8C5GSJ

User account: shutchenson

Reason: I filtered using the command `Kerberos.CNameString` which then I was able to go into the `tcp` stream and get the name.



Wireshark - Follow TCP Stream (tcp.stream eq 7) - TASK 7.pcap

...j...0...
 ...0...0...0...0...0...0...0...0...
 .shutchenson...BLUemoontuesday.\$0"...0...krbtgt...BLUemoontuesday...21000913024805Z...21000913024805Z...30&...0...0...
 ...DESKTOP-L8C5GSJ...
 ...20250122194509Z...BLUemoontuesday.\$0"...0...krbtgt...BLUemoontuesday.b...0^0;...4.2000...
 ...BLUemoontuesday.comshutchenson0...0...0...0...

Fake domain name: google-authenticator.burleson-appliance.net

Reason: I filter out the frame contains to google since in the task it said that he had the issue after clicking a fake google download so I was able to figure out that the name for the file was indeed google but at the end is the true link name of the files which was Burleson-appliance.net which had been downloaded instead.

ip.addr == 10.1.17.0/24 and !ip.addr == 10.1.17.2) && frame contains "google"						
No.	Time	Source	Destination	Protocol	Length	Info
1560	29.683215	10.1.17.215	224.0.0.251	MDNS	82	Standard query 0x0000 PTR _googlecast._tcp.local, "QM" question
1648	30.683998	10.1.17.215	224.0.0.251	MDNS	82	Standard query 0x0000 PTR _googlecast._tcp.local, "QM" question
2230	32.686705	10.1.17.215	224.0.0.251	MDNS	82	Standard query 0x0000 PTR _googlecast._tcp.local, "QM" question
2342	38.310760	10.1.17.215	104.21.64.1	TLSv1.3	491	Client Hello (SNI=google-authenticator.burleson-appliance.net)
7007	66.760171	10.1.17.215	142.251.116.155	TLSv1.3	431	Client Hello (SNI=googleads.g.doubleclick.net)
7164	67.004764	10.1.17.215	142.251.186.106	TLSv1.3	482	Client Hello (SNI=www.google.com)
22236	901.281347	10.1.17.215	142.250.115.101	TLSv1.3	423	Client Hello (SNI=clients2.google.com)
22571	902.192295	10.1.17.215	142.250.115.139	TLSv1.3	423	Client Hello (SNI=clients2.google.com)

C2 server: 5.252.153.241

Reason: I see that a ip was trying to download a file after the hacking had occurred 32 seconds in and this one had occurred 30 seconds after the fact the victim got hacked so the chances that the get files is a malware is most likely.

5028	60.135270	10.1.17.215	5.252.153.241	TCP	60	50143 → 80 [SYN] Seq=0 Win=65535 Len=0 MSS=1460 WS=256 SACK_PERM
5030	60.297535	10.1.17.215	5.252.153.241	TCP	60	50143 → 80 [ACK] Seq=1 Ack=1 Win=262144 Len=0
5031	60.297799	10.1.17.215	5.252.153.241	HTTP	371	GET /api/file/get-file/264872 HTTP/1.1
5034	60.464797	10.1.17.215	5.252.153.241	TCP	60	50143 → 80 [ACK] Seq=318 Ack=766 Win=261376 Len=0
5035	60.525110	10.1.17.215	5.252.153.241	TCP	60	50143 → 80 [RST, ACK] Seq=318 Ack=766 Win=0 Len=0