
RESEARCH / STRATEGY REPORT

FROM SPACE-BASED SOLAR POWER TO A DYSON SWARM

Technical bottlenecks, near-term startup opportunities, and the case for or against a physics PhD

ASSESSMENT DATE 09 NOVEMBER 2026



Core conclusion. The physics of solar collection and directed energy transfer is established. No commercial, utility-scale space-to-Earth power system exists, and a true Dyson swarm is many industrial revolutions beyond present capability. The most promising entrepreneurial path is to solve one economically valuable subsystem problem now; a PhD is useful only when a specific unresolved scientific question blocks that product.

Prepared as an independent research synthesis. Company announcements are distinguished from completed demonstrations; calculations are illustrative and state their assumptions.

01 / EXECUTIVE BRIEF

Decision summary

The term **Dyson swarm** describes many independently orbiting solar collectors intercepting a meaningful fraction of stellar radiation; it is different from a geostationary solar-power satellite serving the Earth grid. Both use familiar physical principles, but their manufacturing, orbital dynamics, heat rejection, resource and energy-distribution requirements differ by enormous orders of magnitude. [1, 17]



The commercially relevant metric is cost per usable watt at the receiver, not just transmitter output.

Assessment: The earliest commercial market is more plausibly **power delivered to spacecraft**, precision optical/RF power transmission hardware, or autonomy and fabrication tools than gigawatt-scale electricity to Earth. The jump from a measured beam to competitive utility power is a complete-system challenge, not a single missing scientific discovery. [1, 6, 10-13]

PhD decision rule. Pursue a PhD when the intended business needs genuine invention in materials, coherent array physics, or a scientifically uncertain transmission architecture. Pursue a startup or join an operating space firm when the limiting work is hardware integration, scaling, controls, qualifications, production, launch, customers and financing.

Five findings

- **Principle feasibility:** Solar PV, microwaves, lasers, phased arrays and orbital deployment all exist; their high-power integration at acceptable mass and cost remains unproven. [1-4]
- **Technology maturity:** Caltech beamed detectable power to Earth in 2023. Star Catcher and Cowboy Space launched test hardware in October 2026, but the reviewed sources do not establish continuing paid orbital energy operations. [2, 10, 12]
- **Cost:** NASA estimated $0.61 and $1.59/kWh for two illustrative 2050 2-GW designs, versus about $0.02-0.05/kWh for modeled terrestrial renewable alternatives. Improvements could change these outcomes; these are not market quotes. [1]
- **Scale:** At 1 AU, a notional swarm intercepting 1% of sunlight needs about 2.8×10^{21} m^2 of effective collecting area. The mass and production implications are profound. [17; illustrative calculation]
- **Founder strategy:** A low-capital software/control wedge followed by a terrestrial hardware demonstration can test a business before orbital flight; deep-space manufacturing belongs to a much later phase.

What evidence means in this report

Term	Interpretation
Demonstrated	A described test was performed; not evidence of commercially useful sustained output.
Announced / contracted	A company or regulator reports a plan, financing, agreement or authorization; performance may remain unproven.
Proposed / estimated	Conceptual designs, models or forward-looking targets rather than operational systems.

02 / What, exactly, is being built?

Three architectures often conflated

System	Primary energy user	Critical implementation difference
Earth-orbit solar power satellite	Terrestrial grid	Earth-orbit deployment; microwave/optical ground link; receiver and grid connection.
Orbital power network	Other spacecraft	Space-to-space beam control, customer tracking and power delivery; avoids terrestrial grid price benchmark.
Heliocentric Dyson swarm	Primarily space industry	Huge solar-interception area; autonomous orbital traffic, interplanetary logistics and off-Earth production.

A rigid spherical shell is not the preferred physical architecture. This report uses "Dyson swarm" for distributed free-flying collectors. Moving the collection system inward toward the Sun can increase incident irradiance, but also intensifies thermal and orbital challenges. [17]

System boundaries and externalities

A useful product metric is **electricity actually usable at a specified receiver, at a known total lifetime cost**. A high transmitter power rating says little about service viability unless energy capture, losses, pointing, availability, receiver area, and infrastructure are all included. The model should also include radio spectrum, radiation safety, operational liability, debris risk and environmental effects. [1, 6, 15]

> A Dyson swarm designed to intercept a substantial fraction of sunlight should **not** be designed to ship all captured power to Earth. Any net additional energy consumed on Earth ultimately becomes heat; enormous Dyson-swarm-scale deliveries would exceed planetary heat-balance limits. Very large future power demand would instead need to be located substantially in space.

03 / The breakthroughs still required

A. Coherent wireless transmission at useful power

Microwave rectennas and electronic beamforming are established; lasers can provide narrower diffraction-limited beams but create additional cloud, pointing, eye-safety and conversion concerns. The unsolved challenge is end-to-end efficiency with very large, flexible apertures under thermal distortion and orbital motion. Demonstrations must measure useful received DC output rather than merely detectable RF or optical signals. [1, 6]

For a uniformly illuminated circular transmitter, the first-null diffraction angle is approximately **theta = 1.22 lambda / D**; beam radius at distance R is approximately **r = 1.22 lambda R / D**. These are idealized estimates, not actual beam patterns from sparse arrays.

Illustrative aperture case	First-null beam radius
2.45 GHz; D = 1 km; GEO-to-ground range = 35,786 km	~5.3 km
2.45 GHz; 1 AU range; desired 10 km radius	Requires ~2,200 km diameter transmitter
Laser at 1 micron; 1 AU range; desired 10 km radius	Requires ~18 m diameter transmitter

The last two rows are thought experiments, not proposed satellite designs. Power and pointing quality, atmospheric effects, receiver architecture and safety constraints can dominate in practice.

Decision-relevant research questions

- Can modular, partially synchronized arrays maintain useful received power despite phase errors, motion, structural flexing and missing elements?
- What aperture topology minimizes cost and mass at a required receiver footprint and availability?
- Can beam termination, sidelobe suppression and receiver tracking be verified robustly for deployment approval?

B. Extremely lightweight, durable photovoltaic modules

Space-qualified III-V multi-junction cells are technologically mature, but price, radiation tolerance, packaging, interconnections and array-level specific power impose severe scale penalties. Laboratory device efficiency is not the same as delivered watts per kilogram of integrated, radiation-aged, deployed array. [4, 5, 19]

A 2026 U.S. Department of Energy workshop proposed by-2035 goals that combine at least 200 W/kg array specific power, retention of at least 70% of beginning-of-life performance at end of life, and cost below $10/W under defined measurement boundaries. These are workshop recommendations, **not completed industry achievements or DOE commitments**. [5]

C. Waste-heat rejection and high-power electronics

In vacuum, radiators primarily reject heat through radiation. For a surface radiating to a much colder background, **P = epsilon sigma A T^4**. At 400 K and emissivity 0.9, 1 GW of waste heat requires roughly **0.77 km^2** of effective emitting area. This omits sunlight, view-factor limits, mass of radiator support and coolant loops. [7; illustrative calculation]

Commercial systems need higher-efficiency RF or optical electronics, thermal architectures compatible with foldable arrays, radiation-qualified power management and credible replacement strategies. [1, 6, 7]

D. Assembly, autonomy, and serviceability

Kilometer-class collectors and antennas imply large module counts, autonomous alignment, formation or structural control, inspectable connections and maintenance. NASA documents a large set of in-space servicing, assembly and manufacturing capabilities, but the integrated, affordable scaling pathway remains unproven. NASA discontinued OSAM-1 in 2024 after major technical, cost and schedule difficulties - a useful caution about assuming autonomy is already routine. [8, 9]

E. Off-Earth manufacturing and resources

A Dyson swarm capturing a nontrivial fraction of solar luminosity is probably incompatible with importing all mass from Earth. Mining, refining, energy-intensive processing, semiconductor manufacturing, robotics, recycling and industrial logistics would have to emerge beyond Earth. None of the reviewed startups demonstrates a self-sustaining off-Earth manufacturing economy. Self-replication might help, but is neither a prerequisite proved necessary nor presently available at industrial scale.

04 / Scale calculations and assumptions

A. One-gigawatt terrestrial output

At 1 AU the solar irradiance is approximately 1,361 W/m^2. For a simplified system efficiency of 10% from incident sunlight to delivered ground electricity, the ideal normal-incidence collection area is:

$$\mathbf{A = 10^9\ W / (1{,}361\ W/m^2 \times 0.10) = 7.35\ million\ m^2 = 7.35\ km^2.}$$

This excludes extra aperture area for margins, performance degradation, and illumination geometry. NASA evaluated two different 2-GW reference designs requiring roughly 11.5 and 19 km^2 of panels, with masses of 5.9 and 10 million kg respectively. Those reference architectures are **not** equivalent to the illustrative 10%-efficiency calculation. [1]

B. Multiplicative losses

To illustrate compounded losses, consider 35% PV conversion, 70% DC-to-RF conversion, 65% propagation/collection, 80% receiver conversion and 90% other electrical efficiency:

$$\mathbf{\eta = 0.35 \times 0.70 \times 0.65 \times 0.80 \times 0.90 = 11.5\%.}$$

These percentages are a hypothetical teaching example, not a validated system budget. Small degradations in several stages strongly affect collector area, transmitter power, radiator load and energy revenue.

C. One percent of the Sun: a Dyson-swarm mass floor


Solar luminosity L = 3.83 x 10^{26} W; capture fraction f = 0.01; radius 1 AU. The effective collector area is **$A = f L / S = 2.81 \times 10^{21}\ m^2$**. At an extraordinarily optimistic integrated areal mass density of 1 kg/m^2, mass would be **2.81×10^{21} kg** - approximately 0.85% of Mercury's mass.

This is a deliberately simple mass floor: support, wiring, propulsion, replacements, power conversion, industrial equipment and deployment overhead would increase requirements. At smaller heliocentric radii, the intercepting area falls with radius squared, but operating conditions become more severe. [17; independent calculation]

Order-of-magnitude warning: One percent of the Sun is ~3.83 x 10^{24} W, about 3.8 quadrillion times the output of a 1-GW station. A gigawatt demonstration and a significant Dyson swarm are not adjacent stages of the same-sized project.

05 / Economics: the hardest commercial filter

NASA's 2024 study evaluated two first-of-a-kind conceptual 2-GW solar-power systems assumed operational in 2050. Its purpose was comparative system assessment, not predicting a guaranteed future market price. [1]



Modelled levelized electricity cost ($/kWh); NASA reference scenarios, not observed market prices.

Launch dominated the baseline cost allocation (about 71% for RD1 and 77% for RD2); manufacturing was next. Under a combined favorable sensitivity case, NASA obtained $0.03/kWh for RD1 and $0.08/kWh for RD2. This indicates that the outcome is contingent on multiple simultaneous improvements, not that these costs are already achievable. [1]

Why an orbital customer may be a better first market

Electricity on Earth competes with established generation and grids; electricity aboard a spacecraft competes with satellite mass, panel area, batteries, downtime and mission constraints. This can make incremental orbit-delivered energy more economically valuable than the same kilowatt-hour on the ground. Nevertheless, the satellite operator must still trust the service, tolerate the orbit geometry and receive a net mass/cost benefit. [10, 11]

Unit economics a founder must estimate

Question	Required quantitative evidence
Who buys?	Named customer segment, use case, power profile and willingness to pay.
Value per watt?	Saved satellite mass, more payload duty cycle, avoided redesign or extended mission.
Total delivered cost?	Transmitter + receiver + launch + operations + insurance + replacement cost.
Service quality?	Received power, duty cycle, accuracy, failures and beam-availability statistics.
Defensibility?	Efficiency, pointing control, hardware mass, software performance or protected know-how.

A startup claiming a large power-beaming market without a physically grounded receiver and orbit model is not yet commercially validated. Financing or a signed power-purchase agreement is a signal of interest, not of feasible long-term generation.

06 / Existing efforts: evidence versus aspiration

The following classifications reflect the sources available through 9 November 2026. Company press releases establish what their authors announced; they do not by themselves independently verify that an in-orbit demonstration achieved its performance target.

Organization	Verified / documented milestone	Still unproven
Caltech SSPP	SSPD-1 / MAPLE transferred power in orbit and produced a detected signal on Earth (2023); materials and deployment tests.	Grid-useful sustained watts, scalable integration, bankable cost.
Star Catcher	Ground optical power beaming; tracking tests; Protostar was announced for Oct. 2026 launch and company reports it launched.	Independently verified power transfer between free flyers; commercial energy service.
Cowboy Space (Aetherflux)	Reason-1 launched Oct. 1, 2026 with laser and beam-steering payload; $275M Series B announced.	Confirmed ground reception from that test; dependable high-power transfer and profitable service.
Virtus Solis	Announced 20-year 100-MW PPA (option to 250 MW) in Sept. 2026.	A functioning orbital plant; its public demo is targeted for Mar. 2027.
Reflect Orbital	FCC approved Earendil-1 demonstrator spectrum/operation in July 2026.	Revenue-scale sunlight delivery; environmental acceptability of large mirror constellations.
SpaceX orbital data centers	FCC accepted for filing a proposal for up to 1M satellites in Feb. 2026.	Not a licensed/operating Dyson swarm; programmatic claim is not completion.

Sources: Caltech [2, 3]; Star Catcher [10, 11]; Cowboy [12, 13]; Virtus [14]; Reflect [15]; FCC [16].

Interpretation of the company landscape

Star Catcher is closest to a near-term service business around energy delivery to spacecraft, because it targets an existing orbital load and proposes to illuminate existing solar panels. Its crucial remaining gate is a repeatable, quantified, independently observed orbital transfer followed by paid supply. [10, 11]

Cowboy Space highlights that valuable on-orbit uses of solar energy may arrive before grid power. Its expansion into computing and launch illustrates product-market uncertainty, not proof that solar power is economically solved. [12, 13]

Virtus Solis is targeting a terrestrial customer rather than an orbital one. The economic commitment is noteworthy, but large off-take announcements should be assessed separately from technical readiness and project financing. [14]

Reflect Orbital avoids converting collected light to RF/laser energy, but trades that problem for orbital illumination geometry, reflector control and impacts on astronomy and the natural night environment. Its approval is not a Dyson-swarm construction milestone. [15]

SpaceX explicitly connected its orbital data-center filing to the Kardashev-II ambition. That is a long-range narrative accompanying a filing, rather than evidence of a viable heliocentric solar-collection architecture. [16]

07 / What has yet to be done: readiness roadmap

1. **Ground beam link** — DEMONSTRATED
2. **Orbital component tests** — DEMONSTRATED
3. **Power between free flyers** — UNDER TEST
4. **Paid orbital energy service** — NOT ESTABLISHED
5. **Utility grid power** — NOT DEMONSTRATED
6. **Self-sustaining solar swarm** — CONCEPTUAL

Milestone gates rather than unsupported dates

Gate	Minimum credible result	Open question
1. Orbital energy transfer	Measured received power between separated spacecraft or from orbit to a ground receiver.	Efficiency and repeatability, not merely optical/RF detection.
2. Operational service	A paying mission receives useful watts over a stated duty cycle.	Is service cheaper than larger onboard arrays/batteries?
3. MW demonstration	High-power integrated collector, transmitter and receiver with safety case.	Scaling, launch, thermal, rectenna footprint.
4. Utility-scale plant	Reliable electricity to a grid connection with disclosed lifetime costs.	Cost parity, approvals, debt financing.
5. Orbital industrial ecosystem	Autonomous construction, regular servicing and substantial in-space fabrication.	Resource throughput and high uptime.
6. Heliocentric expansion	Large-scale off-Earth feedstocks and multi-orbit supply chains.	Interplanetary industry, orbital traffic and power use in space.

Missing cross-cutting institutions and infrastructure

Even successful hardware needs spectrum coordination, optical or microwave exposure limits, space traffic management, debris mitigation, land rights for receiving arrays, insurance, environmental assessment and grid interconnection. Large systems may need international agreements. These are not necessarily problems that an individual PhD student can solve, but they can determine whether an apparently working technical system becomes a business. [1, 6, 15]

08 / Entrepreneurial entry points available now

These are **proposed commercial hypotheses**, not verified business opportunities or guarantees of customer demand. The best idea minimizes early capital expenditure while producing measured evidence that investors or customers can evaluate.

Wedge	First useful prototype	Primary buyer / risk
Beamforming optimization software	GPU model + phased-array benchtop demonstrator, benchmarked against baselines.	Antenna makers / risk: incumbent solutions, simulation-to-hardware gap.
Optical power link component	Low-power aligned laser + PV receiver with closed-loop tracking and robust shutoff.	Space component integrators / risk: safety and qualification.
Ultralight deployable PV module	Verified W/kg, stowage, thermal cycling and degradation tests.	Satellite manufacturers / risk: materials yield, flight heritage.
Autonomous assembly / servicing	Multi-robot ground simulator with failure recovery and supervised autonomy.	Space infrastructure operators / risk: flight integration costs.
Power-delivery network	Orbit and link simulator + customer-designed receiver integration.	Satellite operators / risk: expensive constellation, absent customers.
Off-Earth materials processes	Laboratory extraction/refining pilot matched to real space feedstocks.	Space agency R&D / risk: no near-term large commercial market.

A founder-friendly sequence: software to hardware to orbit

- **0-3 months:** Pick one link budget and use case, identify 10-20 prospective partners, build a first-order mass/cost/orbit model and benchmark existing solutions.
- **3-9 months:** Demonstrate a control or conversion advantage on terrestrial hardware with measured efficiency, power, pointing error, and performance under disturbances.
- **9-18 months:** Narrow toward a flight-qualifiable subsystem, secure customer design feedback and evaluate regulatory/flight-test costs.
- **Later:** Fly only when a clear data gap cannot be closed on the ground and the potential market justifies the test.

The durations above are planning windows for a small prototype-oriented team, not forecasts of orbital deployment or guarantees of technical success.

09 / PhD, startup, or industry apprenticeship?

Route	Best when	Risk to watch
Targeted PhD	Key value requires new device physics, new materials or difficult scientific discovery.	Years spent solving a publishable but commercially irrelevant question.
Start a company	A compelling first product can use existing principles; there is a customer and believable prototype route.	Premature capital requirements, regulatory and hardware execution burden.
Join a space company	Need expertise in hardware qualification, missions, operations, sales and financing.	Less ability to set the long-term technological vision.
Hybrid / spinout	A university lab can de-risk science while venture formation proceeds responsibly.	IP ownership, conflict of interest, licensing and slow product pivots.

What a worthwhile PhD would have to deliver

- A falsifiable engineering hypothesis, e.g. phase control that demonstrably reduces transmitter/receiver mass for fixed received power.
- Access to facilities and collaborators that cannot be obtained economically as an independent startup.
- A plausible pathway from publications to prototype, license, open-source platform, spinout or industrial adoption.
- A supervisor whose active laboratory direction is the enabling technology, not merely the abstract long-term Dyson-swarm aspiration.

A practical choice rule

> Prefer **startup / industry** if the bottleneck is making existing technology reliable and cheap enough to sell. Prefer **PhD** if you can identify a scientific uncertainty whose resolution is a credible competitive moat. Consider **joining a space startup** first if you lack flight hardware experience, customer relationships and a founding team.

Given an existing strength in computational physics and GPU work, a first experiment in electromagnetic inverse design, adaptive phased arrays or distributed optimization is a realistic low-cost entry point. It is not sufficient alone: performance on actual devices, practical receiver economics and customers would still have to be demonstrated.

10 / The critical risk register

Risk	Severity	Practical mitigation / evidence required
Cost fails terrestrial benchmark	High	Enter orbital markets first; model full delivered cost and duty cycle.
Link efficiency falls under motion or weather	High	Closed-loop testing, statistical outage model, fail-safe beam termination.
Mass and heat grow faster than electrical output	High	Integrated mass/thermal budgets early; subsystem measurement.
Regulatory barriers and social license	High	Early counsel, engagement, transparent radiation and astronomy studies.
Capital needed before first revenue	High	Sell a component/software wedge before becoming a full power utility.
Manufacturing/qualification failure	High	Radiation, cycling, deployment and reliability tests with traceable data.
No realistic pathway to off-Earth industry	Very high	Treat this as a generational, separate investment frontier.

Potential falsifiers of the overall thesis

The premise of economically competitive power from orbit would weaken if launch and refurbishment costs fail to fall, if total electrical conversion and collection efficiency plateaus below needed values, or if terrestrial firm low-carbon alternatives outperform even optimistic orbital designs. Conversely, a verified low-mass, high-efficiency module and commercial service with durable customers could materially improve the case. NASA explicitly shows strong sensitivity to combinations of assumptions. [1]

11 / Recommended decision and next actions

The Dyson-swarm goal is a legitimate long-range engineering vision but not a viable first product specification. The most grounded near-term business is to sell a technology that helps spacecraft collect, manage, direct, receive or autonomously use energy. Existing startups have made impressive component-level advances but have not closed the system-wide economics or industrial infrastructure gap.

Recommended 90-day exploration program

Choose a measurable wedge

Select either GPU-accelerated electromagnetic optimization, beam tracking hardware, or ultralight solar array design. Define one benchmark and an alternative product currently used by customers.

Build a quantitative model

Compute link efficiency across orbit cases, transmitter size, power budget, thermals, receiver mass and availability. Compare with explicit uncertainty ranges.

Conduct customer discovery

Speak to satellite integrators and mission operators about the value of extra onboard power, procurement timelines and qualification standards.

Demonstrate one advantage

Validate a simulation improvement against a modest physical experiment, not merely an internally generated plot.

Use evidence to decide the degree

If the dominant obstacle is scientifically unsolved and a specific lab is uniquely suited to it, pursue that PhD. Otherwise seek a founding team, job or commercial prototype path.

Bottom line: A PhD is an instrument for removing scientific risk; a startup is an instrument for removing product and market risk. The best route is whichever removes the most important bottleneck on the critical path from today's technology to a paying first customer - without pretending that a successful early power link is already a Dyson swarm.

APPENDIX A / TECHNICAL NOTES

Calculation notes and limitations

Numerical constants and examples

Symbol / parameter	Value used / definition
Solar irradiance at 1 AU (S)	1,361 W/m2 (approximate mean)
Solar luminosity (L)	3.83 x 10^26 W
Geostationary altitude / example range	35,786 km (nadir approximation, not general slant range)
Microwave example	2.45 GHz; lambda ~0.1224 m
Laser example	Wavelength 1 micron
Stefan-Boltzmann constant	5.670374419 x 10^-8 W m^-2 K^-4
Mercury mass for illustration	3.30 x 10^23 kg

What these calculations do not prove

- The Airy first-null beam radius is a diffraction yardstick, not a turnkey link budget for a sparse electronically steered space array.
- Incident-area calculations do not resolve orbital illumination, panel orientation, transmission loss, thermal derating or operations and maintenance.
- The Dyson mass estimate assumes a full interception equivalent at 1 AU and one kilogram per square meter; it is not a manufacturable bill of materials.
- The NASA economic comparison is a model based on defined reference designs and scenarios, not an empirical average for every possible space solar architecture.
- No rigorous timetable for a true Dyson swarm can be inferred from startup launch schedules, financing rounds or an FCC application.

APPENDIX B / REFERENCES

Sources and further reading

Direct official documents and research papers are favored. Company disclosures are labeled as such. Sources consulted through 9 November 2026. Link titles below are clickable in the PDF.

[1] NASA Office of Technology, Policy, and Strategy (2024). *Space-Based Solar Power*. NASA Report 20230018600. (Primary cost and system engineering source.)
https://www.nasa.gov/wp-content/uploads/2024/01/otps-sbsp-report-final-tagged-approved-1-8-24-tagged-v2.pdf

[2] Caltech (2023). *In a First, Caltech Space Solar Power Demonstrator Wirelessly Transmits Power in Space*. (Institutional experiment account.)
https://www.caltech.edu/about/news/in-a-first-caltechs-space-solar-power-demonstrator-wirelessly-transmits-power-in-space

[3] Abiri, B. et al. (2022). *A Lightweight Space-based Solar Power Generation and Transmission Satellite*. (Technical architecture study.)
https://authors.library.caltech.edu/records/v5pac-cwn85

[4] NASA (2026). *State of the Art of Small Spacecraft Technology: Power Subsystems*. (Space photovoltaics status.)
https://www.nasa.gov/smallsat-institute/sst-soa/power-subsystems/

[5] U.S. Department of Energy (2026). *Space Photovoltaics Workshop: Findings and Participant Recommendations*. (Non-binding research targets.)
https://www.energy.gov/cmei/systems/2026-space-photovoltaics-workshop

[6] *Space-based solar power systems: Architectural evolution, wireless power transmission challenges, and engineering implementation* (2026). (Recent systems review.)
https://www.jstage.jst.go.jp/article/arr/6/3/6_1590/_article/-char/en

[7] U.S. Government Accountability Office (2026). *Science & Tech Spotlight: Data Centers in Space*. GAO-26-109012.
https://www.gao.gov/products/gao-26-109012

[8] NASA (2026). *In-Space Servicing, Assembly, and Manufacturing State of Play - 2026 Edition*.
https://ntrs.nasa.gov/citations/20260008638

[9] NASA (2024). *Update on Status of NASA OSAM-1 Project*. (Cancellation rationale.)
https://www.nasa.gov/missions/update-on-status-of-nasas-osam-1-project/

[10] Star Catcher (2026). *Protostar Orbital Power Beaming Demonstration Announcement*. (Company disclosure, Sept. 28.)
https://www.star-catcher.com/news/protostar-announcement

[11] Star Catcher (2026). *Star Catcher Raises $65 Million*. (Company disclosure, May 12.)
https://www.star-catcher.com/news/star-catcher-raises-65-million-to-build-the-first-power-grid-in-space

[12] Cowboy Space (2026). *Our First Mission Takes Flight*. (Company disclosure, Oct. 1.)
https://www.cowboyspace.com/news/reason-1-takes-flight

[13] Cowboy Space (2026). *Introducing Cowboy Space: A $275 Million Series B*. (Company disclosure, May 11.)
https://www.cowboyspace.com/news/introducing-cowboy-space-series-b

[14] Virtus Solis (2026). *Virtus Solis Signs Landmark 20-Year PPA with Brae Systems*. (Company disclosure, Sept. 30.)
https://www.virtussolis.space/blog/virtus-solis-signs-landmark-20-year-ppa-with-brae-systems

[15] American Astronomical Society (2026). *Public Policy Experts on FCC Approval of Reflect Orbital Earendil-1*. (Regulatory and externality context.)
https://aas.org/press/aas-public-policy-experts-available-comment-fcc-approval-reflect-orbitals-earendil-1-mission

[16] Federal Communications Commission (2026). *Public Notice DA-26-113*. (SpaceX orbital data-center filing accepted for comment.)
https://docs.fcc.gov/public/attachments/DA-26-113A1.pdf

[17] Dyson, F. J. (1960). *Search for Artificial Stellar Sources of Infrared Radiation*. Science 131, 1667-1668.
https://doi.org/10.1126/science.131.3414.1667

[18] Caltech / Pellegrino Laboratory (2025). *DOLCE Flight Operations and Deployable Structure Results*.
https://www.its.caltech.edu/~sslab/PUBLICATIONS/PUBLICATIONS/AIAA_DOLCE_2025_Full_Paper.pdf

[19] Gao, M., Yaghoobi Nia, N., and Vaidya, N. (2026). *Photovoltaics for Space Applications*. Communications Engineering 5, 111.
https://www.nature.com/articles/s44172-026-00701-9

[20] Payload (2026). *Transporter-18 Tests the Building Blocks of Orbital Data Centers*. (Independent industry reporting.)
https://payloadspace.com/transporter-18-tests-the-building-blocks-of-orbital-data-centers/