

Math for the human - robot multilevel POMDP

1 Human (PO)MDP

This is a MDP that the human runs in their mind. It can be formalized as a POMDP, but right now we have a weak POMDP with a belief distribution over the robot's distribution of objects.

1. $S = \langle \iota, \mathcal{I}, d, H \rangle$
 - (a) Here \mathcal{I} is the set of items the robot can pass.
 - (b) Item ι is the object the human wants, and this is hidden information for the robot.
 - (c) d is the dialogue state - what question was asked previously by the robot.
 - (d) Here $B(i \in \mathcal{I} == \iota)$ is the belief distribution of the robot over the items in \mathcal{I} . In the POMDP formulation B would be part of the state that is hidden from the human. Instead we model a distribution that tracks B allowing the human to solve an MDP instead of nested POMDPs. We will go back to the nested POMDP model repeatedly to make sure our MDP model is equivalent.
 - (e) Human's hunch of the robot's belief $H = P(\hat{B}|\eta)$, where \hat{B} is an estimate of the distribution of B , it is over the set of items \mathcal{I} . η is a set of priors that defines the distribution \hat{B} , hence H is over the space of all possible priors values. We propose to use the Dirichlet distribution to model H .
2. $A_h = \langle l, g \rangle$, where A_h is the human action set and l and g are language and gesture actions respectively.
3. If this were a POMDP we would need observation functions and a observation set.
 - (a) $\Omega_h = \langle A_r \rangle$, where A_r is the set of robot actions and Ω_h is the set of human observations.
 - (b) $O = P(A_r|\iota, \mathcal{I}, d, H, B)$ is the observation function and it is hand coded by us so we know it, since we know the robots response to all the belief states.

(c) $T = P(\iota', \mathcal{I}', d', H', B' | \iota, \mathcal{I}, d, H, B, a_h, a_r) = P(\iota', \mathcal{I}', d' | \iota, \mathcal{I}, d, H, B, a_h, a_r) \times P(H' | \iota, \mathcal{I}, d, H, B, a_h, a_r) \times P(B' | \iota, \mathcal{I}, d, H, B, a_h, a_r)$ is the transition function.

4. MDP formulation of this problem would not need the observation set or the observation functions, instead H would get updated based on A_r and A_h . This just has a transition function now defined as $T = P(\iota', \mathcal{I}', d', H' | \iota, \mathcal{I}, d, H, a_h, a_r) = P(\iota', \mathcal{I}', d' | \iota, \mathcal{I}, d, H, a_h, a_r) \times P(H' | \iota, \mathcal{I}, d, H, B, a_h, a_r)$. The conditional independence of the human's hunch H from the distribution over the required item, or set of items left over or the last question asked comes from visible robot actions. $P(H' | \iota, \mathcal{I}, d, H, B, a_h, a_r)$ is being designed by us as an approximation and we need to think of data intensive methods of measuring this transition. If a_r is a pick action and i is the object picked:

$$P(\iota', \mathcal{I}', d' | \iota, \mathcal{I}, d, H, a_h, a_r) = \begin{cases} 1/|\mathcal{I}_1| & \text{if } i! = \iota \\ 0 & \text{otherwise} \end{cases} \quad (1)$$

If a_r is an ask question

$$P(\iota', \mathcal{I}', d' | \iota, \mathcal{I}, d, H, a_h, a_r) = \begin{cases} 1 & \text{if } d' = \text{a.ask} \\ 0 & \text{otherwise} \end{cases} \quad (2)$$

5. The reward for the human subject is not well defined, but we can assume that the net reward is for both human and the robot, since this is a co-operative domain.

2 Robot POMDP