KING POWER




BRINGING TECHNOLOGY INTO SAFETY



I-881 Blue

• PROTECTION
Extra wide toe cap , designed and engineered for comfort. protection,light weight, and flexibility.



• UPPER
Exclusive Japan Microfiber Leather
Chemical Resistant Upper
Breathable,Water Resistant
Full Inner Lining
Light Weight



• OUTSOLE
Injected Polyurethane with special formulated Rubber to provide both work functionality, comfort, ultra light weight, and non marking. New Innovation to provide ultimate slip resistance performance. Tread designed for superior traction, stability, heel shock absorption, and easy clean.
Heat Resistance only up to 120 degree Celsius.



• EXTRA WIDE TOE CAP GREAT FITTING



• FOOTBED
Removable Thick Cushion EVA insole. Comfort heel cushion, arch stability, and air channel system.

TOE PROTECTION | SLIP RESISTANCE | LIGHT WEIGHT | SOLE PROTECTION | ABRASION RESISTANT | OIL RESISTANT

SPECIFICATIONS	
Model	I-881 Blue
Safety Toe	Composite toe cap
Material	Exclusive Japan Microfiber
Color	Blue
Lining	BK mesh lining
Sole	Light weight PU with special formulated Rubber
Size	UK 3-12
Insole	Thick cushion EVA. Provide support, comfort and stay dry

www.kprsafety.com

CE EN20345 | PLS Listed SS 513:2005 LIC:00 294 | R32354 | SIRIM MS ISO 20345: 2008 PC002140 | SNI 7079:2009

I-881-U0025

KING POWER



BRINGING TECHNOLOGY INTO SAFETY



• PROTECTION

Extra wide toe cap for comfort. Quality checked and tested to meet CE EN ISO 20345 standards. Protective scuff toe was designed to help protect and prolong the life of the safety shoe. Steel midsole for work environments that require protection from sole penetration.

TOE PROTECTION | ESD | SLIP RESISTANCE | LIGHT WEIGHT | SOLE PROTECTION | ABRASION RESISTANT | OIL RESISTANT

• UPPER

Buffalo full grain printed leather
Full Inner Lining
Light Weight



• OUTSOLE

Dual Density Injected Polyurethane/ Polyurethane to provide both work functionality, comfort, light weight, and non-marking. New Innovation to provide ultimate slip resistance performance. Tread designed for superior traction, stability, heel shock absorption, and easy clean.
Heat Resistance only up to 120 degree Celsius.



• EXTRA WIDE TOE CAP GREAT FITTING



• FOOTBED

Removable Thick Cushion EVA footbed. Comfort heel cushion, arch stability, and air channel system. Single pack footbed also available for purchase.



SPECIFICATIONS

Model	L-807
Safety Toe	Composite toe cap
Electrical feature	ESD
Material	Buffalo full grain printed leather
Color	Black
Lining	Cambrelle lining
Sole	Dual density PU/PU outsole, SRC
Size	UK 2-13 / EU 35-48
Footbed	Thick cushion EVA. Provide support, comfort and stay dry

• KPR SLIP RESISTANCE TEST RESULTS

	Coefficient of Friction		
		Requirement	KPR L-sole Results*
SRC (SRA +SRB)	SRA Ceramic Tile + SLS	Forward Flat Slip 0.32	0.62-0.63
		Forward Heel Slip 0.28	0.49-0.50
	SRB Stainless Steel + Glycerol	Forward Flat Slip 0.18	0.64-0.69
		Forward Heel Slip 0.13	0.22-0.23

*Slip resistance testing conducted by Intertek (2011)

www.kprsafety.com

EN20345 | PLS Listed SS 513:2005 LIC:00 294 TÜV SÜD PSB | R32354 | SIRIM MS ISO 20345: 2008 PC002140 | SNI 7079:2009

L-807-U0025

KPR®



BRINGING TECHNOLOGY INTO SAFETY




• PROTECTION

Extra wide toe cap for comfort. Quality checked and tested to meet CE EN ISO 20345 standards.
Protective scuff toe was designed to help protect and prolong the life of the safety shoe. Steel midsole for work environments that require protection from sole penetration.

TOE PROTECTION | ESD | SLIP RESISTANCE | LIGHT WEIGHT | SOLE PROTECTION | ABRASION RESISTANT | OIL RESISTANT

• UPPER

Buffalo full grain printed leather
Full Inner Lining
Light Weight



• OUTSOLE

Dual Density Injected Polyurethane to provide both work functionality, comfort, light weight, and non-marking. New innovation to provide ultimate slip resistance performance. Tread designed for superior traction, stability, heel shock absorption, and easy clean. Heat Resistance only up to 120 degree Celsius.



• EXTRA WIDE TOE CAP GREAT FITTING



• FOOTBED

Removable Thick Cushion EVA footbed. Comfort heel cushion, arch stability, and air channel system. Single pack footbed also available for purchase.



SPECIFICATIONS

Model	L-806
Safety Toe	Composite toe cap
Electrical feature	ESD
Material	Buffalo full grain printed leather
Color	Black
Lining	BK mesh lining
Sole	Dual density PU/PU sole, SRC
Size	UK 2-13 / EU 35-48
Footbed	Thick cushion EVA, Provide support, comfort and stay dry

• KPR SLIP RESISTANCE TEST RESULTS

	Coefficient of Friction		
		Requirement	KPR L-sole Results*
SRC (SRA +SRB)	SRA Ceramic Tile + SLS	Forward Flat Slip 0.32	0.62-0.63
		Forward Heel Slip 0.28	0.49-0.50
	SRB Stainless Steel + Glycerol	Forward Flat Slip 0.18	0.64-0.69
		Forward Heel Slip 0.13	0.22-0.23

*Slip resistance testing conducted by Intertek (2011)

www.kprsafety.com

CE EN20345

PLS Listed SS 513:2005 LIC:00 294 TÜV SÜD PSB

R32354

SIRIM MS ISO 20345: 2008 PC002140

SNI 7079:2009

L-806-U0025

KING POWER



BRINGING TECHNOLOGY INTO SAFETY



- TOE PROTECTION
- ESD
- SLIP RESISTANCE
- LIGHT WEIGHT
- SOLE PROTECTION
- ABRASION RESISTANT
- OIL RESISTANT

• PROTECTION

Extra wide toe cap for comfort. Quality checked and tested to meet CE EN ISO 20345 standards. Protective scuff toe was designed to help protect and prolong the life of the safety shoe. Steel midsole for work environments that require protection from sole penetration.

• UPPER

Buffalo full grain printed leather
Full Inner Lining
Light Weight



• OUTSOLE

Dual Density Injected Polyurethane/ Polyurethane to provide both work functionality, comfort, light weight, and non-marking. New Innovation to provide ultimate slip resistance performance. Tread designed for superior traction, stability, heel shock absorption, and easy clean.
Heat Resistance only up to 120 degree Celsius.



• EXTRA WIDE TOE CAP GREAT FITTING



• FOOTBED

Removable Thick Cushion EVA footbed. Comfort heel cushion, arch stability, and air channel system. Single pack footbed also available for purchase.



SPECIFICATIONS

Model	L-706
Safety Toe	Composite toe cap
Electrical feature	ESD
Material	Buffalo full grain printed leather
Color	Black
Lining	Cambrelle lining
Sole	Dual density PU/PU outsole, SRC
Size	UK 2-13 / EU 35-48
Footbed	Thick cushion EVA. Provide support, comfort and stay dry

• KPR SLIP RESISTANCE TEST RESULTS

	Coefficient of Friction		
		Requirement	KPR L-sole Results*
SRC (SRA +SRB)	SRA Ceramic Tile + SLS	Forward Flat Slip 0.32	0.62-0.63
		Forward Heel Slip 0.28	0.49-0.50
	SRB Stainless Stee + Glycerol	Forward Flat Slip 0.18	0.64-0.69
		Forward Heel Slip 0.13	0.22-0.23

*Slip resistance testing conducted by Intertek (2011)

www.kprsafety.com

EN20345

PLS Listed SS 513:2005 LIC:00 294 TÜV SÜD PSB

R32354

SIRIM MS ISO 20345: 2008 PC002140

SNI 7079:2009

L-706-U0025