Simon



JPA009102
LSPr-009-IDN

SNI 0111:2009
LSPr-009-IDN

Certificate No. YQ005211
LSSM-005-IDN
KAN
Komite Akreditasi Nasional
Lembaga Sertifikasi Sistem Mutu
LSSM - 005 - IDN
YOQA
ISO 9001

Seberapa Penting kah Sepatu Safety ?



Kondisi Tidak Aman (*Unsafe Condition)* pada Area Kerja



Kejatuhan Beban


Material Scrap


Tusukan benda Tajam


Oli dan Bahan Kimia


Arus Listrik


Area Panas


Percikan Api

Meminimalisir resiko
dengan penggunaan APD
(Alat Pelindung Diri)

Dasar Hukum : *"Permenakertrans No. Per.08/Men/VII/2010"*

- Pasal 2 ayat (1) menyebutkan pengusaha wajib menyediakan APD bagi pekerja ditempat kerja.
- Pasal 5 menyebutkan pengusaha atau pemgurus wajib mengumumkan secara tertulis dan memasang rambu-rambu mengenai kewajiban penggunaan APD dilokasi kerja.
- Pasal 6 ayat (1) menyebutkan buruh dan orang lain yang memasuki tempat kerja wajib memakai atau menggunakan APD sesyai dengan potensi bahaya dan risiko
- Pasal 7 ayat (1) menyebutkan pengusaha atau pengurus wajib melaksanakan manajemen APD di tempat kerja

Simon
CORPORATION

ST10 PU AND RUBBER (NEW)

Stylish, Comfortable and Lightly safety shoes based on a wealth of technical Experience in Japan

PU

MAKE TO ORDER!

NBR

ST1011

pair:
990 gr

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 35 s/d 46



ST1011 R

pair:
1220 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 35 s/d 46



ST1017

pair:
970 gr

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 35 s/d 46



ST1017 R

pair:
1200 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 35 s/d 46



ST1018

pair:
990 gr

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 35 s/d 46



ST1018 R

pair:
1230 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 35 s/d 46



⚠ Heat resistance Polyurethane 80 °C and Rubber 130 °C are the outsole melting point. This means that the shoes resist only on the hot floor for a few moments. Shoes are not recommended on hot floor for a long time.

INFINITY & SS PRO SERIES

Stylish, Comfortable and Lightly safety shoes based on a wealth of technical Experience in Japan

NBR

READY STOCK!

TS3011R

pair: 1085 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 34 s/d 46



TS8311

pair: 1050 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 34 s/d 46



TS3017R

pair: 1060 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 34 s/d 46



TS8317

pair: 1080 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 34 s/d 46



TS3022R

pair: 1200 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 34 s/d 46



TS8322

pair: 1200 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 36 s/d 46



⚠ Heat resistance Polyurethane 80 °C and Rubber 130 °C are the outsole melting point. This means that the shoes resist only on the hot floor for a few moments. Shoes are not recommended on hot floor for a long time.

INFINITY& EST SERIES

Stylish, Comfortable and durable safety shoes based on a wealth of technical Experience in Japan

MAKE TO ORDER!

READY STOCK!

ST 1011 D6

pair: 1020 gr

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46



Special Order

TS311EST

pair: 965 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 36 s/d 46



TS 3022 R D6

pair: 1250 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 36 s/d 46



Special Order

TS317EST

pair: 945 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 36 s/d 46



TS 3011 R D6

pair: 1100 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 36 s/d 46



Special Order

TS322EST

pair: 1120 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 36 s/d 46



⚠ Heat resistance Polyurethane 80 °C and Rubber 130 °C are the outsole melting point. This means that the shoes only hold on the hot floor with that temperature for a few moments. It is not recommended to use these shoes on hot floors for a long time.

SA & ANTISTATIC SERIES

Stylish, Comfortable and durable safety shoes based on a wealth of technical Experience in Japan

MAKE TO ORDER!

ST1011 T

pair:
990 gr

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance
  Oil Resistance.
  Antistatic 0,1~100 M Ohm
- Size : 35 s/d 46



Antistatic

TS311EST AS

pair:
965 gr

- Outsole : NBR Rubber
- Resistance : 130°C max of heat,
  Antistatic 0,1~100 M Ohm
- Size : 36 s/d 46



Antistatic

ST1017 T

pair:
970 gr

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance
  Oil Resistance
  Antistatic 0,1~100 M Ohm
- Size : 35 s/d 46



Antistatic

TS317EST AS

pair:
945 gr

- Outsole : NBR Rubber
- Resistance : 130°C max of heat,
  Antistatic 0,1~100 M Ohm
- Size : 36 s/d 46



Antistatic

ST1018 T

pair:
990 gr

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance
  Oil Resistance
  Antistatic 0,1~100 M Ohm
- Size : 35 s/d 46



Antistatic

TS322EST AS

Antistatic

pair:
1120 gr



- Outsole:
  NBR Rubber
- Resistance:
  130°C max of heat,
  Antistatic
  (0,1~100 M Ohm)
- Size:
  36 s/d 46

Heat resistance Polyurethane 80 °C and Rubber 130 °C are the outsole melting point. This means that the shoes resist only on the hot floor for a few moments. Shoes are not recommended on hot floor for a long time.

OTHER SERIES

Stylish, Comfortable and durable safety shoes based on a wealth of technical Experience in Japan

MAKE TO ORDER!

ST 1011 WM

pair: 880 gr — Upper : Microfibre

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance, Oil Resistance
- Size : 36 s/d 46



Special Order

ST 1011 WM T

pair: 880 gr — Upper : Microfibre

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance, Oil Resistance
- Size : 36 s/d 46

Antistatic



Special Order

ST 1017 WM

pair: 850 gr — Upper : Microfibre

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance, Oil Resistance
- Size : 36 s/d 46



Special Order

ST 1017 WM T

pair: 850 gr — Upper : Microfibre

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance, Oil Resistance
- Size : 36 s/d 46

Antistatic



Special Order

ST 1018 WM

pair: 865 gr — Upper : Microfibre

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance, Oil Resistance
- Size : 36 s/d 46



Special Order

ST 1018 WM T

pair: 865 gr — Upper : Microfibre

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance, Oil Resistance
- Size : 36 s/d 46

Antistatic



Special Order

⚠ Heat resistance Polyurethane 80 °C and Rubber 130 °C are the outsole melting point. This means that the shoes resist only on the hot floor for a few moments. Shoes are not recommended on hot floor for a long time.

OTHER SERIES

Stylish, Comfortable and durable safety shoes based on a wealth of technical Experience in Japan

MAKE TO ORDER!

ST 1024 R

pair: 1280 gr

Zipper

- Outsole : Rubber (NBR)
- Resistance : 130°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46



Special Order

ST 1044 R

pair: 1430 gr

- Outsole : Rubber (NBR)
- Resistance : 130°C max of heat, Slip resistance Oil Resistance
- Size : 37 s/d 46



Special Order

ST 1022 R

pair: 1290 gr

- Outsole : Rubber (NBR)
- Resistance : 130°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46



Special Order

ST 1022 T R

pair: 1290 gr

- Outsole : Rubber (NBR)
- Resistance : 130°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46

Antistatic



Special Order

ST 1027 R

pair: 1280 gr

- Outsole : Rubber (NBR)
- Resistance : 130°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46



Special Order

Sneaker Series



⚠ Heat resistance Polyurethane 80 °C and Rubber 130 °C are the outsole melting point. This means that the shoes resist only on the hot floor for a few moments. Shoes are not recommended on hot floor for a long time.

PETUNJUK PENGGUNAAN SEPATU PENGAMAN DARI KULIT

1. Pilih ukuran sepatu pengaman yang nyaman untuk kaki (tidak terlalu longgar dan tidak terlalu sempit).
2. Gunakan kaus kaki yang lembut agar terhindar dari lecet dan bau pada sepatu.
3. Jangan memakai sepatu dalam keadaan kaki basah ataupun sepatu basah.
4. Gunakan *shoe horn* untuk membantu kaki masuk ke dalam sepatu dengan lebih mudah.
5. Jangan menginjak bagian belakang sepatu (Backstay) saat pemakaian.
6. Jika menggunakan model tali, pastikan tali sepatu terikat kencang saat digunakan.
7. Untuk sapatu pengaman jenis *antistatic*, pastikan sepatu selalu bersih dari residu pemakaian (debu & lumpur), terutama di bagian luar dan dalamnya agar perfoma *resistansi antistatic*-nya tetap bagus.
8. Pastikan sepatu dibersihkan terlebih dahulu dari residu pemakaian (debu & lumpur) sebelum di semir.
9. Gunakan handuk basah atau kain lembab untuk membersihan residu. Jangan menggunakan alkohol atau *chemical* pelarut lainnya (Thinner, MEK dll).
10. Gunakan sikat halus untuk melakukan penyemiran agar permukaan tetap bersih dan awet. Lakukan secara berkala.
11. Gunakan warna semir sepatu yang warnanya senada dengan sepatu kulit.
12. Keringkan di tempat yang teduh atau di dalam ruangan dengan suhu kamar. Hindari sinar matahari atau sumber panas lainnya secara langsung.
13. Setelah pemakaian taruh gumpalan kertas / koran / *tissue* kedalam sepatu agar tetap kering dan menjaga bentuk sepatu, lalu tempatkan di tempat yang teduh.
14. Jika sepatu pengaman telah mengalami tekanan ataupun impact besar pada area pengeras depan (*Toe cap*) lebih baik sepatu tersebut jangan digunakan kembali.



SNI 0111:2009
LSPr-009-IDN

Certificate No. YQ005211