ST10 PU AND RUBBER (NEW)

Stylish, Comfortable and Lightly safety shoes based on a wealth of technical Experience in Japan

PU

MAKE TO ORDER!

NBR

ST1011

pair: 990 gr

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 35 s/d 46



ST1011 R

pair: 1220 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 35 s/d 46



ST1017

pair: 970 gr

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 35 s/d 46



ST1017 R

pair: 1200 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 35 s/d 46



ST1018

pair: 990 gr

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 35 s/d 46



ST1018 R

pair: 1230 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 35 s/d 46



⚠ Heat resistance Polyurethane 80 °C and Rubber 130 °C are the outsole melting point. This means that the shoes resist only on the hot floor for a few moments. Shoes are not recommended on hot floor for a long time.

INFINITY & SS PRO SERIES

Stylish, Comfortable and Lightly safety shoes based on a wealth of technical Experience in Japan

NBR

READY STOCK!

TS3011R

pair: 1085 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 34 s/d 46



TS8311

pair: 1050 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 34 s/d 46



TS3017R

pair: 1060 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 34 s/d 46



TS8317

pair: 1080 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 34 s/d 46



TS3022R

pair: 1200 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 34 s/d 46



TS8322

pair: 1200 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 36 s/d 46



⚠ Heat resistance Polyurethane 80 °C and Rubber 130 °C are the outsole melting point. This means that the shoes resist only on the hot floor for a few moments. Shoes are not recommended on hot floor for a long time.

INFINITY& EST SERIES

Stylish, Comfortable and durable safety shoes based on a wealth of technical Experience in Japan

MAKE TO ORDER!

READY STOCK!

ST 1011 D6

pair: 1020 gr

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46



Special Order

TS311EST

pair: 965 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 36 s/d 46



TS 3022 R D6

pair: 1250 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 36 s/d 46



Special Order

TS317EST

pair: 945 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 36 s/d 46



TS 3011 R D6

pair: 1100 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 36 s/d 46



Special Order

TS322EST

pair: 1120 gr

- Outsole : Nitril Rubber (NBR)
- Resistance : 130°C max of heat, Oil resistance
- Size : 36 s/d 46



⚠ Heat resistance Polyurethane 80 °C and Rubber 130 °C are the outsole melting point. This means that the shoes only hold on the hot floor with that temperature for a few moments. It is not recommended to use these shoes on hot floors for a long time.

SA & ANTISTATIC SERIES

Stylish, Comfortable and durable safety shoes based on a wealth of technical Experience in Japan

MAKE TO ORDER!

ST1011 T

pair:
990 gr

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance. Antistatic 0,1~100 M Ohm
- Size : 35 s/d 46



Antistatic

TS311EST AS

pair:
965 gr

- Outsole : NBR Rubber
- Resistance : 130°C max of heat, Antistatic 0,1~100 M Ohm
- Size : 36 s/d 46



Antistatic

ST1017 T

pair:
970 gr

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance Antistatic 0,1~100 M Ohm
- Size : 35 s/d 46



Antistatic

TS317EST AS

pair:
945 gr

- Outsole : NBR Rubber
- Resistance : 130°C max of heat, Antistatic 0,1~100 M Ohm
- Size : 36 s/d 46



Antistatic

ST1018 T

pair:
990 gr

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance Antistatic 0,1~100 M Ohm
- Size : 35 s/d 46



Antistatic

TS322EST AS

Antistatic

pair:
1120 gr



- Outsole: NBR Rubber
- Resistance: 130°C max of heat, Antistatic (0,1~100 M Ohm)
- Size: 36 s/d 46

Heat resistance Polyurethane 80 °C and Rubber 130 °C are the outsole melting point. This means that the shoes resist only on the hot floor for a few moments. Shoes are not recommended on hot floor for a long time.

OTHER SERIES

Stylish, Comfortable and durable safety shoes based on a wealth of technical Experience in Japan

MAKE TO ORDER!

ST 1011 WM

pair: 880 gr

Upper : Microfibre

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46



Special Order

ST 1011 WM T

pair: 880 gr

Upper : Microfibre

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46

Antistatic



Special Order

ST 1017 WM

pair: 850 gr

Upper : Microfibre

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46



Special Order

ST 1017 WM T

pair: 850 gr

Upper : Microfibre

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46

Antistatic



Special Order

ST 1018 WM

pair: 865 gr

Upper : Microfibre

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46



Special Order

ST 1018 WM T

pair: 865 gr

Upper : Microfibre

- Outsole : Polyurethane (PU)
- Resistance : 80°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46

Antistatic



Special Order

Heat resistance Polyurethane 80 °C and Rubber 130 °C are the outsole melting point. This means that the shoes resist only on the hot floor for a few moments. Shoes are not recommended on hot floor for a long time.

OTHER SERIES

Stylish, Comfortable and durable safety shoes based on a wealth of technical Experience in Japan

MAKE TO ORDER!

ST 1024 R

pair: 1280 gr

Zipper

- Outsole : Rubber (NBR)
- Resistance : 130°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46



Special Order

ST 1044 R

pair: 1430 gr

- Outsole : Rubber (NBR)
- Resistance : 130°C max of heat, Slip resistance Oil Resistance
- Size : 37 s/d 46



Special Order

ST 1022 R

pair: 1290 gr

- Outsole : Rubber (NBR)
- Resistance : 130°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46



Special Order

ST 1022 T R

pair: 1290 gr

- Outsole : Rubber (NBR)
- Resistance : 130°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46

Antistatic



Special Order

ST 1027 R

pair: 1280 gr

- Outsole : Rubber (NBR)
- Resistance : 130°C max of heat, Slip resistance Oil Resistance
- Size : 36 s/d 46



Special Order

Sneaker Series



⚠ Heat resistance Polyurethane 80 °C and Rubber 130 °C are the outsole melting point. This means that the shoes resist only on the hot floor for a few moments. Shoes are not recommended on hot floor for a long time.