A Lightweight Axisymmetric Electrostatic–Capillary Solver for Taylor-Cone Onset with Planned Experimental Validation

Ethan Yang, Li Ang Dong, Curtis Wai Ip Lau
Independent Schools Foundation Academy
Hong Kong SAR

October 16, 2026

Abstract

Analysis of Taylor-cone formation in electrospray systems requires a computational description of the coupling between electric stress and surface tension; however, the computational cost of detailed multiphysics models can limit systematic parameter studies. To address this issue, this paper presents a lightweight axisymmetric electrostatic–capillary framework for use on standard computers. The method combines sparse finite-difference electrostatics, an immersed representation of the liquid interface, and gas-side normal-field reconstruction to evaluate the Young–Laplace–Maxwell stress balance. Projected stress residuals and flank-field scaling provide complementary diagnostics of candidate cone geometries. Numerical verification covers four systematically refined manufactured-Poisson grids showing approximately second-order convergence, a curved-boundary refinement study, a multistart study of the shape optimizer, and a synthetic-image round trip of the extraction pipeline that meets its preset 1° angle and 2% profile acceptance limits over the two lowest noise levels. That round trip qualifies the extraction chain against analytic silhouettes only; it does not calibrate the chain against recorded images, so the published-image comparison of Section 7 is reported as a consistency check rather than as a measurement. The framework is offered as a reduced, transparent diagnostic tool; full cone–jet dynamics, unique physical onset prediction, and new laboratory validation remain future work.

Contents

1 Introduction **3**

2 Literature Review **4**

3 Research Question and Hypothesis **5**
3.1 Research Question 5
3.2 Hypothesis 5
3.3 Scope 5

4 Theoretical Model and Derivations **5**
4.1 Geometry, Coordinates, and Main Assumptions 6
4.2 Axisymmetric Laplace and Poisson Equations 6
4.3 Boundary Conditions 7
4.4 Finite-Difference Discretization 7

4.5 Classical Taylor-Cone Derivation . . . 8
4.6 Apex Singularity and Physical Regularization . . . 9
4.7 Maxwell Stress and Electric Pressure . . . 9
4.8 Interface Normal and Curvature . . . 10
4.9 Young–Laplace–Maxwell Residual . . . 10
4.10 Reduced Shape Optimization . . . 11
4.11 Effective Space-Charge Shielding . . . 11
4.12 Shielding Metric . . . 12
4.13 Nondimensional Interpretation . . . 12
4.14 Model-Based Onset Criterion . . . 13
4.15 Summary of Theoretical Deliverables . . . 13

5 Solver Architecture **13**
5.1 Implementation Overview . . . 13
5.2 Computational Pipeline . . . 14
5.3 Consumer-Hardware Design . . . 15
5.4 Interactive App . . . 15

6 Numerical Verification and Sensitivity **16**
6.1 Regular manufactured Poisson problem . . . 16
6.2 Curved-boundary refinement . . . 16
6.3 Independent fixed-cone finite-element comparison . . . 17
6.4 Angle and parameter sensitivity . . . 18
6.5 Synthetic-image measurement test . . . 19

7 Public Experimental Data and Balance Diagnosis **20**
7.1 Source and experimental conditions . . . 20
7.2 Photograph measurement . . . 21
7.3 Comparison with reported angles . . . 22
7.4 Extraction sensitivity . . . 24
7.5 Fixed-pressure stress-balance diagnosis . . . 24

8 Safety, Ethics, and Compliance **25**

9 Limitations **26**

10 Conclusion and Future Work **26**

1 Introduction

Electrospray is applied in many advanced systems, from biomolecular analysis to satellite propulsion. In a typical setup, a conductive liquid is fed to the tip of a capillary needle (nozzle) held at an applied voltage relative to a grounded extractor electrode. As the electric field deforms the liquid meniscus, outward electrostatic pull (Maxwell stress) competes with the inward pull of surface tension (capillary stress). When these two forces balance, the liquid deforms into a conical equilibrium known as a Taylor cone. This geometry has a classical theoretical half-angle of $\alpha_T \approx 49.29°$ (commonly referenced as 49.3°) in the ideal, charge-free, conducting limit [1].

Because emitter geometry and applied voltage determine onset stability, systematic parameter sweeps are essential for system design. However, full electrospray dynamics involve moving free boundaries, fluid flow, charge transport, and downstream jet breakup. Simulating these compounding effects usually requires expensive and computationally heavy commercial multiphysics platforms.

This project investigates to what extent a lightweight, mathematically transparent, reduced-order solver can capture onset-level Taylor-cone observables on standard consumer hardware.

Instead of replacing full multiphysics software, we develop a fast, two-dimensional axisymmetric Python solver focused on the core electrostatic–capillary stress balance (Figure 1). The framework combines an immersed-boundary finite-difference solver with an automated image-processing pipeline; the extraction chain is exercised on synthetic silhouettes, and the same balance diagnostics are applied to published cone-jet photographs.

Novelty. This work makes three primary contributions:

1. **Conditioning analysis of stress residuals:** amplitude-projected stress residuals produce a nearly flat optimization landscape near equilibrium. The objective is flat to within its discretization floor over roughly $\pm 1°$ around the minimum, while the position of that minimum shifts over several degrees as the grid resolution, cap radius and flank-sampling window are varied, so the residual magnitude alone does not pin down a unique cone geometry.
2. **Flank power-law crossing diagnostic:** flank-field scaling ($E_n^2 \propto \rho^p$) is introduced as a robust alternative observable. The half-angle at which the scaling exponent crosses the theoretical $p = -1$ threshold is monotonic and grid-convergent, recovering 49.14° to 49.23° across refinement levels (compared to the ideal 49.29°).
3. **Accessible solver and balance diagnosis:** we deliver a solver capable of running production grids in approximately 0.46 s on a consumer laptop, compared against an independent body-fitted finite-element reference, exercised on twelve synthetic test images, and applied as a consistency check to published ethanol cone-jet photographs.

The project has three validation layers. First, the theoretical layer checks the classical Taylor-cone benchmark. Second, the numerical layer verifies the finite-difference electrostatic solver using manufactured solutions, grid-refinement and scaling tests, and internal consistency checks. Third, after school supervision and approval, the experimental layer will image Taylor-cone formation and compare extracted interface profiles, cone half-angles, and onset-voltage trends against simulation outputs. This paper documents the theory, solver architecture, and the numerical and published-image comparisons completed so far.




Figure 1: Physical system schematic (axisymmetric cross-section, not to scale). A metal needle held at potential V_0 feeds conducting liquid to its tip, where the meniscus forms a Taylor cone: at onset the gas–liquid interface makes the classical half-angle $\alpha \approx 49.3^\circ$ with the symmetry axis when the Maxwell stress $\frac{1}{2}\varepsilon_0 E_n^2$ balances the capillary stress $\gamma\kappa$. The grounded extractor electrode ($\phi = 0$) sits at electrode spacing L and carries a central aperture through which the spray passes; the axial dimension is compressed (break marks on the dimension line) so that the meniscus and the electrode can be drawn at one scale. Electric field lines leave the conductor normal to its surface and terminate on the electrode.

2 Literature Review

Taylor established the foundational electrostatic analysis of conducting drops in electric fields [1]. In the ideal electrostatic limit the exterior potential satisfies Laplace's equation and the conical conducting boundary imposes a Legendre-function condition; balancing Maxwell stress against capillary stress yields an equipotential cone with a 49.3° half-angle. This result is a benchmark for the present work rather than a contribution of it.

Subsequent studies and reviews show that practical electrospray operation extends well beyond this static limit. Fernández de la Mora reviewed the fluid dynamics of Taylor cones and cone-jets, emphasizing that cone formation, emitted current, and downstream breakup are separate physical regimes [2]. Melcher and Taylor formulated the broader electrohydrodynamic stress-balance concepts at fluid interfaces [3], and Saville reviewed the Taylor–Melcher leaky-dielectric model,

which accounts for finite liquid conductivity, surface charge, and tangential electric stresses [4]. Fernández de la Mora and Loscertales studied the current emitted by highly conducting Taylor cones [5], Gañán-Calvo connected Taylor-type electrostatic solutions to cone-jet scaling laws [6], and Hartman and coauthors modeled cone-jet electrospray behavior with additional physical complexity [7].

These studies define the scope of our work. A reduced-order onset model should accurately reproduce the classical Taylor limit in the charge-free conducting regime without overclaiming full electrohydrodynamic prediction. Accordingly, our solver omits fluid flow, surface-charge conservation, and droplet breakup, instead focusing on a transparent axisymmetric electrostatic–capillary formulation with effective Poisson space-charge closures and image-based stress diagnostics. The intended contribution is accessibility and transparency: a sparse Python implementation that can be inspected, tested, and run on consumer hardware for onset-level parameter studies.

3 Research Question and Hypothesis

3.1 Research Question

The central research question is:

> To what extent can a lightweight two-dimensional axisymmetric finite-difference solver—coupling immersed-boundary Laplace/Poisson electrostatics, electrostatic–capillary stress diagnostics, and synthetic-image extraction—reproduce classical Taylor-cone benchmarks and diagnose stress balances in experimental cone-jet profiles on consumer hardware?

3.2 Hypothesis

We hypothesize that an immersed-boundary axisymmetric solver will converge at second order, agree with independent body-fitted finite-element solutions within $< 1\%$ for interface pressures, and recover the classical 49.29° Taylor angle via flank-field scaling. Furthermore, when paired with contour extraction validated on synthetic benchmarks (targeting $< 1^\circ$ angle error), the static fixed-pressure stress balance will quantify where real flowing cone-jets depart from purely static electrostatic–capillary equilibrium as voltage increases.

3.3 Scope

This study focuses strictly on onset-level axisymmetric geometry, interface field reconstruction, and static normal-stress balance. Downstream jet breakup, transient fluid flow, and plume dynamics are excluded to isolate how much physical insight can be extracted from a rapid, reduced-order electrostatic model.

4 Theoretical Model and Derivations

This section gives the mathematical foundation of the solver. The model is intentionally reduced-order: it keeps the electrostatic–capillary balance that determines Taylor-cone onset geometry while avoiding a full transient multiphase CFD calculation. The purpose of the derivation is therefore not to claim complete electrospray prediction, but to show exactly which equations are solved, which assumptions are made, and which quantities can be compared to experiment.

4.1 Geometry, Coordinates, and Main Assumptions

The gas and liquid domains are treated in cylindrical coordinates (r, θ, z) with $r \geq 0$. The model assumes axisymmetry, so all fields are independent of θ. The electric potential is $\phi(r, z)$ and the electric field is

$$\mathbf{E} = -\nabla\phi. \tag{1}$$

In cylindrical coordinates under axisymmetry,

$$\mathbf{E} = E_r\mathbf{e}_r + E_z\mathbf{e}_z, \qquad E_r = -\frac{\partial\phi}{\partial r}, \qquad E_z = -\frac{\partial\phi}{\partial z}. \tag{2}$$

The liquid–gas interface is represented as a graph

$$r = R(z), \tag{3}$$

which is adequate for onset-level Taylor-cone shapes before overturning, breakup, or strongly non-axisymmetric dynamics. The conducting-liquid approximation treats the liquid as an equipotential boundary in this model. This is appropriate as a starting limit for the classical Taylor cone, but later leaky-dielectric extensions would require solving additional equations inside the liquid.

4.2 Axisymmetric Laplace and Poisson Equations

Electrostatics obeys Gauss's law,

$$\nabla \cdot \mathbf{D} = \rho_e, \tag{4}$$

where $\mathbf{D} = \varepsilon_0\mathbf{E}$ in the gas domain and ρ_e is the gas-domain charge density. Since $\mathbf{E} = -\nabla\phi$,

$$\nabla \cdot (-\varepsilon_0\nabla\phi) = \rho_e. \tag{5}$$

For constant gas permittivity, this becomes Poisson's equation,

$$\nabla^2\phi = -\frac{\rho_e}{\varepsilon_0}. \tag{6}$$

The charge-free case $\rho_e = 0$ reduces to Laplace's equation,

$$\nabla^2\phi = 0. \tag{7}$$

For an axisymmetric scalar field, the Laplacian is

$$\nabla^2\phi = \frac{1}{r}\frac{\partial}{\partial r}\left(r\frac{\partial\phi}{\partial r}\right) + \frac{\partial^2\phi}{\partial z^2}. \tag{8}$$

Thus the actual PDE solved by the numerical core is

$$\frac{1}{r}\frac{\partial}{\partial r}\left(r\frac{\partial\phi}{\partial r}\right) + \frac{\partial^2\phi}{\partial z^2} = -\frac{\rho_e(r, z)}{\varepsilon_0}. \tag{9}$$

4.3 Boundary Conditions

The simplified electrostatic problem is closed by boundary conditions representing the powered liquid/conductor, grounded electrode, symmetry axis, and artificial outer boundary:

$$\phi = V_0 \qquad \text{on powered conductor or ideal liquid surface,} \tag{10}$$

$$\phi = 0 \qquad \text{on grounded extractor electrode,} \tag{11}$$

$$\frac{\partial \phi}{\partial r} = 0 \qquad \text{on the axis } r = 0, \tag{12}$$

$$\phi = \phi_\infty \quad \text{or} \quad \frac{\partial \phi}{\partial n} = 0 \qquad \text{on far computational boundaries.} \tag{13}$$

The axis condition is not optional: it is required because the potential must remain finite and smooth as $r \to 0$. Far-boundary conditions are numerical approximations; their influence is quantified in Section 6 by enlarging the computational domain and by replacing the far-field condition with a grounded outer boundary.

4.4 Finite-Difference Discretization

Let the grid nodes be

$$r_i = i\Delta r, \qquad z_j = z_{\min} + j\Delta z, \tag{14}$$

where $i = 0, \ldots, n_r - 1$ and $j = 0, \ldots, n_z - 1$. Denote $\phi_{i,j} \approx \phi(r_i, z_j)$. Expanding Eq. (8),

$$\nabla^2 \phi = \frac{\partial^2 \phi}{\partial r^2} + \frac{1}{r}\frac{\partial \phi}{\partial r} + \frac{\partial^2 \phi}{\partial z^2}. \tag{15}$$

For interior nodes with $r_i > 0$, the solver uses centered finite differences:

$$\frac{\partial^2 \phi}{\partial r^2} \approx \frac{\phi_{i+1,j} - 2\phi_{i,j} + \phi_{i-1,j}}{\Delta r^2}, \tag{16}$$

$$\frac{\partial \phi}{\partial r} \approx \frac{\phi_{i+1,j} - \phi_{i-1,j}}{2\Delta r}, \tag{17}$$

$$\frac{\partial^2 \phi}{\partial z^2} \approx \frac{\phi_{i,j+1} - 2\phi_{i,j} + \phi_{i,j-1}}{\Delta z^2}. \tag{18}$$

Therefore the discrete operator at $r_i > 0$ is

$$(\nabla_h^2 \phi)_{i,j} = \frac{\phi_{i+1,j} - 2\phi_{i,j} + \phi_{i-1,j}}{\Delta r^2} + \frac{1}{r_i}\frac{\phi_{i+1,j} - \phi_{i-1,j}}{2\Delta r} + \frac{\phi_{i,j+1} - 2\phi_{i,j} + \phi_{i,j-1}}{\Delta z^2}. \tag{19}$$

This equation produces a sparse matrix because each row couples only to the node itself and its nearest neighbors.

At the axis $r = 0$, Eq. (8) appears singular, but smooth axisymmetric functions satisfy $\partial_r \phi(0, z) = 0$. Using the limiting identity

$$\lim_{r \to 0} \left(\frac{\partial^2 \phi}{\partial r^2} + \frac{1}{r}\frac{\partial \phi}{\partial r} \right) = 2\frac{\partial^2 \phi}{\partial r^2}\bigg|_{r=0}, \tag{20}$$

together with a reflected ghost value $\phi_{-1,j} = \phi_{1,j}$ gives the regularized axis stencil

$$(\nabla_h^2 \phi)_{0,j} = \frac{4(\phi_{1,j} - \phi_{0,j})}{\Delta r^2} + \frac{\phi_{0,j+1} - 2\phi_{0,j} + \phi_{0,j-1}}{\Delta z^2}. \tag{21}$$

This stencil is one of the key numerical details tested by the solver.

4.5 Classical Taylor-Cone Derivation

The Taylor-cone benchmark comes from the ideal limit of a perfectly conducting liquid in a charge-free gas. Near the apex, spherical coordinates (ρ, ϑ) are convenient, where ρ is distance from the apex and ϑ is measured from the axis. Axisymmetric Laplace's equation is

$$\frac{1}{\rho^2}\frac{\partial}{\partial \rho}\left(\rho^2 \frac{\partial \phi}{\partial \rho}\right) + \frac{1}{\rho^2 \sin\vartheta}\frac{\partial}{\partial \vartheta}\left(\sin\vartheta \frac{\partial \phi}{\partial \vartheta}\right) = 0. \tag{22}$$

Seek separated solutions of the form

$$\phi(\rho, \vartheta) = A\rho^{\nu} F(\vartheta). \tag{23}$$

Substitution gives the angular equation

$$\frac{1}{\sin\vartheta}\frac{d}{d\vartheta}\left(\sin\vartheta \frac{dF}{d\vartheta}\right) + \nu(\nu+1)F = 0. \tag{24}$$

With $\mu = \cos\vartheta$, this becomes Legendre's equation,

$$\frac{d}{d\mu}\left[(1-\mu^2)\frac{dF}{d\mu}\right] + \nu(\nu+1)F = 0, \tag{25}$$

so the regular axisymmetric solution is

$$F(\vartheta) = P_{\nu}(\cos\vartheta). \tag{26}$$

Thus

$$\phi(\rho, \vartheta) = A\rho^{\nu} P_{\nu}(\cos\vartheta). \tag{27}$$

The electric field magnitude scales as

$$E \sim |\nabla\phi| \sim \rho^{\nu-1}. \tag{28}$$

Maxwell pressure therefore scales as

$$p_E \sim \varepsilon_0 E^2 \sim \rho^{2\nu-2}. \tag{29}$$

For a cone, the characteristic capillary pressure scales as

$$p_{\gamma} \sim \frac{\gamma}{\rho}. \tag{30}$$

A self-similar conical equilibrium requires these two stress scales to match:

$$2\nu - 2 = -1. \tag{31}$$

Therefore

$$\nu = \frac{1}{2}. \tag{32}$$

The potential near a Taylor cone must consequently scale as

$$\phi(\rho, \vartheta) = A\rho^{1/2} P_{1/2}(\cos\vartheta). \tag{33}$$

A perfect conductor is an equipotential. If the conical surface lies at $\vartheta = \vartheta_0$ and the cone potential is chosen as the reference value, the angular factor must vanish on the cone:

$$P_{1/2}(\cos\vartheta_0) = 0. \tag{34}$$

The physically relevant root is

$$\vartheta_0 \approx 130.7^\circ. \tag{35}$$

The semi-vertical half-angle measured inside the liquid cone is therefore

$$\alpha_T = 180^\circ - \vartheta_0 \approx 49.3^\circ. \tag{36}$$

This is the central analytical benchmark used by the solver. The result is not claimed as new; rather, reproducing it establishes that the model is connected to the correct classical limit.

4.6 Apex Singularity and Physical Regularization

Because $\nu = 1/2$, the ideal Taylor electric field behaves as

$$E \sim \rho^{-1/2}. \tag{37}$$

Thus the ideal mathematical solution predicts

$$E \to \infty \qquad \text{as} \qquad \rho \to 0. \tag{38}$$

This singularity is useful theoretically because it explains why the apex is the dominant high-field region, but it cannot persist physically. Real systems regularize the apex field through finite apex radius, emitted charge, space charge, liquid conductivity, viscosity, finite molecular scales, and non-static cone-jet dynamics. In this project, the numerical model regularizes the singularity through finite grid resolution and through optional Poisson space-charge shielding closures. This is why the space-charge extension is physically motivated even though it remains phenomenological.

4.7 Maxwell Stress and Electric Pressure

The electrostatic Maxwell stress tensor in a medium of permittivity ε is

$$\mathbf{T}_E = \varepsilon \left(\mathbf{E} \otimes \mathbf{E} - \frac{1}{2} E^2 \mathbf{I} \right). \tag{39}$$

The normal electric traction on an interface with unit normal $\mathbf{n}$ is

$$\mathbf{n} \cdot \mathbf{T}_E \mathbf{n} = \varepsilon \left[(\mathbf{E} \cdot \mathbf{n})^2 - \frac{1}{2} E^2 \right]. \tag{40}$$

For an ideal conductor at equilibrium, the electric field inside the liquid is zero and the gas-side tangential electric field vanishes at the conducting surface. Therefore $E = E_n$ on the gas side, and the electric normal pressure pulling on the interface reduces to

$$p_E = \frac{\varepsilon_0}{2} E_n^2. \tag{41}$$

This equation is the source of the important voltage scaling: since $E \propto V_0$ for a linear Laplace problem, $p_E \propto V_0^2$.

4.8 Interface Normal and Curvature

For an interface represented by $r = R(z)$, define the implicit level-set function

$$F(r, z) = r - R(z). \tag{42}$$

A unit normal pointing toward increasing r is

$$\mathbf{n} = \frac{\nabla F}{|\nabla F|} = \frac{(1, -R_z)}{\sqrt{1 + R_z^2}}. \tag{43}$$

The normal electric field sampled at the interface is

$$E_n = \mathbf{E} \cdot \mathbf{n} = \frac{E_r - R_z E_z}{\sqrt{1 + R_z^2}}. \tag{44}$$

Here E_n represents the magnitude of the normal electric field component evaluated on the gas side of the interface. Since the Maxwell stress is proportional to E_n^2, the sign convention does not affect the pressure balance. The axisymmetric curvature of the surface of revolution is

$$\kappa = \frac{1}{R\sqrt{1 + R_z^2}} - \frac{R_{zz}}{(1 + R_z^2)^{3/2}}. \tag{45}$$

The first term is the azimuthal curvature generated by rotating the curve about the axis, and the second term is the meridional curvature of the curve in the (r, z) plane. This is the *sum* of the two principal curvatures, $\kappa = \kappa_1 + \kappa_2$, not the mean curvature $(\kappa_1 + \kappa_2)/2$. The Young–Laplace equation in the form $\gamma\kappa = \Delta p$ uses this sum-curvature convention. This expression is used directly in the residual computation.

4.9 Young–Laplace–Maxwell Residual

For a static conducting liquid interface, capillary pressure balances a constant pressure offset and electric pressure:

$$\gamma\kappa = \Delta p + \frac{\varepsilon_0}{2} E_n^2. \tag{46}$$

Rearranging gives the pointwise residual

$$\mathcal{R}(z) = \gamma\kappa(z) - \Delta p - \frac{\varepsilon_0}{2} E_n(z)^2. \tag{47}$$

A perfect solution of the reduced static model would satisfy $\mathcal{R}(z) = 0$ along the entire interface. In practice, the solver evaluates a candidate interface on a set of N arclength samples with weights w_m, and reports the weighted RMS residual

$$\mathcal{R}_{\mathrm{RMS}} = \left(\frac{\sum_{m=1}^{N} w_m \, \mathcal{R}(z_m)^2}{\sum_{m=1}^{N} w_m} \right)^{1/2}. \tag{48}$$

Since Δp is an unknown constant pressure offset, the implementation removes its weighted-mean contribution by choosing

$$\Delta p = \frac{\sum_{m=1}^{N} w_m \left(\gamma\kappa(z_m) - \frac{\varepsilon_0}{2} E_n(z_m)^2 \right)}{\sum_{m=1}^{N} w_m}. \tag{49}$$

This makes the residual measure shape-dependent imbalance rather than an arbitrary constant pressure offset. The residual is therefore a diagnostic of physical balance, not merely a numerical iteration error.

4.10 Reduced Shape Optimization

A free-boundary problem would solve simultaneously for the interface shape and the electric field. The current solver uses a lower-dimensional approximation: the interface is restricted to an analytic cone-family shape with a small number of shape parameters, such as half-angle and apex radius. Because the applied voltage is not known in advance for a shape that is to be tested against a scale-free balance, the optimizer minimizes an amplitude-projected residual. Writing $p_\gamma = \gamma\kappa$ and $e = E_n/V_0$, and letting $\langle\cdot\rangle_w$ denote an arclength-weighted mean over the fitted flank window, the projection subtracts both weighted means,

$$\tilde{a} = p_\gamma - \langle p_\gamma\rangle_w, \qquad \tilde{b} = e^2 - \langle e^2\rangle_w, \tag{50}$$

and eliminates the unknown stress amplitude in closed form,

$$u = \frac{\langle \tilde{a}\tilde{b}\rangle_w}{\langle \tilde{b}^2\rangle_w}, \qquad \mathcal{R}_{\mathrm{proj}} = \tilde{a} - u\,\tilde{b}, \qquad J(\mathbf{a}) = \langle \mathcal{R}_{\mathrm{proj}}^2\rangle_w^{1/2}. \tag{51}$$

The best-fit amplitude u also yields a predicted onset voltage $V_0^* = \sqrt{2u/\varepsilon_0}$ wherever $u > 0$. Candidate shapes whose interface cannot be sampled or whose projection is degenerate are assigned a large fixed rejection value rather than a smooth penalty. This formulation keeps the problem computationally light and interpretable. Its limitation is that the discretized boundary representation can shift the optimized angle away from the ideal Taylor value, so an optimized angle carries a numerical error that the parameterization itself cannot remove; the sensitivity study of Section 6 quantifies its size.

4.11 Effective Space-Charge Shielding

Poisson's equation requires a closure for ρ_e. The project uses a hierarchy of effective closures rather than claiming a complete microscopic emission model. The Gaussian closure is

$$\rho_e(r,z) = \rho_0 \exp\left[-\frac{(r-r_a)^2 + (z-z_a)^2}{2\ell^2}\right], \tag{52}$$

where (r_a, z_a) is the charge-cloud center and ℓ is the cloud width. This closure is useful for controlled numerical experiments because the location, sign, and magnitude of charge are explicit.

The threshold closure activates charge only in high-field regions:

$$\rho_e = \rho_{\max}\left[1 - \exp\left(-\frac{|\mathbf{E}| - E_c}{E_s}\right)\right]_+, \tag{53}$$

where E_c is a critical field scale, E_s controls smoothness, and $\rho_{\max}$ is a saturation density. The notation $[x]_+ = \max(x, 0)$ ensures that nodes with $|\mathbf{E}| < E_c$ produce zero effective charge.

Because ρ_e depends on $\mathbf{E}$ and $\mathbf{E}$ depends on ϕ, the threshold model is nonlinear. The solver uses fixed-point iteration:

$$\nabla^2\phi^{(k+1)} = -\rho_e^{(k)}/\varepsilon_0, \tag{54}$$

$$\mathbf{E}^{(k+1)} = -\nabla\phi^{(k+1)}, \tag{55}$$

$$\widetilde{\rho}_e^{(k+1)} = F(|\mathbf{E}^{(k+1)}|), \tag{56}$$

$$\rho_e^{(k+1)} = (1-\omega)\rho_e^{(k)} + \omega\widetilde{\rho}_e^{(k+1)}, \tag{57}$$

where $0 < \omega \le 1$ is an under-relaxation parameter. After the first iteration, the loop stops once the relative changes in ρ_e, in ϕ, and in the peak field magnitude are all below a prescribed tolerance, or when a maximum iteration count is reached.

4.12 Shielding Metric

To quantify field reduction, the solver compares a space-charge solution against a charge-free Laplace reference. A local region-of-interest metric is

$$S_E = 1 - \frac{\max_{\Omega_{\mathrm{ROI}}} |\mathbf{E}_{\mathrm{shielded}}|}{\max_{\Omega_{\mathrm{ROI}}} |\mathbf{E}_{\mathrm{Laplace}}|}. \tag{58}$$

A positive value means the peak field in the chosen apex-local region is reduced relative to the Laplace case. A negative value indicates either field enhancement, sign sensitivity, or that the chosen region is dominated by boundary artifacts. The region of interest is important because global peak fields may occur at electrode corners or artificial computational boundaries rather than at the cone apex.

4.13 Nondimensional Interpretation

Let L be a characteristic length scale and V_0 the applied voltage scale. Define

$$\hat{r} = \frac{r}{L}, \qquad \hat{z} = \frac{z}{L}, \qquad \hat{\phi} = \frac{\phi}{V_0}. \tag{59}$$

The electric field scale is

$$E_0 = \frac{V_0}{L}. \tag{60}$$

The electric pressure scale is

$$p_{E,0} = \varepsilon_0 \frac{V_0^2}{L^2}, \tag{61}$$

while the capillary pressure scale is

$$p_{\gamma,0} = \frac{\gamma}{L}. \tag{62}$$

Their ratio is the electric Bond number

$$Bo_E = \frac{\varepsilon_0 V_0^2}{\gamma L}. \tag{63}$$

This dimensionless group expresses how strongly electric stress competes with surface tension. Increasing voltage raises Bo_E, while increasing surface tension lowers it. This relationship motivates experimental onset-voltage trends: larger surface tension or larger characteristic length scale generally requires higher voltage for comparable electric-capillary balance, although real electrospray onset also depends on conductivity, flow, electrode shape, and emission physics.

A dimensionless charge density can be defined as

$$\hat{\rho}_e = \frac{L^2 \rho_e}{\varepsilon_0 V_0}, \tag{64}$$

so the nondimensional Poisson equation becomes

$$\hat{\nabla}^2 \hat{\phi} = -\hat{\rho}_e. \tag{65}$$

This scaling clarifies why space charge is important when $L^2 \rho_e / (\varepsilon_0 V_0)$ is not negligible.

4.14 Model-Based Onset Criterion

The physical experiment will define onset as the lowest applied voltage at which a stable Taylor-cone-like interface persists for a fixed observation window. A simulation cannot observe stability directly unless it includes time-dependent fluid dynamics, so the solver must use a reduced static criterion. The planned model-based onset estimate is the lowest applied voltage satisfying three conditions:

1. the residual-minimizing interface is Taylor-cone-like and remains inside the computational geometry;
2. the half-angle lies in a physically plausible onset range near the classical Taylor-cone limit;
3. the RMS Young–Laplace–Maxwell residual falls below a pre-declared tolerance relative to the capillary pressure scale γ/L.

Equivalently, an auxiliary pressure-balance criterion may be reported when the apex-region Maxwell pressure becomes comparable to the capillary pressure scale:

$$\frac{\varepsilon_0 E_{n,\mathrm{apex}}^2/2}{\gamma/L} = O(1). \tag{66}$$

The exact threshold used for final comparison will be fixed before experimental data are analyzed. This prevents tuning the numerical onset criterion after seeing the measurements.

4.15 Summary of Theoretical Deliverables

The theoretical model produces the following measurable or computable quantities:

- potential $\phi(r, z)$;
- electric-field components E_r and E_z;
- electric-field magnitude $|\mathbf{E}|$;
- Maxwell pressure $\varepsilon_0 E_n^2/2$;
- interface curvature κ;
- Young–Laplace–Maxwell residual $\mathcal{R}$;
- residual-minimizing half-angle for a restricted interface family;
- space-charge shielding metric S_E;
- model-based onset-voltage estimate under a declared criterion.

These quantities directly connect the theory to the solver architecture and to the planned experimental comparison.

5 Solver Architecture

5.1 Implementation Overview

The solver is implemented as a modular Python package. Its main modules are summarized in Table 1. The design goal is to keep the numerical core transparent and testable while using sparse linear algebra for consumer-hardware feasibility.

Table 1: Main solver modules.

Module	Responsibility
`config.py`	Parameter dataclasses (physical, grid, solver, space charge)
`grid.py`	Axisymmetric grid and indexing convention
`operators.py`	Sparse Laplace/Poisson finite-difference operator
`boundary_conditions.py`	Dirichlet boundary insertion
`electrostatics.py`	Laplace/Poisson solve entry points
`taylor_analytical.py`	Analytic Taylor-cone potential for far-field boundary conditions
`fields.py`	Electric-field reconstruction and interpolation
`geometry.py`	ImplicitCone with C^1 rounded cap-flank geometry
`immersed.py`	Fractional-distance immersed Dirichlet stencils
`interface.py`	Interface geometry, curvature, half-angle extraction
`residual.py`	Young–Laplace–Maxwell residual diagnostics
`space_charge.py`	Gaussian and threshold space-charge closures
`optimization.py`	Cone-family shape optimization with onset projection
`verification.py`	Manufactured-solution and Taylor-angle verification helpers
`app_backend.py`	Streamlit-independent backend for interactive app
Imaging and extraction helpers (`experimental/`)	
`image_processing.py`	Image preprocessing and contour extraction
`profile_extraction.py`	Pixel-to-profile conversion and half-angle fitting
`synthetic_validation.py`	Synthetic image rendering and extraction tests
`comparison.py`	Profile alignment and geometric error metrics

5.2 Computational Pipeline

A typical solver run follows the sequence summarized in Figure 2:

1. Input physical and numerical parameters, including voltage, surface tension, domain size, and grid resolution.
2. Build a two-dimensional axisymmetric (r, z) grid.
3. Construct electrode and boundary masks (or use immersed boundary representation).
4. Assemble the sparse axisymmetric Laplace/Poisson matrix.
5. Apply boundary conditions (staircase or immersed Dirichlet stencils) and solve $A\boldsymbol{\phi} = \boldsymbol{b}$.
6. Reconstruct E_r, E_z, and $|\mathbf{E}|$.
7. Sample a candidate interface $R(z)$ from the ImplicitCone geometry.
8. Compute interface normals, curvature, Maxwell pressure (from immersed E_n reconstruction), capillary pressure, and residual.
9. For immersed free-boundary optimization, project out the onset voltage V_0^* per candidate.
10. Optionally update the space-charge closure and repeat the Poisson solve until convergence.
11. Return scalar diagnostics, field arrays and figure objects, and optionally a JSON summary of the run.




Figure 2: Computational workflow for the charge-free immersed formulation. Geometry and discretization are followed by the electrostatic solution and two interface diagnostics: stress-balance residuals and flank-field scaling. Voltage-amplitude projection is optional.

5.3 Consumer-Hardware Design

The solver uses sparse matrices rather than dense matrices. For a grid of $n_r \times n_z$ nodes, the number of unknowns scales as $n_r n_z$, while the finite-difference operator has only a small number of nonzero stencil entries per row. This allows small-to-moderate grids to run quickly on a standard laptop.

Computational Performance. Over the grid range measured here ($N = 675$ to 85,073 points) the wall-clock time of a single-threaded immersed Laplace solve is fitted by $\mathcal{O}(N^{0.99})$. A production-quality 121×177 grid (21,417 points) solves in approximately 0.46 s on an Apple M4 laptop with 16 GB of memory. Sparse direct factorization is asymptotically superlinear in two dimensions, so this exponent should be read as an empirical description of the tested range rather than a bound.

5.4 Interactive App

A Streamlit application exposes basic parameters such as voltage, surface tension, electrode spacing, domain radius, grid resolution, and space-charge model. It is organized into four pages — Overview, Solver, Verification and Documentation — and returns scalar diagnostics together with visualizations of potential, electric-field magnitude, space-charge density, interface overlay, and

residual profile. The Verification page provides two checks: a recovered-angle test that sweeps the cone half-angle and locates the flank-field exponent crossing, and an imposed-Taylor identity test that compares the projected onset amplitude against the analytic value. Both impose the analytical Taylor potential on the outer boundary. The app is a demonstration and analysis interface; the scientific contribution remains the solver and validation workflow.

6 Numerical Verification and Sensitivity

The numerical assessment examines the discretization, treatment of curved boundaries, reconstruction of interface fields, and parameter sensitivity. A manufactured solution provides an exact reference for the regular operator, while an independent finite-element discretization is used to assess the curved-interface solution. Synthetic images with known geometries provide a separate evaluation of the measurement procedure.

6.1 Regular manufactured Poisson problem

The source-derived quartic test uses $\phi = r^4 + z^4 + r^2 z^2$ and the axisymmetric source $18r^2 + 16z^2$. On grids 17×19, 33×37, 65×73, and 129×145, recorded RMS errors were 1.82×10^{-3}, 4.45×10^{-4}, 1.10×10^{-4}, and 2.73×10^{-5}. Consecutive observed orders were 2.035, 2.018, and 2.009.

Discretization error is evaluated as the RMS difference between the numerical and exact potentials at interior nodes. For halved mesh spacings, the observed order is $q = \log(e_h/e_{h/2})/\log 2$. As shown in Figure 3, the FD error decreases systematically with refinement, and the observed order approaches two. An independently assembled bilinear Q1 finite-element discretization exhibits the same asymptotic behavior. These results are consistent with second-order accuracy for the regular axisymmetric Poisson operator.




Figure 3: Regular-grid convergence. Errors are measured against the exact manufactured potential; h is the geometric mean of the radial and axial mesh spacings in model length units.

6.2 Curved-boundary refinement

The effect of curved-boundary representation is examined by comparing immersed and staircase discretizations of the same rounded cone, of 30° half-angle and 0.5 mm apex radius, on grids of

31×45, 45×65, 61×89, and 87×129. To maintain consistent spatial sampling, the potential is evaluated at the same 56 gas-side locations on all grids. The change between successive levels is defined by

$$D_\ell = \left[\sum_{j=1}^{56} \left(\phi_\ell(\mathbf{x}_j) - \phi_{\ell-1}(\mathbf{x}_j) \right)^2 \right]^{1/2} .$$

Figure 4 shows that D_ℓ decreases from 10.334 to 4.264 and 2.549 V for the immersed discretization. The corresponding staircase values are 25.731, 7.107, and 11.267 V. Apparent orders calculated from these changes are 2.854 and 1.429 for the immersed treatment, compared with 4.148 and -1.280 for the staircase treatment. The immersed formulation therefore exhibits a consistent decrease in inter-level variation over the tested grids, whereas the staircase representation produces a reversal at the finest pair of levels. This comparison characterizes the refinement sensitivity of the curved-boundary solution.




Figure 4: Curved-boundary refinement. Potential changes use fixed gas-side points; apparent orders are calculated from consecutive changes.

6.3 Independent fixed-cone finite-element comparison

An independent comparison is performed between the immersed finite-difference (FD) solver and a body-fitted, piecewise-linear P1 finite-element (FEM) discretization of the same charge-free electrostatic problem. The domain radius and axial extent are 12.5 and 10 mm, respectively. The rounded cone has a half-angle of 49.29°, an apex at $z = 8.6$ mm, and a cap radius of 50 μm. A potential of 1000 V is prescribed on the cone, with the outer boundary grounded. Three FD grids, 65×97, 129×193, and 257×385, are compared with successively refined FEM meshes. Both solutions are evaluated at common gas-side locations and at 41 interface positions over $z = 3$–6 mm.

The finest-level relative RMS differences are 0.024% for potential, 0.226% for the vector electric field, 0.381% for the interface-normal field, and 0.817% for Maxwell pressure $p_E = \varepsilon_0 E_n^2/2$. The projected-voltage difference is 1.071%, and the projected-residual difference is 2.518% when normalized by the RMS of the centered capillary pressure. Identical curvature, arclength weights, pressure projection, and voltage-amplitude definitions are used in the two calculations. The agreement in Figure 5 consequently extends from the primary potential solution to the derived interface stresses and projected residuals.




Figure 5: Fixed-cone FD–FEM comparison. (a) Gas-point differences. (b) Interface-normal field. (c) Maxwell pressure at 1000 V. (d) Amplitude-projected residual.

6.4 Angle and parameter sensitivity

The sensitivity of the angle diagnostics is assessed over candidate half-angles of 46°–52° by varying mesh resolution, domain size, cap size, flank-sampling window, and outer-boundary condition. Figure 6 compares the projected-residual landscape with the exponent obtained by fitting $E_n^2 \propto \rho^p$, where ρ denotes distance from the virtual cone vertex. Under the analytical Taylor far-field condition, the residual-minimizing angle moves within roughly 47.5°–50°, whereas the $p = -1$ crossing remains within 49.07°–49.25°. Replacing this boundary condition with a grounded outer boundary increases the residual and shifts the exponent curve. The two diagnostics therefore resolve different features: the crossing measures consistency with the imposed Taylor scaling, while the residual minimum reflects the finite-domain stress balance.

Initialization sensitivity is further examined using five angle–apex-radius starting pairs for Powell optimization on the 31×45 grid. The final half-angles span 40.20°–42.79°, and the apex-radius parameters range from 0.0704 to 0.0887 in model length units, that is 0.70 to 0.89 mm on the 10 mm model unit. Despite these distinct endpoints, the projected RMS residuals remain within 0.01257–0.01333 Pa (Figure 7). This weak variation in objective value indicates an angle–radius ambiguity in the fitted parameterization. Accordingly, the residual magnitude and the recovered geometry provide complementary information on the optimization result.




Figure 6: Angle sensitivity. Residual minima and field-exponent crossings respond differently to numerical settings.




Figure 7: Multistart optimization. Specified starts and final parameter pairs are paired with their final projected residuals; apex radii are plotted in millimetres, where one model length unit equals 10 mm.

6.5 Synthetic-image measurement test

The accuracy of image-based geometry extraction is assessed on analytic cone silhouettes. Each silhouette is a conical profile with a spherical-cap apex, drawn at 0.02 mm/pixel for a needle of radius 0.4 mm, and is pushed through the preprocessing, edge-detection, contour-extraction and flank-fitting chain used for recorded frames. The test matrix crosses three half-angles (45°, 49.29° and 55°) with four Gaussian noise levels whose standard deviations are 1.3, 4.0, 12.7 and 40.0 greyscale levels, corresponding to nominal signal-to-noise ratios of 40, 30, 20 and 10 dB.

Image scale and axis location are prescribed as calibration data: the symmetry axis is taken from the needle centerline, which is mounted on the optical axis and therefore known a priori, and the noise realization uses random seed 20260922. The absolute angle error is defined as $|\alpha_{\text{extracted}} - \alpha_{\text{true}}|$, and the profile nRMSE is the RMS radial difference from the analytic profile normalized

by the visible cone length. Over the two lowest noise levels, at which the acceptance criteria are asserted, the largest angle error is 0.027° and the largest profile nRMSE is 0.62%, and every accepted case satisfies both criteria (Figure 8). The angle criterion holds across all twelve cases; heavy noise degrades the profile but not the fitted slope, so at the highest noise level the 55° silhouette returns a profile nRMSE of 10.5% and exceeds the 2% profile criterion while its angle error remains 0.010°.

These values quantify the implementation accuracy of the extraction chain, not the uncertainty of a measurement. Because every silhouette is rendered from the same analytic profile that the fit is compared against, the test exercises the software path — rendering, thresholding, contour tracking and least-squares flank fitting — and does not represent illumination variation, contact-line pinning, optical distortion, or the finite resolution of a recorded frame. The extraction chain is therefore qualified for the numerical round trip only; the comparisons of Section 7 inherit the scope stated there.




Figure 8: Synthetic-image accuracy. Each marker is one analytic-image case; dashed lines show the preset 1° and 2% acceptance limits. Both axes are logarithmic.

7 Public Experimental Data and Balance Diagnosis

Scope. This section analyzes previously published ethanol cone-jet images and reported angles; no new laboratory measurements are presented, and the images and reported series belong to the source study. Because the synthetic qualification of the extraction pipeline (Section 6.5) covers only analytic silhouettes and does not calibrate the chain against recorded images, the angle comparison is presented as a consistency check between two published image-derived series rather than as validation of the solver.

7.1 Source and experimental conditions

The framework is applied to the ethanol cone-jet photographs and angle–voltage measurements reported by Yang et al. [8]. The photographs are obtained from Figure 5 of that study, and the full cone angles are digitized from Figure 6 and converted to half-angles using $\alpha = \theta/2$. The selected conditions correspond to a flow rate of $Q = 0.10$ μL/s, a nozzle-to-plate spacing of $H = 2$ mm, and an aperture diameter of $D = 2$ mm. The experimental inputs and numerical parameters are summarized in Table 2.

Table 2: Experimental inputs and numerical settings.

Quantity	Value	Source/status
Nozzle outer / inner diameter	0.30 / 0.16 mm	Yang et al., Sec. 1
Plate outer / aperture diameter	80 / 2 mm	Yang et al., Sec. 1; Fig. 6
Nozzle-to-plate spacing	2 mm	Yang et al., Fig. 6
Ethanol flow rate	0.10 μL/s	Yang et al., Figs. 5–6
Temperature; surface tension	25 °C; 0.022 N/m	Yang et al., Table 1
Image scale bar	300 μm / 191 pixels	Yang et al., Fig. 5
Outer-domain radius	80 mm	Numerical setting
Exposed needle length	5 mm	Numerical setting
Tip radius; local cell size	6 μm; 4 μm	Numerical setting
Pressure calibration voltage	1.7203 kV	Lowest reported point

The experimental geometry is represented in an axisymmetric (r, z) domain, with the nozzle exit at $z = 0$ and the grounded annular plate at $z = 2$ mm. The radial coordinate r is measured from the symmetry axis. The aperture and plate outer radii are 1 and 40 mm, respectively, as illustrated in Figure 9. The liquid surface and nozzle are held at the applied experimental voltage. The exposed needle length, tip regularization, and outer-domain dimensions are prescribed as numerical parameters.




Figure 9: Axisymmetric representation of the experimental case. Plate and aperture dimensions are reported inputs; the outer-domain radius is a numerical setting.

7.2 Photograph measurement

Four photographs acquired at 1.80, 1.95, 2.10, and 2.30 kV are analyzed using a common spatial calibration of $300/191 = 1.57068$ μm/pixel. A grayscale threshold of 110 is used for the nominal

extraction. The paired left and right boundaries determine the registered axis, and linear fits over 30–75% of the visible height yield the cone half-angle. The fitted virtual tip is used for profile alignment, whereas the visible height is measured directly from the nozzle exit to the observed tip. Figure 10 presents the extracted contours and registered axes superimposed on the source photographs.




Figure 10: Ethanol photographs with extracted contours. Source: Yang et al., Figure 5; contour and axis overlays are from the present analysis.

As the voltage increases from 1.80 to 2.30 kV, the extracted half-angle increases from 22.26° to 41.64°, while the visible height decreases from 301.6 to 147.6 μm (Table 3). The registered profiles in Figure 11 show the associated widening and axial shortening of the observed cone. Presenting the profiles on a common physical scale allows these geometric changes to be compared directly.

7.3 Comparison with reported angles

Quantitative comparison is restricted to the three voltage pairs whose mismatch is below 0.005 kV: 1.80, 1.95, and 2.10 kV. The photo-derived and reported half-angles are listed separately in Table 3. Their absolute differences are 1.970°, 1.520°, and 0.520°, respectively, corresponding to a mean absolute difference of 1.337° and an RMS difference of 1.468°. Figure 12 shows that both measurement series increase with voltage, with the largest matched discrepancy occurring at 1.80 kV. As a consistency check between two independently published image-derived series, the comparison is informative; because the extraction pipeline is qualified only by a synthetic round trip and not against recorded images, the absolute differences should not be read as a calibrated measurement error.




Figure 11: Registered profiles and visible heights. Dashed flank fits summarize the extracted contours.

Table 3: Photo-derived and reported half-angles.

Photo V (kV)	Reported V (kV)	Photo α (°)	Reported α (°)	$\lvert\Delta\alpha\rvert$ (°)	Photo height (μm)
—	1.7203	—	19.80	—	—
1.80	1.8005	22.26	24.23	1.970	301.6
1.95	1.9503	29.45	30.97	1.520	224.6
2.10	2.1000	36.34	36.86	0.520	174.3
—	2.2503	—	42.99	—	—
2.30	—	41.64	—	—	147.6

Dashes indicate an unpaired source observation. The reported series and photographs come from separate figures in the same experimental study.




Figure 12: Experimental angle comparison. Photo extraction and reported markers are distinguished; differences use the three matched voltages.

7.4 Extraction sensitivity

The influence of segmentation is assessed by repeating the extraction at grayscale thresholds of 90, 110, and 130. The maximum half-angle range is 0.204° for the three voltage-matched cases and 0.322° for the 2.30 kV photograph. At the nominal threshold, the RMS distances from the extracted contours to their straight-flank fits are 1.082, 0.837, 0.848, and 0.579 μm in ascending voltage order (Figure 13). The threshold-induced variation is smaller than the matched inter-source angle differences. These results distinguish the sensitivity of the extraction procedure from the geometric fit error and the discrepancy between measurement sources.




Figure 13: Extraction sensitivity. Threshold-induced angle changes and nominal straight-flank fit distances.

7.5 Fixed-pressure stress-balance diagnosis

The applicability of the constant-pressure balance is examined using the reported half-angle as a geometric input at each voltage. The gas-side electric field is computed at the corresponding applied voltage. Over the central 25–75% of the cone height, the residual and its area-weighted mean are defined as

$$R(z;V) = \gamma\kappa(z) - \frac{\varepsilon_0}{2}E_n(z;V)^2 - \Delta p, \qquad \overline{R} = \langle R \rangle_A.$$

The pressure offset is calibrated at the lowest-voltage condition according to

$$\Delta p = \left\langle \gamma\kappa - \frac{\varepsilon_0}{2}E_n^2 \right\rangle_{A,V=1.7203\,\mathrm{kV}} \simeq 6.458 \text{ Pa},$$

with field values interpolated from the precomputed solutions. This pressure is then held constant over the remaining voltage conditions. The mean residuals are approximately 0, −44, −123, −201, and −278 Pa for the five reported conditions. The increasingly negative residual indicates that the sum of electric pressure and the fixed pressure offset exceeds the capillary pressure of the reconstructed interface. Calibration imposes mean balance at the lowest voltage, while the spatial residual retains the local variation along the interface.

A spherical reference problem is used to assess the accuracy of the normal-field reconstruction; refining its local spacing from 6 to 2 μm reduces the mean field error from 0.440% to 0.094% and

the maximum error from 1.245% to 0.328%. The balance analysis is repeated with a 2 μm spacing, exposed needle lengths of 2 and 10 mm, and a tip radius of 12 μm. For each setting, the pressure is calibrated at the same lowest-voltage condition. As shown in Figure 14, the negative high-voltage residual trend persists across these variations. The combined results indicate a systematic departure from the constant-pressure static balance for the selected observed-angle series over the tested numerical settings.




Figure 14: Field and balance checks. (a) Sphere-reference normal-field errors. (b) Mean residuals at the reported angles for five numerical settings.

8 Safety, Ethics, and Compliance

The project contains a computational component and a proposed experimental validation component. The computational component can proceed independently. The physical experiment will not begin until appropriate school approval, local scientific review, risk assessment, and qualified adult supervision are secured.

The proposed experimental validation may involve high voltage and flammable solvent, so it must be treated as a hazardous-device and hazardous-chemical activity. Before purchasing, assembling, or operating any apparatus, the project team will prepare required approval forms, a full risk assessment, safety data sheet documentation, supervision plan, schematic review, operating boundaries, and emergency shutoff procedures. Operation will occur only in a supervised school or laboratory environment, with appropriate enclosure, interlock, current limiting, grounding, ventilation, PPE, and waste-disposal procedures as required by school and competition rules.

No live high-voltage demonstration is planned for a public fair setting. Experimental data, images, videos, and analysis results will be presented instead. The apparatus is intended for microfluidic Taylor-cone observation and image-based validation, not as a projectile device or propulsion demonstration. The project will comply with all applicable Hong Kong selection-fair and Regeneron ISEF-affiliated rules.

9 Limitations

The present solver is intentionally reduced-order. It does not solve full transient Navier–Stokes equations, full Taylor–Melcher leaky-dielectric surface charge conservation, droplet breakup, plume dynamics, or complete thruster performance. The effective space-charge closures are phenomenological models for studying Poisson shielding trends, not predictive emitted-current laws.

The axisymmetric assumption is appropriate for onset-level symmetric geometries but may fail after non-axisymmetric instabilities or downstream jet breakup appear. The finite-difference grid representation introduces geometric error, especially near sharp conical interfaces. The refinement study quantifies this: the recovered half-angle approaches the ideal Taylor value as the grid is refined (49.14°, 49.20° and 49.23° at the three tested levels), so the remaining deviation is a measured discretization error rather than an unquantified one.

Experimental validation will also have limitations. Cone-angle extraction depends on image resolution, optical alignment, lighting, threshold selection, calibration accuracy, and frame selection. Onset voltage may depend on fluid impurities, humidity, flow stability, electrode condition, and subjective stability criteria unless carefully standardized. Therefore, final conclusions will be stated in terms of quantified agreement and uncertainty rather than exact prediction.

10 Conclusion and Future Work

This project develops a lightweight sparse Python solver for onset-level Taylor-cone modeling. The solver couples an axisymmetric electrostatic solution to a Young–Laplace–Maxwell interface residual, reconstructs the interface field on a rounded cone, and recovers the classical Taylor half-angle. Its discretization is verified against manufactured solutions, against a staircase representation of the same curved boundary, and against an independent body-fitted finite-element discretization.

The verification study reported in Section 6 covers an independent finite-element comparison, curved-boundary refinement, angle and parameter sensitivity, and a synthetic-image round trip of the extraction pipeline that meets its preset 1° angle and 2% profile acceptance limits over the two lowest noise levels. The public-image analysis of Section 7 reports a mean absolute half-angle difference of 1.337° between two published image-derived series and a systematic negative residual trend under a fixed-pressure closure. Because the extraction chain is qualified only for that numerical round trip and not against recorded images, the image-derived angles are presented as a published-image comparison rather than as a qualified measurement. The study therefore motivates the planned experimental validation rather than replacing it.

Future work includes improving sharp-interface boundary representation, coupling threshold space charge inside the shape-optimization loop, adding more physically constrained charge/current closures, extending toward leaky-dielectric effects where justified, and comparing against higher-fidelity simulations or published experimental datasets. The intended contribution is not to replace full multiphysics simulation, but to provide a transparent, reproducible, and computationally accessible model for Taylor-cone onset studies.

References

[1] G. I. Taylor. Disintegration of water drops in an electric field. *Proceedings of the Royal Society of London. Series A. Mathematical and Physical Sciences*, 280(1382):383–397, 1964.

[2] Juan Fernández de la Mora. The fluid dynamics of taylor cones. *Annual Review of Fluid Mechanics*, 39:217–243, 2007.

[3] J. R. Melcher and G. I. Taylor. Electrohydrodynamics: A review of the role of interfacial shear stresses. *Annual Review of Fluid Mechanics*, 1:111–146, 1969.

[4] D. A. Saville. Electrohydrodynamics: The taylor–melcher leaky dielectric model. *Annual Review of Fluid Mechanics*, 29:27–64, 1997.

[5] J. Fernández de la Mora and I. G. Loscertales. The current emitted by highly conducting taylor cones. *Journal of Fluid Mechanics*, 260:155–184, 1994.

[6] A. M. Gañán-Calvo. Cone-jet analytical extension of taylor's electrostatic solution and the asymptotic universal scaling laws in electrospraying. *Physical Review Letters*, 79(2):217–220, 1997.

[7] R. P. A. Hartman, D. J. Brunner, D. M. A. Camelot, J. C. M. Marijnissen, and B. Scarlett. Electrohydrodynamic atomization in the cone–jet mode: Physical modeling of the liquid cone and jet. *Journal of Aerosol Science*, 30(7):823–849, 1999.

[8] Pengfei Yang, Yuxing Peng, Hongliang Yi, and Jian Wu. Experimental study on ethanol electrostatic spray mode and Taylor cone-jet characteristics. *Journal of Experiments in Fluid Mechanics*, 39(3):54–62, 2025.