

# Where a Quantum Reservoir Works: A Transferable Operating Band

Markus Baumann<sup>\*</sup> , Itamar Fink<sup>\*</sup>, Johannes Wittmann<sup>\*</sup>, and Jonas Stein<sup>\*</sup> 

<sup>\*</sup>*QAR-Lab, Department of Computer Science, LMU Munich, Munich, Germany*

Corresponding author: markus.baumann@campus.lmu.de

**Abstract**—Quantum reservoir computing performs temporal machine learning by training only a linear readout on the measured outputs of a fixed quantum system, leaving the quantum dynamics itself untrained. This makes the approach attractive for near-term hardware, but it sharpens a question that has remained largely unresolved: which device settings render the fixed dynamics useful rather than merely high-dimensional. We address this question for a stateful dissipative gate-model reservoir and show that strong performance concentrates in a well-defined operating region governed by input drive, recurrent coupling, and controlled dissipation. This region is transferable: an operating band identified on a subset of tasks predicts effective settings on held-out tasks and held-out reservoir initializations alike. Mechanism ablations establish that the region is causal rather than incidental, and an inexpensive memory-based diagnostic recovers it prior to task-specific evaluation.

**Index Terms**—quantum reservoir computing, dissipative dynamics, memory capacity, phase diagrams, operating regimes

## I. INTRODUCTION

Reservoir computing rests on an unusually economical idea: a fixed dynamical system, left untrained, transforms an input signal into a high-dimensional trace of its recent history, and learning reduces to fitting a single linear readout on top of that trace [1], [2], [3], [4]. The dynamics are never optimized, only observed. This economy is precisely what makes the approach appealing for near-term quantum hardware: native quantum evolution can serve as the reservoir and only the classical readout must be trained [5], [6], [7], [8]. Yet the same economy relocates the entire burden of the method onto the fixed dynamics, and so onto a question that is easy to state and surprisingly hard to answer: what makes those dynamics useful?

Recent QRC work now spans noisy gate-model devices, continuous-variable and oscillator reservoirs, weak-measurement protocols, photonic reservoirs, noise-engineered reservoirs, and experimental optical memory control [9], [10], [11], [12], [13], [14]. Classical reservoir theory has long since refused the obvious answer. Usefulness is not maximal expressivity. A reservoir earns its keep by holding a balance—retaining recent input, forgetting old input in a controlled way, and exposing nonlinear functions of that history to the readout [15], [4]. A quantum reservoir inherits this lesson but complicates it, because the three ingredients are no longer free dials. They are downstream consequences of distinct physical resources: how strongly the input perturbs the carried state, how coherently the system mixes that state across its parts, and how

it is allowed to dissipate [7], [16], [17]. A large Hilbert space supplies dimension, but dimension alone preserves no memory; drive that is too strong overwrites history, and dynamics with no dissipation never forget in the way fading memory requires.

We take this seriously as an organizing principle rather than a caveat. For a stateful dissipative gate-model reservoir, we treat the space of these three resources as the proper setting in which to ask when the reservoir works, and we map it. The picture that emerges is not a single tuned operating point but a connected region—gentle input, nonmaximal coupling, controlled damping—in which good performance concentrates and from which it does not stray arbitrarily across tasks. The contribution of this paper is that region itself: its existence, its transfer across tasks and reservoir initializations, the mechanisms that sustain it, and a memory-based diagnostic that locates it before any task-specific search.

## II. PROTOCOL

**Reservoir.** The reservoir is a fixed quantum system that processes a scalar time series one step at a time, carrying its state forward as memory. Concretely, the state is a density matrix that is never reset between steps: each new input perturbs the state left behind by the previous step, so recent history accumulates in the system rather than being overwritten. The input enters as a small rotation whose angle is set by the current value,

$$\rho_{t,0} = U_{\text{in}}(u_t)\rho_{t-1,L}U_{\text{in}}^\dagger(u_t), \quad U_{\text{in}}(u_t) = \bigotimes_i R_y(\beta u_t). \quad (1)$$

The input strength  $\beta$  controls how strongly each step disturbs the carried state.

The perturbed state then evolves through a small number of identical layers. Each layer does three things in turn: it mixes each qubit locally with a frozen rotation, couples neighbors around a ring, and lets the qubits dissipate through a noise channel,

$$\rho_{t,\ell} = \mathcal{D}_\gamma^{\otimes n} \left[ U_\lambda U_{\text{mix}} \rho_{t,\ell-1} U_{\text{mix}}^\dagger U_\lambda^\dagger \right], \quad U_\lambda = \prod_{(i,j) \in E_{\text{ring}}} e^{-i\lambda Z_i Z_j}. \quad (2)$$

The coupling strength  $\lambda$  sets how much stored history is mixed across qubits, and the damping rate  $\gamma$  sets how quickly the system forgets. These three quantities— $\beta$ ,  $\lambda$ , and  $\gamma$ —are the only controls we vary; every gate is otherwise frozen, and




Fig. 1. Validation phase maps at the fixed  $\gamma = 0.12$  slice. The first panel uses all four tasks. Each following panel recomputes the map after removing one task from the validation aggregate. If the bright low-rank region remains in the same place, the operating band is not driven by a single task. Gold circles mark coordinates that repeatedly fall in the top validation quintile; the star marks the medoid of the primary band.

only a linear readout is trained on the measured outputs. Each control corresponds to one ingredient required by reservoir theory:  $\beta$  governs how new information competes with old memory,  $\lambda$  generates nonlinear mixing of past inputs, and  $\gamma$  provides the controlled forgetting on which fading memory depends. The space  $\theta = (\beta, \lambda, \gamma)$  is therefore not an arbitrary grid of knobs but the natural coordinate system in which to ask whether the reservoir is useful.

**Configuration.** Unless stated otherwise, the reservoir uses four qubits, two layers, ring coupling, uniform input injection, amplitude damping, and a readout built from single-qubit  $Z$  and ring-pair  $ZZ$  expectation values. Training is ridge regression on these features alone. The phase grid spans  $\beta/\pi = \{0, 0.02, 0.04, 0.07, 0.10, 0.22, 0.50\}$ ,  $\lambda/\pi = \{0, 0.05, 0.10, 0.12, 0.16, 0.28, 0.42\}$ , and  $\gamma = \{0, 0.05, 0.12, 0.22, 0.30\}$  over reservoir seeds 42–61. Hyperparameters are selected on validation data only; holdout data never participate in defining the operating region.

**Tasks, metric, and splits.** We use four scalar one-step prediction tasks with chronological splits. Mackey–Glass is a chaotic delay series [18], Lorenz uses the next  $x$  coordinate of an RK4-integrated Lorenz trajectory [19], NARMA10 is a nonlinear tenth-order memory benchmark [20], and Sunspots is the annual sunspot activity series from `statsmodels`. Mackey–Glass, Lorenz, and NARMA10 use washout/train/validation/holdout lengths 300/1600/400/400; Sunspots uses 20/150/50/60. Inputs are scaled to  $[-1, 1]$  and targets are standardized. The reported error is normalized mean-squared error,  $\text{NMSE} = \langle (y - \hat{y})^2 \rangle / (\text{Var}(y) + 10^{-12})$ , computed separately on validation and holdout splits. For each reservoir setting the ridge parameter is selected only by validation NMSE from  $\{10^{-8}, 10^{-7}, \dots, 10^3\}$ .

**Operating band.** To locate the useful region we rank, rather than threshold, performance. For each task  $j$  and reservoir seed  $s$ , a setting  $\theta$  receives a validation percentile rank  $r_{j,s}(\theta)$ , with lower rank meaning better validation error. We then define the operating band as the set of settings that land in the top

fraction  $p$  for at least a fraction  $q$  of all task-seed pairs,

$$B_{p,q} = \{\theta : \Pr_{j,s}[r_{j,s}(\theta) \leq p] \geq q\}. \quad (3)$$

Ranks are always formed within each task-seed replicate, so task scale and seed difficulty do not dominate the aggregate. This is deliberately a frequency-level definition, weaker than demanding a single universal optimum: it asks whether a region behaves well repeatedly across tasks and initializations. In leave-one-task or leave-one-seed tests, the band is built from the remaining replicates and then scored on the withheld replicate. In the holdout audit, the validation-defined band is frozen first and then evaluated once on holdout ranks and NMSE. Confidence intervals are nonparametric bootstrap percentile intervals for the mean with 50,000 resamples and a fixed random seed.

### III. EVIDENCE

Across the control space, low validation rank does not spread arbitrarily; it gathers into a compact, connected region, and relaxing the selection threshold grows that region smoothly rather than fragmenting it—the signature of a single operating regime rather than a scatter of coincidences (Fig. 1). The damping coordinate is selected by the validation scan, not fixed by hand: the strict  $B_{20,0.7}$  core lies at  $\gamma = 0.12$ , while the broader  $B_{30,0.7}$  band extends into neighboring nonzero damping slices (Fig. 2). A region that merely fit the four tasks jointly would prove little, so we test whether it survives the removal of the information it was built from. It does: when one task is withheld and the band is defined from the rest, the held-out task still lands in the top quartile on average, with mean validation rank 0.222 and CI  $[0.205, 0.239]$ ; when a seed is withheld instead, the held-out seed behaves the same way, with mean rank 0.162 and CI  $[0.146, 0.178]$ . The region is thus a search prior that generalizes across both task identity and reservoir initialization, not a fit to either.

The same validation-defined band also holds on data it never touched: after the band is frozen, evaluating once on the chronological holdout split leaves it top-quartile on unseen data




Fig. 2. Damping-slice check for the same validation-ranked grid. Bright color indicates better validation rank; the broader same-consistency band persists beyond the selected  $\gamma = 0.12$  slice.

TABLE I  
HOLDOUT PERFORMANCE AFTER VALIDATION-ONLY BAND SELECTION. MEANS ARE OVER TWENTY SEEDS PER TASK; “ALL” AVERAGES THE 80 TASK-SEED ROWS.

| Task         | Band NMSE | Medoid NMSE | Band rank |
|--------------|-----------|-------------|-----------|
| Mackey–Glass | 7.07e-05  | 6.08e-05    | 0.122     |
| Lorenz       | 1.43e-05  | 1.80e-05    | 0.167     |
| NARMA10      | 0.527     | 0.486       | 0.149     |
| Sunspots     | 0.215     | 0.210       | 0.235     |
| <b>All</b>   | 0.186     | 0.174       | 0.168     |

(Table I). Repeating the identical protocol on a nearby four-qubit, three-layer variant tests whether the phenomenon is tied to the exact depth choice; the table reports band existence, held-out rank, and Jaccard overlap with the base control region (Table II). That the band is real rather than cosmetic is confirmed by perturbing the dynamics that sustain it: removing damping, removing recurrent mixing, or replacing amplitude damping with dephasing each erases the region entirely, with retention values 0.00, 0.00, and 0.00 under the same criterion. The collapse is total rather than gradual, exactly as expected if the regime is held in place by input strong enough to write but not overwrite, mixing that builds nonlinear features, and damping that preserves usable memory rather than merely adding noise (Fig. 3). Finally, the region can be found before any task-specific search: memory capacity correlates strongly and negatively with validation rank,  $\rho_s = -0.88$ , as do the information-processing capacities [15], whereas raw feature diversity does not (Fig. 4).

#### IV. DISCUSSION AND SCOPE

For this reservoir family, useful learning is organized by a transferable operating regime rather than by task-specific tuning—a hypothesis whose credibility comes from variety. Four tasks with little in common, spanning smooth chaos, nonlinear memory, and irregular real-world data, obey the

TABLE II  
ARCHITECTURE ROBUSTNESS AFTER VALIDATION-ONLY BAND SELECTION. OVERLAP IS JACCARD OVERLAP WITH THE BASE BAND IN THE SHARED  $(\beta, \lambda, \gamma)$  GRID.

| Setting            | Band? | Held-out rank | Overlap |
|--------------------|-------|---------------|---------|
| 4q, 2 layers, Z+ZZ | yes   | 0.168         | 1.00    |
| 4q, 3 layers, Z+ZZ | yes   | 0.160         | 0.22    |




Fig. 3. Why the operating band is meaningful. (a) Bright coordinates are frequently selected by validation. (b–d) Removing damping, removing mixing, or replacing amplitude damping by dephasing concentrates rank loss around the same gold band, showing that the useful region depends on these mechanisms.

same region, and that region holds when any one task or any one seed is withheld; what survives this much variation is hard to dismiss as a fluke. The reading we draw is deflationary. The useful region is not picked out by Hilbert-space size or by feature diversity but by memory, which suggests that a quantum reservoir succeeds not because its state space is large but because drive, coupling, and dissipation together keep memory and nonlinearity in balance—the principle classical reservoir theory named long ago [15], [4]. This is also why the ablations bite: strip out damping or mixing and the regime does not weaken, it disappears. The boundaries are drawn on purpose. Everything here is simulated, on one architecture family, with measurement treated as free, so finite-shot noise, calibration drift, and readout cost are all absent and could each deform the regime [11], [21]; we therefore claim neither quantum advantage nor hardware efficiency. The claim is smaller and sturdier—that the operating regime is the right object to study, that it transfers, and that memory is how to find it.

#### V. CONCLUSION

The usefulness of a dissipative quantum reservoir is not a property of size alone but of where it is operated. Across tasks and reservoir initializations, strong performance gathers in a transferable region where input drive, recurrent coupling, and dissipation hold memory and nonlinearity in balance. The regime transfers, collapses under targeted mechanism removals,




Fig. 4. Memory-based diagnostics identify the operating region before task-specific search. (a) The task-free memory map shows  $\log(1 + MC)$  on the same  $\gamma = 0.12$  control slice as the phase maps. The gold operating-band points lie inside the structured memory-rich region, showing that the band is visible from reservoir dynamics alone. (b) Across all sampled settings and seeds, higher memory predicts lower validation rank, giving a global quantitative version of the same effect. (c) Screening efficiency: the fraction of genuinely good reservoirs retained as a function of how many settings are kept. Screening by memory or information-processing capacity recovers the useful settings far earlier than random selection, while raw feature diversity remains much weaker.

and can be found in advance by memory-based diagnostics rather than raw feature diversity. The result is intentionally limited: all experiments are simulated, measurement is treated as free, and finite shots, calibration drift, device noise, and readout cost remain outside the present claim.

#### Reproducibility appendix.

**Package.** The [project repository](#) contains the code, checked-in CSV/JSON results, and final figures used in this paper.

**Frozen reservoir.** The simulator evolves the full density matrix exactly, with no finite-shot sampling. It starts from  $\rho_0 = |0 \dots 0\rangle\langle 0 \dots 0|$  and is carried between time steps without reset. For each seed, `default_rng(s)` draws one fixed mixer  $U_{\text{mix}} = \bigotimes_i R_x(\theta_i)$  with  $\theta_i \sim U[0, 2\pi]$ ; this mixer is reused at every step and layer. Each layer applies  $U_\lambda U_{\text{mix}}$  on ring edges, then local amplitude damping. The readout is ridge regression on exact  $Z_i$  and ring-pair  $Z_i Z_j$  expectations, with an unpenalized intercept.

**Selection and diagnostics.** The  $(\beta, \lambda, \gamma)$  grid and task splits are in Sec. II. Ridge penalties  $\{10^{-8}, \dots, 10^3\}$  are chosen by validation NMSE only; holdout data are used only after the band is fixed. MC/IPC diagnostics use an independent  $U[-1, 1]$  drive of length 900, washout 150, ridge  $\alpha = 10^{-8}$ , and a 70/30 chronological split. MC sums held-out positive  $R^2$  over delays 1–10. IPC adds linear delays 1–20, quadratic Legendre delays 1–10, and ten cross-delay products, clipping negative  $R^2$  to zero. CIs are nonparametric bootstrap percentile intervals with 50,000 resamples and a fixed seed.

#### REFERENCES

- [1] W. Maass, T. Natschlager, and H. Markram, “Real-time computing without stable states: A new framework for neural computation based on perturbations,” *Neural Computation*, vol. 14, no. 11, pp. 2531–2560, 2002.
- [2] H. Jaeger and H. Haas, “Harnessing nonlinearity: Predicting chaotic systems and saving energy in wireless communication,” *Science*, vol. 304, no. 5667, pp. 78–80, 2004.
- [3] M. Lukoševičius and H. Jaeger, “Reservoir computing approaches to recurrent neural network training,” *Computer Science Review*, vol. 3, no. 3, pp. 127–149, 2009.
- [4] G. Tanaka *et al.*, “Recent advances in physical reservoir computing: A review,” *Neural Networks*, vol. 115, pp. 100–123, 2019.
- [5] K. Fujii and K. Nakajima, “Harnessing disordered-ensemble quantum dynamics for machine learning,” *Physical Review Applied*, vol. 8, p. 024030, 2017.
- [6] S. Ghosh, A. Opala, M. Matuszewski, T. Paterek, and T. C. H. Liew, “Quantum reservoir processing,” *npj Quantum Information*, vol. 5, p. 35, 2019.
- [7] J. Chen, H. I. Nurdin, and N. Yamamoto, “Temporal information processing on noisy quantum computers,” *Physical Review Applied*, vol. 14, p. 024065, 2020.
- [8] P. Mujal, R. Martínez-Peña, J. Nokkala, J. García-Bení, G. L. Giorgi, M. C. Soriano, and R. Zambrini, “Opportunities in quantum reservoir computing and extreme learning machines,” *Advanced Quantum Technologies*, vol. 4, p. 2100027, 2021.
- [9] J. Nokkala, R. Martínez-Peña, G. L. Giorgi, V. Parigi, M. C. Soriano, and R. Zambrini, “Gaussian states of continuous-variable quantum systems provide universal and versatile reservoir computing,” *Communications Physics*, vol. 4, p. 53, 2021.
- [10] L. C. G. Govia, G. J. Ribeill, G. E. Rowlands, H. K. Krovi, and T. A. Ohki, “Quantum reservoir computing with a single nonlinear oscillator,” *Physical Review Research*, vol. 3, p. 013077, 2021.
- [11] P. Mujal, R. Martínez-Peña, G. L. Giorgi, M. C. Soriano, and R. Zambrini, “Time-series quantum reservoir computing with weak and projective measurements,” *npj Quantum Information*, vol. 9, p. 16, 2023.
- [12] T. Kubota, Y. Suzuki, S. Kobayashi, Q. H. Tran, N. Yamamoto, and K. Nakajima, “Temporal information processing induced by quantum noise,” *Physical Review Research*, vol. 5, p. 023057, 2023.
- [13] J. García-Bení, G. L. Giorgi, M. C. Soriano, and R. Zambrini, “Scalable photonic platform for real-time quantum reservoir computing,” *Physical Review Applied*, vol. 20, p. 014051, 2023.
- [14] I. Paparelle *et al.*, “Experimental memory control in continuous-variable optical quantum reservoir computing,” *Nature Photonics*, vol. 20, pp. 413–420, 2026.
- [15] J. Dambre, D. Verstraeten, B. Schrauwen, and S. Massar, “Information processing capacity of dynamical systems,” *Scientific Reports*, vol. 2, p. 514, 2012.
- [16] R. Martínez-Peña and J.-P. Ortega, “Quantum reservoir computing in finite dimensions,” *Physical Review E*, vol. 107, p. 035306, 2023.
- [17] A. Sannia, R. Martínez-Peña, M. C. Soriano, G. L. Giorgi, and R. Zambrini, “Dissipation as a resource for quantum reservoir computing,” *Quantum*, vol. 8, p. 1291, 2024.
- [18] M. C. Mackey and L. Glass, “Oscillation and chaos in physiological control systems,” *Science*, vol. 197, no. 4300, pp. 287–289, 1977.
- [19] E. N. Lorenz, “Deterministic nonperiodic flow,” *Journal of the Atmospheric Sciences*, vol. 20, no. 2, pp. 130–141, 1963.
- [20] K. S. Narendra and K. Parthasarathy, “Identification and control of dynamical systems using neural networks,” *IEEE Transactions on Neural Networks*, vol. 1, no. 1, pp. 4–27, 1990.
- [21] O. Ahmed, F. Tennie, and L. Magri, “Optimal training of finitely sampled quantum reservoir computers for forecasting of chaotic dynamics,” *Quantum Machine Intelligence*, vol. 7, p. 31, 2025.