

Where a Quantum Reservoir Works: A Transferable Operating Band

Markus Baumann^{*} , Itamar Fink^{*}, Johannes Wittmann^{*}, and Jonas Stein^{*} 

^{*}QAR-Lab, Department of Computer Science, LMU Munich, Munich, Germany

Corresponding author: markus.baumann@campus.lmu.de

Abstract—In quantum reservoir computing, a fixed quantum system transforms an input signal, and learning is reduced to training a simple linear readout on its measured outputs. Because the quantum dynamics are never optimized, the method is appealing for today’s hardware—but it leaves a basic question open: what settings actually make a fixed quantum system useful for learning, rather than just complex? We answer this for a dissipative gate-model reservoir by mapping how performance varies across three physical controls: how hard the input drives the system, how strongly its parts couple, and how fast it dissipates. Good performance does not appear randomly across these settings; it concentrates in a single, well-defined operating region. Crucially, this region transfers—a region identified on one set of tasks predicts the best settings for new tasks and new reservoir configurations. We confirm the region is real by showing it collapses when we remove the mechanisms that create it, and we show it can be located cheaply, in advance, using a simple memory diagnostic. Reservoir tuning thus becomes a search for a transferable, memory-preserving regime rather than a hunt for one benchmark-specific optimum.

Index Terms—quantum reservoir computing, dissipative dynamics, memory capacity, phase diagrams, operating regimes

I. INTRODUCTION

Reservoir computing uses a fixed dynamical system to transform recent input history, then trains only a linear readout [1]–[4]. This is attractive for quantum hardware, where native dynamics can supply the reservoir and only the classical readout is optimized [5]–[8]. Recent QRC work spans noisy gate-model devices, continuous-variable and oscillator reservoirs, weak-measurement protocols, photonic reservoirs, noise-engineered reservoirs, and experimental optical memory control [9]–[14]. But if the dynamics are fixed, the central question becomes: which settings make them useful?

Classical reservoir theory answers that usefulness is not maximal expressivity but a balance of memory, nonlinear mixing, and controlled forgetting [4], [15]. In a quantum reservoir these ingredients become physical resources: input drive, coherent coupling, and dissipation [7], [16], [17]. We therefore map this control space directly. For a stateful dissipative gate-model reservoir, good performance concentrates in a connected region—gentle input, nonmaximal coupling, controlled damping—that transfers across tasks and reservoir initializations. The contribution is the region itself, the mechanisms that sustain it, and a memory-based diagnostic that locates it before task-specific search.

II. PROTOCOL

A. Reservoir

The reservoir processes a scalar time series without resetting its density matrix, so the carried state stores recent history. At step t , the new input perturbs the previous state through a uniform rotation,

$$\rho_{t,0} = U_{\text{in}}(u_t)\rho_{t-1,L}U_{\text{in}}^\dagger(u_t), \quad U_{\text{in}}(u_t) = \bigotimes_i R_y(\beta u_t). \quad (1)$$

The input strength β controls how strongly each step writes into the carried state.

The perturbed state then passes through identical layers: a frozen local mixer, ring ZZ coupling, and a dissipative channel,

$$\begin{aligned} \rho_{t,\ell} &= \mathcal{D}_\gamma^{\otimes n} \left[U_\lambda U_{\text{mix}} \rho_{t,\ell-1} U_{\text{mix}}^\dagger U_\lambda^\dagger \right], \\ U_\lambda &= \prod_{(i,j) \in E_{\text{ring}}} e^{-i\lambda Z_i Z_j}. \end{aligned} \quad (2)$$

The coupling strength λ controls recurrent mixing and γ controls forgetting. We vary only $\theta = (\beta, \lambda, \gamma)$; all other gates are frozen and only a linear readout is trained. The three axes therefore correspond directly to input drive, nonlinear mixing, and controlled forgetting.

This is a minimal testbed, not an optimized model. Four qubits and two layers keep the phase grid searchable, the ring coupling still gives recurrent many-body mixing, and the modest $Z + ZZ$ readout observes local and nearest-neighbor correlations rather than the full density matrix.

B. Configuration

Unless stated otherwise, we use four qubits, two layers, ring coupling, uniform input injection, amplitude damping, and a readout from single-qubit Z and ring-pair ZZ expectations. Training is ridge regression on these features alone. The grid spans $\beta/\pi = \{0, 0.02, 0.04, 0.07, 0.10, 0.22, 0.50\}$, $\lambda/\pi = \{0, 0.05, 0.10, 0.12, 0.16, 0.28, 0.42\}$, and $\gamma = \{0, 0.01, 0.05, 0.12, 0.22, 0.30\}$ over seeds 42–61. Hyperparameters are selected on validation data only; holdout data never define the operating region. The resulting balanced panel contains $4 \times 20 = 80$ task-seed replicates for every grid coordinate.




Fig. 1. Validation phase maps at the fixed $\gamma = 0.12$ slice. The first panel uses all four tasks. Each following panel recomputes the map after removing one task from the validation aggregate. If the bright low-rank region remains in the same place, the operating band is not driven by a single task. Gold circles mark coordinates that repeatedly fall in the top validation quintile; the star marks the primary-band medoid projected onto this slice.

C. Tasks, Metric, and Splits

We use four scalar one-step prediction tasks: Mackey–Glass chaos [18], the next x coordinate of an RK4 Lorenz trajectory [19], NARMA10 memory prediction [20], and annual Sunspots from `statsmodels`. Mackey–Glass, Lorenz, and NARMA10 use washout/train/validation/holdout lengths 300/1600/400/400; Sunspots uses 20/150/50/60. Inputs are scaled to $[-1, 1]$ and targets are standardized. The error is normalized mean-squared error, $\text{NMSE} = \langle (y - \hat{y})^2 \rangle / (\text{Var}(y) + 10^{-12})$, computed separately on validation and holdout splits. Ridge is selected only by validation NMSE from $\{10^{-8}, 10^{-7}, \dots, 10^3\}$.

D. Operating Band

To locate the useful region we rank performance within each task j and seed s . A setting θ receives validation percentile rank $r_{j,s}(\theta)$, with lower rank better. The operating band contains settings that land in the top fraction p for at least a fraction q of task-seed pairs,

$$B_{p,q} = \{\theta : \Pr[r_{j,s}(\theta) \leq p] \geq q\}. \quad (3)$$

This frequency-level definition asks whether a region behaves well repeatedly, not whether one coordinate wins every task. In leave-one-task or leave-one-seed tests, the band is built from the remaining replicates and scored on the withheld replicate. In the holdout audit, the validation-defined band is frozen first and evaluated once on holdout ranks and NMSE. Confidence intervals are nonparametric bootstrap percentile intervals for the mean with 50,000 resamples and a fixed seed. Because ranks are formed within each task-seed replicate before aggregation, no large-error task or difficult seed can dominate the band.

III. RESULTS

Across the control space, low validation rank gathers into a compact, connected region rather than a scatter of isolated optima (Fig. 1). The damping coordinate is selected by validation: the near-zero $\gamma = 0.01$ slice is a weak contrast, while the strict $B_{20,0.7}$ core appears for $\gamma = 0.12$ – 0.30 with




Fig. 2. Damping-slice check for the same validation-ranked grid. Bright color indicates better validation rank. The near-zero damping slice at $\gamma = 0.01$ provides a contrast, while the operating band appears across stronger nonzero damping slices.

medoid $\gamma = 0.22$ (Fig. 2). Leave-one-out tests show transfer. When one task is withheld, the band built from the rest scores mean held-out rank 0.193 with CI $[0.176, 0.210]$; when one seed is withheld, the corresponding mean rank is 0.151 with CI $[0.139, 0.163]$.

The validation-defined band also holds on data it never touched: after freezing the band, a single chronological holdout evaluation remains top-quartile (Table I). A nearby four-qubit, three-layer variant preserves the phenomenon, with overlap reported against the base control region (Table II). Mechanism ablations then test causality: removing damping, removing recurrent mixing, or replacing amplitude damping with dephasing erases the band, with retention values 0.00, 0.00, and 0.00 (Fig. 3). Finally, the region can be found before task-specific search: memory capacity correlates strongly with validation rank, $\rho_s = -0.88$, as do information-processing

TABLE I
HOLDOUT PERFORMANCE AFTER VALIDATION-ONLY BAND SELECTION.
MEANS ARE OVER TWENTY SEEDS PER TASK; “ALL” AVERAGES THE 80
TASK-SEED ROWS.

Task	Band NMSE	Medoid NMSE	Band rank
Mackey–Glass	7.05e-05	5.26e-05	0.104
Lorenz	1.51e-05	1.52e-05	0.136
NARMA10	0.560	0.607	0.204
Sunspots	0.209	0.209	0.168
All	0.192	0.204	0.153

TABLE II
ARCHITECTURE ROBUSTNESS AFTER VALIDATION-ONLY BAND SELECTION.
OVERLAP IS JACCARD OVERLAP WITH THE BASE BAND IN THE SHARED
(β, λ, γ) GRID.

Setting	Band?	Held-out rank	Overlap
4q, 2 layers, Z+ZZ	yes	0.153	1.00
4q, 3 layers, Z+ZZ	yes	0.154	0.04




Fig. 3. Why the operating band is meaningful. (a) Bright coordinates are frequently selected by validation. (b–d) Removing damping, removing mixing, or replacing amplitude damping by dephasing concentrates rank loss around the same gold band, showing that the useful region depends on these mechanisms.

capacities [15], whereas raw feature diversity does not (Fig. 4).

IV. DISCUSSION AND SCOPE

For this reservoir family, useful learning is organized by a transferable operating regime rather than by task-specific tuning. Four tasks spanning smooth chaos, nonlinear memory, and irregular real-world data obey the same region, and the region holds when any one task or seed is withheld. The useful region is not picked out by Hilbert-space size or raw feature diversity but by memory, suggesting that drive, coupling, and dissipation keep memory and nonlinearity in the balance classical reservoir theory identified [4], [15]. The scope is deliberately narrow: all results are simulated, on one architecture family, with measurement treated as free, so finite-shot noise, calibration drift, and readout cost remain outside the claim [11], [21]. We claim neither quantum advantage nor hardware efficiency; we

claim that the operating regime is the right object to study, that it transfers, and that memory helps find it.

V. CONCLUSION

The usefulness of a dissipative quantum reservoir is not a property of size alone but of where it is operated. Strong performance gathers in a transferable region where drive, coupling, and dissipation balance memory and nonlinearity. The regime transfers, collapses under targeted mechanism removals, and can be found in advance by memory-based diagnostics.

Reproducibility appendix.

Package. The [project repository](#) contains the code, checked-in CSV/JSON results, and final figures used in this paper.

Frozen reservoir. The simulator evolves the full density matrix exactly, with no finite-shot sampling. It starts from $\rho_0 = |0 \dots 0\rangle\langle 0 \dots 0|$ and carries state between time steps without reset. For each seed, `default_rng(s)` draws one fixed mixer $U_{\text{mix}} = \bigotimes_i R_x(\theta_i)$, $\theta_i \sim U[0, 2\pi)$, reused at every step and layer. Each layer applies $U_\lambda U_{\text{mix}}$ on ring edges, then local amplitude damping. The readout is ridge regression on exact Z_i and ring-pair $Z_i Z_j$ expectations with an unpenalized intercept.

Selection and diagnostics. The (β, λ, γ) grid and task splits are in Sec. II. Ridge penalties $\{10^{-8}, \dots, 10^3\}$ are chosen by validation NMSE only; holdout data are used only after the band is fixed. MC/IPC diagnostics use an independent $U[-1, 1]$ drive of length 900, washout 150, ridge $\alpha = 10^{-8}$, and a 70/30 chronological split. MC sums held-out positive R^2 over delays 1–10. IPC adds linear delays 1–20, quadratic Legendre delays 1–10, and ten cross-delay products, clipping negative R^2 to zero. CIs are nonparametric bootstrap percentile intervals with 50,000 resamples and a fixed seed.

REFERENCES

- [1] W. Maass, T. Natschlger, and H. Markram, “Real-time computing without stable states: A new framework for neural computation based on perturbations,” *Neural Computation*, vol. 14, no. 11, pp. 2531–2560, 2002.
- [2] H. Jaeger and H. Haas, “Harnessing nonlinearity: Predicting chaotic systems and saving energy in wireless communication,” *Science*, vol. 304, no. 5667, pp. 78–80, 2004.
- [3] M. Lukoševičius and H. Jaeger, “Reservoir computing approaches to recurrent neural network training,” *Computer Science Review*, vol. 3, no. 3, pp. 127–149, 2009.
- [4] G. Tanaka *et al.*, “Recent advances in physical reservoir computing: A review,” *Neural Networks*, vol. 115, pp. 100–123, 2019.
- [5] K. Fujii and K. Nakajima, “Harnessing disordered-ensemble quantum dynamics for machine learning,” *Physical Review Applied*, vol. 8, p. 024030, 2017.
- [6] S. Ghosh, A. Opala, M. Matuszewski, T. Paterek, and T. C. H. Liew, “Quantum reservoir processing,” *npj Quantum Information*, vol. 5, p. 35, 2019.
- [7] J. Chen, H. I. Nurdin, and N. Yamamoto, “Temporal information processing on noisy quantum computers,” *Physical Review Applied*, vol. 14, p. 024065, 2020.
- [8] P. Mujal, R. Martnez-Pea, J. Nokkala, J. Garca-Ben, G. L. Giorgi, M. C. Soriano, and R. Zambrini, “Opportunities in quantum reservoir computing and extreme learning machines,” *Advanced Quantum Technologies*, vol. 4, p. 2100027, 2021.
- [9] J. Nokkala, R. Martnez-Pea, G. L. Giorgi, V. Parigi, M. C. Soriano, and R. Zambrini, “Gaussian states of continuous-variable quantum systems provide universal and versatile reservoir computing,” *Communications Physics*, vol. 4, p. 53, 2021.




Fig. 4. Memory-based diagnostics identify the operating region before task-specific search. (a) The task-free memory map shows $\log(1 + MC)$ on the same $\gamma = 0.12$ control slice as the phase maps. The gold operating-band points lie inside the structured memory-rich region, showing that the band is visible from reservoir dynamics alone. (b) Across all sampled settings and seeds, higher memory predicts lower validation rank, giving a global quantitative version of the same effect. (c) Screening efficiency: the fraction of genuinely good reservoirs retained as a function of how many settings are kept. Screening by memory or information-processing capacity recovers the useful settings far earlier than random selection, while raw feature diversity remains much weaker.

- [10] L. C. G. Govia, G. J. Ribeill, G. E. Rowlands, H. K. Krovi, and T. A. Ohki, “Quantum reservoir computing with a single nonlinear oscillator,” *Physical Review Research*, vol. 3, p. 013077, 2021.
- [11] P. Mujal, R. Martínez-Peña, G. L. Giorgi, M. C. Soriano, and R. Zambrini, “Time-series quantum reservoir computing with weak and projective measurements,” *npj Quantum Information*, vol. 9, p. 16, 2023.
- [12] T. Kubota, Y. Suzuki, S. Kobayashi, Q. H. Tran, N. Yamamoto, and K. Nakajima, “Temporal information processing induced by quantum noise,” *Physical Review Research*, vol. 5, p. 023057, 2023.
- [13] J. García-Bení, G. L. Giorgi, M. C. Soriano, and R. Zambrini, “Scalable photonic platform for real-time quantum reservoir computing,” *Physical Review Applied*, vol. 20, p. 014051, 2023.
- [14] I. Paparelle *et al.*, “Experimental memory control in continuous-variable optical quantum reservoir computing,” *Nature Photonics*, vol. 20, pp. 413–420, 2026.
- [15] J. Dambre, D. Verstraeten, B. Schrauwen, and S. Massar, “Information processing capacity of dynamical systems,” *Scientific Reports*, vol. 2, p. 514, 2012.
- [16] R. Martínez-Peña and J.-P. Ortega, “Quantum reservoir computing in finite dimensions,” *Physical Review E*, vol. 107, p. 035306, 2023.
- [17] A. Sannia, R. Martínez-Peña, M. C. Soriano, G. L. Giorgi, and R. Zambrini, “Dissipation as a resource for quantum reservoir computing,” *Quantum*, vol. 8, p. 1291, 2024.
- [18] M. C. Mackey and L. Glass, “Oscillation and chaos in physiological control systems,” *Science*, vol. 197, no. 4300, pp. 287–289, 1977.
- [19] E. N. Lorenz, “Deterministic nonperiodic flow,” *Journal of the Atmospheric Sciences*, vol. 20, no. 2, pp. 130–141, 1963.
- [20] K. S. Narendra and K. Parthasarathy, “Identification and control of dynamical systems using neural networks,” *IEEE Transactions on Neural Networks*, vol. 1, no. 1, pp. 4–27, 1990.
- [21] O. Ahmed, F. Tennie, and L. Magri, “Optimal training of finitely sampled quantum reservoir computers for forecasting of chaotic dynamics,” *Quantum Machine Intelligence*, vol. 7, p. 31, 2025.