

CRYPTO & PRIVACY VILLAGE



DEF CON 27

Developers

Developers


Presenters: Crypto-Privacy Village

- idk
 I2P Application Developer
 Mostly my desk or the yard, sometimes a hammock!
 hankhill19580@gmail.com
 https://qithub.com/eyedeekay
 https://reddit.com/u/alreadyburnt

Presenters: Monero Village

- zzz I2P Developer
- Location Obfuscation is a pretty big part of the point
- zzz@mail.i2phttp://zzz.i2p

Current I2P API's



A sketch of the I2P API's, their relationship to eachother, and their relationship to the router.

I2CP

I2CP is the core I2P API, it underlies many of the other I2P API's. It is also the most complex to use outside of Java, but recently several libraries have emerged that provide $\frac{1}{2}$ partial or full I2CP functionality from other languages. C, Java, and Javascript libraries are available, as is one Go library with partial support.

- https://geti2p.net/en/docs/protocol/i2cp https://geti2p.net/spec/i2cp

Create a connection

```
package susc
import (
   "fmt"
// StreamTCPConnect asks SAM for a TCP-Like connection to dest, has to be called on a new
func (c *Client) StreamTCPConnect(id int32, dest string) error {
    r, err := c.Command("STREAM CONNECT ID=%d DESTINATION=%s\n", id, dest)
    if err != nil {
       return err
    result := r.Pairs["RESULT"]
    if result != "OK" {
       return fmt.Errorf("Reply Error")
    return nil
```

<u> IannuT92I</u>

Java applications can also embed their own instances of ISPTunnel in order to use it to set up ISP tunnels. However, even non-java applications can take advantage of drop-in configuration of ISPtunnel via iSptunnel.config.d in the java iSp router, or tunnels.configuration of ISPtunnel via iSptunnel.configuration of ISP router. In this way, regular clear-web applications can provide alternate configurations that automatically orntigure their ISP tunnels. If you should also provide alternate configurations that are was application or the provide and into an ISP application without necessarily requiring any modification to the application's code.

https://geti2p.net/en/docs/api/i2ptunnel

Establish a session

```
return r.Pairs["DESTINATION"], nil
                                        return "", fmt.Errorf("Reply error")
                                                            if result != "OK" {
                                                    result := r.Pairs["RESULT"]
                                                             return "", err
                                                               if err != nil {
                                                                   , snoitqo
                                                                    sīdīype,
                                                                      'ısəp
                                                                        ʻpτ
                  "SESSION CREATE STYLE=STREAM ID=%d DESTINATION=%s %s %s/n",
                                                           r, err := c.Command(
                                                         "TN3ISNART" = feab
                                                                } "" == 129b li
func (c *Client) CreateStreamSession(id int32, dest, sigtype, options string) (string,
                                                                    // your socket.
         // CreateStreamSession: finally creates a streaming session. You can now use
                                                                          "fmt"
                                                                          import (
                                                                       backage susc
```

I2PControl

I2PControl is a little different. Rather than setting up connections between I2P applications, it's used for configuring and retrieving information about the router programmatically.

• https://geti2p.net/en/docs/api/i2pcontrol

Do the handshake

```
package susc
import (
    "fmt"
)
// Hello does the handshake with the SAM bridge
func (c *Client) Hello() error {
    reply, err := c.Command("HELLO VERSION MIN=3.0 MAX=3.2\n")
    if err != nil {
        return err
    }
    if reply.Topic != "HELLO" {
        return fmt.Errorf("Unknown Reply: %+v\n", r)
    }
    if reply.Pairs["RESULT"] != "OK" {
        return fmt.Errorf("Handshake did not succeed\nReply:%+v\n", r)
    }
    return nil
}
```

<u>S noisyeV MAS</u>

The current recommended API for applications of all types to communicate via I2P is the SAMV3 API. It provides a convenient way to set up, communicate through, and tear down I2P connections. It is designed so that it can implement the API familiar to your programming language in a simple and straightforward way. For example, we can implement a Socket in Java or a net.Conn in Go.

SAM will by and large be the focus of this workshop.

Evmes\iqe\isob\docs\apple\pingq\ioo\docs\apple\pingq\ioo\apple\pinq\ioo\apple\pinq\ioo\apple\pingq\ioo\apple\pingq\ioo\apple\pinq\ioo\apple\pingq\ioo\

VS

γ κebςλ barser

backage susc

```
return r, nil
                            r.Pairs[kvPair[0]] = kvPair[len(kvPair)-l]
return nil, fmt.Errorf("Malformed key-value-pair./n%s/n", kvPair)
                                            if len(kvPair) != 2 {
                                                  if kvPair != nil {
                                   Pairs: make(map[string]string, len(parts).
                                                     Type: parts[1],
                                                     Topic: parts[0],
                                                            L := g K e b J \lambda 
                 return nil, fmt.Errorf("Malformed Reply./n%s/n", line)
                                                     if len(parts) < 3 {
                                         parts := strings.Split(line, ")
                                           line = strings.TrimSpace(line)
                                func ParseReply(line string) (*Reply, error) {
                                                     // object for later use.
// ParseReply takes a string reply from the SAM bridge and turns it into a Reply
                                                  Pairs map[string]string
                                                            Type string
                                                            Topic string
                                                         type Reply struct {
                                                         // convenience sake
           // Reply is a structure that represents a reply to the SAM bridge for
                                                               "strings"
                                                                   "imi"
                                                                   import (
```

Which API do You Need?

If you need to make connections between applications automatically, then you need the ${\bf SAMv3\ API.}$

If you need to monitor or adjust the I2P router's connection, bandwidth usage, or change it's status, then you need the I2PControl API.

If you need to set up tunnels for an already-existing Web Application, then I2Ptunnel, either by embedding it in your application or by placing files into i2ptunnel.config.d.

If you need to simply check the presence of an I2P router before making connections, one way is to make a quick connection to the I2CP API. If you're writing a Java application, the I2CP API may also be a good choice. Besides that, unless you know why you need to use I2CP, you probably just need SAM.

A function to send commands

```
package susc
import (
    "bufio"
    "fmt"
)

// Command is a helper to send one command and return the reply as a string
func (c *Client) Command(str string, args ...interface{}) (*Reply, error) {
    if _, err := fmt.Fprintf(c.TCPConn, str, args...); err != nil {
        return nil, err
    }
    reader := bufio.NewReader(c.TCPConn)
    line, _, err := reader.ReadLine()
    if err != nil {
        return nil, err
    }
    return ParseReply(string(line))
```

But Why Not Just Tell Users to Set Up I2PTunnel via the existing WebUI?

LIPPtunnel is good at forwarding existing services to IZP, and it can concievably be used for many applications. It does provide a SOCKS proxy after all. However, setting up izPtunnels is an involved process, with lots of settings that are intimidating to your users. Using SAM, you set up the connections and apply all the options inside the application itself, giving you the all-important oppourtunity to set up sane defaults on application itself.

A good example can be found in applications that are federated with Activitypub. While IzPfunnel is perfectly capable of making AP applications available over IZP, not many new users will correctly configure the AP-based service correctly on their first try. The process of setting up connections, deciding whether or not to "Bridge" clearnet connections are included and the number of tunnels in destination "Pool," and most other IZP connections or remain strictly anonymous, deciding tunnel length and the number of tunnels in your destination "Pool," and most other IZP connections.

Examples

"" nruter

```
return i2pB64enc.EncodeToString(s[:387+alen])
                     // from the binary representation and re-encode it to base64.
            // take the first 387 bits, + the length reported by the length bits,
                                      alen := binary.BigEndian.Uint16(s[385:387])
                           // Take the length bits from the binary representation
                                      s, _ := i2pB64enc.DecodeString(destination)
                                  // Decode the base64 string to it's binary form
                                                               } "" =! noitenitseb li
                                                 func Base64(destination string) {
                                                      // though it's not part of the spec
              // It's very helpful for SAM libraries to include a function like this even
         // Base64 returns the base64 destination of the tunnel from the full destination.
                                                                      return &c, nil
                                                                  return nil, err
                                                                     jf err != nil {
                                    c.TCPConn, err = net.DialTCP("tcp", nil, samaddr)
                     // When you create your client, establish your connection to SAM.
                                                                  return nil, err
                                                                     if err != nil {
                          samaddr, err := net.ResolveTCPAddr("tcp", "127.0.0.1:7656")
                                         // The default SAM address is localhost:7656
                                                                        var c cilent
                                                                     //var err error
                                                      func NewClient() (*Client, error) {
           // NewClient: To create a new client, create a TCP Connection to a SAM Service.
   i2pB32enc *base32.Encoding = base32.NewEncoding("abcdefghijklmnopqrstuvwxyz234567")
   pase64.NewEncoding("ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz0123456789-~")
                                                         i2pB64enc *base64.Encoding =
                                                                    // encoder to use it.
           // I2P uses a slightly altered base64 alphabet. You will need to customize your
                                                                         *net.TCPConn
                                                                    type Client struct {
                                // Client: A SAM Client is just a socket once it's set up.
                                                                    "encoding/binary"
                                                                    "40esed/baidong"
                                                                    "encoding/base32"
                                                                                import (
                                                                            backage susc
                                                           A simple TCP client
                                               library, but probably not. sam3 is better.
   examples for Def Con 27. When it's done being a basic example it might become a socket
ways the concepts of SAM map onto it's clearnet equivalents. It's been created as a set of
   This isn't intended to be very "good" right now, but rather to illustrate the simplest
                                                    Simplest Useful SAM Streaming Client.
                                                                                 osns
```

What else do you need to think about?

Are you primarily:

- Publishing information or recieving it?
- Do you need ordered, Streaming-style communications
- Do you need unordered or semi-reliable Datagram-style communication
- Do you do peer discovery? How do you do peer discovery?
- When you do peer discovery, do you need to trust a service?
- Do you need to bootstrap off of a DHT?
- Do you want clients to be able to boostrap off of eachother?
- Do you want to also connect to clearnet clients?
- Do you need to be anonymous in mixed clearnet/I2P mode?
- Do you need to send datagrams in mixed clearnet/I2P mode?
- Do you want to allow people to bridge anonymous and non-anonymous clients?

Two big things that SAM can't do and how to easily forget about them

Tell you that an I2P router is running when SAM is not enabled

To do this effectively, you need to check for the existence of an I2CP port, but you don't need to actually use I2CP for anything else.

Adjust the I2P Router's settings

To do this, you need to use i2pcontrol.

MA2 zi jadW

ASM is a simple API for confrolling **connections** on the ISP iSp router in a way which is familiar to people who write internet applications. To use it, you simply set up a SAM connection and then use it like a streaming connection or to send datagrams, either with or without a repliable address. You can use these connections just like their TCP/IP or without a repliable address. You can use these connections just like their TCP/IP or without a repliable address.

Embedding an I2P Router in your Java Application

Not quite done with this one yet. For now, the link.

http://i2p-projekt.i2p/en/docs/applications/embedding

Stages of the SAM Setup process

- 1. Handshake
- 2. Session Establishment
- Communication

Wait, how to I finally make sure that it has the SAM API enabled?

Now that we're sure an I2P router is installed, we need to make sure that a SAM API is available to your application to use. Since 0.9.42, all platforms that use SAM can also use clients.config.d. That way, you can drop a file in to an I2P router you have just installed or one that exists on the computer already, without needing to worry about overwriting or otherwise harmfully altering a potentially sensitive configuation file.

Handshake

- \bullet This is done so that you can negotiate the features of your SAM client with the SAM service.
- First, establish a socket connection to the I2P router's SAM Port.
 From the client, it's a simple "HELLO" message which can contain optional version
- and suthentication information. • When the maximum supported SAM • When the server replies, it will respond with OK and the maximum supported SAM

Wait, what if I don't want to make my clients install a JVM?

Two projects at least have been working on using the 'Jlink' tool to produce an I2P router that does not require the use of a JVM, those include izp-zero from the Monero project and the Zero-Dependency installer from the I2P project. These may be preferable choices if you are bundling a router to use with a non-java application and are averse to requiring your users to install a JVM.

Connections/Messaging

- Now that you've established a session, you can start making connections and/or sending messages.
- Streaming connections are bi-directional, and can either be connected as a client to a server or listened upon to accept connections as a server to a client.
 Predictably, the commands you send to the SAM bridge to set up each kind of connection is "STREAM CONNECT" for connections and "STREAM ACCEPT" for listeners.
- Datagrams can be sent after a datagram style session has been established by sending datagrams to the socket. They can be repliable and include a return address or raw and not include a return address.
- Once you have created a Streaming connection, any further communication on that socket will be done with IZP, whether it be an HTTP Client, a connection between bittorrent peers, or any other kind of Streaming communication.

Wait, how can I make sure the router I am bundling is current?

```
Well here's how I once did it in a Makefile:
# geti2p is an alias for i2pinstaller.exe
geti2p: i2pinstaller.exe
# This downloads the I2P installer using the url composed by the 'make url'
# target.
i2pinstaller.exe: url
    wget -c `cat geti2p.url` -0 i2pinstaller.exe
# This fetches an RDF listing of I2P versions from launchpad and looks for
# the most recent stable version. Using this information, it then constructs
# a URL to download the Windows I2P router installer from Launchpad.
    echo -n 'https://launchpad.net' | tee .geti2p.url
    curl -s https://launchpad.net/i2p/trunk/+rdf | \
        grep specifiedAt | \
        head -n 3 | \
        tail -n 1 | \
        sed 's|
                                <lp:specifiedAt rdf:resource="||g' | \</pre>
    sed 's|+rdf"/>||g' | tee -a .geti2p.url
echo -n '+download/i2pinstall_' | tee -a .geti2p.url
    curl -s https://launchpad.net/i2p/trunk/+rdf | \
        grep specifiedAt | \
        head -n 3 | \
        tail -n 1 | \
        sed 'sl
                                <lp:specifiedAt rdf:resource="/i2p/trunk/||g' | \</pre>
        sed 's|/+rdf"/>||g' | tee -a .geti2p.url
    echo '_windows.exe' | tee -a .geti2p.url
    cat .geti2p.url | tr -d '\n' | tee geti2p.url
    rm -f .geti2p.url
```

Connections/Messaging

- Streaming connections are bi-directional, and can either be connected as a client to • Now that you've established a session, you can start making connections and/or
 - . segessem gnibnes
- datagrams to the socket. They can be repliable and include a return address or raw Datagrams can be sent after a datagram style session has been established by sending connection is "STREAM CONNECT" for connections and "STREAM ACCEPT" for listeners. Predictably, the commands you send to the SAM bridge to set up each kind of a server or listened upon to accept connections as a server to a client.
- bittorrent peers, or any other kind of Streaming communication. socket will be done with I2P, whether it be an HTTP Client, a connection between • Once you have created a Streaming connection, any further communication on that and not include a return address.

Kicking off a child installer with NSIS

because 0.9.42 isn't out yet.

```
copied to the I2P application data directory. We can ONLY do it in this case because we
    As you can see, after the i2pinstaller.exe is done running, a clients.config file is
                                                                              SectionEnd
                                                                            :9SIJ99bn9
                                                               "pile "clients.config"
                                                           "9SI/efedqqA$" dje9luOj92
                                                               "pile "clients.config"
                                                    SetOutPath "C://ProgramData/i2p"
                                                               "pile "clients.config"
                                                      SetOutPath "$PROGRAMFILES\i2p"
                                                ExecWait "$INSTDIR/i2pinstaller.exe"
                                                             File "i2pinstaller.exe"
                                                                "?won ii listani ot daiw
 MessageBox MB_YESNO "Your system does not appear to have i2p installed.$/n$/nDo you
                                                                          :9SIJəƏnipəd
                                                                      Goto endGetI2P
                      TffileExists "$PROGRAMFILES\iZp\iZp.exe" endGetI2P beginGetI2P
                                                                  SetOutPath $INSTDIR
                                                                        "Getion "GetI2P"
                                   and that application can be the I2P installer package.
check for the existence of the file, and second, it can start a new Windows application,
Scriptable Install System. NSIS has the ability to do two essential things. First, it can
    One common way of creating a Windows installer for an application is to use Mullsoft
```

already determines that I2P was not installed, and it is ONLY in this example in this way

Make your Code Re-Usable!

Because of the deliberate similarity to existing streaming and datagram communications, every language makes it possible to reduce this process to one or two steps at sensible layers of abstraction. Starting from the most similar, like a Socket in Java, a connection in Javascript, or a net.Conn in Go. The actual thing will vary from language to language, but when creating a library, you should probably start with a whatever's closest to a Socket

Once you've done that, you've laid the foundation to alter the other network parts of your language. In many cases, it may be possible to forward a connection using the code you've already written, or to replace an underlying structure with your SAM-enabled version.

In a surprisingly short amount of time, you too can develop extensive tooling that makes building new I2P applications and, more importantly, adapting your existing applications to use I2P simple, reliable, and familiar.

Or you can literally just write your own i2ptunnel that you can embed in your existing application. I did that once. It works really well. I don't think we need a gazillion 'socat for I2P' out there but some would argue we didn't need a third so who am I to judge.

Bundling an I2P Router with your SAM Application

Sometimes, the details of setting up your SAM application require you to know whether an I2P router is present and ready to accept SAM connections or not. As of release 0.9.42 in a few weeks, this becomes a very easy problem to solve. Let's take a slightly complicated case as an example, a non-JVM, non-plugin application for Windows.

Since there's a good chance your SAM Application is in a non-Java, non-JVM language, it may be difficult or impossible to build as a plugin for the I2P router. If that's the case, then we can't assume a router is there.

Since this is a Windows machine, we can't assume that a package manager is available with a viable I2P router to install. If that's the case, we'll have to install our own.