GUESS for Software and Systems

Import graphs and call graphs, layers and cycles, the modules everything depends on, change impact, and whether code follows its own folders

Contents

1 Why networks? 1

2 Getting code in 2
2.1 Read a package's import graph Basic . . . 2

3 Structure 3
3.1 Draw the layers Basic . . . 3
3.2 Which modules does everything depend on? Basic . . . 5

4 Cycles 5
4.1 Find the import cycles Intermediate . . . 5

5 Change impact 5
5.1 What could a change break? Basic . . . 5
5.2 Who controls access to whom? Advanced . . . 6

6 Organisation 6
6.1 Does the code follow its folders? Intermediate . . . 6
6.2 A package-level view Basic . . . 6

7 Call graphs 7
7.1 Map who calls whom in a module Intermediate . . . 7

8 Case studies 7
8.1 Case study: the cycle hidden in `import networkx as nx` Intermediate . . . 7
8.2 Case study: GUESS, read by GUESS Basic . . . 8

Why networks?

Software is built from parts that depend on each other: modules import modules, functions call functions, services call services, packages require packages. Most architecture questions are network questions:

- What depends on what, and in which direction?
- Are there cycles, and are they dangerous?

- If I change this module, what could break?
- Which parts does everything rely on, and which are safe to change?
- Is the code organised the way its folders say it is?

This book assumes the Kitchen for loading, querying and drawing. It analyses Python code, which GUESS can read without running it. The same recipes work on any dependency graph you can export, for example as DOT from tools for other languages. Its data are in the cookbooks' `data` folder:

file	what it is
`networkx-imports.gdf`	The module import graph of the networkx package, version 3.7: 288 modules and 784 import links (importer → imported).
`guess-imports.gdf`	GUESS's own Python package: 42 modules and 106 import links, a snapshot taken while writing this book.

Both were made with `makeFromImports` (first recipe). They're snapshots so that the numbers in this book stay true. Run the command on the installed packages to see their current state.

Getting code in

Read a package's import graph Basic

You have a Python package (installed, or a folder of source). **You want** its modules and who imports whom.

Ingredients: an installed package or a source folder · `makeFromImports`

```
makeFromImports("networkx")
sizeBy(lines, 3, 30)
dotLayout()
```

How it works. `makeFromImports(target)` parses every `.py` file of a package (by name, such as `"networkx"`, or a folder or file path) without running it. It makes a node per module and an edge from each module to each module of the same package it imports. Nodes get `module` (the dotted name), `package` (the parent package), `depth`, `lines`, `functions` and `classes`. Edges get `weight` (the number of import statements) and `toplevel` (false when the import happens only inside a function, a *deferred* import). `level=2` merges modules into their subpackages for a bird's-eye view, `external=true` adds the outside packages imported, and `tests=true` includes test modules. In the browser, the packages GUESS ships with (networkx, numpy, igraph) and GUESS itself (`"guess"`) can be read the same way.

Variations. For other languages, most ecosystems have a tool that writes the dependency graph as DOT, and `makeFromDOT` opens it. Function call graphs come from `makeFromCalls` (*Call graphs*, below).

Structure

Draw the layers Basic

```
makeFromGDF("guess-imports.gdf")
labelBy(label)
g.nodes.labelpos = "inside"
fitNodesToLabels()
dotLayout()
colorBy(generation, lightgray, purple)
```




Figure 1: GUESS's modules, layered by imports

How it works. Laid out top to bottom with `dotLayout()`, an import graph shows the system's layers: modules at the top import, and modules at the bottom are imported. `generation` is each module's topological level, from 0 for modules nothing imports (here only the package itself) downwards. Cycles are broken for the layout, and the edges that close them point upwards. In GUESS, the data model (`model`) and the colour table (`colors`) are at the bottom, imported by nearly everything, and the session at the top ties the parts together.

Which modules does everything depend on? Basic

```
makeFromGDF("guess-imports.gdf")
addNodeField("instability", DOUBLE, 0)
for n in g.nodes:
    ca, ce = n.indegree, n.outdegree
    n.instability = ce / (ca + ce) if ca + ce else 0
for n in sortBy(indegree)[-5:]: print(n.module, n.indegree, n.outdegree,
 ↪  round(n.instability, 2))
```

How it works. `indegree` counts the modules that import a module (its *afferent coupling*, in Robert Martin's terms) and `outdegree` the modules it imports (*efferent coupling*). Martin's *instability* is outdegree ÷ (indegree + outdegree). Near 0, a module is depended on but depends on little: it's hard to change (everything relies on it) but has little reason to change. Near 1, a module depends on others but nothing depends on it, so it's easy to change. Healthy code points dependencies towards stable modules. `guess.model` is imported by 33 of GUESS's 42 modules, and its instability is close to 0, as a data model's should be.

Cycles

Find the import cycles Intermediate

```
makeFromGDF("guess-imports.gdf")
cycles = [grp for grp in groupBy(strongcomponent) if len(grp) > 1]
[sorted(n.module for n in grp) for grp in cycles]
for grp in cycles:
    for e in (grp <-> grp): print(e.node1.module, "->", e.node2.module,
     ↪  "deferred" if not e.toplevel else "")
```

How it works. `strongcomponent` groups modules that can reach each other by following imports: every group of two or more is a cycle (two modules that import each other, or a longer loop). Python tolerates an import cycle when at least one import in it runs late, inside a function, after both modules have loaded. A cycle of only top-level imports can fail at start-up depending on which module is imported first. GUESS has three two-module cycles (`algorithms`–`igr`, `model`–`states` and `styles`–`visuals`). In each, at least one direction is deferred, so all three are safe. `feedbackEdges()` lists a small set of edges whose removal would break every cycle: the places to refactor first.

Change impact

What could a change break? Basic

You want to know, before changing a module, which other modules could be affected.

```
makeFromGDF("guess-imports.gdf")
affected = ancestors(guess_model)
affected.color = red
guess_model.color = orange
```

```
len(affected), len(g.nodes)
```

How it works. An edge runs from importer to imported, so the modules that can be affected by a change to `model` are its *ancestors*: everything that imports it, directly or through others. Here that's 34 of 42 modules. Change it carefully and test widely. `descendants(m)` goes the other way: everything `m` needs, which is what you must ship or mock to test it alone.

Who controls access to whom? Advanced

```
makeFromGDF("guess-imports.gdf")
dominatorTree(guess_session)
sorted(set(n.idom for n in g.nodes if n.idom))
```

How it works. In the graph reached from `session`, a module's *immediate dominator* (`idom`) is the last module that every import path from `session` to it must pass through. Modules that dominate others are gatekeepers. Here most modules are dominated by `session` itself (it imports them directly), and a few are reached only through `commands`, `colors`, `geo` or `glyphs`. That's a map of which modules load which, useful when deciding what to load lazily.

Organisation

Does the code follow its folders? Intermediate

```
makeFromGDF("networkx-imports.gdf")
remove(module == "networkx")
leidenClusters()
compareClusters(leiden_class, package)
colorize(leiden_class)
```

How it works. The folders (packages) are the intended structure, and the communities of the import graph are the actual one: groups of modules that import each other more than they import the rest. `compareClusters` scores the agreement (1 = identical). For networkx it's about 0.65: broadly organised by folder, with algorithms that lean on other folders' helpers. Look at the modules whose community differs from their folder. They're often misplaced, or a sign that two folders are really one.

Pitfalls. The package root distorts everything. Nearly every networkx module does `import networkx as nx`, which links each module to the root, so the first step is `remove(module == "networkx")`. The same happens in any package whose `__init__.py` re-exports its contents.

A package-level view Basic

```
makeFromImports("networkx", level=2)
labelBy(module)
sizeBy(lines, 10, 60)
circoLayout()
```

How it works. `level=2` merges every module into its two-level parent (`networkx.algorithms.flow.maxflow` becomes `networkx.algorithms`), giving a dozen subpackages and the imports between them: the architecture diagram a newcomer needs, drawn from the code rather than from memory.

Call graphs

Map who calls whom in a module Intermediate

```
makeFromCalls("guess.structure")
sizeBy(indegree, 6, 30)
colorize(public)
labelBy(function)
forceAtlas2Layout()
unused = [n.function for n in g.nodes if n.indegree == 0 and not n.public]
unused
```

How it works. `makeFromCalls(module)` makes a node per function and method, and an edge for each call it can resolve by name: `f()`, `self.f()`, `Class.f()`. Nodes get `function`, `cls`, `lines`, `params` and `public` (no leading underscore). The most-called functions are the module's helpers. Private functions that nothing in the module calls are candidates for dead code. Here there are three: `_constraint`, `_effsize` and `_generation`. None of them is dead. They compute the `constraint`, `effsize` and `generation` fields, and they're listed in a table of computed fields rather than called. So before deleting a function, check that it isn't used from outside (`grep`), registered in a table or as a callback, or called through a variable.

Pitfalls. Matching by name is an approximation. Calls through variables, to other modules or by dynamic dispatch are missed, and two functions with the same name in different classes can be confused. Treat the graph as a map for reading code, not a proof.

Case studies

Case study: the cycle hidden in `import networkx as nx` Intermediate

```
makeFromGDF("networkx-imports.gdf")
len(feedbackEdges()), len(strongcomponent.distinct)
root = (module == "networkx")
root[0].indegree
remove(root)
recompute()
len(feedbackEdges())
max(groupBy(strongcomponent), key=len)
```

At first sight networkx is riddled with cycles: `feedbackEdges()` lists 260 edges to break. Nearly all of them pass through the package root. Its `__init__.py` imports the subpackages so that users can write `nx.shortest_path`, and 253 modules import the root back. Remove the root and recompute, and only 9 cycle-closing edges remain. Most sit in one knot of seven modules inside `networkx.utils`, which provides the decorators and backend dispatching that the rest of the library

builds on. The pattern is typical of convenient top-level APIs. It's harmless at run time, because Python finishes loading the root before the submodules use it, but it hides the real structure from naive analysis. Remove the facade before you read the architecture.

Case study: GUESS, read by GUESS Basic

```
makeFromGDF("guess-imports.gdf")
sizeBy(lines, 8, 50)
colorBy(indegree, lightgray, red)
labelBy(label)
dotLayout()
sortBy(lines)[-3:]
```

The book's last recipe is the program reading itself. GUESS's largest modules are `layouts` (the layout algorithms), `model` (graphs, nodes, edges and fields) and `session` (the console and the protocol to the page). Colour by indegree and the foundation is plain: `model` and `colors` are imported by most of the system, and each command module (`structure`, `analysis`, `geo`, `builders`…) is imported only by the session, which installs it. That's the shape you want: new commands, like the ones added for these cookbooks, can be written without touching anything that depends on them.