GUESS for Social Network Analysis

Ego networks, centrality and brokerage, cohesion, roles, homophily, directed and two-mode ties, with three worked case studies

Contents

1 Why networks? 2

2 Ego networks 2
2.1 Draw one person's world Basic . . . 2
2.2 Ego density and effective size Basic . . . 4

3 Centrality and power 4
3.1 Which kind of central? Basic . . . 4
3.2 The Medici: power from position Intermediate . . . 4

4 Brokerage and structural holes 6
4.1 Find the brokers between groups Intermediate . . . 6

5 Cohesive subgroups 6
5.1 Cores, cliques and cohesive blocks Intermediate . . . 6
5.2 Communities and the split they predict Basic . . . 7

6 Roles and positions 7
6.1 Find structurally equivalent members Advanced . . . 7

7 Homophily and mixing 9
7.1 Do like link to like? Basic . . . 9

8 Directed ties 9
8.1 Reciprocity, triads and status Intermediate . . . 9

9 Two-mode networks 10
9.1 People and the events they attend Intermediate . . . 10
9.2 Project onto one kind Intermediate . . . 11

10 Case studies 13
10.1 Case study: the karate club split Intermediate . . . 13
10.2 Case study: marriage, money and the Medici Intermediate . . . 15
10.3 Case study: the formal and the informal organisation Advanced . . . 15

Why networks?

Social network analysis studies people (or teams, firms, countries) through their relations: who advises, befriends, marries, cites or trades with whom. The questions are old. Who holds power? Who connects groups that otherwise don't talk? Do people cluster with others like them? Do roles exist that different people fill in the same way? What the network adds is that the answers depend on *patterns of ties*, not just on each person's attributes.

This book assumes the Kitchen (*The GUESS Kitchen*) for loading, querying and drawing. Its data, in the cookbooks' `data` folder, are classic small networks whose results you can compare with the literature:

file	what it is
`karate.gdf`	Zachary's karate club: 34 members of a university club that split in two after a dispute between the instructor (`m1`) and the club's officer (`m34`). `club` says which side each joined. Edge `weight` is the number of contexts in which two members met.
`florentine.gdf`	Marriage ties among 15 leading families of Renaissance Florence (Padgett).
`southern-women.gdf`	Davis, Gardner and Gardner's two-mode data: 18 women and the 14 social events (`E1`–`E14`) each attended. `kind` is `woman` or `event`.
`adamic-glance.gdf`	Links among 40 influential US political blogs in 2004, with each blog's `leaning`. Directed.
`sample.gdf`	GUESS's own example: an organisation of 402 employees in departments (`dept`), with communication frequency (`freq`) on the ties.

Network data has two shapes. In *sociocentric* (whole-network) data, every tie in a bounded group is recorded, as in the karate club. In *egocentric* data, each respondent describes their own contacts and the ties among them. Most recipes work on both; ego recipes work on either.

Ego networks

Draw one person's world Basic

You have a whole network. **You want** to see it from one member's point of view: their contacts (alters) and how those contacts are tied to each other.

Ingredients: `karate.gdf` · `egoNetwork` · `subgraph`

```
makeFromGDF("karate.gdf")
ego = egoNetwork(m1)
subgraph(ego, "m1's world")
radialLayout(m1)
rescaleLayout(700, 700)
m1.color = red
labelBy(label)
alters = ego.difference([m1])
```

```
len(alters), len(alters <-> alters)
```




Figure 1: The instructor's ego network

How it works. `egoNetwork(node, depth)` is the node plus everyone within `depth` steps (1 by default). `subgraph` opens it as a graph of its own (`use("main")` goes back), so the layout arranges only the ego network. `showOnly(ego)` would instead hide everything else in place. `alters <-> alters` is the set of ties among the contacts. The instructor has 16 contacts with 18 ties among them out of 120 possible, so his contacts mostly don't know each other: he is the hub that holds his side of the club together.

Variations. `egoNetwork(m1, 2)` adds friends of friends. For egocentric survey data, load each

respondent's network as its own graph (`newGraph`, then `use` to switch between them) or keep them in one graph with an `ego` field.

Ego density and effective size Basic

You want numbers that summarise an ego network, to compare people.

```
makeFromGDF("karate.gdf")
alters = egoNetwork(m34).difference([m34])
ties = len(alters <-> alters)
possible = len(alters) * (len(alters) - 1) / 2
ties / possible                          # ego density
m34.effsize, m34.constraint
```

How it works. *Ego density* is the share of possible ties among the alters that exist: high when the alters form a closed group, low when the ego bridges otherwise separate people. Burt's *effective size* (`effsize`) counts alters minus their redundancy: 10 contacts who all know each other are effectively fewer than 10. *Constraint* (`constraint`) is high when an ego's contacts are few and tied to each other, which leaves the ego no alternatives. Both are built-in node fields, computed for every node on first use, so `sortBy(constraint)[:5]` gives the least constrained people.

Centrality and power

Which kind of central? Basic

You want to know who is important, and to understand why the measures disagree.

```
makeFromGDF("karate.gdf")
for n in sortBy(betweenness)[-5:]:
    print(n.label, n.degree, round(n.betweenness, 1), round(n.eigenvector, 3))
```

How it works. Each measure models a different idea of importance. *Degree* is activity: how many ties. *Betweenness* is control: how often a node lies on the shortest paths between others, so its removal would lengthen them. *Closeness* is reach: how few steps to everyone. *Eigenvector* centrality is status: ties to people who are themselves well tied. The instructor and the officer top every list here. Further down the lists differ. Member `m32` has only 6 ties but almost the betweenness of `m33`, who has 12, because `m32`'s friends are on both sides of the club.

Pitfalls. Betweenness and closeness assume things flow along shortest paths. Gossip, which wanders, is better modelled by `rwbetweenness` (random-walk betweenness) or `pagerank`.

The Medici: power from position Intermediate

You have the Florentine marriage network. **You want** to see why one family dominated without having the most of anything.

Ingredients: `florentine.gdf` · `betweenness` · `scatterLayout`

```
makeFromGDF("florentine.gdf")
kkLayout()
sizeBy(betweenness, 10, 50)
```

```
colorBy(degree, lightgray, red)
labelBy(name)
Medici.degree, Strozzi.degree
round(Medici.betweenness, 1), round(Strozzi.betweenness, 1)
```




Figure 2: Florentine marriages, sized by betweenness

How it works. The Medici have six marriage ties, the Strozzi four, but the Medici lie on nearly half of all shortest paths between families. They married into families that weren't tied to each other, so other families reached each other through them. This is Padgett's classic argument: the Medici's

power came from bridging, not from size.

Variations. `scatterLayout(degree, betweenness)` with labels on puts each family at its degree (x) and betweenness (y). Families far above the diagonal are brokers.

Brokerage and structural holes

Find the brokers between groups Intermediate

You have an organisation with formal departments. **You want** the people who connect departments.

Ingredients: `sample.gdf` · `interEdges` · `constraint` · `cutNodes`

```
makeFromGDF("sample.gdf")
crossing = interEdges(dept)
crossing.color = red
addNodeField("ndepts", INTEGER, 0)
for n in g.nodes: n.ndepts = len(set(m.dept for m in n.getNeighbors()))
brokers = (ndepts >= 3)
brokers.color = orange
sortBy(brokers, constraint)[:5]
len(crossing), len(brokers)
```

How it works. A *structural hole* is a gap between two groups with no direct ties. People who span it see information from both sides early and can broker between them. This recipe stores, for each person, how many departments their contacts belong to (`ndepts`). Among those spanning three or more, the least constrained are the strongest brokers. `cutNodes()` gives the extreme case: people whose departure would disconnect part of the organisation.

Pitfalls. A tie across a hole is valuable only if the groups differ in what they know. Check that the groups are meaningful before celebrating the brokers.

Cohesive subgroups

Cores, cliques and cohesive blocks Intermediate

You want the tight-knit groups inside a network.

```
makeFromGDF("karate.gdf")
frLayout()
colorBy(coreness, lightgray, red)
[sorted(n.label for n in c) for c in largestCliques()]
cohesiveBlocks()
```

How it works. A *clique* is a group where everyone is tied to everyone: the strictest definition, and brittle (one missing tie breaks it). A *k-core* relaxes it: everyone has at least k ties inside the group. `coreness` gives each member's deepest core, so colouring by it shows the club's dense centre. *Cohesive blocks* (Moody and White) are nested groups that stay connected after removing any $k-1$ members, so they catch groups held together by many independent paths.

Communities and the split they predict Basic

```
makeFromGDF("karate.gdf")
frLayout()
louvainClusters()
colorize(modularity_class)
shapeBy(club)
compareClusters(modularity_class, club)
```

How it works. Community detection finds groups denser inside than between. Here, colour is the found community and shape is the side each member actually joined after the split. The two largely coincide: the fault line was visible in the friendships before the club broke up. See the case study for a sharper version.

Roles and positions

Find structurally equivalent members Advanced

You want *roles*: sets of people tied in the same way to the same others, whether or not they're tied to each other. Leaders who share the same followers, or followers who share the same leaders, are examples.

Ingredients: `karate.gdf` · `blockmodel` · `collapseBy`

```
makeFromGDF("karate.gdf")
frLayout()
blockmodel(4)
colorize(position)
legendFor(position)
```




Figure 3: Four positions in the karate club

How it works. `blockmodel(k)` compares every pair of members' tie profiles (whom they're tied to) by correlation and groups the most similar into k positions, stored in `position`. The printed *image matrix* gives the density of ties from each position to each other. A dense diagonal cell means a cohesive position. A dense off-diagonal cell with a sparse diagonal means a role that serves another, such as followers who all tie to the same leaders but not to each other. In the karate club, two large positions follow the two sides. A third position, members 5, 6, 7, 11 and 17, is a satellite of the instructor: tied to him and to each other but to almost no one else. A fourth is the pair 25 and 26, who share the same few officer-side contacts.

Variations. `collapseBy(position)` draws the reduced graph: one node per position. Try several k: there is no single right number, only more or less useful simplifications.

Pitfalls. Communities and positions answer different questions. A position can hold people with no ties to each other at all (the followers of one leader), and a community can mix leaders and followers.

Homophily and mixing

Do like link to like? Basic

You have a network and an attribute. **You want** to know whether ties stay within groups.

Ingredients: `adamic-glance.gdf` · `assortativity` · `mixingMatrix`

```
makeFromGDF("adamic-glance.gdf")
colorize(leaning)
interEdges(leaning).color = gray
assortativity(leaning)
mixingMatrix(leaning)
```

How it works. `assortativity(field)` is near 1 when ties stay within values, 0 when they mix at random, and negative when they cross values. `mixingMatrix` shows the counts behind it. For these 40 blogs the assortativity is about 0.29: positive, but 210 of the 706 links cross sides. These are the most prominent blogs, which watched and answered each other. Adamic and Glance's study of many more blogs found the two sides far more separated.

Pitfalls. Homophily has two explanations that the network alone can't separate: people choose similar others (*selection*), or tied people grow alike (*influence*). Telling them apart needs data over time.

Directed ties

Reciprocity, triads and status Intermediate

You have directed ties (advice, citation, links). **You want** to know how often they're returned and whether they form a hierarchy.

```
makeFromGDF("adamic-glance.gdf")
reciprocity()
mutualEdges().color = red
triadCensus()
sortBy(authority)[-3:], sortBy(hub)[-3:]
```

How it works. *Reciprocity* is the share of directed ties returned. The *triad census* counts the 16 kinds of three-node configuration. Many transitive triads (A→B, B→C, A→C) and few cycles (A→B→C→A) suggest a ranking. Many cycles suggest exchange among equals. Among the blogs, 61% of links are returned, and transitive triads outnumber cycles 455 to 29: a pecking order, not a ring. `authority` and `hub` (HITS) split status into being pointed to by good hubs (authorities) and pointing to good authorities (hubs).

Two-mode networks

People and the events they attend Intermediate

You have a two-mode (bipartite) network: people and the groups, events or organisations they belong to. **You want** to see it, and then to study the people through what they share.

Ingredients: `southern-women.gdf` · `bipartiteLayout` · `project`

```
makeFromGDF("southern-women.gdf")
bipartiteLayout(kind)
colorize(kind)
labelBy(name)
```




Figure 4: Women and the events they attended

How it works. `bipartiteLayout(field)` draws the two kinds of nodes in two rows and orders each row to reduce crossings, so groups of women who attend the same events cluster together.

Project onto one kind Intermediate

```
makeFromGDF("southern-women.gdf")
project(kind, "woman", method="newman")
frLayout()
```

```
sizeBy(affiliations, 8, 30)
sizeBy(weight, 1, 8)
louvainClusters(); colorize(modularity_class)
labelBy(name)
```




Figure 5: The women's network, projected

How it works. `project(kind, "woman")` makes a new graph of just the women, tying two when they attended an event together, and switches to it (the two-mode graph stays: `use("main")` goes back). Every edge stores `shared`, the number of events in common, and `weight` according to `method`:

method	weight	use when
`"count"`	the events shared	events are similar in size
`"jaccard"`	shared ÷ events either attended	some people attend everything
`"newman"`	each shared event adds 1/(its size − 1)	big events say less about a tie than small ones

`affiliations` is each woman's number of events. The communities found in the projection recover the two cliques that Davis and the Gardners described.

Variations. `project(kind, "event")` gives the dual: events tied by the women they share, which shows how the social calendar hung together.

Pitfalls. Projection makes dense, clique-ridden networks (everyone at one event becomes a clique), so degree and clustering in the projection are inflated. Compare with the two-mode graph, and prefer weighted measures.

Case studies

Case study: the karate club split Intermediate

Zachary watched a university karate club for two years, during which a dispute between the instructor and the club's officer split it in two. He asked whether the split could be predicted from the friendships before it.

```
makeFromGDF("karate.gdf")
frLayout()
(m1, m34).color = red
(m1, m34).size = 30
labelBy(label)
```

First, look: the instructor (`m1`) and the officer (`m34`) sit at the centres of two loosely joined halves.

```
fl = minCut(m1, m34)
fl
```

Zachary's own prediction was a minimum cut: the fewest friendship ties that, removed, separate the two leaders. `minCut(a, b)` returns those ties.

```
addNodeField("side", VARCHAR, None)
for n in g.nodes:
    closer = len(shortestPath(n, m1)) <= len(shortestPath(n, m34))
    n.side = "Mr Hi" if closer else "Officer"
compareClusters(side, club, method="ari")
louvainClusters(resolution=0.6)
compareClusters(modularity_class, club, method="ari")
colorize(club)
shapeBy(modularity_class)
```




Figure 6: Sides joined (colour) against detected communities (shape)

Reading it. A naive rule (each member follows whichever leader is fewer steps away) gets an adjusted Rand index of 0.67 against the real split. It misplaces members 25, 26 and 32, who are close to the instructor in steps but bound to the officer's side by their friends. Louvain at a coarse resolution (two communities) does better, at 0.88, and gets exactly one member wrong: `m9`. Three of his five friends were on the officer's side, yet he followed the instructor. Zachary's explanation is one no network holds: he was close to his black-belt examination, and staying with the instructor protected years of training. Report the mistakes, not just the score.

Case study: marriage, money and the Medici Intermediate

```
makeFromGDF("florentine.gdf")
kkLayout()
labelBy(name)
heatMap(Medici)
for n in sortBy(betweenness)[-4:]:
    print(n.name, n.degree, round(n.betweenness, 1), round(n.constraint, 2))
```

The heat map colours families by marriage distance from the Medici. Eleven of the other fourteen families are within two steps, and several reach each other only through them. Their constraint is the lowest of any family, because their in-laws weren't in-laws of each other. Now remove them and see what's left:

```
ss("with")
remove(Medici)
recompute()
colorize(component)
graphStats()
```

`recompute()` matters here. Computed fields such as `component` and `betweenness` are calculated the first time they're used and kept, so after editing the graph, recompute them. Without the Medici the network falls into three pieces: the Acciaiuoli alone, the Pazzi and Salviati together, and the other eleven. Their marriages were the glue of the elite, which is why marrying into them was worth so much. `ls("with")` brings them back.

Case study: the formal and the informal organisation Advanced

Every organisation has two structures: the chart (departments, reporting lines) and the network of who actually talks to whom. Where they differ is where coordination happens, or fails.

```
makeFromGDF("sample.gdf")
colorize(dept)
louvainClusters()
compareClusters(modularity_class, dept)
mixingMatrix(dept, show=False)["dept4"]
```

The found communities agree with departments fairly well (normalized mutual information about 0.75, where 1 is identical), but Louvain finds 44 communities for 21 departments: departments contain several working groups. `mixingMatrix(dept)[d]` shows where one department's ties go.

```
assortativity(dept)
subgraph(freq > 100, "heavy ties")
assortativity(dept)
```

`subgraph(freq > 100, "heavy ties")` opens a graph of just the 367 heavy communication ties and the people they join (`use("main")` goes back). If assortativity by department rose there, departments would be where the real work happens. If it fell, the important work would cross department lines. Here it barely moves (0.77 to 0.76): heavy and light ties follow the chart alike. The exceptions are the brokers (*Find the brokers between groups*): the few people whose heavy ties

cross departments.