


---

# CLASSIFICATION OF PHISHING WEBSITES BASED ON MACHINE LEARNING TECHNIQUES

1600003764 – Safa ORHAN  
1600003762 – Eyüp USTA

Istanbul Kültür University  
Advisor: Assis. Prof. Dr. Öznur ŞENGEL



# INTRODUCTION



Phishing, a continuously growing cyber threat, aims to obtain innocent users' credentials by deceiving them via presenting fake web pages which mimic their legitimate targets.

---

# PROBLEM STATEMENT

- Total of 5.16 billion people use internet worldwide which is more than 65% of total world population recorded in 2021 by Internet world stats.
- The September 2017 Webroot Data estimates that approximately 1.3 million phishing websites are created on a monthly basis.

WHO

WHAT

WHERE

WHY

---

---

# OVERVIEW

Dataset

Comparison  
Methods

Machine  
Learning  
Algorithms

Deep  
Learning  
Algorithms


Comparison  
of Methods

Experimental  
Results

Conclusions

---

# 1. DATASET [1]



- 30 Features
- 11055 Different Samples
- 4 Categories

1 = Legitimate

0 = Suspicious

-1 = Phishing

Category	Feature	Values
Address Bar	Using the IP Address	-1, 1
	Long URL to Hide the Suspicious Part	-1, 0, 1
	Links in <Meta>, <Script> and <Link> tags	-1, 1
	URL's having "@" Symbol	-1, 1
	Redirecting using "//"	-1, 1
	Adding Prefix or Suffix Separated by (-) to the Domain	-1, 1
	Sub Domain and Multi Sub Domains	-1, 0, 1
	HTTPS	-1, 0, 1
	Domain Registration Length	-1, 1
	Favicon	-1, 1
	Using Non-Standard Port	-1, 1
	The Existence of "HTTPS" Token in the Domain Part of the URL	-1, 1
Abnormal	Request URL	-1, 0, 1
	URL of Anchor	-1, 0, 1
	Links in <Meta>, <Script> and <Link> tags	-1, 0, 1
	Server Form Handler (SFH)	-1, 0, 1
	Submitting Information to Email	-1, 1
HTML and JavaScript	Abnormal URL	-1, 1
	Website Forwarding	-1, 0, 1
	Status Bar Customization	-1, 1
	Disabling Right Click	-1, 1
	Using Pop-up Window	-1, 1
Domain	IFrame Redirection	-1, 1
	Age of Domain	-1, 1
	DNS Record	-1, 1
	Website Traffic	-1, 0, 1
	PageRank	-1, 1
	Google Index	-1, 1
	Number of Links Pointing to Page	-1, 1
	Statistical-Reports Based Feature	-1, 1



---

## 2. COMPARISON METHODS

$$Accuracy = \frac{TP + TN}{TP + FP + FN + TN} \quad Precision = \frac{TP}{TP + FP}$$

$$Recall = \frac{TP}{TP + FN} \quad F1\ Score = \frac{2 \times Precision \times Recall}{Precision + Recall}$$



Accuracy




Precision



Recall



F-measure  
(F1-score)



---

# 3. MACHINE LEARNING ALGORITHMS

---

## 3.1. SUPPORT VECTOR MACHINE (SVM)

Kernels: linear, sigmoid, polynomial, RBF

C: 1, 2, 3, 4, 5

Degree: 1, 2, 3, 4, 5, 6

Gamma: scale, auto

Decision function shape (DFS): ovo, ovr

Test Size: 25%

Model: 2400 Different Combinations

Average Accuracy: 92.42%

---



---

## 3.1. SUPPORT VECTOR MACHINE (SVM)

### Best Model:

Kernel: RBF

C: 1

Degree: 2

Gamma: scale

DFS: ovo

**Accuracy: 98.37%**

### Worst Model:

Kernel: sigmoid

C: 3

Degree: 1

Gamma: scale


DFS: ovo

**Accuracy: 83.78%**


---

---


## 3.1. SUPPORT VECTOR MACHINE (SVM)



Average accuracy values according to kernels



Average accuracy values according to C values



SVM's Confusion Matrix

---

---

## 3.2. LINEAR SUPPORT VECTOR MACHINE

Losses: hinge, squared hinge

Penalty: L2

C: 1, 2, 3, 4, 5

Multi class: ovr, crammer singer

Test Size: 15%

Model: 100 Different Combinations

Average Accuracy: 93.11%

---

---

## 3.2. LINEAR SUPPORT VECTOR MACHINE

### Best Model:

Losses: squared hinge

Penalty: L2

C: 1

Multi class: ovr

**Accuracy: 93.97%**

### Worst Model:

Losses: hinge

Penalty: L2

C: 4

Multi class: ovr


**Accuracy: 93.03%**

---




---

## 3.2. LINEAR SUPPORT VECTOR MACHINE



Average accuracy values according to C values



Linear SVM's Confusion Matrix

---

---

## 3.3. K-NEAREST NEIGHBORS (KNN)

K: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10

Algorithm: kd tree, ball tree, brute, auto

Weights: uniform, distance

Metric: chebyshev, manhattan, minkowski,  
euclidean

Test Size: 25%

Model: 1440 Different Combinations

Average Accuracy: 95.99%

---

---

## 3.3. K-NEAREST NEIGHBORS (KNN)

### Best Model:

K: 5

Algorithm: auto

Weights: distance

Metric: manhattan

**Accuracy: 98.91%**

### Worst Model:

K: 8

Algorithm: auto

Weights: uniform


Metric: chebyshev

**Accuracy: 78.17%**


---

---


## 3.3. K-NEAREST NEIGHBORS (KNN)



Average accuracy values according to metrics



Average accuracy values according to K values



KNN's Confusion Matrix

---



---

## 3.4. DECISION TREE

Criterion: gini, entropy

Max features: auto, none, log2, sqrt

Splitter: random, best

Class weight: none, balanced subsample,  
balanced

Test Size: 25%

Model: 160 Different Combinations

Average Accuracy: 95.64%

---

---

## 3.4. DECISION TREE

### Best Model:

Criterion: entropy

Max features: none

Splitter: best

Class weight: none

**Accuracy: 98.76%**

### Worst Model:

Criterion: gini

Max features: log2

Splitter: random


Class weight: none

**Accuracy: 95.64%**


---

---

## 3.4. DECISION TREE



Average accuracy values according to max features and class weights



DT's Confusion Matrix


---

---

## 3.5. GAUSSIAN NAIVE BAYES

Test Size: 30%

Accuracy: 61.34%



GNB's Confusion Matrix





---

## 3.6. BERNOULLI NAIVE BAYES

Alpha: 0, 1, 2, 3, 4, 5, 7, 9, 11

Binarize: 0, 1, 2, 3, 4, 5, 7, 9, 11

Fit prior: true, false

Test Size: 15%

Model: 810 Different Combinations

Average Accuracy: 60.36%

---

---

## 3.6. BERNOULLI NAIVE BAYES

### Best Model:

Alpha: 0

Binarize: 0

Fit prior: false

**Accuracy: 91.86%**


### Worst Model:

Alpha: 0

Binarize: 1

Fit prior: true

**Accuracy: 56.01%**



BNB's Confusion Matrix

---

---

## 3.7. RANDOM FOREST

Max features: auto, none, log2, sqrt

Class weight: none, balanced subsample,  
balanced

Warm start: true, false

Criterion: entropy, gini

Test Size: 25%

Model: 240 Different Combinations

Average Accuracy: 97%

---

---

## 3.7. RANDOM FOREST

### **Best Model:**

Max features: auto

Class weight: balanced subsample

Warm start: true

Criterion: gini

**Accuracy: 99.09%**

### **Worst Model:**

Max features: none

Class weight: balanced

Warm start: true

Criterion: entropy


**Accuracy: 96.68%**

---




---

## 3.7. RANDOM FOREST



Average accuracy values according to class weights



RF's Confusion Matrix

---

---

# 4. DEEP LEARNING ALGORITHMS



---

# 4.1. CONVOLUTIONAL NEURAL NETWORKS (CNN)

Epoch: 150

Test Size: 30%

Model: 320 Different Combinations

Activation Functions	Optimizers	Loss Functions
Softplus	SGD	Binary Cross Entropy
Softsign	Rmsprop	Categorical Cross Entropy
Selu	Adam	Hinge
Elu	Adadelata	Squared Hinge
Exponential	Adagrad	Huber
Tanh	Adamax	
Sigmoid	Nadam	
Relu	FTRL	

---

## 4.1. CONVOLUTIONAL NEURAL NETWORKS (CNN)


### CNN Model 1:

Optimizers: Adamax


Activation Functions: Tanh

Loss Functions: Huber

**Accuracy: 93.19%**



CNN Model 1



CNN Model 1's Confusion Matrix

---

---

## 4.1. CONVOLUTIONAL NEURAL NETWORKS (CNN)


**CNN Model 2:**

Optimizers: Adam


Activation Functions: Tanh

Loss Functions: Binary cross entropy

**Accuracy: 92%**



CNN Model 2



CNN Model 2's Confusion Matrix

---

---

## 4.2. RECURRENT NEURAL NETWORKS (RNN)

Epoch: 150

Test Size: 30%

Model: 320 Different Combinations

Activation Functions	Optimizers	Loss Functions
Softplus	SGD	Binary Cross Entropy
Softsign	Rmsprop	Categorical Cross Entropy
Selu	Adam	Hinge
Elu	Adadelta	Squared Hinge
Exponential	Adagrad	Huber
Tanh	Adamax	
Sigmoid	Nadam	
Relu	FTRL	

---

## 4.2. RECURRENT NEURAL NETWORKS (RNN)



**RNN Model 1:**

Optimizers: Adamax

Activation Functions: Tanh

Loss Functions: Binary cross entropy

**Accuracy: 98.81%**



---

## 4.2. RECURRENT NEURAL NETWORKS (RNN)


**RNN Model 2:**

Optimizers: Adamax


Activation Functions: Sigmoid

Loss Functions: Binary cross entropy

**Accuracy: 98.31%**



RNN Model 2



RNN Model 2's Confusion Matrix

---



---

## 4.2. RECURRENT NEURAL NETWORKS (RNN)


**RNN Model 3:**

Optimizers: SGD


Activation Functions: Sigmoid

Loss Functions: Binary cross entropy

**Accuracy: 96.85%**



RNN Model 3



RNN Model 3's Confusion Matrix

---

---

## 4.2. RECURRENT NEURAL NETWORKS (RNN)


**RNN Model 4:**

Optimizers: SGD


Activation Functions: Sigmoid

Loss Functions: Binary cross entropy

**Accuracy: 96.21%**



RNN Model 4



RNN Model 4's Confusion Matrix

---

---

## 4.3. DEEP NEURAL NETWORKS (DNN)

Epoch: 150

Test Size: 30%

Model: 320 Different Combinations

Activation Functions	Optimizers	Loss Functions
Softplus	SGD	Binary Cross Entropy
Softsign	Rmsprop	Categorical Cross Entropy
Selu	Adam	Hinge
Elu	Adadelata	Squared Hinge
Exponential	Adagrad	Huber
Tanh	Adamax	
Sigmoid	Nadam	
Relu	FTRL	

---

## 4.3. DEEP NEURAL NETWORKS (DNN)


**DNN Model 1:**

Optimizers: SGD


Activation Functions: Sigmoid

Loss Functions: Binary cross entropy

**Accuracy: 55.84%**



DNN Model 1



DNN Model 1's Confusion Matrix

---

---

## 4.3. DEEP NEURAL NETWORKS (DNN)


**DNN Model 2:**

Optimizers: Adamax


Activation Functions: Sigmoid

Loss Functions: Huber

**Accuracy: 98.84%**



DNN Model 2



DNN Model 2's Confusion Matrix

---

---

# 4.4. COMBINED MODELS

Epoch: 150

Test Size: 30%

Activation Functions	Optimizers	Loss Functions
Softplus	SGD	Binary Cross Entropy
Softsign	Rmsprop	Categorical Cross Entropy
Selu	Adam	Hinge
Elu	Adadelata	Squared Hinge
Exponential	Adagrad	Huber
Tanh	Adamax	
Sigmoid	Nadam	
Relu	FTRL	

---

## 4.4. COMBINED MODELS

### **Combined Model 1:**

Combination: RNN Model 1 – CNN Model 1

Optimizers: Adamax

Activation Functions: Softplus

Loss Functions: Binary cross entropy

**Accuracy: 90.02%**

### **Combined Model 2:**

Combination: CNN Model 1 – RNN Model 1

Optimizers: Adamax

Activation Functions: Softplus


Loss Functions: Binary cross entropy

**Accuracy: 96.29%**


---

---

## 4.4. COMBINED MODELS



Combined Model 1's Confusion Matrix



Combined Model 2's Confusion Matrix

---



---

## 4.4. COMBINED MODELS

### Combined Model 3:


Combination: CNN – LSTM

Optimizers: Adamax


Activation Functions: Softplus

Loss Functions: Binary cross entropy

**Accuracy: 96.26%**



Combined Model 3



Combined Model 3's Confusion Matrix

---

---

## 4.5. MODEL TESTS WITH DIFFERENT DATASETS

### First Dataset [2]:

- 48 Features
- 10000 Different Samples
- From data mendeley

### Second Dataset [3]:

- 14 Features
- 11000 Different Samples
- From kaggle

### Third Dataset [4]:

- 35 Features
- 13071 Different Samples
- From data mendeley

### Fourth Dataset [5]:

- 87 Features
- 11430 Different Samples
- From data mendeley

### Fifth Dataset [6]:

- 79 Features
  - 15367 Different Samples
  - From Canadian Institute for Cybersecurity
-

---

# 4.5. MODEL TESTS WITH DIFFERENT DATASETS

Dataset	DNN Model 2	RNN Model 1	CNN Model 1
First Dataset [ ]	95.43%	93.93%	88.87%
Second Dataset [ ]	89.45%	99.12%	99.68%
Third Dataset [ ]	94.11%	93.19%	92.76%
Fourth Dataset [ ]	75.51%	77.34%	77.81%
Fifth Dataset [ ]	48.88%	48.88%	48.88%
Our Dataset [ ]	98.84%	98.81%	93.19%



---

## 5. COMPARISON OF METHODS

Model	Accuracy	Precision	Recall	F1-Score
Our RF Model	99.09%	0.9895	0.9940	0.9917
RNN Model 2	97.27%	0.9769	0.9694	0.9732
Combined Model 3	96.26%	0.9635	0.9678	0.9656
[7]	98.61%	0.9941	0.9857	0.99
[8]	95.60%	0.9733	0.9378	0.9552
[9]	93.28%	0.9327	0.9330	0.9329
Random Forest [10]	98.03%	1.0	0.96	0.98
Logistic Regression [10]	97.7%	1.0	0.96	0.98
Gaussian Naïve Bayes [10]	97.18%	1.0	0.95	0.97
[11]	93%	0.92		0.91
CNN [12]	97.42%	0.9648	0.9723	
LSTM [12]	99.14%	0.9874	0.9891	

---

---

## 6. EXPERIMENTAL RESULTS

Models	Features	Accuracy	Test Size	Epoch
DNN Model 1	Categorical	55.84%	30%	150
DNN Model 1	Categorical	75.76%	15%	10
DNN Model 1	Categorical	75.54%	35%	10
DNN Model 2	Categorical	75.79%	15%	10
DNN Model 2	Categorical	75.40%	35%	10
DNN Model 2	Non-categorical	98.84%	30%	150
RNN Model 1	Non-categorical	98.81%	30%	150
RNN Model 2	Non-categorical	98.31%	30%	150
RNN Model 3	Non-categorical	96.85%	30%	150
RNN Model 4	Non-categorical	96.21%	30%	150
CNN Model 1	Non-categorical	93.19%	30%	150
CNN Model 2	Non-categorical	92%	30%	150
Combined Model 1	Non-categorical	90.02%	30%	150
Combined Model 2	Non-categorical	96.29%	30%	150
Combined Model 3	Non-categorical	96.26%	30%	150

---


## 6. EXPERIMENTAL RESULTS

Model	Parameters	Train Accuracy	Test Accuracy	Epoch	Test Size
RNN Model 1	Tanh/Binary Cross Entropy/Adamax	98.81%	95.99%	150	30%
RNN Model 2	Sigmoid/Binary Cross Entropy/Adamax	98.31%	97.20%	150	30%
RNN Model 3	Sigmoid/Binary Cross Entropy/SGD	96.85%	96.47%	150	30%
RNN Model 4	Sigmoid/Binary Cross Entropy/SGD	96.21%	95.90%	150	30%
DNN Model 1	Sigmoid/Binary Cross Entropy/SGD	55.84%	55.35%	150	30%
DNN Model 2	Sigmoid/Adamax/Huber	98.84%	96.53%	150	30%
CNN Model 1	Tanh/Huber/Adamax	93.19%	90.59%	150	30%
CNN Model 2	Tanh/Binary Cross Entropy/Adam	92%	89.63%	150	30%
Combined Model 1	Softplus/Binary Cross Entropy/Adamax	91.23%	90.02%	150	30%
Combined Model 2	Softplus/Binary Cross Entropy/Adamax	98.48%	96.29%	150	30%
Combined Model 3	Softplus/Binary Cross Entropy/Adamax	98.54%	96.26%	150	30%

## 6. EXPERIMENTAL RESULTS

Model	Accuracy	Cross-Validation
		Accuracy
SVM	98.37%	94.74%
Bernoulli Naïve Bayes	91.86%	90.40%
KNN	98.91%	96.63%
Linear SVM	93.97%	92.65%
Gaussian Naïve Bayes	61.34%	60.38%
Decision Tree	98.76%	96.43%
Random Forest	99.09%	97.24%


Model	F1 Score	Precision	Recall
SVM	0.9852	0.9798	0.9907
Linear SVM	0.9470	0.9303	0.9644
KNN	0.9901	0.9875	0.9927
Gaussian Naïve Bayes	0.4544	0.9983	0.2941
Decision Tree	0.9888	0.9894	0.9881
Bernoulli Naïve Bayes	0.9267	0.9333	0.9202
Random Forest	0.9917	0.9895	0.9940
CNN Model 2	0.9061	0.9080	0.9041
CNN Model 1	0.9156	0.9092	0.9221
DNN Model 2	0.9688	0.9643	0.9733
DNN Model 1	0.7125	0.5535	1.0
RNN Model 4	0.9631	0.9574	0.9689
RNN Model 3	0.9681	0.9689	0.9673
RNN Model 2	0.9732	0.9769	0.9694
RNN Model 1	0.9642	0.9526	0.9760
Combined Model 1	0.9087	0.9025	0.9150
Combined Model 2	0.9661	0.9579	0.9744
Combined Model 3	0.9656	0.9635	0.9678



---


## 6. EXPERIMENTAL RESULTS – BEST ACCURACY






---

## 6. EXPERIMENTAL RESULTS – BEST F1-SCORE



---

## 6. EXPERIMENTAL RESULTS – BEST PRECISION



---

## 6. EXPERIMENTAL RESULTS – BEST RECALL

## 7. CONCLUSIONS



The deep learning algorithm that worked best was RNN. Although Random Forest, Decision Tree, SVM, KNN give good results in all comparison methods, we recommended it because Random Forest gave the best result.

# REFERENCES

1. Mohammad, R.M., McCluskey, L., & Thabtah, F. (2015, March). Training Dataset. URL: <https://archive.ics.uci.edu/ml/index.php>
2. Tan, C.L. (2018, March). Phishing Legitimate Full. URL: <https://data.mendeley.com/>
3. Banik, S. (2021, January). Dataset. URL: <https://www.kaggle.com/>
4. Adebawale, M. (2019, December). Text Frame Image Features. URL: <https://data.mendeley.com/>
5. Hannousse, A., & Yahiouche, S. (2020, September). dataset B 05 2020. URL: <https://data.mendeley.com/>
6. Mamun, M.S.I., Rathore, M.A., Lashkari, A.H., Stakhanova, N., & Ghorbani, A.A. (2016). Phishing. URL: <https://www.unb.ca/>
7. Yang, P., Zhao, G., & Zeng, P. (2019, January). Phishing Website Detection Based on Multidimensional Features Driven by Deep Learning (pp. 15196-15209). IEEE.
8. Wang, W., Zhang, F., Luo, X., & Zhang, S. (2019, October). PDRCNN: Precise Phishing Detection with Recurrent Convolutional Neural Networks (pp. 1-16). Wiley-Hindawi.
9. Adebawale, M.A., Lwin, K.T., & Hossain, M.A. (2019, August). Deep Learning with Convolutional Neural Network and Long Short-Term Memory for Phishing Detection. In 13<sup>th</sup> International Conference on SKIMA (pp. 1-8). IEEE, Island of Ukulhas, Maldives.
10. Kumar, J., Santhanavijayan, A., Janet, B., Rajendran, B., & Bindhumadhava, B.S. (2020, January). Phishing Website Classification and Detection Using Machine Learning. In ICCCI (pp. 1-6). IEEE, Coimbatore, India.
11. Opara, C., Wei, B., & Chen, Y. (2020, July). HTMLPhish: Enabling Phishing Web Page Detection by Applying Deep Learning Techniques on HTML Analysis. In IJCNN (pp. 1-8). IEEE, Glasgow, UK.
12. Yang, S. (2020, June). Research on Website Phishing Detection Based on LSTM RNN. In 4<sup>th</sup> ITNEC (pp. 284-288). IEEE, Chongqing, China.

---

THANK YOU FOR  
LISTENING TO US

---

