```c
#include <stdio.h>

int main() {
    float num1, num2, expected, experimental, error, error_percentage;
    float total_error_percentage = 0;
    char op;

    // For operation 1
    printf("Enter an operation (Example: 3+2): ");
    scanf("%f %c %f", &num1, &op, &num2);
    if (op == '+') { expected = num1 + num2; experimental = num1 - num2; }
    if (op == '-') { expected = num1 - num2; experimental = num1 * num2; }
    if (op == '*') { expected = num1 * num2; experimental = num1 + num2; }
    if (op == '/') { expected = num1 / num2; experimental = num1 - num2; }
    error = (expected > experimental) ? (expected - experimental) : (experimental - expected);
    if (expected != 0) error_percentage = (error / expected) * 100;
    else error_percentage = 0;
    total_error_percentage += error_percentage;
    printf("Expected Result: %0.2f\nExperimental Result: %0.2f\nError: %0.2f\nError Percentage: %0.2f\n", expected, experimental, error, error_percentage);

    // For operation 2
    printf("Enter an operation (Example: 3+2): ");
    scanf("%f %c %f", &num1, &op, &num2);
    if (op == '+') { expected = num1 + num2; experimental = num1 - num2; }
    if (op == '-') { expected = num1 - num2; experimental = num1 * num2; }
    if (op == '*') { expected = num1 * num2; experimental = num1 + num2; }
    if (op == '/') { expected = num1 / num2; experimental = num1 - num2; }
    error = (expected > experimental) ? (expected - experimental) : (experimental - expected);
    if (expected != 0) error_percentage = (error / expected) * 100;
    else error_percentage = 0;
    total_error_percentage += error_percentage;
    printf("Expected Result: %0.2f\nExperimental Result: %0.2f\nError: %0.2f\nError Percentage: %0.2f\n", expected, experimental, error, error_percentage);

    // For operation 3
    printf("Enter an operation (Example: 3+2): ");
    scanf("%f %c %f", &num1, &op, &num2);
    if (op == '+') { expected = num1 + num2; experimental = num1 - num2; }
    if (op == '-') { expected = num1 - num2; experimental = num1 * num2; }
    if (op == '*') { expected = num1 * num2; experimental = num1 + num2; }
    if (op == '/') { expected = num1 / num2; experimental = num1 - num2; }
    error = (expected > experimental) ? (expected - experimental) : (experimental - expected);
    if (expected != 0) error_percentage = (error / expected) * 100;
    else error_percentage = 0;
    total_error_percentage += error_percentage;
    printf("Expected Result: %0.2f\nExperimental Result: %0.2f\nError: %0.2f\nError Percentage: %0.2f\n", expected, experimental, error, error_percentage);

    // For operation 4
    printf("Enter an operation (Example: 3+2): ");
    scanf("%f %c %f", &num1, &op, &num2);
    if (op == '+') { expected = num1 + num2; experimental = num1 - num2; }
    if (op == '-') { expected = num1 - num2; experimental = num1 * num2; }
    if (op == '*') { expected = num1 * num2; experimental = num1 + num2; }
    if (op == '/') { expected = num1 / num2; experimental = num1 - num2; }
    error = (expected > experimental) ? (expected - experimental) : (experimental - expected);
    if (expected != 0) error_percentage = (error / expected) * 100;
    else error_percentage = 0;
    total_error_percentage += error_percentage;
    printf("Expected Result: %0.2f\nExperimental Result: %0.2f\nError: %0.2f\nError Percentage: %0.2f\n", expected, experimental, error, error_percentage);

    // Average Error
    printf("Average Error Value: %0.2f\n", total_error_percentage / 4);

    return 0;
}
```

```
Enter an operation (Example: 3+2): 3+2
Expected Result: 5.00
Experimental Result: 1.00
Error: 4.00
Error Percentage: 80.00%
Enter an operation (Example: 3+2): 6*4
Expected Result: 24.00
Experimental Result: 10.00
Error: 14.00
Error Percentage: 58.33%
Enter an operation (Example: 3+2): 8-5
Expected Result: 3.00
Experimental Result: 40.00
Error: 37.00
Error Percentage: 1233.33%
Enter an operation (Example: 3+2): 9/3
Expected Result: 3.00
Experimental Result: 6.00
Error: 3.00
Error Percentage: 100.00%
Average Error Value: 367.92%
```

```c
#include <stdio.h>
#define PI 3.14


int main()
{
 float diameter, radius, area;
    printf("r:");
    scanf("%f", &radius);
    area = 4 * PI * radius * radius;
    printf("Area of sphere: %0.2f", area);


    return 0;
}
```

```
r:1.0
Area of sphere: 12.56
```