

BookLib Kubernetes Manifests (Reviewer Package)

This package contains Kubernetes YAML manifests for deploying the **BookLib** microservice system.

Each `agg\_\*.yaml` file represents one valid BookLib configuration (gateway/aggregator + required services/variants).

Prerequisites

- A working Kubernetes cluster
- `kubectl` configured (`kubectl get nodes` works)

Install (example)

1) Create namespace:

```
``bash
```

```
kubectl create namespace booklib
```

2. Deploy service manifests (variants) and ads:

```
kubectl apply -n booklib -f adv.yaml
kubectl apply -n booklib -f gb_1.yaml
kubectl apply -n booklib -f gb2.yaml
kubectl apply -n booklib -f inven.yaml
kubectl apply -n booklib -f inven2.yaml
kubectl apply -n booklib -f recom.yaml
kubectl apply -n booklib -f recom2.yaml
kubectl apply -n booklib -f rev.yaml
kubectl apply -n booklib -f rev2.yaml
```

3. Activate one configuration:

```
kubectl apply -n booklib -f agg_0.yaml # example configuration
kubectl get pods -n booklib
```

Access

Find the gateway/aggregator service and port-forward it:

```
kubectl get svc -n booklib
kubectl port-forward -n booklib svc/<aggregator-service-name> 8080:80
```

Then open: <http://localhost:8080>

Switching configuration

```
kubectl delete -n booklib -f agg_0.yaml  
kubectl apply -n booklib -f agg_61.yaml
```

Notes

- Keep only the required service variant running per configuration (scale unused variants to 0 if needed).
- Troubleshooting:
 - `kubectl describe pod -n booklib <pod>`
 - `kubectl logs -n booklib <pod>`