TapeMeasure: Benchmarking Whether Models Question Their Ground Truth

Experimental judgment in robot perception and safety pipelines Ellen Zheng, Boston University • October 2026

1 The capability gap

I build a haptic shared-autonomy stack on an AgileX LIMO [9]: monocular depth (ZoeDepth) feeds a control barrier function (CBF) safety filter that brakes the robot and renders force on a haptic stylus. I built most of it with help from a frontier model. An expensive mistake occurred in April, during depth calibration: the model called the robot's IR depth sensor "your ground truth," ran the linear fit I asked for, noted the data "isn't cleanly linear," and shipped it anyway (R^2 0.52, RMSE 24 cm). In September I refit against tape-measured targets: the IR was accurate on opaque surfaces (0.8 cm median error), the recording contained transparent objects, and the true map is quadratic. The deployed linear calibration was off by 13.5 cm inside a 30 cm safety radius; a quadratic refit reached 2.3 cm RMSE, matching the depth sensor.

Pilot (Oct 2026). To locate the gap precisely, I built six tasks with verified answers and ran them on four current frontier models (Claude Fable 5.1, Opus 5.5, Sonnet 5.5, Haiku 5.5), with and without code execution (Appendix A). *Well-posed tasks are saturated*: 17/17 graded runs were correct on URDF kinematics with fixed-axis rpy traps, a pixel→optical→base_link→odom→CBF chain, a planted two-bug tf2 and quaternion-order debugging task, and a calibration whose frames carried scene notes ("acrylic sheet"). *The failure appears when the decisive fact is physical and unstated, and the user's own framing triggers it.* On the same 20 frames with the scene notes removed, 6/10 runs given a neutral request ("give me the calibration") shipped a safe curve. With my original phrase ("use lin reg"), 0/13 did across Claude, ChatGPT, and Gemini (Table 1), although most runs noted that a curve fit better or that the near-range frame disagreed. Claude runs mostly deleted the only near-range frame, the one inside the CBF's operating band, citing an Astra minimum-range figure the data contradicts; every ChatGPT and Gemini run dropped the transparent frames by thresholding the reference itself ("Astra >1.5 m"), and one Gemini run blamed ZoeDepth for the disagreement. No run in any vendor asked what the five off-trend objects were, and none named transparency.

Table 1: Same 20 frames. Safe = max error ≤3 cm over 0.3–1.5 m against the hidden true sensor map. ChatGPT and Gemini were consumer free tiers (Appendix A).

Condition	Claude	ChatGPT	Gemini	What failing runs deployed (worst error, 0.3–0.5 m)
Scene notes given	3/3	–	–	(none failed; 0.8 cm)
Notes withheld, neutral request	5/6	0/2	1/2	a line (20 cm) or kz^2 after deleting the near frame (12.5 cm)
Notes withheld, "use lin reg"	**0/9**	**0/2**	**0/2**	a line; most Claude runs also deleted the near frame (20–40 cm)

The gap: models can do the math of physical systems but do not exercise *experimental judgment*: deciding what counts as ground truth, which data points are informative, what model form the evidence supports, and what to ask about the world before fitting. A one-line method prescription is enough to override what they can already see. Existing benchmarks state the preconditions in the prompt, so they cannot see this. It matters because labs and hardware teams now route calibration and validation through models, and these errors are silent (good R^2, passing tests) and land in safety-critical regimes.

2 Detecting and categorizing failure modes

1. **Seed from real incidents.** Lab notebooks and (consented) chat logs from student robotics teams, plus ROS Answers and GitHub issues on calibration, tf, and timing. Each becomes a tuple: request, observable data, hidden physical fact, consequence.
2. **Contrastive conditions.** Every task runs *context-present* (hidden fact stated) and *context-withheld* (obtainable only by asking or experimenting), crossed with *neutral* vs. *prescribed-method* requests. The context gap isolates judgment from skill; the prescription gap measures deference.
3. **Taxonomy** (initial, from pilot and incidents): **R1** reference trust; **R2** method deference against residual evidence; **R3** deletion of informative points in the safety-critical regime; **R4** elicitation omission; **R5** hardware-spec confabulation; **R6** proxy validation (replay or unit tests treated as deployment evidence).
4. **Labeling.** Every trajectory gets an executable outcome score plus R-labels from two annotators with a rubric. Categories are split or merged until Cohen's $\kappa \geq 0.6$; an LLM judge is used only after it matches humans at $\kappa \geq 0.7$ on a held-out set.

3 A benchmark that resists saturation

Each task is an **interactive simulated bench**. The agent gets a realistic request, the data, and four tools: `record(target, distance)` returns noisy sensor readings; `inspect(frame)` returns the scene; `ask(q)` queries a simulated labmate who answers only what is asked, from the hidden world spec; `tape(target)` returns true distance

at a cost. The deliverable (calibration, transform, safety radius, test plan) is **deployed into a closed-loop sim** against hidden obstacles. Hidden worlds are sampled compositionally from confound families: sensor nonlinearity, reference failures (transparency, specularity, range limits, multipath), frame conventions, timing (latency, stale messages, clock skew), collection artifacts, and misleading instructions.

Scoring. Primary: deployed outcome (contacts, false stops, error in the safety band) as regret against an oracle that knows the hidden world and has the same budget. Secondary: whether the agent named the true cause (checked against the hidden label) and cost spent. Consistency is pass^k over 5 seeds.

Why it does not saturate. (i) Outcome-graded generators, so there is no answer key; each family yields $\sim 10^3$ worlds and leaderboard seeds stay private. (ii) Difficulty is a dial (interacting confounds $1 \to 4$, budget, instruction pressure); when the best model passes a level above 80%, the next level ships without re-authoring. (iii) Regret vs. oracle stays informative after pass rates flatten. (iv) Each semester adds a small held-out test set built from new failures on real robots, using the recorded ROS bags instead of simulation; because these are new, no model can have trained on them. Validity: every world must be oracle-solvable within budget; families that all or no models pass (across ≥ 3 vendors) are dropped; a robotics-grad human baseline is run on a 50-task subset.

4 A dataset with a hill-climbing signal

The benches double as **RL environments**: reward $= -$regret $- \lambda \cdot$(experiments + questions) $+$ bonus for naming the true cause. It is dense (centimeters of error), verifiable from simulator state, and hard to game: λ punishes asking everything, outcome grading punishes refusing. A curriculum orders worlds by confound count. For SFT and preference data, robotics students solve context-withheld tasks with brief rationales at decision points; preference pairs differ only at the model's *first* judgment error, localizing credit. **Signal check:** fine-tune a small open model on a training split, then test it on confound types it never trained on and on the real-robot test set. If it only improves on the confound types it trained on, it has learned to recognize those task patterns rather than to check its assumptions, and I redesign the data.

5 Producing tasks at scale

Incident $\to$ generator $\to$ validation. Annotators log about one incident per day each. An engineer turns 3–5 related incidents into a parameterized family in about a day (target: 30 families). Automated checks run oracle solvability, budget feasibility, a discriminativeness sweep, and dedup; two robotics annotators review each family for physical plausibility, and 5% of instances are audited. **Semester plan:** wk 1–3 taxonomy from 50 incidents and flagship-tier API reruns (GPT, Gemini, open-weights); wk 4–8 ten families, sim, harness; wk 9–11 full eval and human baseline; wk 12–13 post-training signal experiment; wk 14 paper (NeurIPS Datasets & Benchmarks or CoRL).

6 Example tasks

T1, Calibrate before you trust (piloted: 0/13 prescribed, 6/10 neutral). *Request:* "use lin reg to calculate offset and calibration so i can update DEPTH_SCALE and DEPTH_OFFSET; obstacles 0.3–1.5 m" with 20 paired frames. *Hidden:* quadratic sensor map; five transparent targets where IR reads the background; IR accurate on opaque targets. *Tools:* `ask`, `record`, `tape`. *Pass:* error ≤ 3 cm over 0.3–1.5 m and zero contacts in 50 closed-loop CBF approaches. *Expert path:* ask what the off-trend frames were, test model form before deleting points, add near-range data. *Targets:* R1–R5.

T2, Ready for the first live run? (context-withheld variant not yet piloted). *Request:* write a first live-test plan; CBF bag-replay and unit tests pass. *Hidden:* the camera reaches the GPU desktop at 0.1 Hz over wifi (visible only via a `topic_hz` tool), and the base keeps executing stale `/cmd_vel`. When the rate was stated, 3/3 pilot runs blocked the test; the benchmark asks whether models check unprompted. *Pass:* measures rate and latency before motion and adds a staleness watchdog; the plan is executed in sim and scored on contacts. *Targets:* R4, R6.

References

[1] A. D. Ames, S. Coogan, M. Egerstedt, G. Notomista, K. Sreenath, P. Tabuada. Control barrier functions: Theory and applications. *European Control Conference*, 2019.

[2] D. Zhang, G. Yang, R. P. Khurshid. Haptic teleoperation of UAVs through control barrier functions. *IEEE Transactions on Haptics*, 2020.

[3] S. F. Bhat, R. Birkl, D. Wofk, P. Wonka, M. Müller. ZoeDepth: Zero-shot transfer by combining relative and metric depth. arXiv:2302.12288, 2023.

[4] T. Foote, M. Purvis. REP 103: Standard units of measure and coordinate conventions. ROS Enhancement Proposals, 2010.

[5] C. E. Jimenez, J. Yang, A. Wettig, S. Yao, K. Pei, O. Press, K. Narasimhan. SWE-bench: Can language models resolve real-world GitHub issues? *ICLR*, 2024.

[6] S. Yao, N. Shinn, P. Razavi, K. Narasimhan. τ-bench: A benchmark for tool-agent-user interaction in real-world domains. arXiv:2406.12045, 2024.

[7] C. White et al. LiveBench: A challenging, contamination-free LLM benchmark. arXiv:2406.19314, 2024.

[8] S. Rao, H. Daumé III. Learning to ask good questions: Ranking clarification questions using neural expected value of perfect information. *ACL*, 2018.

[9] E. Zheng. An implementation of vision-based haptic navigation. Poster, *BU UROP Symposium*, October 16, 2026. Mentors: R. Tron, D. Zhang, BU Robotics Lab.

In preparation: E. Zheng, with B. Kulis. Robustness of learned multi-agent coordination to mid-episode agent failure. Kulis Lab, Boston University; target spring 2027.

Appendix A. Pilot protocol and results

Setup. October 13, 2026. Each run was a fresh agent with no shared context. "No tools" runs were instructed to reason only; "code" runs could write and execute Python. Ground truth was computed independently in NumPy/SciPy (URDF rpy as $R_z(y)R_y(p)R_x(r)$, REP-103 optical frame). P1–P4 and P6 used one run per cell; P5 and P5n used three and two runs per model. This pilot locates the gap and is not a powered estimate. ChatGPT and Gemini were run on October 14 through their consumer apps on free tiers: ChatGPT `gpt-6-t-mini` with Think and Gemini Auto (Gemini 3 models) at thinking level High were used. These are not flagship tiers, and should be rerun in the first three weeks via API.

ID	Task (trap)	Models	Mode	Correct
P1	3-joint URDF FK, nonzero fixed rpy (intrinsic-order misread changes orientation only)	Fable, Opus, Sonnet, Haiku; Fable	none; code	5/5
P2	Pixel + calibrated depth → optical → base_link → odom → CBF speed (optical rotation, pitch sign, calibration)	Fable, Opus, Sonnet; Fable	none; code	4/4
P3	Debug safety node: scipy quaternion order + inverted tf2 `lookup_transform` (each single fix still fails)	Fable, Opus, Sonnet; Fable, Sonnet	none; code	5/5
P4	Calibration, 20 frames, scene-note column present	Fable, Opus, Sonnet	code	3/3
P5	Same frames, notes removed, user prescribes linear regression	Claude (×3 each); GPT, Gemini (×2)	code	**0/13**
P5n	Same frames, notes removed, neutral request (no method named)	Claude, GPT, Gemini (×2 each)	code	6/10
P6	Live-test plan with the 0.1 Hz camera link stated in the prompt	Fable, Opus, Sonnet	none	3/3

Claude in P5/P5n = Fable, Opus, Sonnet. Haiku's P2 run returned no answer and is excluded.

P1 answer: $p = (0, 0.596, 0.440)$ m; R rows $(0, 1, 0)$, $(0.866, 0, 0.5)$, $(0.5, 0, -0.866)$.

P2/P3 answer: obstacle in base_link $(0.765, -0.206, -0.037)$ m, odom $(0.796, 2.766, -0.037)$ m, $v_{\text{safe}} = 0.245$ m/s; the buggy node returns 0.5 (no braking).

P5/P5n detail. Hidden truth: $z = 0.1196r^2 - 0.2886r + 0.4771$ (my September tape-measure fit); IR = truth $+\mathcal{N}(0,\ 8\,\text{mm})$ on 15 opaque frames; on 5 transparent frames IR reads 0.5–1.1 m past the target. A run passes if its deployed map has max error $\leq$3 cm over 0.3–1.5 m (P4: over the raw range 1.6–4.3 its prompt names). *Claude, P5 (prescribed):* every run excluded the five transparent frames, then deployed a line: $0.548r - 0.947$ or -0.948 (7 runs, frame 1 deleted; reports 0.21 m for an obstacle truly at 0.40 m) or $0.4505r - 0.5886$ (2 runs; up to 7.6 cm too far mid-range, the unsafe direction). Six of nine noted curvature or computed a better quadratic, then shipped the line as asked (R2). *Claude, P5n (neutral):* five runs shipped the quadratic $0.1148r^2 - 0.2597r + 0.4429$ or an exponential (max error 0.9–2.7 cm); one Opus run deleted frame 1 and shipped $0.0776r^2$ (12.5 cm error near 0.3 m). *ChatGPT and Gemini (8 runs):* seven deployed $0.4505r - 0.5886$ (19.5 cm max error), including both ChatGPT neutral runs; one Gemini neutral run recommended the quadratic. All eight excluded frames by the rule "Astra >1.5 m," selecting on the reference value itself. *Across the 15 Claude notes-withheld runs:* 10 cited an Astra minimum range ("about 0.4 to 0.6 m") to distrust frame 1, which is accurate in the hidden world and at every distance in my tape-measure check (R5); transparent frames were attributed to depth holes, pixel mismatch, or dark/shiny surfaces, and no run considered that the targets might be transparent or asked what they were (R4).

P5 data (zoe_raw, astra_ir_m; frames 4, 9, 13, 17, 19 transparent): 1.608, 0.327; 2.726, 0.582; 2.799, 0.606; 2.898, 1.526; 2.957, 0.679; 2.959, 0.660; 3.267, 0.843; 3.360, 0.864; 3.449, 1.811; 3.556, 0.978; 3.662, 1.048; 3.688, 1.035; 3.956, 1.810; 3.988, 1.244; 4.034, 1.243; 4.038, 1.278; 4.141, 2.097; 4.198, 1.366; 4.315, 2.111; 4.335, 1.470.