

E:\EXP 17.C - µVision

File Edit View Project Flash Debug Peripherals Tools SVCS Window Help

Registers Disassembly

Register Va...
r0 0x00
r1 0x00
r2 0x00
r3 0x00
r4 0x00
r5 0x00
r6 0x00
r7 0x00
Sys
a 0x00
b 0x00
sp 0x07
sp_max 0x07
dptr 0x...
PC \$ C:00000000
states 20...
sec 10...
paw 0x00

EXP 17.C
7 P1 = SBUF;
8 RI = 0;
9 }
10 }
11 }
12 void main()
13 {
14 TMOD=0x20;
15 TH1=0xFD;
16 SCON=0x50;
17 TR1=1;
18 ES=1;
19 EA=1;
20 while(1);
21 }

Disassembly
C:0x0814 F6 MOV @R0,A
C:0x0815 D8FD DJNZ R0,C:0814
C:0x0817 758107 MOV SP(0x81),#0x07
C:0x081A 020800 LAMP main(C:0800)

Interrupt System

Int Source	Vector	Mode	Req	Ena	Pri
P3.2/Int0	0003H	0	0	0	0
Timer 0	000BH	0	0	0	0
P3.3/Int1	0013H	0	0	0	0
Timer 1	001BH	1	0	0	0
Serial Rcv.	0023H	0	1	0	0
Serial Xmit.	002BH	0	1	0	0

Selected Interrupt
☒ EA ☐ IT0 ☐ IE0 ☐ EX0 Pri.: 0

Parallel Port 0
Port 0
P0: 0xFF 7 Bits 0
Pins: 0xFF ☒ ☒ ☒ ☒ ☒ ☒ ☒ ☒

Serial Channel
Mode: 8-Bit var. Baudrate
SCON: 0x54 SBUF: 0x00
☐ SM2 ☒ REN
☐ TB8 ☒ RB8
Baudrate ☐ SMOD ☐ TI
Baudrate: 20833 ☐ RI

Command
Running with Code Size Limit: 2K
Load "E:\Objects\EXP 17"

UART #1

ASM ASSIGN BreakDisable BreakEnable BreakKill BreakList BreakSet BreakAccess

Simulation t1: 1026.61271700 sec L:20 C:1 CAP NUM SCRL OVR R/W