

E:\EXP 16.uvproj - µVision

File Edit View Project Flash Debug Peripherals Tools SVCS Window Help

Registers Disassembly

Register Value

Register	Value
r0	0x00
r1	0x00
r2	0x00
r3	0x00
r4	0x00
r5	0x00
r6	0x00
r7	0x00
sp	0x00
sp_max	0x00
dptr	0x00
PC	0x00
states	0x00
sec	0x00
psw	0x00

Disassembly

```
28: TH1 = 0xFD; // Baud rate 9600
C:0x0CAC 758DFD MOV TH1(0x8D),#0xFD
29: TR1 = 1; // Start Timer1
30:
```

EXP 16.C

```
24 void main(void)
25 {
26     SCON = 0x50; // UART mode 1, 8-bit, REN enabled
27     TMOD = 0x20; // Timer1 mode 2 (auto-reload)
28     TH1 = 0xFD; // Baud rate 9600
29     TR1 = 1; // Start Timer1
30
31     IE = 0x90; // EA = 1, ES = 1 (enable serial interrupt)
32
33     TI = 1; // Enable printf
34
35     while(1)
36     {
37         printf("Hello World\n");
38         delay();
39     }
40 }
```

Interrupt System

Int Source	Vector	Mode	Req	Ena	Pri
P3.2/int0	0003H	0	0	0	0
Timer 0	000BH	0	0	0	0
P3.3/int1	0013H	0	0	0	0
Timer 1	001BH	1	0	0	0
Serial Rcv.	0023H	0	1	0	0
Serial Xmt.	002BH	1	1	0	0

Selected Interrupt

☒ EA ☐ IT0 ☐ IE0 ☐ EX0 Pri.: 0

Command

Running with Code Size Limit: 2K

Load "E:\Objects\EXP 16"

UART #1

```
>> INTERRUPT RECEIVED: 2
Hello World
Hello World
```

ASM ASSIGN BreakDisable BreakEnable BreakKill BreakList BreakSet BreakAccess

Simulation t1: 6718.00784450 sec L:28 C:1 CAP NUM SCRL OVR R/W