Status	Finished
Started	Wednesday, 21 October 2026, 10:37 PM
Completed	Wednesday, 21 October 2026, 10:42 PM
Duration	4 mins 44 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which method can be used to read all lines of a file into a list?

- a. readlines() ✓
- b. readline()
- c. read()
- d. readlist()

The correct answer is: readlines()

Question **2**

Correct

Mark 1.00 out of 1.00

Which method is used to truncate a file to a specific size?

- a. shrink()
- b. reduce()
- c. truncate() ✓
- d. resize()

The correct answer is: truncate()

Question **3**

Correct

Mark 1.00 out of 1.00

What does the encoding parameter in the open() function specify?

a. The size of the file
b. The encoding format of the file ✓
c. The mode of the file
d. The buffer size

The correct answer is: The encoding format of the file

Question **4**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in write mode ('w') and the file already exists?

a. It does nothing
b. It appends data to the file
c. It raises an error
d. It clears the old data and starts fresh ✓

The correct answer is: It clears the old data and starts fresh

Question **5**

Correct

Mark 1.00 out of 1.00

Which method is used to sets the position of a file pointer

a. seek() ✓
b. tell()
c. ftell()
d. fseek()

The correct answer is: seek()

Question **6**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
f = open("test.txt", "w")
f.write("Hello, world!")
f.close()
f = open("test.txt", "r")
print(f.read())
f.close()
```

a. Hello, world! ✓

b. Hello

c. world

d. An error is raised

The correct answer is: Hello, world!

Question **7**

Correct

Mark 1.00 out of 1.00

What does the following code do?

fo = open("foo.txt", "w")

a. Opens a file in binary mode

b. Opens an existing file in read mode

c. Appends to an existing file

d. Creates a new file for writing ✓

The correct answer is: Creates a new file for writing

Question **8**

Correct

Mark 1.00 out of 1.00

What does the buffering parameter in the open() function control?

- a. The buffer size for the file operations ✓
- b. The access mode of the file
- c. The file's read/write position
- d. The encoding of the file

The correct answer is: The buffer size for the file operations

Question **9**

Correct

Mark 1.00 out of 1.00

Select the incorrect file access mode

- a. rw+ ✓
- b. r
- c. ab+
- d. wb+

The correct answer is: rw+

Question **10**

Correct

Mark 1.00 out of 1.00

What will the read() method return if used on an empty file?

- a. An empty string ✓
- b. None
- c. EOFError
- d. 0

The correct answer is: An empty string

Question **11**

Correct

Mark 1.00 out of 1.00

What is the use of seek() method in files?

a. sets the file's current position within the file

b. sets the file's previous position at the offset

c. none of the mentioned

d. sets the file's current position at the offset ✓

The correct answer is:
sets the file's current position at the offset

Question **12**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for writing, we use ____

a. outfile = open("c:\\scores.txt", "w") ✓

b. outfile = open("c:\scores.txt", "w")

c. outfile = open(file = "c:\\scores.txt", "w")

d. outfile = open(file = "c:\scores.txt", "w")

The correct answer is:
outfile = open("c:\\scores.txt", "w")

Question **13**

Correct

Mark 1.00 out of 1.00

Which function is used to open a file in Python?

a. open_file()

b. open() ✓

c. openfile()

d. file()

The correct answer is: open()

Question **14**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

a. move the file pointer five characters behind from the current position

b. moves the file pointer to the end of a file

c. move the file pointer to beginning of the file

d. move the file pointer five characters ahead from the current position ✓

The correct answer is:
move the file pointer five characters ahead from the current position

Question **15**

Correct

Mark 1.00 out of 1.00

Which method is used to read a specific number of characters from a file?

a. readchar()

b. read(size) ✓

c. readlines()

d. readline()

The correct answer is: read(size)