

LLM Optimization

Jordan Boyd-Graber

University of Maryland

Quantization

Slides adapted from https://huggingface.co/docs/optimum/concept_guides/quantization

Motivation for Quantization

Why Quantize?

- **Memory efficiency:** reduces model size
- **Faster inference:** accelerates computation on specialized hardware
- **Lower energy use:** fewer bits mean less data movement
- **Deployment ease:** run on edge or CPU devices

Why Not Quantize?

- **Accuracy loss:** rounding and clipping errors
- **Sensitivity:** some layers (e.g., embeddings, layernorm) don't work
- **Hardware dependence:** performance gains vary by platform
- **Complexity:** requires calibration or quantization-aware retraining

LLAMA Example (from Meta)

- For models trained in FP16 (16-bit), converting to INT8 (8-bit) reduces memory usage by 50%, while INT4 (4-bit) reduces it by 75%.
- INT8 quantization can provide a 2-4x speedup on modern hardware, while INT4 can offer even greater speedups.

Types of Quantization: float16 vs. int8

Reduced-Precision Floating Point (FP16)

$$x = (-1)^s \times (1 + m) \times 2^{e-15}$$

Component	Bits	Range	Notes
Sign	1	\pm	Sign bit
Exponent	5	$[-14, +15]$	Reduced range
Mantissa	10	—	Reduced precision

Integer Quantization (INT8)

Component	Bits	Notes
Sign + Magnitude	8	Two's complement integer

Types of Quantization: float16 vs. int8

Reduced-Precision Floating Point (FP16)

$$x = (-1)^s \times (1 + m) \times 2^{e-15}$$

Component	Bits	Range	Notes
Sign	1	\pm	Sign bit
Exponent	5	$[-14, +15]$	Reduced range
Mantissa	10	—	Reduced precision

Integer Quantization (INT8)

Component	Bits	Notes
Sign + Magnitude	8	Two's complement integer

Affine Quantization: Mapping Float Values to INT8

Core Equation

$$x = S \times (x_q - Z)$$

- x — original **floating-point** value.

$$x_q \in [-128, 127], \quad S > 0, \quad Z \in \mathbb{Z}$$

Affine Quantization: Mapping Float Values to INT8

Core Equation

$$x = S \times (x_q - Z)$$

- x — original **floating-point** value.
- S — **scale factor** that maps integer steps to real value intervals.

$$x_q \in [-128, 127], \quad S > 0, \quad Z \in \mathbb{Z}$$

Affine Quantization: Mapping Float Values to INT8

Core Equation

$$x = S \times (x_q - Z)$$

- x — original **floating-point** value.
- S — **scale factor** that maps integer steps to real value intervals.
- x_q — **quantized integer** representation (usually in $[-128, 127]$).

$$x_q \in [-128, 127], \quad S > 0, \quad Z \in \mathbb{Z}$$

Affine Quantization: Mapping Float Values to INT8

Core Equation

$$x = S \times (x_q - Z)$$

- x — original **floating-point** value.
- S — **scale factor** that maps integer steps to real value intervals.
- x_q — **quantized integer** representation (usually in $[-128, 127]$).
- Z — **zero-point offset**, ensuring $x = 0$ maps to an integer in range.

$$x_q \in [-128, 127], \quad S > 0, \quad Z \in \mathbb{Z}$$

Affine Quantization: Mapping Float Values to INT8

Core Equation

$$x = S \times (x_q - Z)$$

- x — original **floating-point** value.
- S — **scale factor** that maps integer steps to real value intervals.
- x_q — **quantized integer** representation (usually in $[-128, 127]$).
- Z — **zero-point offset**, ensuring $x = 0$ maps to an integer in range.

Typical ranges:

$$x_q \in [-128, 127], \quad S > 0, \quad Z \in \mathbb{Z}$$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- Float range: $x_{\min} = -1.0$, $x_{\max} = 2.0$
- Integer range: $q_{\min} = -128$, $q_{\max} = 127$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- Float range: $x_{\min} = -1.0$, $x_{\max} = 2.0$
- Integer range: $q_{\min} = -128$, $q_{\max} = 127$
- Compute scale:

$$S = \frac{x_{\max} - x_{\min}}{q_{\max} - q_{\min}} = \frac{3}{255} \approx 0.01176$$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- Float range: $x_{\min} = -1.0$, $x_{\max} = 2.0$
- Integer range: $q_{\min} = -128$, $q_{\max} = 127$
- Compute scale:

$$S = \frac{x_{\max} - x_{\min}}{q_{\max} - q_{\min}} = \frac{3}{255} \approx 0.01176$$

- Compute zero-point:

$$Z = \text{round}\left(q_{\min} - \frac{x_{\min}}{S}\right) = \text{round}(-128 + 85) = -43$$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- $S = 0.01176$
- $Z = -43$

Forward mapping:

$$x_q = \text{round}\left(\frac{x}{S} + Z\right)$$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- $S = 0.01176$
- $Z = -43$

Forward mapping:

$$x_q = \text{round}\left(\frac{x}{S} + Z\right)$$

Examples:

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- $S = 0.01176$
- $Z = -43$

Forward mapping:

$$x_q = \text{round}\left(\frac{x}{S} + Z\right)$$

Examples:

$$x = -0.8$$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- $S = 0.01176$
- $Z = -43$

Forward mapping:

$$x_q = \text{round}\left(\frac{x}{S} + Z\right)$$

Examples:

$$x = -0.8 \rightarrow$$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- $S = 0.01176$
- $Z = -43$

Forward mapping:

$$x_q = \text{round}\left(\frac{x}{S} + Z\right)$$

Examples:

$$x = -0.8 \quad \rightarrow \quad \text{round}\left(\frac{-0.8}{0.01176} - 43\right)$$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- $S = 0.01176$
- $Z = -43$

Forward mapping:

$$x_q = \text{round}\left(\frac{x}{S} + Z\right)$$

Examples:

$$x = -0.8 \quad \rightarrow \quad \text{round}\left(\frac{-0.8}{0.01176} - 43\right) = -111$$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- $S = 0.01176$
- $Z = -43$

Forward mapping:

$$x_q = \text{round}\left(\frac{x}{S} + Z\right)$$

Examples:

$$\begin{array}{l} x = -0.8 \quad \rightarrow \quad \text{round}\left(\frac{-0.8}{0.01176} - 43\right) = -111 \\ x = 0.5 \end{array}$$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- $S = 0.01176$
- $Z = -43$

Forward mapping:

$$x_q = \text{round}\left(\frac{x}{S} + Z\right)$$

Examples:

$$\begin{array}{ll} x = -0.8 & \rightarrow \text{round}\left(\frac{-0.8}{0.01176} - 43\right) = -111 \\ x = 0.5 & \rightarrow \end{array}$$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- $S = 0.01176$
- $Z = -43$

Forward mapping:

$$x_q = \text{round}\left(\frac{x}{S} + Z\right)$$

Examples:

$$\begin{aligned}x = -0.8 &\rightarrow \text{round}\left(\frac{-0.8}{0.01176} - 43\right) = -111 \\x = 0.5 &\rightarrow \text{round}\left(\frac{0.5}{0.01176} - 43\right)\end{aligned}$$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- $S = 0.01176$
- $Z = -43$

Forward mapping:

$$x_q = \text{round}\left(\frac{x}{S} + Z\right)$$

Examples:

$$\begin{aligned}x = -0.8 &\rightarrow \text{round}\left(\frac{-0.8}{0.01176} - 43\right) = -111 \\x = 0.5 &\rightarrow \text{round}\left(\frac{0.5}{0.01176} - 43\right) = -1\end{aligned}$$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- $S = 0.01176$
- $Z = -43$

Forward mapping:

$$x_q = \text{round}\left(\frac{x}{S} + Z\right)$$

Examples:

$$\begin{aligned}x = -0.8 &\rightarrow \text{round}\left(\frac{-0.8}{0.01176} - 43\right) = -111 \\x = 0.5 &\rightarrow \text{round}\left(\frac{0.5}{0.01176} - 43\right) = -1 \\x = 1.5 &\end{aligned}$$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- $S = 0.01176$
- $Z = -43$

Forward mapping:

$$x_q = \text{round}\left(\frac{x}{S} + Z\right)$$

Examples:

$$\begin{aligned}x = -0.8 &\rightarrow \text{round}\left(\frac{-0.8}{0.01176} - 43\right) = -111 \\x = 0.5 &\rightarrow \text{round}\left(\frac{0.5}{0.01176} - 43\right) = -1 \\x = 1.5 &\rightarrow\end{aligned}$$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- $S = 0.01176$
- $Z = -43$

Forward mapping:

$$x_q = \text{round}\left(\frac{x}{S} + Z\right)$$

Examples:

$$\begin{aligned}x = -0.8 &\rightarrow \text{round}\left(\frac{-0.8}{0.01176} - 43\right) = -111 \\x = 0.5 &\rightarrow \text{round}\left(\frac{0.5}{0.01176} - 43\right) = -1 \\x = 1.5 &\rightarrow \text{round}\left(\frac{1.5}{0.01176} - 43\right)\end{aligned}$$

Worked Example: Forward Quantization ($x \rightarrow x_q$)

Setup

- $S = 0.01176$
- $Z = -43$

Forward mapping:

$$x_q = \text{round}\left(\frac{x}{S} + Z\right)$$

Examples:

$$\begin{aligned}x = -0.8 &\rightarrow \text{round}\left(\frac{-0.8}{0.01176} - 43\right) = -111 \\x = 0.5 &\rightarrow \text{round}\left(\frac{0.5}{0.01176} - 43\right) = -1 \\x = 1.5 &\rightarrow \text{round}\left(\frac{1.5}{0.01176} - 43\right) = 85\end{aligned}$$

But how to set the mapping? (post hoc)

- Area of active research
- You have to quantize each layer
- Error propagates
- Strategy: Select the quantization that minimizes the overall error

But how to set the mapping? (post hoc)

- Area of active research
- You have to quantize each layer
- Error propagates
- Strategy: Select the quantization that minimizes the overall error
 - ▶ On a representative data
 - ▶ Order matters!

Recap

- Modern models are big
- Quantization lets you run them on smaller computers (or phones)
- While it degrades accuracy, you can strategically quantize to minimize it

