

Sequence Models

Jordan Boyd-Graber

University of Maryland

Backpack Models (Attention)

Slides adapted from Joshua Wagner, Matthias Assenmacher, Jay Alammar

Plan for Today

- Transition from linear NLM structures
- What made Transformer Language Models “a thing”
 - ▶ Attention
 - ▶ Multi-layer, multi-head
 - ▶ Transformers
- Hint at why they generalize so well (representations)

History of attention

NEURAL MACHINE TRANSLATION BY JOINTLY LEARNING TO ALIGN AND TRANSLATE

Dzmitry Bahdanau
Jacobs University Bremen, Germany

KyungHyun Cho Yoshua Bengio*
Université de Montréal

How to represent final state given previous words:

$$c = q(\{h_1, \dots, h_T\}) \quad (1)$$


New context vector is weighted sum of the hidden states:

$$c_t = \sum_{i=1}^{T_x} \alpha_{t,i} h_i. \quad (2)$$

Where the coefficients are

$$\alpha_{t,i} = \text{align}(y_t, x_i) = \frac{\exp(\text{score}(s_{t-1}, h_i))}{\sum_{i'=1}^n \exp(\text{score}(s_{t-1}, h_{i'}))} \quad (3)$$

History of attention



Attention Is All You Need

Ashish Vaswani*
Google Brain
avaswani@google.com

Noam Shazeer*
Google Brain
noam@google.com

Niki Parmar*
Google Research
nikip@google.com

Jakob Uszkoreit*
Google Research
usz@google.com

Llion Jones*
Google Research
llion@google.com

Aidan N. Gomez* †
University of Toronto
aidan@cs.toronto.edu


Łukasz Kaiser*
Google Brain
lukaszkaier@google.com

Illia Polosukhin* ‡
illia.polosukhin@gmail.com

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^{\top}}{\sqrt{d_k}}\right)V \quad (4)$$


Key-Value Attention

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^\top}{\sqrt{d_k}}\right) V \quad (4)$$




Key-Value Attention

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^\top}{\sqrt{d_k}}\right)V \quad (4)$$



Key-Value Attention

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right)V \quad (4)$$



Returning to Backpack Language Model Example: "That trick was sick"

Sentence: "That trick was sick"

that	trick	was	sick
$C(\text{that})_0$	$C(\text{trick})_0$	$C(\text{was})_0$	$C(\text{sick})_0$
$(0 \ 0 \ 0 \ 0)$	$(0 \ 0 \ 1 \ 0)$	$(0 \ 0 \ 0 \ 0)$	$(1 \ 0 \ 1 \ 0)$
$C(\text{that})_1$	$C(\text{trick})_1$	$C(\text{was})_1$	$C(\text{sick})_1$
$(0 \ 0 \ 0 \ 0)$	$(0 \ 0 \ 0 \ 0)$	$(0 \ 0 \ 0 \ 0)$	$(0 \ 1 \ 0 \ 1)$

Explanation:

- Each word has two sense vectors: $C(x_i)_1$ and $C(x_i)_2$.
- "that" and "was" have zero vectors for both senses.
- "trick" has a non-zero vector for $C(\text{trick})_1$ at the third position (evokes skateboarding), while the second vector is zero.
- "sick" has two non-zero vectors: $C(\text{sick})_1$ and $C(\text{sick})_2$: positive for skateboard, negative for health.

Returning to Backpack Language Model Example: "That trick was sick"

Sentence: "That trick was sick"

that	trick	was	sick
$C(\text{that})_0$	$C(\text{trick})_0$	$C(\text{was})_0$	$C(\text{sick})_0$
$\begin{pmatrix} 0 & 0 & 0 & 0 \end{pmatrix}$	$\begin{pmatrix} 0 & 0 & 1 & 0 \end{pmatrix}$	$\begin{pmatrix} 0 & 0 & 0 & 0 \end{pmatrix}$	$\begin{pmatrix} 1 & 0 & 1 & 0 \end{pmatrix}$
$C(\text{that})_1$	$C(\text{trick})_1$	$C(\text{was})_1$	$C(\text{sick})_1$
$\begin{pmatrix} 0 & 0 & 0 & 0 \end{pmatrix}$	$\begin{pmatrix} 0 & 0 & 0 & 0 \end{pmatrix}$	$\begin{pmatrix} 0 & 0 & 0 & 0 \end{pmatrix}$	$\begin{pmatrix} 0 & 1 & 0 & 1 \end{pmatrix}$

Explanation:

- Each word has two sense vectors: $C(x_i)_1$ and $C(x_i)_2$.
- "that" and "was" have zero vectors for both senses.
- "trick" has a non-zero vector for $C(\text{trick})_1$ at the third position (evokes skateboarding), while the second vector is zero.
- "sick" has two non-zero vectors: $C(\text{sick})_1$ and $C(\text{sick})_2$: positive for skateboard, negative for health.

Returning to Backpack Language Model Example: "That trick was sick"

Sentence: "That trick was sick"

that	trick	was	sick
$C(\text{that})_0$	$C(\text{trick})_0$	$C(\text{was})_0$	$C(\text{sick})_0$
$(0 \ 0 \ 0 \ 0)$	$(0 \ 0 \ 1 \ 0)$	$(0 \ 0 \ 0 \ 0)$	$(1 \ 0 \ 1 \ 0)$
$C(\text{that})_1$	$C(\text{trick})_1$	$C(\text{was})_1$	$C(\text{sick})_1$
$(0 \ 0 \ 0 \ 0)$	$(0 \ 0 \ 0 \ 0)$	$(0 \ 0 \ 0 \ 0)$	$(0 \ 1 \ 0 \ 1)$

Explanation:

- Each word has two sense vectors: $C(x_i)_1$ and $C(x_i)_2$.
- "that" and "was" have zero vectors for both senses.
- "trick" has a non-zero vector for $C(\text{trick})_1$ at the third position (evokes skateboarding), while the second vector is zero.
- "sick" has two non-zero vectors: $C(\text{sick})_1$ and $C(\text{sick})_2$: positive for skateboard, negative for health.

Returning to Backpack Language Model Example: "That trick was sick"

Sentence: "That trick was sick"

that	trick	was	sick
$C(\text{that})_0$	$C(\text{trick})_0$	$C(\text{was})_0$	$C(\text{sick})_0$
$(0 \ 0 \ 0 \ 0)$	$(0 \ 0 \ 1 \ 0)$	$(0 \ 0 \ 0 \ 0)$	$(1 \ 0 \ 1 \ 0)$
$C(\text{that})_1$	$C(\text{trick})_1$	$C(\text{was})_1$	$C(\text{sick})_1$
$(0 \ 0 \ 0 \ 0)$	$(0 \ 0 \ 0 \ 0)$	$(0 \ 0 \ 0 \ 0)$	$(0 \ 1 \ 0 \ 1)$

Explanation:

- Each word has two sense vectors: $C(x_i)_1$ and $C(x_i)_2$.
- "that" and "was" have zero vectors for both senses.
- "trick" has a non-zero vector for $C(\text{trick})_1$ at the third position (evokes skateboarding), while the second vector is zero.
- "sick" has two non-zero vectors: $C(\text{sick})_1$ and $C(\text{sick})_2$: **positive for skateboard**, negative for health.

Returning to Backpack Language Model Example: "That trick was sick"

Sentence: "That trick was sick"

that	trick	was	sick
$C(\text{that})_0$	$C(\text{trick})_0$	$C(\text{was})_0$	$C(\text{sick})_0$
$(0 \ 0 \ 0 \ 0)$	$(0 \ 0 \ 1 \ 0)$	$(0 \ 0 \ 0 \ 0)$	$(1 \ 0 \ 1 \ 0)$
$C(\text{that})_1$	$C(\text{trick})_1$	$C(\text{was})_1$	$C(\text{sick})_1$
$(0 \ 0 \ 0 \ 0)$	$(0 \ 0 \ 0 \ 0)$	$(0 \ 0 \ 0 \ 0)$	$(0 \ 1 \ 0 \ 1)$

Explanation:

- Each word has two sense vectors: $C(x_i)_1$ and $C(x_i)_2$.
- "that" and "was" have zero vectors for both senses.
- "trick" has a non-zero vector for $C(\text{trick})_1$ at the third position (evokes skateboarding), while the second vector is zero.
- "sick" has two non-zero vectors: $C(\text{sick})_1$ and $C(\text{sick})_2$: positive for skateboard, **negative for health**.

Selecting the sense

Recap: Definition of $\alpha_{\ell,i,j}$:

$$\alpha_{\ell,i,j} = \begin{cases} 0 & \text{if } j \neq i \\ \sum_{r \neq i} \frac{C(\mathbf{x}_r)_{\ell+2}}{C(\mathbf{x}_r)_2 + C(\mathbf{x}_r)_3} & \text{if } j = i \end{cases} \quad (5)$$

Selecting the sense

Recap: Definition of $\alpha_{\ell,i,j}$:

$$\alpha_{\ell,i,j} = \begin{cases} 0 & \text{if } j \neq i \\ \sum_{r \neq i} \frac{C(\mathbf{x}_r)_{\ell+2}}{C(\mathbf{x}_r)_2 + C(\mathbf{x}_r)_3} & \text{if } j = i \end{cases} \quad (5)$$

How can you make this happen with attention?

Doing this with attention

What are the values?

What are the keys?

Doing this with attention

What are the values?

$$V = \begin{pmatrix} 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \end{pmatrix}$$

What are the keys?

Doing this with attention

What are the values?

What are the keys?

$$K = \begin{pmatrix} 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

But what are the queries?

But what are the queries?

$$\alpha_{\ell,i,j} = \begin{cases} 0 & \text{if } j \neq i \\ \sum_{r \neq i} \frac{C(\mathbf{x}_r)_{\ell+2}}{C(\mathbf{x}_r)_2 + C(\mathbf{x}_r)_3} & \text{if } j = i \end{cases} \quad (6)$$

But what are the queries?

$$\alpha_{\ell,i,j} = \begin{cases} 0 & \text{if } j \neq i \\ \sum_{r \neq i} \frac{C(\mathbf{x}_r)_{\ell+2}}{C(\mathbf{x}_r)_2 + C(\mathbf{x}_r)_3} & \text{if } j = i \end{cases} \quad (6)$$

$$Q = \begin{pmatrix} 0 & 0 & \frac{2}{3} & \frac{1}{3} \\ 0 & 0 & \frac{2}{3} & \frac{1}{3} \\ 0 & 0 & \frac{2}{3} & \frac{1}{3} \\ 0 & 0 & \frac{2}{3} & \frac{1}{3} \\ 0 & 0 & \frac{2}{3} & \frac{1}{3} \\ 0 & 0 & \frac{2}{3} & \frac{1}{3} \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 \end{pmatrix}$$

Putting it all together

$$\text{softmax}\left(\frac{QK^{\top}}{\sqrt{d}}\right) = \begin{pmatrix} 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{pmatrix} \quad (7)$$

Putting it all together

$$\text{softmax}\left(\frac{QK^{\top}}{\sqrt{d}}\right) = \begin{pmatrix} 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{pmatrix} \quad (7)$$

So summing over all senses, we get the sentiment 1000 (Only contributing from skateboard sense of “sick”).

