

---

## Table of Contents

Lab7 Week 8 Maze 1 Concepts 15/18/2015 .....	1
define pacman .....	1
Display Pacman .....	1
define maze .....	2
show final destination .....	3
Move Pacman about the maze .....	4
your code goes here ***** .....	5

## Lab7 Week 8 Maze 1 Concepts 15/18/2015

run this file and then modify it to complete the maze make sure it is in the same directory at your trans and rot functions


```
% Maze 1 Maze 1
close all; clear all;clc;
```

### define pacman

```
xcoords = [0 1 2 3 2    3 2 1 0];
ycoords = [2 1 1 2 2.5 3 4 4 3];
pacman = [xcoords;ycoords;ones(1,length(xcoords))]; % homogeneous
           coordinates
% note pacman's centeroid is 1.5 in x and 2.5 in y
```

### Display Pacman

```
figure(10)
fill(xcoords,ycoords,'r')
axis([0 5 0 5])
grid on; axis equal; hold on
title('my pacman for ENGR231 note center is 1.5, 2.5 wrt 0,0')
```



## define maze

create a new figure for maze and subsequent work

```
close all
figure(777)

% outer edges
mm = [[0;0], [25;0], [25;25], [0;25], [0;10], [15;10], [15;15],
      [5;15], [5;20]];
mazey1 = [[0;0], [0;5]] % vertical at end
% inner closure
mazex2= [[0;5], [20;5], [20;20], [5;20]];


plot(mm(1,:),mm(2,:), 'k', 'linewidth', 3)
hold on
plot(mazex2(1,:),mazex2(2,:), 'k', 'linewidth', 3)
plot(mazey1(1,:), mazey1(2,:), 'k', 'linewidth', 3)
axis([-5, 30, -5, 30])
grid on;
title('pacman maze Version 1')
```

```
mazey1 =
```

```
0      0
```


---

0 5



**show final destination**

```
plot(14,12.5, 'k*', 'linewidth', 5)
```




## Move Pacman about the maze

note the use of pause shows an animation if you run the completed file

```
% starting position
pac0 = trans(0,0)*pacman; % no translation
fill(pac0(1,:),pac0(2,:), 'r')

% move 12 units to right with no rotation
pac1= trans(12,0)*trans(1.5,2.5)*rot(0)*trans(-1.5,-2.5)*pacman;
fill(pac1(1,:),pac1(2,:), 'b')

% move to 21,0 put mouth facing up
% first move center of pacman to (0,0) rotate 90 degrees CW move back
to
% (1.5,2.5) then translate 21 in x referenced from the starting
position
pac2 = trans(21,0)*trans(1.5,2.5)*rot(90)*trans(-1.5,-2.5)*pacman;
fill(pac2(1,:),pac2(2,:), 'g')
```



**your code goes here \*\*\*\*\***

```
%[rand rand rand] gives you different colours everytime you run it!
% How Exciting!!! haha

pac3 = trans(0,10)*pac2;
fill(pac3(1,:),pac3(2,:),[rand rand rand])
% moving pacman 3 image 10 units in y

pac4 = trans(21,20)*trans(1.5,2.5)*rot(180)*trans(-1.5,-2.5)*pacman;
fill(pac4(1,:),pac4(2,:),[rand rand rand])
% creating pacman 4 by rotating orginial pacman by 180 degrees then
% translating 21 units in x and 20 units in y

pac5 = trans(1,20)*trans(1.5,2.5)*rot(-90)*trans(-1.5,-2.5)*pacman;
fill(pac5(1,:),pac5(2,:),[rand rand rand])
% creating pacman 5 by rotating orginial pacman by -90 degrees then
% translating 1 unit in x and 20 units in y


pac6 = trans(0,-5)*pac5;
fill(pac6(1,:),pac6(2,:),[rand rand rand])
% moving pacman 5 image -5 units in y

pac7 = trans(1,10)*pacman;
fill(pac7(1,:),pac7(2,:),[rand rand rand])
```

---

```
% moving original pacman image 1 unit in x and 10 units in y

pac8 = trans(10,0)*pac7;
fill(pac8(1,:),pac8(2,:),[rand rand rand])
% moving pacman 7 image 10 units in x
```



*Published with MATLAB® R2016a*