



Ember code-mods





ember-codemods

[Repositories](#) 25 [Packages](#) [People](#) 4 [Projects](#)

Pinned repositories

**directory**
A directory of Ember codemods
☆ 5 🍴 1

**ember-qunit-codemod**
JavaScript ☆ 37 🍴 19

**ember-native-class-codemod**
A codemod-cli project for converting Ember objects to es6 native classes
JavaScript ☆ 60 🍴 25

[Type](#) [Language](#) [Sort](#)

ember-tracked-properties-codemod
A codemod for transforming your ember app code to start using '@tracked' properties.
JavaScript MIT 🍴 2 ☆ 7 🕒 2 📄 18 Updated 6 days ago

ember-no-implicit-this-codemod
Template codemod for refactoring from '{{foo}}' to '{{this.foo}}'
ember template codemod
JavaScript MIT 🍴 13 ☆ 15 🕒 10 📄 10 Updated 7 days ago

power-select-deprecation-codemod
JavaScript 🍴 1 ☆ 0 🕒 0 📄 6 Updated 8 days ago


Top languages

JavaScript

Most used topics


codemod ember codemods emberjs jsodeshift

People

4 >

[Report abuse](#)

Automation for code refactoring

- <https://github.com/ember-codemods>
- [Ember native class codemod](#) ✓
- [Ember angle bracket mod](#) ✓
- There's tonnes



ember-codemods/ember-native-class-codemod

☰ README.md

🔗 ember-native-class-codemod

build **passing** npm package **2.1.0**

A codemod for transforming your ember app code to native JavaScript class syntax with decorators!

🔗 Usage

First, install the dependencies that the codemod relies on. These are addons that the codemod will add imports from:

```
ember install ember-classic-decorator  
ember install ember-decorators
```

Then, boot up your application. Then, the codemod can be run using the following command:

```
npx ember-native-class-codemod http://localhost:4200/path/to/server [OPTIONS] path/of/files/ or/some*
```

Make sure test coverage is sufficient

```
ezy@gun:~/Sites/mymisd/src/main/client$ yarn test:cov
yarn run v1.22.4
$ COVERAGE=true ember test
Environment: test
```

```
1..2558
# tests 2558
# pass 2558
# skip 0
# todo 0
# fail 0

# ok
Done in 217.99s.
```

All files app/routes

65.57% Statements 120/183 **56.99%** Branches 53/93 **56.94%** Functions 41/72 **66.86%** Lines 117/175

Press *n* or *j* to go to the next uncovered block, *b*, *p* or *k* for the previous block.

File ▲		Statements ▾	
accessibility.js		0%	0/0
application.js	<div><div></div></div>	43.9%	36/82
appointments.js		0%	0/0
authenticated.js	<div><div></div></div>	100%	14/14
base.js	<div><div></div></div>	91.67%	11/12

src/main/client/app/routes/base.js

```
{ } package.json JS apply-new-business.js 1 JS base.js 2 X JS welcome.js
src > main > client > app > routes > JS base.js > ...
Michael, a month ago | 4 authors (Adam Buczynski and others)
1  /* eslint-disable ember/no-controller-access-in-routes */
2  import Route from '@ember/routing/route';
3  import ProcessError from 'my-msd/mixins/process-error';
4
5  export default Route.extend(ProcessError, {
6    fallBackRoute: 'authenticated.index',
7
8    activate() {
9      this._super();
10     this.send('scrollToTop');
11   },
12
13   actions: {
14     error(error) {
15       this.processError(error, this.fallBackRoute);
16     },
17
18     ~ willTransition() {
19       if (this.controller.onExit && typeof this.controller.onExit === 'function') {
20         this.controller.onExit();
21       }
22       return true;
23     },
24
25     ~ didTransition() {
26       if (typeof this.controller.clearError === 'function') {
27         this.controller.clearError();
28       }
29
30       if (typeof this.controller.onEnter === 'function') {
31         this.controller.onEnter();
32       }
33       return true;
34     },
35   },
36 });
37
```

Run the code-mod

```
kitchen@kitchens-MacBook-Pro mymsd % cd src/main/client
kitchen@kitchens-MacBook-Pro client % npx ember-native-class-codemod http://localhost:4200 '/Users/kitchen/Sites/mymsd/src/main/client/app/routes/base.js'
```

Downloading Chromium r818858 - 132.4 Mb [=====] 100% 0.0s
Downloading Chromium r686378 - 110.2 Mb [=====] 100% 0.0s
error evaluating `ember-cli-mirage/db-collection`: Cannot set property default of #<Object> which has only a getter
error evaluating `my-msd/components/modals/about-letters`: Could not find module `letters/components/modals/about-letters` imported from `my-msd/components/modals/about-letters`
error evaluating `my-msd/components/modals/already-applied`: Could not find module `housing/components/modals/already-applied` imported from `my-msd/components/modals/already-applied`
error evaluating `my-msd/components/modals/callback-confirmation`: Could not find module `housing/components/modals/callback-confirmation` imported from `my-msd/components/modals/callback-confirmation`
error evaluating `my-msd/components/modals/check-phone-number`: Could not find module `housing/components/modals/check-phone-number` imported from `my-msd/components/modals/check-phone-number`
error evaluating `my-msd/components/modals/debt/debt-component`: Could not find module `debt/components/modals/debt/debt-component` imported from `my-msd/components/modals/debt/debt-component`
error evaluating `my-msd/components/modals/dependent-children`: Could not find module `housing/components/modals/dependent-children` imported from `my-msd/components/modals/dependent-children`
error evaluating `my-msd/components/modals/letters-notification-info`: Could not find module `letters/components/modals/letters-notification-info` imported from `my-msd/components/modals/letters-notification-info`
error evaluating `my-msd/helpers/format-date-night`: Could not find module `housing/helpers/format-date-night` imported from `my-msd/helpers/format-date-night`
error evaluating `my-msd/routes/appointments`: Could not find module `@ember/route` imported from `my-msd/routes/appointments`
error evaluating `my-msd/routes/info-youth`: Could not find module `housing/routes/info-youth` imported from `my-msd/routes/info-youth`
Processing 1 files...
Spawning 1 workers...
Sending 1 files to free worker...
All done.
Results:
0 errors
0 unmodified
0 skipped
1 ok
Time elapsed: 6.655seconds
kitchen@kitchens-MacBook-Pro client %

Profit

```
package.json JS apply-new-business.js 2 JS base.js 5 X JS index.js
src > main > client > app > routes > JS base.js > BaseRoute > didTransition
Michael, a month ago | 4 authors (You and others)
1 ~ import classic from 'ember-classic-decorator';
2 import { action } from '@ember/object';
3 /* eslint-disable ember/no-controller-access-in-routes */
4 import Route from '@ember/routing/route';
5 import ProcessError from 'my-msd/mixins/process-error';
6
7 You, 3 months ago | 2 authors (You and others)
8 @classic
9 ~ export default class BaseRoute extends Route.extend(ProcessError) {
10   fallBackRoute = 'authenticated.index';
11
12   activate() {
13     super.activate();
14     this.send('scrollTop');
15   }
16
17   @action
18   error(error) {
19     this.processError(error, this.fallBackRoute);
20   }
21
22   @action
23   willTransition() {
24     if (this.controller.onExit && typeof this.controller.onExit === 'function') {
25       this.controller.onExit();
26     }
27     return true;
28   }
29
30   @action
31   didTransition() {
32     if (typeof this.controller.clearError === 'function') {
33       this.controller.clearError();
34     }
35
36     if (typeof this.controller.onEnter === 'function') {
37       this.controller.onEnter();
38     }
39     return true;
40   }
41 }
```

The codemod accepts the following options:

Option	Value	Default	Details
<code>--class-fields</code>	boolean	true	Enable/disable transformation using class fields
<code>--decorators</code>	boolean	true	Enable/disable transformation using decorators
<code>--classic-decorator</code>	boolean	true	Enable/disable adding the <code>@classic</code> decorator, which helps with transitioning Ember Octane
<code>--type</code>	String	Empty (match all types in path)	Apply transformation to only passed type. The type can be one of <code>services</code> , <code>routes</code> , <code>components</code> , <code>controllers</code>
<code>--quote</code>	String	'single'	Whether to use double or single quotes by default for new statements that are added during the codemod.

Run your tests and submit your merge request

