PYTHON DATA APPS

Dash in 30 Minutes

From a Plotly chart to an interactive app, and what happens behind the scenes

Demos: `demos/01 … 06` in this repo · `pip install -r requirements.txt`

Plan

1. Plotly alone vs Dash: why a server 4 min
2. Building a page: layout, Plotly figures, widgets 5 min
3. Callbacks: how the browser hands work back to Python 7 min
4. Click a point, drill into another chart 4 min
5. Letting VS Code + Copilot write Dash for you 5 min
6. Showcase: a full app 4 min

1 · PLOTLY ALONE

Plotly: interactive figures, no server

```
import plotly.express as px
from data import bonds

fig = px.scatter(bonds, x="maturity", y="spread",
                 color="sector", hover_name="issuer")
fig.write_html("plotly_only.html")
```

- Python builds the figure **once**, as JSON
- The HTML holds the data + plotly.js
- Zoom, hover, legend clicks: all JavaScript in the browser



This chart is live: zoom, hover, click the legend. No server.

1 · PLOTLY ALONE

Where Plotly alone stops

Fine in the browser

- zoom, pan, hover, select
- toggle traces in the legend
- dropdowns/sliders that switch between data already in the file


Needs Python again

- "show me Energy only", recomputed
- query a database, call a model, run a pricer
- data too big to ship into one HTML file
- one chart driving another, with real logic

Plotly has no back end. Once the HTML is written, nothing can ask Python a new question.


Plotly vs Dash

Plotly alone: one way, once



No server: nothing is listening after the file is written.

Dash: a conversation



2 · BUILDING A PAGE

The smallest Dash app


```python
from dash import Dash, html, dcc
import plotly.express as px
from data import bonds

app = Dash(__name__)        # Flask server + Dash front end

fig = px.scatter(bonds, x="maturity", y="spread", color="sector")

app.layout = html.Div([     # the page: a tree of components
    html.H1("Corporate bonds"),
    html.P(f"{len(bonds)} bonds"),
    dcc.Graph(figure=fig),  # any Plotly figure goes here
])

if __name__ == "__main__":
    app.run(debug=True)     # http://127.0.0.1:8050
```





```
cd demos; python 02_hello_dash.py
```

2 · BUILDING A PAGE

A layout is a tree of components

- `html.*`: one class per HTML tag: `Div`, `H1`, `P`, `Table`, `Button` …
- `dcc.*`: interactive pieces: `Graph`, `Dropdown`, `Slider`, `Tabs` …
- Each component has **props**: `children`, `style`, `className`, `value`, `figure` …
- An `id` names a component so callbacks can read or write its props
- CSS files in `assets/` are loaded automatically



Dash serialises this tree to JSON (GET /_dash-layout);
the browser turns it into real HTML elements.

blue = has an id, so callbacks can use it

Plotly figures inside Dash

`dcc.Graph` takes any Plotly figure: `plotly.express` or `graph_objects`, same code as in a notebook.

```
dcc.Graph(
    id="chart",
    figure=px.line(df, x="date", y="spread"),
    config={"displayModeBar": False},
    style={"height": "400px"},
)
```

A graph is also an input. The browser fills these props when the user acts:


prop	set when you…
`clickData`	click a point
`hoverData`	hover a point
`selectedData`	box / lasso select
`relayoutData`	zoom or pan

We use `clickData` in section 4.

Widgets you get for free

component	its value prop
`dcc.Dropdown` (single / multi)	`value`
`dcc.Checklist`, `dcc.RadioItems`	`value`
`dcc.Slider`, `dcc.RangeSlider`	`value`
`dcc.Input` (text, number…)	`value`
`dcc.DatePickerSingle` / `Range`	`date` / `start_date` …
`dcc.Tabs`	`value`
`html.Button`	`n_clicks`
`dcc.Interval` (a timer)	`n_intervals`
`dcc.Store`, `dcc.Upload`, `dcc.Download`	data / files

add-ons: `dash-ag-grid`, `dash-bootstrap-components`, `dash-mantine-components`





```
cd demos; python 03_widgets.py
```

A callback: "when this changes, run that"

```python
from dash import Dash, html, dcc, callback, Output, Input

app.layout = html.Div([
    html.H1("Corporate bonds"),
    dcc.Dropdown(sectors, "Banks", id="sector"),
    html.P(id="summary"),
    dcc.Graph(id="chart"),
])

@callback(Output("summary", "children"),
          Output("chart", "figure"),
          Input("sector", "value"))
def update(sector):
    print(f"server: update({sector!r})")
    d = bonds[bonds.sector == sector]
    text = f"{len(d)} {sector} bonds, avg {d.spread.mean():.0f} bp"
    fig = px.scatter(d, x="maturity", y="spread", color="issuer")
    return text, fig
```




```
cd demos; python 04_callback.py
```

Input = `(id, prop)` to watch.
Output = `(id, prop)` to fill with the return value.

How the browser hands the work back to Python



3 · CALLBACKS, BEHIND THE SCENES

The actual messages (captured from demo 04, trimmed)

request `POST /_dash-update-component`

```
{
  "output": "..summary.children...chart.figure..",
  "outputs": [{"id": "summary", "property": "children"},
              {"id": "chart", "property": "figure"}],
  "inputs": [{"id": "sector", "property": "value",
              "value": "Energy"}],
  "changedPropIds": ["sector.value"]
}
```

response `200`, 8.7 KB

```
{
  "multi": true,
  "response": {
    "summary": {"children": "15 Energy bonds, average spre
    "chart": {"figure": {"data": [ ... ], "layout": { ...
  }
}
```

Terminal: `server: update(sector='Energy')`

The browser sends values, the server returns values. The figure travels as JSON every time, so keep returned figures lean.

3 · CALLBACKS

The callback toolkit

need	use
several inputs / outputs	list several `Input(...)` / `Output(...)`; return a tuple
read a value without triggering (e.g. "Apply" button)	`State("id", "prop")`
which input fired?	`ctx.triggered_id`
skip the call at page load	`prevent_initial_call=True`
leave an output unchanged	return `no_update` (or raise `PreventUpdate`)
change part of a big figure	`Patch()`: send only the diff
keep per-user data between calls	`dcc.Store` (not Python globals)
pure UI logic, no Python needed	`clientside_callback` (runs in JavaScript)
long jobs (minutes)	`background=True` callbacks with a job queue

4 · CLICK TO DRILL DOWN

Click a bond, see its history

```python
overview = px.scatter(bonds, x="maturity", y="spread",
                      color="rating", hover_name="issuer",
                      custom_data=["cusip"])   # rides along with each point

app.layout = html.Div([
    dcc.Graph(id="overview", figure=overview),
    dcc.Graph(id="detail"),
])

@callback(Output("detail", "figure"),
          Input("overview", "clickData"))
def show_history(click):
    if click is None:                       # page load: nothing clicked
        cusip = bonds.cusip.iloc[0]
    else:
        cusip = click["points"][0]["customdata"][0]
    h = history[history.cusip == cusip]
    return px.line(h, x="date", y="spread", title=cusip)
```




```
cd demos; python 05_drilldown.py
```

What one click does

1 plotly.js
fires a click event for the point under the mouse

↓

2 dcc.Graph
sets its prop clickData = {points: [{x, y, customdata}]}

↓

3 Dash renderer
overview.clickData is an Input → POST it

↓

4 Server
show_history(click): cusip → filter → px.line

↓

5 Response
{"detail": {"figure": …}}, 17.6 KB

↓

6 plotly.js redraws the right-hand chart

request captured from demo 05 (trimmed)


```
{
  "output": "detail.figure",
  "inputs": [{
    "id": "overview", "property": "clickData",
    "value": {"points": [{
      "curveNumber": 2, "pointNumber": 4,
      "x": 30, "y": 191.4,
      "hovertext": "Maple Foods",
      "customdata": ["MAP30203"]
    }]}
  }],
  "changedPropIds": ["overview.clickData"]
}
```


A click is just another prop change. Same loop as the dropdown: any chart can drive any other.

5 · VS CODE + COPILOT

Let Copilot write the Dash code

1. Open `demos/` in VS Code, select the venv
2. Copilot Chat → **Agent** mode (it can create and run files)
3. Describe **one** feature in plain words
4. Run, look, ask for the next change
5. Paste errors from the Dash error panel back into the chat

> You describe the **what** (ids, inputs, outputs). Copilot writes the boilerplate.

Prompt 1

Create `my_app.py`: a Dash app showing a scatter of `bonds`, maturity vs spread, coloured by sector, issuer on hover.

Prompt 2

Add a sector dropdown above the chart (default Banks). When it changes, show only that sector and a sentence with the count and average spread.

Prompt 3

When I click a bond, show its spread history from `history` in a second chart. Use `custom_data` for the cusip.

5 · VS CODE + COPILOT

Give Copilot the rules once

`demos/.github/copilot-instructions.md` is read with every request in this workspace:


```
- Use Dash 3 or later. Import with
  `from dash import Dash, html, dcc, callback, Output, Input`.
  Do NOT use dash_core_components / dash_html_components.
- Start the app with app.run(debug=True)  (run_server is gone).
- Get the data with `from data import bonds, history`.
- Give every component a callback uses an explicit id.
- No global state in callbacks; use dcc.Store.
- After a change, list each Input(id.prop) -> Output(id.prop).
```

Why it matters

- Models have seen years of **old** Dash code: `dash_core_components`, `app.run_server`, `@app.callback`
- Naming the data and its columns stops invented files
- "List the Input → Output pairs" lets you check the wiring before reading the code

6 · SHOWCASE

A bond monitor in ~140 lines




```
cd demos; python 06_full_app.py
```

6 · SHOWCASE

What's inside, mapped to today's ideas

feature	how
Filters drive KPIs, scatter, grid, sector chart	one callback, 4 Inputs → 8 Outputs
Click a bubble or select a grid row → history	`clickData` + `selectedRows`, `ctx.triggered_id`
Sortable, filterable table	`dash_ag_grid.AgGrid`
Live re-pricing every 2 s	`dcc.Interval` as an Input; a toggle enables it
Download the filtered bonds	`dcc.Download` + `State` + `prevent_initial_call`
Styling	`assets/style.css`, picked up automatically

> Same loop everywhere: a prop changes in the browser → POST → your function → new props.

WRAP-UP

Taking it further

Deploy

- `server = app.server` → `gunicorn app:server`
- several workers ⇒ no globals; share state via `dcc.Store`, a cache or a DB
- cache slow loads (`flask-caching`)

Grow

- multi-page apps: `use_pages=True` + `pages/`
- big data on charts: `Patch` , `plotly-resampler`
- docs: `dash.plotly.com` · AG Grid: `dash.plotly.com/dash-ag-grid`

Questions?