

Fadjar Fathurrahman  
Hermawan Kresno Dipojono

# Implementing Density Functional Theory

September 28, 2019

Springer Nature



# Preface

Importance of density functional theory

Implementation of density functional theory in various program packages (free and commercial)

Several books about density functional theories

The problem: not yet giving necessary details

This book is our humble attempt to demystifying several aspects of practical density functional theory to beginners in the field.

Objective of this book: show the reader how to implement a density functional theory for simple system containing only model potential (such as harmonic potential) and to non-local pseudopotentials which are usually used in typical DFT calculations for molecular and crystalline systems.

Outline of the book: 1d, 2d, 3d, Schrodinger equation, Poisson equation, Kohn-Sham equation for local (pseudo)potentials, Kohn-Sham equation for nonlocal pseudopotentials.

This is for *acknowledgments*.

Bandung,  
month year

*Fadjar Fathurrahman*  
*Hermawan Kresno Dipojono*



# Contents

<b>1</b>	<b>An introduction to density functional theory</b>	<b>1</b>
	References	1
<b>2</b>	<b>Schroedinger equation in 1d</b>	<b>3</b>
2.1	Approximating second derivative	4
2.2	Harmonic potential	6
2.3	Higher order finite difference	8
2.4	Exercises	9
<b>3</b>	<b>Schroedinger equation in 2d</b>	<b>11</b>
3.1	Finite difference grid in 2d	11
3.2	Laplacian operator	12
3.3	Iterative methods for eigenvalue problem	13
<b>4</b>	<b>Schroedinger equation in 3d</b>	<b>15</b>
<b>5</b>	<b>Numerical solution of Poisson equation</b>	<b>17</b>
<b>6</b>	<b>Kohn-Sham equation part I</b>	<b>19</b>
<b>7</b>	<b>Numerical solution of Kohn-Sham equation (part II)</b>	<b>21</b>
<b>A</b>	<b>Introduction to Julia programming language</b>	<b>23</b>
A.1	Installation	23

A.2	Using Julia .....	23
A.2.1	Using Julia REPL .....	23
A.2.2	Julia script file .....	24
A.3	Basic programming construct .....	25
A.4	Mathematical operators .....	25
<b>B</b>	<b>Introduction to Octopus DFT code .....</b>	<b>27</b>
<b>Index</b>	<b>.....</b>	<b>29</b>

## Chapter 1

# An introduction to density functional theory

Intro to DFT [1].

Kohn-Sham equation

$$\nabla^2 + V(\mathbf{r})\psi_i(\mathbf{r}) = E\psi_i(\mathbf{r}) \quad (1.1)$$

## References

1. Test Kohn Sham





## Chapter 2

### Schroedinger equation in 1d

The equation we want to solve is (in Hartree atomic unit):

$$\left[ -\frac{1}{2} \frac{d^2}{dx^2} + V(x) \right] \psi(x) = E \psi(x) \quad (2.1)$$

with the boundary conditions:

$$\lim_{x \rightarrow \pm\infty} \psi(x) = 0 \quad (2.2)$$

We will discretize the wave function, potentials, and various spatial quantities using regular grid within the finite computational interval  $[x_{\min}, x_{\max}]$ . This computational interval should be chosen such that the boundary condition 2.2 approximately satisfied.

We will choose the grid points  $x_i$ ,  $i = 1, 2, \dots$  as:

$$x_i = x_{\min} + (i - 1)h \quad (2.3)$$

where  $N$  is the number of grid points and  $h$  is the spacing between the grid points is:

$$h = \frac{x_{\max} - x_{\min}}{N - 1} \quad (2.4)$$

The following code can be used to initialize the grid points:

```
function init_FD1d_grid( x_min::Float64, x_max::Float64, N::Int64 )
    L = x_max - x_min
    h = L / (N-1)
    x = zeros(Float64, N)
    for i = 1:N
        x[i] = x_min + (i-1)*h
    end
    return x, h
end
```

end

```
init_FD1d_grid( X, N ) = init_FD1d_grid( X[1], X[2], N )
```

## 2.1 Approximating second derivative

With the following notation:  $\psi_i = \psi(x_i)$ , we can use 3-point finite difference to approximate second derivative of  $\psi(x)$ :

$$\frac{d^2}{dx^2} \psi_i = \frac{\psi_{i+1} - 2\psi_i + \psi_{i-1}}{h^2} \quad (2.5)$$

Take  $\{\psi_i\}$  as (column) vector, we can represent the second derivative operation as matrix multiplication:

$$\psi'' = \mathbb{D}^{(2)} \psi \quad (2.6)$$

where  $\mathbb{D}^{(2)}$  is the second derivative matrix operator

$$\mathbb{D}^{(2)} = \frac{1}{h^2} \begin{bmatrix} -2 & 1 & 0 & 0 & 0 & \cdots & 0 \\ 1 & -2 & 1 & 0 & 0 & \cdots & 0 \\ 0 & 1 & -2 & 1 & 0 & \cdots & 0 \\ \vdots & \ddots & \ddots & \ddots & \ddots & \ddots & \vdots \\ 0 & \cdots & 0 & 1 & -2 & 1 & 0 \\ 0 & \cdots & \cdots & 0 & 1 & -2 & 1 \\ 0 & \cdots & \cdots & \cdots & 0 & 1 & -2 \end{bmatrix} \quad (2.7)$$

An example implementation can be found in file `build_D2_matrix_3pt.jl`.

```
"""
Build second derivative matrix using 3-points centered
finite difference approximation.

# Arguments
- `N::Int64`: number of grid points
- `h::Float64`: spacing between grid points
"""
function build_D2_matrix_3pt( N::Int64, h::Float64 )
    mat = zeros{Float64}(N,N)
    for i = 1:N-1
        mat[i,i] = -2.0
        mat[i,i+1] = 1.0
        mat[i+1,i] = mat[i,i+1]
    end
end
```

```
mat[N,N] = -2.0  
return mat/h^2  
end
```

Test with Gaussian function:


$$\psi(x) = e^{-\alpha x^2} \quad (2.8)$$

which second derivative can be calculated as

$$\psi''(x) = (-2\alpha + 4\alpha^2 x^2) e^{-\alpha x^2} \quad (2.9)$$

They are implemented in the following code

```
function my_gaussian(x; α=1.0)  
    return exp(-α*x^2)  
end  
  
function d2_my_gaussian(x; α=1.0)  
    return (-2*α + 4*α^2 * x^2) * exp(-α*x^2)  
end
```



**Fig. 2.1** Finite difference approximation to a Gaussian function and its second derivative

## 2.2 Harmonic potential

We will start with a simple potential with known exact solution, namely the harmonic potential:

$$V(x) = \frac{1}{2} \omega^2 x^2 \quad (2.10)$$

The Hamiltonian in finite difference representation:

$$H = -\frac{1}{2}D^{(2)} + V \quad (2.11)$$

where  $V$  is a diagonal matrix whose elements are:

$$V_{ij} = V(x_i)\delta_{ij} \quad (2.12)$$

Code to solve harmonic oscillator:

```
using Printf
using LinearAlgebra
using PGFPlotsX
using LaTeXStrings

include("init_FD1d_grid.jl")
include("build_D2_matrix_3pt.jl")

function pot_harmonic( x; ω=1.0 )
    return 0.5 * ω^2 * x^2
end

function main()
    # Initialize the grid points
    xmin = -5.0
    xmax = 5.0
    N = 51
    x, h = init_FD1d_grid(xmin, xmax, N)
    # Build 2nd derivative matrix
    D2 = build_D2_matrix_3pt(N, h)
    # Potential
    Vpot = pot_harmonic.(x)
    # Hamiltonian
    Ham = -0.5*D2 + diagm( 0 => Vpot )
    # Solve the eigenproblem
    evals, evecs = eigen( Ham )
    # We will show the 5 lowest eigenvalues
    Nstates = 5
    @printf("Eigenvalues\n")
    for i in 1:Nstates
        @printf("%5d %18.10f\n", i, evals[i])
    end

    # normalize the first three eigenstates
    for i in 1:3
        ss = dot(evecs[:,i], evecs[:,i])*h
        evecs[:,i] = evecs[:,i]/sqrt(ss)
    end

    # Plot up to 3rd eigenstate
```

```


f = @pgf Axis({ title="N="*string(N), height="10cm", width="15cm",
    ↪ xmajorgrids, ymajorgrids },
    PlotInc(Coordinates(x, evcs[:,1])),
    LegendEntry("1st eigenstate"),
    PlotInc(Coordinates(x, evcs[:,2])),
    LegendEntry("2nd eigenstate"),
    PlotInc(Coordinates(x, evcs[:,3])),
    LegendEntry("3rd eigenstate"),
)
pgfsave("IMG_main_harmonic_01_"*string(N)*".pdf", f)
end

main()

```

Compare with analytical solution.

Plot of eigenfunctions:



**Fig. 2.2** Eigenstates of harmonic oscillator

## 2.3 Higher order finite difference

To obtain higher accuracy

Implementing higher order finite difference.

## **2.4 Exercises**

Gaussian potential





## Chapter 3

### Schroedinger equation in 2d

Schrodinger equation in 2d:

$$\left[ -\frac{1}{2}\nabla^2 + V(x,y) \right] \psi(x,y) = E \psi(x,y) \quad (3.1)$$

where  $\nabla^2$  is the Laplacian operator:

$$\nabla^2 = \frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial y^2} \quad (3.2)$$

#### 3.1 Finite difference grid in 2d

```
struct FD2dGrid
    Npoints::Int64
    Nx::Int64
    Ny::Int64
    hx::Float64
    hy::Float64
    dA::Float64
    x::Array{Float64,1}
    y::Array{Float64,1}
    r::Array{Float64,2}
    idx_ip2xy::Array{Int64,2}
    idx_xy2ip::Array{Int64,2}
end

function FD2dGrid( x_domain, Nx, y_domain, Ny )
    x, hx = init_FD1d_grid(x_domain, Nx)
    y, hy = init_FD1d_grid(y_domain, Ny)
    dA = hx*hy
    Npoints = Nx*Ny
    r = zeros(2,Npoints)
```

```

ip = 0
idx_ip2xy = zeros(Int64,2,Npoints)
idx_xy2ip = zeros(Int64,Nx,Ny)
for j in 1:Ny
    for i in 1:Nx
        ip = ip + 1
        r[1,ip] = x[i]
        r[2,ip] = y[j]
        idx_ip2xy[1,ip] = i
        idx_ip2xy[2,ip] = j
        idx_xy2ip[i,j] = ip
    end
end
return FD2dGrid(Npoints, Nx, Ny, hx, hy, dA, x, y, r, idx_ip2xy,
    ↪ idx_xy2ip)
end

```

### 3.2 Laplacian operator

Given second derivative matrix in  $x$ ,  $\mathbb{D}_x^{(2)}$ ,  $y$  direction,  $\mathbb{D}_y^{(2)}$ , we can construct finite difference representation of the Laplacian operator  $\mathbb{L}$  by using

$$\mathbb{L} = \mathbb{D}_x^{(2)} \otimes \mathbb{I}_y + \mathbb{I}_x \otimes \mathbb{D}_y^{(2)} \quad (3.3)$$

where  $\otimes$  is Kronecker product. In Julia, we can use the function `kron` to form the Kronecker product between two matrices A and B as `kron(A,B)`.

```


function build_nabla2_matrix( fdgrid::FD2dGrid; func_1d=build_D2_matrix_3pt )
    Nx = fdgrid.Nx
    hx = fdgrid.hx
    Ny = fdgrid.Ny
    hy = fdgrid.hy

    D2x = func_1d(Nx, hx)
    D2y = func_1d(Ny, hy)

    ∇2 = kron(D2x, speye(Ny)) + kron(speye(Nx), D2y)
    return ∇2
end

```

Example to the approximation of 2nd derivative of 2d Gaussian function



**Fig. 3.1** Two-dimensional Gaussian function and its finite difference approximation of second derivative

### 3.3 Iterative methods for eigenvalue problem

The Hamiltonian matrix:

```
 $\nabla^2$  = build_nabla2_matrix( fdgrid, func_ld=build_D2_matrix_9pt )
Ham = -0.5* $\nabla^2$  + spdiags( 0 => Vpot )
```

The Hamiltonian matrix size is large. The use eigen method to solve this eigenvalue problem is not practical. We also do not need to solve for all eigenvalues. We must resort to the so called iterative methods.



## Chapter 4

### Schroedinger equation in 3d

Extension to 3d [?]

Schrodinger equation in 3d:

$$\left[ -\frac{1}{2}\nabla^2 + V(\mathbf{r}) \right] \psi(\mathbf{r}) = E \psi(\mathbf{r}) \quad (4.1)$$

where  $\mathbf{r}$  is abbreviation to  $(x, y, z)$ . where  $\nabla^2$  is the Laplacian operator:

$$\nabla^2 = \frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial y^2} + \frac{\partial^2}{\partial z^2} \quad (4.2)$$

```
const ® = kron
function build_nabla2_matrix( fdgrid::FD3dGrid; func_ld=build_D2_matrix_3pt )
    D2x = func_ld(fdgrid.Nx, fdgrid.hx)
    D2y = func_ld(fdgrid.Ny, fdgrid.hy)
    D2z = func_ld(fdgrid.Nz, fdgrid.hz)
    IIX = speye(fdgrid.Nx)
    IIy = speye(fdgrid.Ny)
    IIz = speye(fdgrid.Nz)
    V2 = D2x®IIy®IIz + IIX®D2y®IIz + IIX®IIy®D2z
    return V2
end
```



## Chapter 5

# Numerical solution of Poisson equation

We will turn our attention to the Poisson equation:

$$\nabla^2 V_H(\mathbf{r}) = 4\pi \rho(\mathbf{r}) \quad (5.1)$$

Introduction to conjugate gradient problem

3d dimensional problem





## **Chapter 6**

### **Kohn-Sham equation part I**

Using local potential only



## **Chapter 7**

### **Numerical solution of Kohn-Sham equation (part II)**

Using nonlocal potential (pseudopotential)



## Appendix A

### Introduction to Julia programming language

This chapter is intended to as an introduction to the Julia programming language.

This chapter assumes familiarity with command line interface.

#### A.1 Installation

Go to <https://julialang.org/downloads/> and download the suitable file for your platform. For example, on 64 bit Linux OS, we can download the file `julia-1.x.x-linux-x86_64.tar.gz` where 1.x.x referring to the version of Julia. After you have downloaded the tarball you can unpack it.

```
tar xvf julia-1.x.x-linux-x86_64.tar.gz
```

After unpacking the tarball, there should be a new folder called `julia-1.x.x`. You might want to put this directory under your home directory (or another directory of your preference).

#### A.2 Using Julia

##### A.2.1 Using Julia REPL

Let's assume that you have put the Julia distribution under your home directory. You can start the Julia interpreter by typing:



You can experiment with Julia REPL by typing `julia` at terminal:

We also can put the code in a text file with `.jl` extension and execute it with the command:

```
julia filename.jl
```

The following code

```
function say_hello(name)
    println("Hello: ", name)
end
say_hello("efefer")
```

### A.3 Basic programming construct

Julia has similarities with several popular programming languages such as Julia, MATLAB, and R, to name a few.

### A.4 Mathematical operators

```
if a >= 1
    println("a is larger or equal to 1")
end
```

Example code 3

```
using PGFPlotsX
using LaTeXStrings
include("init_FD1d_grid.jl")
function my_gaussian(x::Float64; α=1.0)
    return exp( -α*x^2 )
end
function main()
    A = -5.0
    B = 5.0
    Npoints = 8
    x, h = init_FD1d_grid( A, B, Npoints )

    NptsPlot = 200
    x_dense = range(A, stop=B, length=NptsPlot)

    f = @pgf{
        Axis( {height = "6cm", width = "10cm" },
```

```
PlotInc( {mark="none"}, Coordinates(x_dense, my_gaussian.(x_dense)) ),
LegendEntry(L"f(x)"),
PlotInc( Coordinates(x, my_gaussian.(x)) ),
LegendEntry(L"Sampled $f(x)$"),
)
)
pgfsave("TEMP_gaussian_1d.pdf", f)
end
main()
```



## **Appendix B**

### **Introduction to Octopus DFT code**

Prerequisites:

- Autotools and GNU Make
- C, C++ and Fortran compilers
- Libxc

```
autoreconf --install  
./configure --prefix=path_to_install  
make  
make install
```



# **Index**

Kohn-Sham equation, 1