

Note: time unit conversions

- $1\text{ ns} = 1\text{e-6 ms} = 0.000001\text{ millisecond}$
- $1\text{ millisecond (ms)} = 0.001\text{ seconds}$
- $1\text{ microsecond} = 0.001\text{ milliseconds}$
- alternatively
  - $10\text{e-9} = \text{nanosecond (ns)}$
  - $10\text{e-6} = \text{microsecond (mu s)}$
  - $10\text{e-3} = \text{millisecond (ms)}$

## Computing $\pi$

We now start with the first parallelization tasks. We will

- see how a python application can be parallelized
- discuss **data parallelism** and **task parallelism**

We use the example of computing  $\pi$  because it is a simple example that still takes some time to compute, so perfect for our instructional purposes.

The way this works is with **Monte-Carlo** methods--this means approximating exact results with random numbers and simulation.

### The geometry behind

- assume a unit radius
- then the surface of the square is  $4r^2$
- the surface of the circle is  $\pi r^2$
- if we can compute the surfaces, we can call them  $M$  for the circle and  $N$  for the square
- then we have  $M / N = \pi r^2 / 4 r^2$
- solving for  $\pi$  we get  $\pi = 4 M / N$

How do we get  $M$  and  $N$ ?

**Exercise: implement the algorithm (time?)**

- using only standard python and the `random.uniform` function

```
In [1]: import random
import math

def calc_pi(N):
    "Compute pi using N random samples"
    M = 0
    for i in range(N):
        # Simulate random coordinates
        x = random.uniform(-1, 1)
        y = random.uniform(-1, 1)
        if x**2 + y**2 < 1: # don't need sqrt b/c 1**2 = 1
            M += 1

    return 4*M/N
```

```
In [2]: time_forloop = %timeit -o calc_pi(10**6)
```

599 ms  $\pm$  11.8 ms per loop (mean  $\pm$  std. dev. of 7 runs, 1 loop each)

Before starting to parallelize, we should make the inner function (the for loop) as efficient as possible. We discuss two options

1. vectorization with `numpy`
2. native code generation with `numba`

Vectorization works by applying the computation over an array of numbers, instead of each number individually.

What does `numba` do?

- when we execute python code, the line is *interpreted* and directly performed. the speed of this depends on how the programming language is designed (*interpretation*)
- an alternative is *compiled* code, where we write in some language and then translate the code to machine code. Only after this we execute the program. (*ahead-of-time compilation*)
- `numba` sits in between the two and performs *just-in-time compilation*. It generates optimized machine code---that is faster than python code---, at runtime. This means that our code is compiled to machine code as we define the function.

- this is faster than python code but has additional overhead from compiling

## Numpy

In [3]: *# can use this to show how to get to the function below*

```
import numpy as np
np.random.uniform(-1, 1, (1, 1))
points = np.random.uniform(-1, 1, (2, 100))
(points**2).sum(axis=0)
(points**2).sum(axis=0) < 1
np.count_nonzero((points**2).sum(axis=0) < 1)

M = np.count_nonzero((points**2).sum(axis=0) < 1)

4 * M / 100
```

Out[3]: 3.0

```
In [4]: def calc_pi_numpy(N):
        "Compute pi using N samples with numpy"
        points = np.random.uniform(-1, 1, (2, N))
        # M = np.count_nonzero((points**2).sum(axis=0) < 1)
        M = np.count_nonzero((points**2).sum(axis=0) < 1)
        return 4 * M / N
```

In [5]: calc\_pi\_numpy(10\*\*6)

Out[5]: 3.141612

In [6]: time\_numpy = %timeit -o calc\_pi\_numpy(10\*\*6)

16.5 ms ± 242 µs per loop (mean ± std. dev. of 7 runs, 100 loops each)

```
In [7]: speedup = time_forloop.average / time_numpy.average
        print(f"Using numpy is {speedup:.2f} times faster than using the for loop")
```

Using numpy is 36.35 times faster than using the for loop

This is a *vectorized* version of the algorithm: It demonstrates **data parallelism** where a single operation is applied over a collection of data.

This contrasts to **task parallelism** where different independent procedures are applied in parallel. Example: cutting vegetables while simmering the split peas.

### Discussion Is this all better?

What are the downside of the vectorized implementation, and of data parallelism in general?

- it uses more memory
- it is perhaps less intuitive
- it is more monolithic and it cannot easily be broken up into parts -- in contrast to the example below.

### Challenge: Daskify

Write `calc_pi_dask` to make the numpy version parallel. Compare speed and memory performance with the numpy version.

Remember that `dask.array` mimics the numpy API.

In [8]: *#can use this to illustrate how get to to the function below*

```
import dask.array as da
points = da.random.uniform(-1, 1, (2, 100))
(points**2).sum(axis=0).compute() < 1
work = da.count_nonzero((points**2).sum(axis=0) < 1)
work.compute()
```

Out[8]: 75

```
In [9]: def calc_pi_dask(N):
        "Compute pi using N samples with dask"
        points = da.random.uniform(-1, 1, (2, N))
        work = da.count_nonzero((points**2).sum(axis=0) < 1)

        # using the physical number of cores, as we found out in previous episode
        M = work.compute(num_workers=4)
        return 4 * M / N
```

In [10]: calc\_pi\_dask(10\*\*6)

Out[10]: 3.144296

```
In [11]: time_dask = %timeit -o calc_pi_dask(10**6)
23.5 ms ± 920 µs per loop (mean ± std. dev. of 7 runs, 10 loops each)

In [12]: speedup = time_forloop.average / time_dask.average
print(f"Using dask is {speedup:.2f} times faster than using the for loop")
```

Using dask is 25.52 times faster than using the for loop

### Compare memory and performance

```
In [13]: from memory_profiler import memory_usage
import matplotlib.pyplot as plt

In [14]: # Little wrappers to make life easy
N = 10**8
def pi_with_numpy():
    return calc_pi_numpy(N)

def pi_with_dask():
    return calc_pi_dask(N)


In [15]: memory_numpy = memory_usage(pi_with_numpy, interval=0.01)
time_numpy = %timeit -o pi_with_numpy()
1.64 s ± 22.4 ms per loop (mean ± std. dev. of 7 runs, 1 loop each)

In [16]: memory_dask = memory_usage(pi_with_dask, interval=0.01)
time_dask = %timeit -o pi_with_dask()
770 ms ± 52.6 ms per loop (mean ± std. dev. of 7 runs, 1 loop each)

In [17]: speedup = time_numpy.average / time_dask.average
print(f"Using dask is {speedup:.2f} times faster than using numpy")
```

Using dask is 2.14 times faster than using numpy

```
In [18]: plt.plot(memory_numpy, label="numpy")
plt.plot(memory_dask, label="dask")
plt.xlabel("Time step")
plt.ylabel("Memory in MB")
plt.legend()
plt.show()
```



## Using numba to accelerate python code

numba makes it easy for us to build accelerated functions. We can call the decorator `numba.jit`. What does it do? -- It sends the function, to which we apply the decorator, to machine code when we execute the cell

```
In [19]: import numba

@numba.jit
def sum_range_numba(a):
    "Compute the sum of the numbers in the range [0, a)"
    x = 0
    for i in range(a):
        x += 1
```

```
return x
```

Let's time three different versions of this.

```
In [20]: ## Naive python iterators
time_naive = %timeit -o sum(range(10**7))
```

164 ms ± 18.1 ms per loop (mean ± std. dev. of 7 runs, 10 loops each)

```
In [21]: # numpy
time_numpy = %timeit -o np.arange(10**7).sum()
```

15.6 ms ± 158 µs per loop (mean ± std. dev. of 7 runs, 100 loops each)

```
In [22]: # numba
time_numba = %timeit -o sum_range_numba(10**7)
# sometimes a warning appears "[could be that ..] intermediate result is being cached".
# re-running usually helps
```

153 ns ± 4.25 ns per loop (mean ± std. dev. of 7 runs, 10,000,000 loops each)

```
In [23]: speedup = time_numpy.average / time_numba.average
print(f"Using numba is {speedup:.2f} times faster than using numpy")
```

Using numba is 101685.51 times faster than using numpy

So, numba is 100k times faster (?)

$(14.7.5 * 10e-3) / (128 * 10e-9) = (17.5 * 10e-3) / (12.8 * 10e-8) = 10e-5$

numba JIT does not work on every python or numpy feature, but a function is a good candidate if written with a python for-loop over a large range of values, as with `sum_range_numba()`.

#### Note on just-in-time compilation

- there may be little or no speed-up when function is called the first time
- similarly, when using `timeit` you may get the following message
  - The slowest run took 14.83 times longer than the fastest. This could mean that an intermediate result is being cached.
- reason: on the first call, the JIT compiler needs to compile the function. on subsequent runs, the function is reused
- the same function can only be reused if it is called with the same argument types (int, float, etc)

```
In [24]: %time sum_range_numba(10**7)
```

CPU times: user 3 µs, sys: 1 µs, total: 4 µs  
Wall time: 5.48 µs

```
Out[24]: 10000000
```

```
In [25]: %time sum_range_numba(10.**7)
```

CPU times: user 39.2 ms, sys: 0 ns, total: 39.2 ms  
Wall time: 45.4 ms

```
Out[25]: 10000000
```

```
In [26]: %time sum_range_numba(10.**7)
```

CPU times: user 4 µs, sys: 0 ns, total: 4 µs  
Wall time: 6.2 µs

```
Out[26]: 10000000
```

#### Challenge: numbify `calc_pi`

Create a numba version of `calc_pi`. Time it.

```
In [27]: # note we're moving back to a function that looks similar to the original function
@numba.jit
def calc_pi_numba(N):
    "Compute pi using N samples with numba"
    M = 0
    for i in range(N):
        # Simulate random coordinates
        x = random.uniform(-1, 1)
        y = random.uniform(-1, 1)
        if x**2 + y**2 < 1.0: # don't need sqrt b/c 1**2 = 1
            M += 1

    return 4*M/N
```

```
In [28]: calc_pi_numba(10**7)
```

Out[28]: 3.1418116

In [29]: `time_numba = %timeit -o calc_pi_numba(10**6)`

7.53 ms ± 238 µs per loop (mean ± std. dev. of 7 runs, 100 loops each)

In [30]: `speedup = time_dask.average / time_numba.average  
print(f"Using numba is {speedup:.2f} times faster than using dask")`

Using numba is 102.15 times faster than using dask

## Conclusion

- measuring - knowing: always profile your code to see which parallelization method works best
- numba often outperforms other methods, but it is not always possible to rewrite code so that one can use numba with it

Processing math: 100%